
Chapter 13. References

- ABB Environmental Services, Inc. (ABB-ES). *Operable Unit (OU) 12 Final Remedial Investigation Report, Loring Air Force Base*, Limestone, Maine, 1997.
- Archie, G.E. Electrical resistivity log as an aid in determining some reservoir characteristics. *Am. Inst. Mining and Metal, (Engr. Transl.)* 146: 54-62 (1942).
- Basel, M., and K.S. Udell. Two-dimensional study of steam injection into porous media. *Multiphase Transport in Porous Media*, 127: 39-46 (1989).
- BERC. *Steam Enhanced Extraction Demonstration at Site 5, Alameda Point*. Field Feasibility Demonstration for the U.S. Navy, DO-9. Berkeley, CA: Environmental Restoration Center, University of California at Berkeley, 2000.
- Beane, W. Brandon, and R. Behre. Quarry Site—Former Loring Air Force Base, Orientation of Joints East and West of CDM Fault. State of Maine: Department of Environmental Protection, (Unpublished Map), 1998.
- Betz, C., A. Farber, C.M. Green, H.P. Koschitzky, and R. Schmidt. *Removing Volatile and Semivolatile Contaminants from the Unsaturated Zone by Injection of Steam/Air Mixture in Contaminated Soil*, London: Thomas Telford, 1998.
- Brandon, W., and R. Hoey. “Examination of the relationship of rock structure to groundwater flow in a fractured limestone aquifer.” Poster presented at the *USEPA/National Ground Water Association Fractured Rock Conference: State of the Science and Measuring Success in Remediation, Portland, ME*, September 13-15, 2004.
- Brandon, W.C., and R. Steimle. “Issues Identified From Several Remedial Pilot Studies in Fractured Rock.” Poster presented at the *Fourth International Conference on Remediation of Chlorinated and Recalcitrant Compounds, Battelle Memorial Institute, Monterey, CA*, May 2004.
- Butler, J.J., Jr. *The Design, Performance, and Analysis of Slug Tests*, Boca Raton, Florida: Lewis Publishers, 1998.
- CDM. *Fracture and Fault Analysis of the Quarry Site, Loring Air Force Base, Limestone, Maine*, CDM Federal Programs Corp., 1992.
- Cooper, H. H., Jr., J.D. Bredehoeft, and I.S. Papadopolos. Response of a finite diameter well to an instantaneous charge of water. *Water Resources Research* 3(1): 263-269 (1967).
- Davis, E.L. *How Heat Can Accelerate In-situ Soil and Aquifer Remediation: Important Chemical Properties and Guidance on Choosing the Appropriate Technique*, EPA/540/S-97/502. Cincinnati, OH: U.S. Environmental Protection Agency, 1997.
- Davis, E.L. *Steam Injection for Soil and Aquifer Remediation*, EPA/540/S-97/505. Cincinnati, OH: U.S. Environmental Protection Agency, 1998.
- Davis, E.L. *Wyckoff/Eagle Harbor Steam Injection Treatability Studies*, Report to Region X, U.S. Environmental Protection Agency, 2002.
- DeVoe, C., and K.S. Udell. “Thermodynamic and hydrodynamic behavior of water and DNAPLs during heating.” In *Proceedings from the First Conference on Remediation of Chlorinated and Recalcitrant Compounds, Monterey CA*, 1998.
- Dusilek, P., P. Kvapil, and K.S. Udell. “Remediation of a partially fractured aquifer system containing a TCE source using steam enhanced extraction.” Paper presented at the 2001 *International Containment and Remediation Technology Conference & Exhibition*, Orlando, FL, June 10-13, 2001.
- Eaker, C. *Full-scale steam enhanced extraction at Visalia Pole Yard*. Personal communication, 2003.
- Earth Tech and SteamTech. *Site 61 Treatability Study Report, Steam Injection. Northwest Main Base, Operable Unit 8*. Edwards AFB, CA: Draft report submitted to U.S. Air Force Flight Test Center, Environmental Restoration Division, 2003.
- Engelder, T. Tectonic implications drawn from differences in the surface morphology on two joint sets in the Appalachian Valley and Ridge, Virginia. *Geology*, 32: 413-416 (2004).
- Gildea, M.L., and L.D. Stewart. *Demonstration of Steam Injection as an Enhanced Source Removal Technology for Aquifer Restoration*. Tyndall AFB, FL: Report for U.S. Air Force Research Laboratory, ARA Project #5241, 1997.

-
- Golder Associates, Inc. "Fracman: Interactive discrete feature data analysis." *Geometric Modeling and Exploration Simulation, Version 2.6*, 1998.
- Harding Lawson Associates, Inc. (HLA) *Phase I Data Report and Interpretation, Additional Site Characterization, Quarry Pilot Study*, 1998.
- Harding Lawson Associates, Inc. *Final Basewide Groundwater Operable Unit (OU 12) Feasibility Study Report, Installation Restoration Program, Loring Air Force Base*, 1999a.
- Harding Lawson Associates, Inc. *Final Proposed Plan for Operable Unit (OU) 12, Installation Restoration Program, Loring Air Force Base*, 1999b.
- Harding Lawson Associates, Inc. *Loring Air Force Base, Phase II Data Report and Interpretation, Additional Site Characterization, Quarry Pilot Study*, 1999c.
- Heron, G., M. Van Zutphen, T.H. Christensen, and C.G. Enfield. Soil heating for enhanced remediation of chlorinated solvents: A laboratory study on resistive heating and vapor extraction in a silty, low-permeable soil contaminated with trichloroethylene. *Environmental Science and Technology* 32 (10): 1474-1481 (1998a).
- Heron, G., T.H. Christensen, T. Heron, and T.H. Larsen. "Thermally enhanced remediation at DNAPL sites: The competition between downward mobilization and upward volatilization." In *Proceedings of the First International Conference on Remediation of Chlorinated and Recalcitrant Compounds*, Monterey, CA, 1998b.
- Heron, G., D. LaBrecque, and H. Sowers. "Steam stripping/hydrous pyrolysis oxidation for in-situ remediation of a TCE DNAPL spill." In *Proceedings of the 2000 Battelle Conference on Chlorinated and Recalcitrant Compounds*, Monterey, CA, 2000.
- Heron, G., S. Carroll, and S.G. Nielsen. Full-scale removal of DNAPL constituents using steam enhanced extraction and electrical resistance heating. *Ground Water Monitoring and Remediation* (In Press, Winter 2005).
- Hilberts, B. "In-situ steam stripping." In *Proceedings of the First International TNO Conference on Contaminated Soil*, Dordrecht, NL, 1986.
- Hunt, J.R., N. Sitar, and K.S. Udell. Nonaqueous phase liquid transport and cleanup 1. Analysis of mechanisms. *Water Resources Research* 24 (8): 1247-1258 (1988a).
- Hunt, J.R., N. Sitar, and K.S. Udell. Nonaqueous phase liquid transport and cleanup 2. Experimental Studies. *Water Resources Research* 24 (8): 1259-1269 (1988b).
- Hvorslev, M.J. *Time Lag and Soil Permeability in Groundwater Observations*, Bulletin 36. Vicksburg, MS: U.S. Army Corp of Engineers Waterways Experiment Station, 1951.
- Imhoff, P.T., A. Frizzell, and C.T. Miller. Evaluation of thermal effects on the dissolution of a nonaqueous phase liquid in porous media. *Environmental Science & Technology* 31: 1615-1622 (1997).
- Integrated Water Resources. *Deployment of a Dynamic Underground Stripping-Hydrous Pyrolysis/Oxidation System at the Savannah River Site 321-M Solvent Storage Tank Area, Final Report*. Prepared for Westinghouse Savannah River Company, 2002.
- Itamura, M.T., and K.S. Udell. "An analysis of optimal cycling time and ultimate chlorinated hydrocarbon removal from heterogeneous media using cyclic steam injection." In *Proceedings of the ASME Heat Transfer and Fluids Engineering Divisions*, 1995.
- IWR. *Deployment of a Steam Injection/Extraction System at LC34, Cape Canaveral Air Station, Final Report*. Prepared for MSE-Technology Applications, Inc., 2003.
- Jeffers, P.M., L.M. Ward, L.M. Woytowitch, and N.L. Wolfe. Homogeneous hydrolysis rate constants for selected chlorinated methanes, ethanes, ethenes, and propanes, *Environmental Science & Technology* 23 (8): 965-969 (1989).
- Kaslusky, S.F., and K.S. Udell. A theoretical model of air and steam co-injection to prevent downward migration of DNAPLs during steam enhanced extraction. *Journal of Contaminant Hydrology* 55: 213-232 (2002).
- Keller, A.A. "Steam injection to displace DNAPLs from fractured media." In *International Association of Hydrological Science*, Oxfordshire, UK, 1998.
- Ketcheson, D.R., and W.G. Zwiers. "Evaluation of in-situ restoration technologies for a DNAPL impacted fractured carbonate rock site at Smithville, Ontario. In *Proceedings of the Air & Water Management Association's 90th Annual Meeting & Exhibition*, Toronto, Ontario, Canada, 1997.
- Konopnicki, D.T., E.F. Traverse, A. Brown, and A.D. Deibert. Design and evaluation of the Shiells Canyon field steam-distillation drive pilot project. *JPT: Journal of Petroleum Technology* 31: 546-552 (1979).
- LaBrecque, D.J., A.L. Ramirez, W.D. Daily, A.M. Binley, and S.A. Schima. ERT monitoring of environmental processes. *Measurement Science and Technology* 7: 375-383 (1996).
- Leif, R.N., M. Chiarappa, R.D. Aines, R.L. Newmark, K.G. Knauss, and C. Eaker. "In situ hydrothermal oxidative destruction of DNAPLs in a creosote contaminated site." In *Proceedings of the First International Conference on Remediation of Chlorinated and Recalcitrant Compounds*, Monterey, CA, 1998.

-
- Llera, F.J., M. Sato, K. Nakatsuka, and H. Yokoyama. Temperature dependence of the electrical resistivity of water-saturated rocks. *Geophysics* 55: 576-585 (1990).
- MacFarlane, S., D. Mackay, and W.Y. Shiu. "Application of screening model for assessing subsurface NAPL contamination and remediation. In *Proceedings of the Air & Water Management Association's 90th Annual Meeting & Exhibition*, Toronto, Ontario, Canada, 1997.
- Mackie, B.E. "Interconnectivity study of a fractured rock aquifer." In *Remediation in Rock Masses*, Reston, Virginia: ASCE Press, 2000, 56-67.
- Mandl, G., and C.W. Volek. Heat and mass transport in steam-drive processes. *Soc. Pet. Eng. J.* 9: 59-79 (1969).
- Mercer, J.W., and R.M. Cohen. A review of immiscible fluids in the subsurface: properties, models, characterization and remediation. *Journal of Contaminant Hydrology* 6: 107-163 (1990).
- Michalski, A., and R. Britton. The role of bedding fractures in the hydrology of sedimentary bedrock – Evidence from the Newark Basin, New Jersey. *Ground Water* 35: 318-327 (1997).
- Michalski, A., and G.M. Klepp. Characterization of transmissive fractures by simple tracing of in-well flow, *Ground Water* 28:191-198 (1990).
- Morin, R.H., L.A. Senior, and E.R. Decker. Fractured-aquifer hydrogeology from geophysical logs: Brunswick Group and Lockatong Formation, Pennsylvania. *Ground Water* 38: 182-192 (2000).
- Newmark, R.L. *Demonstration of Dynamic Underground Stripping at the LLNL Gasoline Spill Site, Vol. 1-4*, UCRL-ID-116964. Livermore, CA: Lawrence Livermore National Laboratory, 1994.
- Newmark, R.L., and R.D. Aines. *Dumping Pump and Treat: Rapid Cleanups Using Thermal Technology*, UCRL-JC-126637. Livermore, CA: Lawrence Livermore National Laboratory, 1997.
- Newmark, R.L., and R.D. Aines. They all like it hot: Faster cleanup of contaminated soil and groundwater. *Science and Technology Review* (1998).
- Novakowski, K.S. Analysis of pulse interference tests. *Water Resources Research* 25 (11): 2377-2387 (1989).
- Novakowski, K.S., and P.A. Lapcevic. Regional hydrogeology of the Silurian and Ordovician sedimentary rock underlying Niagara Falls, Ontario, Canada. *Journal of Hydrology* 104: 211-236 (1988).
- Novakowski, K., P. Lapcevic, G. Bickerton, J. Voralek, L. Zanini, and C. Talbot. *The Development of a Conceptual Model for Contaminant Transport in the Dolostone Underlying Smithville, Ontario*, Smithville Phase IV Bedrock Remediation Program, 1999.
- Oochs, S.O., R.A. Hodges, R.W. Falta, T.F. Kmetz, J.J. Supar, N.N. Brown, and D.L. Parkinson. Predicted heating patterns during steam flooding of coastal plain sediments at the Savannah River Site. *Environmental & Geological Geoscience* 9 (1): 51-60 (2003).
- Pankow, J.F., and J.A. Cherry. *Dense Chlorinated Solvents and Other DNAPLs in Groundwater: History, Behavior, and Remediation*. Portland, Oregon: Waterloo Press, 1996.
- Parker, B., J. Cherry, K.J. Goldstein, A.R. Vitolins, D. Navon, G.A. Anderson, J.P. Wood, Matrix influence on contaminant mass distribution in a fractured shale, Abstract IB-34, A.R. Gavashar & A.S.C. Chen, eds., *Remediation of Chlorinated and Recalcitrant Compounds, Proceedings of the Fourth International Conference on Remediation of Chlorinated and Recalcitrant Compounds*, Monterey, CA, Battelle Press, Columbus OH, May 2004.
- Perry, W.J. Sequential deformation in the central Appalachians. *American Journal of Science* 278: 518-542 (1978).
- Ramey Jr., H.J. "A current review of oil recovery by steam injection." In *Proceedings of the Seventh World Petroleum Congress*, 1966.
- Roy, D.C. *Geologic Map of the Caribou and Northern Presque Isle 15' Quadrangles, Maine*, 1987.
- Schmidt, R., J. Gudbjerg, T.O. Sonnenborg, and K.H. Jensen. Removal of NAPLs from the unsaturated zone using steam: Prevention of downward migration by injecting mixtures of steam and air. *Journal of Contaminant Hydrology* 55: 233-260 (2002).
- Schwille, F. *Dense Chlorinated Solvents in Porous and Fractured Media*. Chelsea, M: Lewis Publishers, 1977.
- Shapiro, A.M. Cautions and suggestions for geochemical sampling in fractured rock. *Ground Water Monitoring and Remediation* 22 (3): 151-164 (2002).
- She, H.Y., and B. Sleep. The effect of temperature on capillary pressure-saturation relationships for air-water and perchloroethylene-water systems. *Water Resources Research* 34: 2587-2597 (1998).
- Sleep, B.E., and Y. Ma. Thermal variation of organic fluid properties and impact on thermal remediation feasibility. *Journal of Soil Contamination* 6 (3): 281-306 (1997).

-
- Sleep, B.E., and P.D. McClure. The effect of temperature on adsorption of organic compounds to soils. *Can. Geotech. J.* 38: 46-52 (2001).
- SteamTech Environmental Services. *Steam Stripping and Hydrous Pyrolysis Pilot Project for the Portsmouth Gaseous Diffusion Plant, Portsmouth, Ohio*, DOE/OR/11-3032&D1. Department of Energy, 1999.
- SteamTech Environmental Services. *Pilot Study of Steam Enhanced Remediation for Mitigation of Residual DNAPL in Fractured Rock, Limestone, Maine*, Preliminary Draft Work Plan, 2001; Final Draft Work Plan, 2002.
- SteamTech Environmental Services. *In-Situ Remediation to Remove Non-Aqueous Phase Liquids Located in the Subsurface at the North-East Site Area A, Young-Rainey STAR Center, Largo, Florida*, SM Stoller and Department of Energy, 2003.
- Stephenson, K.M., and K.S. Novakowski. The Analysis of Pulse Interference Tests Conducted in a Fractured Rock Aquifer Bounded by a Constant Free Surface. *Journal of Contaminant Hydrology* (Accepted for publication 2004).
- Stephenson, K.M., K.S. Novakowski, E. Davis, and G. Heron. Hydraulic characterization for steam enhanced remediation conducted in fractured rock. *Journal of Contaminant Hydrology* (Submitted 2003).
- Stewart, L.D., and K.S. Udell. Mechanisms of residual oil displacement by steam injection. *SPE Reservoir Engineering* 1233-1242 (1988).
- Thiem, G. *Hydrologische Methoden*, Gebhardt, Leipzig, 1906.
- Udell, K.S., and L.D. Stewart. *Field Study of In Situ Steam Injection and Vacuum Extraction for Recovery of Volatile Organic Solvents*, UCB-SEEHRL Report No. 89-2. Berkeley, CA: University of California, 1989.
- Udell, K.S., N. Sitar, J.R. Hunt, and L.D. Stewart. *Process for In Situ Decontamination of Subsurface Soil and Groundwater*, United States Patent #5,018,576, 1991.
- Udell, K.S., and L.D. Stewart, Jr. *Combined Steam Injection and Vacuum Extraction for Aquifer Cleanup*, " In *Proceedings of the First International Conference on Subsurface Contamination by Immiscible Fluids*, Rotterdam, Netherlands: Weyer (ed.) Balkema, 327-336, 1992.
- Udell, K.S., and M.T. Itamura. *Pilot Demonstration of Steam Enhanced Extraction to Remediate Soils Containing JP-5 Jet Fuel*, Port Hueneme, CA: NAS Lemoore Final Technical Report, Department of the Navy, 1995.
- Udell, K.S. "Heat and mass transfer in clean-up of underground toxic wastes." In *Annual Reviews of Heat Transfer, Vol. 7*, New York: Chang-Lin Tien, Begell House, Inc., 333-405, 1996.
- Udell, K.S., M. Itamura, and L. Alvarez-Cohen. *NAS Lemoore JP-5 Cleanup Demonstration*. <http://www.abacus.me.berkeley.edu/BERC/projects/Lemoore> 1997
- USACE. *Geophysical Exploration for Engineering and Environmental Investigation*, EM1110-1-1802, 1995.
- U.S. Department of Energy. *Pinellas Environmental Restoration Project. Northeast Site Area A NAPL Remediation*, Grand Junction, CO: Young - Rainey STAR Center. U.S. Department of Energy, 2003.
- U.S. EPA. *Use of Airborne, Surface, and Borehole Geophysical Techniques at Contaminated Sites*, EPA/625/R-92/007. Cincinnati, OH: U.S. Environmental Protection Agency, 1993.
- U.S. EPA. *In Situ Steam Enhanced Recovery Process, Hughes Environmental Systems, Inc., Innovative Technologies Report*, EPA/540/R-94/510. Cincinnati, OH: U.S. Environmental Protection Agency, 1995.
- U.S. EPA. *Record of Decision, Operable Unit 12, Loring Air Force Base, Limestone, Maine*, EPA/ROD/R01-99/118. Cincinnati, OH: U.S. Environmental Protection Agency, 1999.
- U.S. EPA. *Innovations in Site Characterization: Geophysical Investigation at Hazardous Waste Sites*, EPA/542/R-00/003. Cincinnati, OH: U.S. Environmental Protection Agency, 2000.
- U.S. EPA. *Final Quality Assurance Project Plan for the SteamTech Environmental Services Inc. Steam Enhanced Remediation Technology Demonstration at Loring Air Force Base, Maine*, Cincinnati, OH: Including Amendments 1- 4 (March 28, 2002; August 7, 2002; October 2002).
- Volek, C.W., and J.A. Pryor. Steam distillation drive - Brea Field, California. *JPT: Journal of Petroleum Technology* 24: 899-906 (1972).
- Yuan, Z.G., and K.S. Udell. Steam distillation of a single component hydrocarbon liquid in porous media. *International Journal of Heat Transfer* 36 (4): 887-897 (1993).



Please make all necessary changes on the below label, detach or copy, and return to the address in the upper left-hand corner.

If you do not wish to receive these reports CHECK HERE ; detach, or copy this cover, and return to the address in the upper left-hand corner.

PRESORTED STANDARD
POSTAGE & FEES PAID
EPA
PERMIT No. G-35

State of Maine
Department of Environmental Protection
Augusta, Maine 04333

United States
Environmental Protection Agency
National Risk Management
Research Laboratory
Cincinnati, OH 45268

Official Business
Penalty for Private Use
\$300

EPA/540/R-05/010
August 2005



Recycled/Recyclable
Printed with vegetable based ink on paper that contains a minimum of 50% post-consumer fiber content processed chlorine free