








Natural Channel Design Review Checklist



Richard Starr USFWS

2.0 Preliminary Design							
2.1 Goals and Restoration Potential							
Does the project have clear goals?							
Was the restoration potential based on the assessment data provided?							
Was a restoration strategy developed and explained based on the restoration potential?							
2.2 Design Criteria							
Were design criteria provided and explained?							
Is the design criteria representative of reference reaches within the project area or of the same valley type, geology, and land use?							
2.3 Conceptual Design							
Was the conceptual channel alignment provided and developed within the design criteria?							
Were typical bankfull cross sections provided and developed within the design criteria?							
Were typical drawings of in-stream structures provided and their use and location explained?							
Was a draft planting plan provided?							
Overall Conceptual Design Comment(s)							







Need for a Review Checklist

PROBLEMS

- Stream restoration design complexity
- Many different design methodologies
- Inconsistency in design deliverables
- Communication difficulties
- Many failed projects










Need for a Review Checklist

SOLUTION

- Outlined critical design steps established
- Defined design expectations
- Improved communication
- Increased successful projects
- NCD Methodology











Checklist Components

- Watershed and Geomorphic Assessment
 - Watershed assessment
 - Basemapping
 - Geomorphic assessment
 - Bankfull verification
- Preliminary Design
 - Goals and restoration potential
 - Design criteria
 - Conceptual design

- Final Design
 - Natural channel design
 - Sediment transport
 - In-stream structures
 - Vegetation design
- Maintenance and Monitoring Plans
- Overall Design Review
- Site Visit










What is Not in the Checklist

- Additional design deliverables
- Permitting
- Erosion and sediment plans
- Flood studies
- Biological and physiochemical processes
- Construction methods
- Not a "how to" design document
- Not a text book














Was the watershed assessment methodology described?















Was the project drainage area provided?














Was the percent impervious cover for the watershed provided?












Was the current land use described along with future conditions?












Were watershed hydrology calculations performed?













Base Mapping

Does the project include base mapping?














Was the geomorphic assessment

methodology described?













Were vertical and lateral stability analyses completed?















Was it shown whether the instability was localized or system-wide?














Was the cause and effect relationship of the instability identified?













Was the channel evolution predicted?













Were constraints that would inhibit

restoration identified?












Hydraulic Assessment











Hydraulic Assessment

Was stream velocity, shear stress, and stream power shown in relation to stage and discharge?















Bankfull Verification

- Was bankfull verification analysis completed?
- Were USGS gauges or regional curves used to validate bankfull discharge?












Bankfull Verification


If gauges or regional curves were not available, were other methods, such as hydrology and hydraulic models used?



















Goals and Restoration Potential

- Does the project have clear goals?
- Was the restoration potential based on the assessment data provided?
- Was a restoration strategy developed and explained based on the restoration potential?










Design Criteria

Were design criteria provided and explained?











Design Criteria

Is the design criteria representative of reference reaches within the project area or of the same valley type, geology, and land use?

	Common					
	R	Reference Reach Ratios				
Parameter	MIN	MAX	MIN	MAX		
Stream Type (Rosgen)	C/E 4		B4			
Bankfull Mean Velocity, Vbkf (ft/s)	3.5	5.0	4.0	6.0		
Width to Depth Ratio, W/D (ft/ft)	5.0	12.0	12.0	18.0		
Riffle Max Depth Ratio, Dmax/Dbkf	1.2	1.4	1.2	1.4		
Bank Height Ratio, Dtob/Dmax (ft/ft)	1.0	1.1	1.0	1.1		
Meander Length Ratio, Lm/Wbkf	7.0	12.0	N/a	N/a		
Rc Ratio, Rc/Wbkf	1.2	2.0	N/a	N/a		
Meander Width Ratio, Wblt/Wbkf	2.0	8.0	N/a	N/a		
Sinuosity, K	1.20	1.60	1.1	1.2		
Valley Slope, Sval (ft/ft)	0.0050	0.0150	0.020	0.030		
Riffle Slope Ratio, Srif/Schan	1.5	2.0	1.1	2.5		
Run Slope Ratio, Srun/Srif	0.50	0.80	N/a	N/a		
Glide Slope Ratio, Sglide/Schan	0.30	0.50	0.3	0.5		
Pool Slope Ratio, Spool/Schan	0.00	0.20	0.0	0.4		
Pool Max Depth Ratio, Dmaxpool/Dbkf	2.0	3.5	2.0	3.5		
Pool Width Ratio, Wpool/Wbkf	0.8	1.2	1.1	1.5		
Pool-Pool Spacing Ratio, Lps/Wbkf	2.5	7.0	1.5	5.0		










Was the concept channel alignment provided and developed within the design criteria?












Were typical bankfull cross sections provided and developed within the design criteria?












Were typical drawings of in-stream structures provided and their use and location explained?











Was a draft planting plan provided?










Was a proposed channel alignment provided and developed within the design criteria?












Were proposed channel dimensions provided and developed within the design criteria?












Do the proposed channel dimensions show the adjacent floodplain or flood prone area?












Was a proposed channel profile provided and developed within the design criteria.











Sediment Transport

- Was sediment transport analysis required? If required, was the type of sediment transport analysis explained?
- Were existing versus design relationships of shear stress, velocity, and stream power versus stage or discharge provided?
- Did sediment transport capacity analyses show that the stream bed would not aggrade or degrade over time?










Sediment Transport

Did sediment transport competency analysis show what particle sizes would be transported with a bankfull discharge?












Sediment Transport

For gravel/cobble bed streams, does the proposed design move particles that are larger than the D100 of the stream bed?












Were in-stream structures required?














If required, was the reason for their location and use explained?










Was the relationship between the type of in-stream structure used and its role in providing stability explained?












Were detail drawings provided for each in-stream structure?











Natural Channel Design

Were specifications provided and explained for instream structures and erosion control measures?

Section 5: Erosion and Sediment Control

A. DESCRIPTION

- Erosion and Sediment Control shall be performed in accordance with the 2003
 District of Columbia Standards and Specifications for Soil Erosion and Sediment
 Control, as published by Department of Health, Environmental Health Administration,
 Bureau of Environmental Quality, Watershed Protection Division.
- Erosion and Sediment Control will consist of the installation, maintenance, and removal of all sediment control devices shown in the Construction Specifications and Plans, excluding the temporary stream diversion, and additional Erosion and Sediment Control measures required by the Project Inspector or the District Sediment Control Inspector.
- 3. The Contractor shall inspect and maintain (repair) all erosion and sediment controls daily to ensure that the controls are functioning properly.
- 4. All of the work shall be performed as indicated in the Construction Plans and Specifications, or as specified by the Project Inspector. Construction shall not begin until all Erosion and Sediment Control facilities have been installed and approved by the Project Inspector.
- The Contractor shall stay within the limits of disturbance (LOD) shown on the Construction Plans, and minimize disturbance within the working area wherever possible
- 6. It is the responsibility of the Contractor to prevent any mud and surface debris accumulation beyond the limit of disturbance, and is responsible for daily clean up.
- All perimeter controls and erosion and sediment control structures and devices shall be maintained throughout the life of the project, conforming to the detailed sequence of construction, or as directed by the Project Inspector or the District Sediment Control Inspector.
- 8. Load Protection Mats are not included in this item.

B. MATERIALS

 Temporary seeding shall conform to the requirements given for "Temporary Seeding" (Section 23).

C. MEASUREMENT AND PAYMENT

- 1. This item will not be measured but will be paid for at the Contract lump sum price for Erosion and Sediment Control per each Project Area. The lump sum price shall be full compensation for the installation, maintenance, and removal of all sediment control devices as indicated in the Construction Specifications and Plans, or as required by the Project Inspector or the District Sediment Control Inspector, excluding the "Temporary Stream Diversion" (Section 7). All labor, tools, equipment, and incidentals including temporary seeding necessary to complete the work are included in the lump sum price per each Project Area.
- 2. A Contingency item for Silt Fence is included on the bid itemization. Silt Fence shown on the Construction Plans shall be included in the lump sum price for Erosion










Vegetation Design

- Was a vegetation design provided?
- Does the design address the use of permanent vegetation for long term stability?


























Maintenance Plan

Was a maintenance plan provided?







Maintenance Plan

Does it clearly state when maintenance will be required and if so, is it quantifiable?













Maintenance Plan

Does it clearly state how erosion will be addressed and by whom?













Monitoring Plan

- Was a monitoring plan provided?
- Does it have measurable, quantifiable performance standards?
- Does it have clearly defined thresholds of success and failure?







Monitoring Plan

Is monitoring required for at least 3 years?

Does it state who is required to conduct the

monitoring?













Overall Design Review

- Does the design address the project objectives?
- Is there any component of the design that adversely affects the success of the project?





















Geomorphic Assessment

Was the geomorphic assessment methodology described?

Stream:	HICKEY RU	HICKEY RUN		Obse	Observer(s): RRS, KDI			KR Q/	VQC:	SD T	otal Score:	41.94					
Reach:	HR - 3	HR - 3			Comments: GPS Coordi							Very H	Very High				
Location:	XS - 6	XS - 6 3/17/2003				LM:38° 91' 29 8" /	9.8" / 76° 96' 56.3" +/-14'			N	iotes:	Left Ba	Left Bank - Took BF from cross-section, side of rod				
Date:						RM:38° 91' 27.8" /						flush wi	flush with rebar cap closest to bank				
		Fre	dibility Vari	ables							Rank	Erosion Pot	ential				
Rank Height / F	Bankfull Height									,	•	•		,			
Bank Height					sion Potental Notes						Very Low	Low	Moderate	High V	Very High	Extrem	
5.82	0.53	10.98	10.00	Extreme				Bank Heis	-1-4/	Value	1.00-1.10	1.11-1.19	1.20-1.50	1.60-2.00	2.10-2.80	>2.80	
				LATTERIC			æ	Bankfull H		Index	1.0-1.9	2.0-3.9	4.0-5.9	6.0-7.9	8.0-9.0	10	
Root Depth / Bank Height Ratio Root Depth Bank Height Value Index Bank I				Bank Erosion Po	tental	Notes	ž			Value	1.00-0.90	0.89-0.50	0.49-0.30	0.29-0.15	0.14-0.05	<0.05	
1.00	5.82	0.17	7.60	High		Notes	1	Root Depth / Bank Height		Index	1.0-1.9	2.0-3.9	4.0-5.9	6.0-7.9	8.0-9.0	10	
		0.17	7.00 Hi		igh		3			Value	100-80	79-55	54-30	29-15	14-5	<5	
Weighted Root Density							Ιã				1.0-1.9	2.0-3.9	4.0-5.9	6.0-7.9	8.0-9.0	10	
Root Density (9	Root Depth /	Value	Index	Bank Erosion Po	tental	Notes	뼺	Density	Density								
	Bank Height						£	Bank Angle		Value	0-20	21-60	61-80	81-90	91-119	>119	
75.00	0.17	12.89	8.12	Very High							1.0-1.9	2.0-3.9	4.0-5.9	6.0-7.9	8.0-9.0	10	
Bank Angle								Surface Prot	e Protection	Value	100-80	79-55	54-30	29-15	14-10	<10	
Bank Angle (°))		Index	Bank Erosion Po	tental	Notes		Surface 1100	ction	Index	1.0-1.9	2.0-3.9	4.0-5.9	6.0-7.9	8.0-9.0	10	
82.00			6.21	High								Adjustment					
urface Protect	ion							Bedrock	k	Bedrock I	oanks have a v	ery low erosi	on potential				
Surface Protection				index Bank Erosion Poter		Notes		Boulder	Boulders Boulder banks have a low crosion potential.								
(%)	(%)		Index	Bank Erosion Po	ion Potental	Notes	-	Cobble		Substract 10 points. No adjustment if sand/gravel compose greater than 50% of bar							
5.00				00 Extreme				Sand/Silt/Clay Loam Add 5 points.									
Adjustment					Notes	Gravel Add 5-10 points depending on percentage of bank material compose						omposed of s	and.				
Bank Materials 0.00							ž	Sand Add 10 points.									
Adjustment						Notes	ă	Silt / Clay No adjustment.									
Bank Stratification 0.00							Stratification										
		TALSCORE	41.94					Ad	45-10 p	oints deper	rding on positi			elation to be	nkfull stage.		
							_			-							
	Bank Profile										1 2 3	Section 2	CONTRACT OF THE PARTY OF THE PA	URCON'S B	I. Validation	D. FEED VA	
Horizontal Vertical					Bank Profile					100	A STORY OF	Mark Company		1000	A-1818	1013	
Distance Height Not		Notes	1 1			Dank Frome				1	THE LIBER	1000	STATE OF	100000		1000	
	(1.13)	SLBRK					_		6.00		Service Service	272753	200		1		
			_		_			.	5.50		Santa Park	Winter S	100	THE REAL	10	E Editor	
(2.40)		SL BRK			•			L		100	1000 At A	Sec.	5 300		Section 1	5 1 5 Day	
(1.48)	(0.68)														Total Control of the	6.000	
(1.48) 1.20	(0.51)	GTPIN			1			L	5.00				1000				
(1.48) 1.20 1.20	(0.51)	TTPIN	∃		1			E	4.50	1	是7年		M			2	
(1.48) 1.20 1.20 1.20	(0.51) 0.00 (0.51)	TTPIN GTPIN			1			Ė	4.50 4.00		属 化		M		11	1	
(1.48) 1.20 1.20 1.20 1.20 2.35	(0.51) 0.00 (0.51) 1.00	G TPIN SL BRK			1				4.50 4.00 3.50				M	3	1	3	
(1.48) 1.20 1.20 1.20 1.20 2.35 2.76	(0.51) 0.00 (0.51) 1.00 1.50	TTPIN GTPIN SLBRK SLBRK							4.50 4.00 3.50 3.00					3			
(1.48) 1.20 1.20 1.20 1.70 2.35	(0.51) 0.00 (0.51) 1.00	G TPIN SL BRK							4.50 4.00 3.50 3.00 2.50	S	100					1	
(1.48) 1.20 1.20 1.20 1.20 2.35 2.76	(0.51) 0.00 (0.51) 1.00 1.50	TTPIN GTPIN SLBRK SLBRK						-	4.50 4.00 3.50 3.00 2.50 2.00	1	70					1	
(1.48) 1.20 1.20 1.20 1.20 2.35 2.76 2.91	(0.51) 0.00 (0.51) 1.00 1.50 2.00	TTPIN GTPIN SL BRK SL BRK SL BRK						-	4.50 4.00 3.50 3.00 2.50 2.00 1.50	1							
(1.48) 1.20 1.20 1.20 1.20 2.35 2.76 2.91 3.25	(0.51) 0.00 (0.51) 1.00 1.50 2.00 2.50	GTPIN GTPIN SL BRK SL BRK SL BRK SL BRK				\			4.50 4.00 3.50 3.00 2.50 2.00 1.50 1.00		小				T.	No. of	
(1.48) 1.20 1.20 1.20 1.20 2.35 2.76 2.91 3.25 3.80 3.96	(0.51) 0.00 (0.51) 1.00 1.50 2.00 2.50 3.20 4.10	TTPIN GTPIN SL BRK			/	/			4.50 4.00 3.50 3.00 2.50 2.00 1.50 1.00 0.50								
(1.48) 1.20 1.20 1.20 1.20 2.35 2.76 2.91 3.25 3.80	(0.51) 0.00 (0.51) 1.00 1.50 2.00 2.50 3.20 4.10	GTPIN SL BRK SL BRK SL BRK SL BRK SL BRK SL BRK SL BRK	T			<u></u>			4.50 4.00 3.50 3.00 2.50 2.00 1.50 1.00							1000	



