Reconciling region-, facility-, & component-level emissions data


David Lyon
Daniel Zavala-Araiza
Ramon Alvarez
Steven Hamburg

Do not cite or reproduce without permission from EDF.



Barnett Shale October 16 – 30, 2013








Figure 1. Multi-scale measurements used to characterize methane emissions from oil and gas sources in the Barnett Shale.

Harriss et al.


Different measurement scales

- Region-level
 - aircraft mass balance, tower & satellite inversion modeling
- Facility-level
 - tracer flux, near-field dispersion modeling & mass balance
- Component-level
 - direct flow measurements, bagging, metering



Regional mass balance


76 ± 13 total and 60 ± 11 fossil metric tons CH₄ hr⁻¹ ≈ 1.3 – 1.9% loss rate (Karion et al., Smith et al.)




Facility-level emissions inventory

72 (+10/-9) total & 46(+8/-6) O&G metric tons CH₄ hr⁻¹ ≈ 1.0 – 1.4% loss rate (Lyon et al.)

Barnett Well Pad Emission Rate Distribution




Total Methane Emissions



Methane Emissions (kg/h)



Barnett O&G CH₄ Emission Estimates




Karion et al. estimate is average of flight envelopes. Other estimates are for 25 county region.

Do not cite or reproduce.

Barnett production segment component-level inventory

- Regional activity factors
 - Drillinginfo
 - TX Railroad Commission
 - GHGRP
- Regional & national emission factors
 - GHG Inventory
 - UT production studies
 - Environ/CenSARA O&G inventory
 - HARC/TCEQ tank reports
 - AP-42 engine exhaust

Barnett Production CH₄ Emission Estimates



Do not cite or reproduce.

Insights from multi-scale comparison

- Region- and facility-level based estimates of Barnett O&G methane emissions are similar.
- Regional variation in activity factors result in different component-level estimates than prorated national GHGI.
- Some source estimates improved with updated EFs.
- Current best estimates component-level emissions are lower than facility-level estimate but with overlapping uncertainty.
- "Super-emitter" sources may explain the difference.
 - e.g., stuck dump valves, blowdowns, tank control malfunctions