

RCRA Revision Checklist 101

---

ENVIRONMENTAL PROTECTION AGENCY

[FRL 4103-4]

40 CFR Parts 264 and 265

Wood Preserving; Standards and Interim Status Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities

AGENCY: Environmental Protection Agency.

ACTION: Administrative stay.

---

SUMMARY: The Environmental Protection Agency is today announcing an administrative stay of the requirements for drip pad coatings, sealers, or covers for existing drip pads at wood preserving plants. The effect of the stay is to extend the effective date of coating, sealer, or cover requirements for existing drip pads until October 30, 1992.

EFFECTIVE DATE: February 6, 1992.

ADDRESSES: The official record for this administrative stay is identified as Docket Number F-92-DPAS-FFFFF and is located in the EPA RCRA Docket, room M2427, 401 M Street, SW., Washington, DC 20460. The public must make an appointment in order to review docket materials by calling (202) 260-9327. The docket is available for inspection from 9 a.m. to 4 p.m., Monday through Friday, excluding Federal holidays. The public may copy material from any regulatory docket at a cost of \$0.15 per page.

FOR FURTHER INFORMATION CONTACT: For general information contact the RCRA Hotline, toll free at (800) 424-9346, or at (202) 382-3000. For technical information concerning this notice, contact David J. Carver, Office of Solid Waste (OS-333), U.S. Environmental Protection Agency, 401 M Street, SW., Washington, DC 20460, (202) 260-6775.

> > > > Preamble has not been included in this file. < < < <

PART 264-STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE TREATMENT, STORAGE, AND DISPOSAL FACILITIES

1. The authority citation for part 264 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6924, and 6925.

2. Section 264.573 is amended by revising paragraph (a)(4) to read as follows:

§ 264.573 Design and operating requirements.

(a) \* \* \*

(4) Be impermeable, e.g., concrete pads must be sealed, coated, or covered with an impermeable material such that the entire surface where drippage occurs or may run across is capable of containing such drippage and mixtures of drippage and precipitation, materials, or other wastes while being routed to an associated collection system.

Note: The requirement that existing drip pads be impermeable, e.g., that drip pads be sealed, coated, or covered, with an impermeable material is administratively stayed. The stay will remain in effect until October 30, 1992.

\* \* \* \* \*

PART 265-INTERIM STATUS STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE TREATMENT, STORAGE, AND DISPOSAL FACILITIES

3. The authority citation for part 265 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6924, 6925 and 6935.

4. Section 265.443 is amended by revising paragraph (a)(4) to read as follows:

§ 265.443 Design and operating requirements.

(a) \* \* \*

(4) Be impermeable, e.g., concrete pads must be sealed, coated, or covered with an impermeable material such that the entire surface where drippage occurs or may run across is capable of containing such drippage and mixtures of drippage and precipitation, materials, or other wastes while being routed to an associated collection system.

Note: The requirement that existing drip pads be impermeable, e.g., that drip pads be sealed, coated, or covered

with an impermeable material is administratively stayed. The stay will remain in effect until October 30, 1992.

Note: The requirement that new drip pads be impermeable, e.g., that new drip pads be sealed, coated, or covered with an impermeable material is administratively stayed. The stay will remain in effect until further administrative action is taken.

\* \* \* \* \*

[FR Doc. 92-3504 Filed 2-14-92; 8:45 am]

BILLING CODE 6560-50-M

---

End of Federal Register article

---