FRSPRD_D2.FRS_PROGRAM_TRIBE

U	*	PGM_SYS_ID	VARCHAR2 (30 BYTE)
U	*	PGM_SYS_ACRNM	VARCHAR2 (20 BYTE)
	*	EPA_ID	NUMBER (9)
U		BIA_CODE	NVARCHAR2 (5)
U	*	TRIBE_NAME	NVARCHAR2 (350)
	*	SOURCE_OF_DATA	VARCHAR2 (25 BYTE)
		LAST_REPORTED_DATE	DATE
		SENSITIVE_IND	CHAR (1 BYTE)
	*	PUBLIC_IND	CHAR (1 BYTE)
	*	CREATE_DATE	DATE
		UPDATE_DATE	DATE
	*	USER_ID	VARCHAR2 (160 BYTE)
		START_DATE	DATE
		END_DATE	DATE
		REFRESH_DATE	DATE
	*	CREATE_SOURCE_OF_DATA	VARCHAR2 (25 BYTE)
		UPDATE_SOURCE_OF_DATA	VARCHAR2 (25 BYTE)
		REFRESH_SOURCE_OF_DATA	VARCHAR2 (25 BYTE)
F	*	FRS_PROGRAM_FACILITY_PGM_SYS_ID	VARCHAR2 (30 BYTE)
F	*	FRS_PROGRAM_FACILITY_PGM_SYS_ACRNM	VARCHAR2 (20 BYTE)

- FPT_TRIBE_UN (PGM_SYS_ID, PGM_SYS_ACRNM, BIA_CODE, TRIBE_NAME)
- FPT_EPA_ID_FK (EPA_ID)
- FRS_PROGRAM_TRIBE_FRS_PROGRAM_FACILITY_FK (FRS_PROGRAM_FACILITY_I
- FPT_TRIBE_UN (PGM_SYS_ID, PGM_SYS_ACRNM, BIA_CODE, TRIBE_NAME)

FRSPRD_D2.FRS_PROGRAM_SUPP_INTEREST

P	*	SUP_INTEREST_ID	NUMBER
UF	*	PGM_SYS_ACRNM	VARCHAR2 (20 BYTE)
UF	*	PGM_SYS_ID	VARCHAR2 (30 BYTE)
U		SUP_PGM_SYS_ACRNM	VARCHAR2 (20 BYTE)
U		SUP_PGM_SYS_ID	VARCHAR2 (30 BYTE)
U		SUP_INTEREST_TYPE	VARCHAR2 (60 BYTE)
		START_DATE	DATE
		START_DATE_QUALIFIER	VARCHAR2 (50 BYTE)
		END_DATE	DATE
		END_DATE_QUALIFIER	VARCHAR2 (50 BYTE)
	*	SOURCE_OF_DATA	VARCHAR2 (25 BYTE)
		LAST_REPORTED_DATE	DATE
U		REPORTED_SUP_INTEREST_TYPE	VARCHAR2 (60 BYTE)
	*	CREATE_DATE	DATE
		UPDATE_DATE	DATE
	*	USER_ID	VARCHAR2 (160 BYTE)
		SENSITIVE_IND	CHAR (1 BYTE)
		PUBLIC_IND	CHAR (1 BYTE)
		REFRESH_DATE	DATE
		INTEREST_TYPE	VARCHAR2 (400 BYTE)

- FPSI_PK (SUP_INTEREST_ID)
- FPSI_UK (SUP_PGM_SYS_ID, SUP_PGM_SYS_ACRNM, SUP_INTEREST_TYPE, PGM_SYS_ACRNM, PGM_SYS_ID, REPORTED_SUP_INTEREST_TYPE)
- FRS_PROG_SUPP_INT_ACRNMID_FK (PGM_SYS_ID, PGM_SYS_ACRNM)
- FPSI_IDX (PGM_SYS_ID, PGM_SYS_ACRNM, NVL("SUP_PGM_SYS_ID",'X'), NVL("SUP_PGM_SYS_ACRNM",'x'), NVL("SUP_INTEREST_TYPE",'x'), NVL("REPORTED_SUP_INTEREST_TYPE",'x'))
- FPSI_PK (SUP_INTEREST_ID)
- FPSI_UK (SUP_PGM_SYS_ID, SUP_PGM_SYS_ACRNM, SUP_INTEREST_TYPE, PGM_SYS_ACRNM, PGM_SYS_ID, REPORTED_SUP_INTEREST_TYPE)

FRSPRD_D2.FRS_PROGRAM_MAILING_ADDRESS

PF	*	PGM_SYS_ID	VARCHAR2 (30 BYTE)
PF	*	PGM_SYS_ACRNM	VARCHAR2 (20 BYTE)
P	*	AFFILIATION_TYPE	VARCHAR2 (40 BYTE)
		MAILING_ADDRESS	VARCHAR2 (100 BYTE)
		STD_MAIL_ADDRESS	VARCHAR2 (150 BYTE)
		SUPPLEMENTAL_ADDRESS	VARCHAR2 (100 BYTE)
		STD_SUPPLEMENTAL_ADDRESS	VARCHAR2 (150 BYTE)
		CITY_NAME	VARCHAR2 (30 BYTE)
		STD_CITY_NAME	VARCHAR2 (60 BYTE)
		STATE_CODE	VARCHAR2 (5 BYTE)
		STATE_NAME	VARCHAR2 (35 BYTE)
		POSTAL_CODE	VARCHAR2 (14 BYTE)
		COUNTRY_NAME	VARCHAR2 (44 BYTE)
	*	SOURCE_OF_DATA	VARCHAR2 (25 BYTE)
		LAST_REPORTED_DATE	DATE
		SENSITIVE_IND	CHAR (1 BYTE)
	*	PUBLIC_IND	CHAR (1 BYTE)
		USER_ID	VARCHAR2 (160 BYTE)
P	*	ADDRESS_ID	VARCHAR2 (12 BYTE)
		REFRESH_DATE	DATE
		GEO_DERIVED_LOC_ADDRESS	VARCHAR2 (250 BYTE)
		GEO_DERIVED_HOUSE_NUMBER	VARCHAR2 (20 BYTE)
		GEO_DERIVED_STREET_NAME	VARCHAR2 (80 BYTE)
		GEO_DERIVED_BASE_NAME	VARCHAR2 (64 BYTE)
		GEO_DERIVED_PREFIX	VARCHAR2 (32 BYTE)
		GEO_DERIVED_SUFFIX	VARCHAR2 (32 BYTE)
		GEO_DERIVED_STYPE_BEFORE	VARCHAR2 (32 BYTE)
		GEO_DERIVED_AFTER	VARCHAR2 (32 BYTE)
		GEO_DERIVED_POSTAL_CODE	VARCHAR2 (16 BYTE)
		GEO_DERIVED_STATE_CODE	VARCHAR2 (5 BYTE)
		GEO_DERIVED_CITY_NAME	VARCHAR2 (100 BYTE)
		GEO_DERIVED_COUNTY_NAME	VARCHAR2 (100 BYTE)
		GEO_DERIVED_COUNTY_FIPS	VARCHAR2 (5 BYTE)
		GEO_DERIVED_COUNTRY	VARCHAR2 (100 BYTE)
		GEO_DERIVED_FULL_ADDRESS	VARCHAR2 (1000 BYTE)
		GEO_DERIVED_ADDR_TYPE	VARCHAR2 (50 BYTE)
		GEO_DERIVED_QA_HOUSE_NUMBER	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_STREET_NAME	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_PREFIX	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_SUFFIX	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_STYPE	VARCHAR2 (200 BYTE)
		GEO_DERIVED_QA_CITY	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_POSTAL_CODE	VARCHAR2 (100 BYTE)
		GEO_DERIVED_MULTI_ADDRESS_FLAG	VARCHAR2 (1 BYTE)
		GEO_DERIVED_PLACENAME	VARCHAR2 (200 BYTE)
		GEO_DERIVED_GEOCODER_MESSAGE	VARCHAR2 (1000 BYTE)
		STD_PARSED_STREET_NAME	VARCHAR2 (240 BYTE)
		STD_PARSED_STREET_NUMBER	VARCHAR2 (15 BYTE)
		STD_PARSED_PRE_DIR_CODE	VARCHAR2 (6 BYTE)
		STD_PARSED_STREET_SUFFIX	VARCHAR2 (12 BYTE)
		STD_PARSED_POST_DIR_CODE	VARCHAR2 (6 BYTE)
		STD_ADDR_TYPE	VARCHAR2 (50 BYTE)
		STD_POSTAL_CODE	VARCHAR2 (16 BYTE)
		STD_STATE_CODE	VARCHAR2 (5 BYTE)
		STD_COUNTY_NAME	VARCHAR2 (35 BYTE)
		STD_COUNTRY	VARCHAR2 (100 BYTE)
		STD_FULL_ADDRESS	VARCHAR2 (1000 BYTE)
	*	CREATE_DATE	DATE
		UPDATE_DATE	DATE
		START_DATE	DATE
		END_DATE	DATE
		COUNTRY_FIPS_CODE	VARCHAR2 (2 BYTE)
		COUNTY_NAME	VARCHAR2 (35 BYTE)
		DATA_QUALITY_CODE	VARCHAR2 (20 BYTE)
		STD_STATE_NAME	VARCHAR2 (35 BYTE)
		COUNTRY_ISO_3166_1_ALPHA_2	VARCHAR2 (2 CHAR)
		COUNTY_FIPS_CODE	VARCHAR2 (5 BYTE)

- FRS_PROG_MAIL_ADDR_PK (PGM_SYS_ID, PGM_SYS_ACRNM, AFFILIATION_TYPE, ADDRESS_ID)
- FPMA_ADDRESS_FK (ADDRESS_ID)
- FRS_PROG_MAIL_ADDR_ACRNMID_FK (PGM_SYS_ID, PGM_SYS_ACRNM)
- FRS_PGM_MAILING_ADDRESS_IDX3 (ADDRESS_ID)
- FPMA_IDX (PGM_SYS_ID, PGM_SYS_ACRNM, AFFILIATION_TYPE)
- FPM_IDX (NVL("PUBLIC_IND",'x'))
- FPM_IDX2 (AFFILIATION_TYPE)
- FRS_PGM_MAILING_ADDRESS_IDX1 (PGM_SYS_ID, PGM_SYS_ACRNM, NVL("STD_MAIL_ADDRESS",'x'), NVL("STD_SUPPLEMENTAL_ADDRESS",'x'))
- FRS_PGM_MAILING_ADDRESS_IDX2 (PGM_SYS_ID, PGM_SYS_ACRNM)
- FRS_PGM_MAILING_ADDRESS_IDX4 (PGM_SYS_ACRNM, PGM_SYS_ID, NVL("STD_SUPPLEMENTAL_ADDRESS",'!@#'), AFFILIATION_TYPE, NVL("MAILING_ADDRESS",'!@#'), NVL("STATE_CODE",'!@#'), NVL("STATE_NAME",'!@#'), NVL("POSTAL_CODE",'!@#'), NVL("STD_CITY_NAME",'!@#'))
- FRS_PGM_MAILING_ADDRESS_IDX5 (PGM_SYS_ACRNM, PGM_SYS_ID, NVL("STD_MAIL_ADDRESS",'x'), NVL("MAILING_ADDRESS",'x'), NVL("STD_SUPPLEMENTAL_ADDRESS",'x'), NVL("STD_STATE_CODE",'x'), NVL("STD_STATE_NAME",'x'), NVL("POSTAL_CODE",'x'), NVL("STD_CITY_NAME",'x'))
- FRS_PROG_MAIL_ADDR_PK (PGM_SYS_ID, PGM_SYS_ACRNM, AFFILIATION_TYPE, ADDRESS_ID)

FRSPRD_D2.FRS_PROGRAM_SIC

UF	*	PGM_SYS_ID	VARCHAR2 (30 BYTE)
UF	*	PGM_SYS_ACRNM	VARCHAR2 (20 BYTE)
U		PGM_SUB_SYS_ID	VARCHAR2 (20 BYTE)
U	*	REGISTRY_TYPE	VARCHAR2 (40 BYTE)
U	*	SIC_CODE	VARCHAR2 (4 BYTE)
	*	PRIMARY_INDICATOR	VARCHAR2 (10 BYTE)
	*	SOURCE_OF_DATA	VARCHAR2 (25 BYTE)
		LAST_REPORTED_DATE	DATE
		SENSITIVE_IND	CHAR (1 BYTE)
	*	PUBLIC_IND	CHAR (1 BYTE)
		USER_ID	VARCHAR2 (160 BYTE)
		CREATE_DATE	DATE
		UPDATE_DATE	DATE
		START_DATE	DATE
		END_DATE	DATE

- FRS_PROGRAM_SIC_UK (SIC_CODE, PGM_SYS_ID, PGM_SYS_ACRNM, PGM_SUB_SYS_ID, REGISTRY_TYPE)
- FRS_PROG_SIC_ACRNMID_FK (PGM_SYS_ID, PGM_SYS_ACRNM)
- FRS_PROGRAM_SIC_UK (SIC_CODE, PGM_SYS_ID, PGM_SYS_ACRNM, PGM_SUB_SYS_ID, REGISTRY_TYPE)

FRSPRD_D2.FRS_PROGRAM_FACILITY

P	*	PGM_SYS_ACRNM	VARCHAR2 (20 BYTE)
P	*	PGM_SYS_ID	VARCHAR2 (30 BYTE)
	*	REGISTRY_ID	VARCHAR2 (12 BYTE)
		PRIMARY_NAME	VARCHAR2 (150 BYTE)
		LOCATION_ADDRESS	VARCHAR2 (100 BYTE)
		SUPPLEMENTAL_LOCATION	VARCHAR2 (100 BYTE)
		CITY_NAME	VARCHAR2 (60 BYTE)
		COUNTY_NAME	VARCHAR2 (35 BYTE)
		FIPS_CODE	VARCHAR2 (5 BYTE)
		STATE_CODE	VARCHAR2 (5 BYTE)
		STATE_NAME	VARCHAR2 (35 BYTE)
		COUNTRY_NAME	VARCHAR2 (44 BYTE)
		POSTAL_CODE	VARCHAR2 (14 BYTE)
		FEDERAL_FACILITY_CODE	CHAR (1 BYTE)
		FEDERAL_AGENCY_CODE	VARCHAR2 (5 BYTE)
		TRIBAL_LAND_CODE	CHAR (1 BYTE)
		LEGISLATIVE_DIST_NUM	VARCHAR2 (2 BYTE)
		HUC_CODE_8	VARCHAR2 (8 BYTE)
		HUC_CODE_12	VARCHAR2 (12 BYTE)
		EPA_REGION_CODE	VARCHAR2 (2 BYTE)
		FACILITY_TYPE_NAME	VARCHAR2 (40 BYTE)
		DATA_QUALITY_CODE	VARCHAR2 (20 BYTE)
		GEO_DERIVED_LOC_ADDRESS	VARCHAR2 (250 BYTE)
		GEO_DERIVED_HOUSE_NUMBER	VARCHAR2 (20 BYTE)
		GEO_DERIVED_STREET_NAME	VARCHAR2 (80 BYTE)
		GEO_DERIVED_BASE_NAME	VARCHAR2 (64 BYTE)
		GEO_DERIVED_PREFIX	VARCHAR2 (32 BYTE)
		GEO_DERIVED_SUFFIX	VARCHAR2 (32 BYTE)
		GEO_DERIVED_STYPE_BEFORE	VARCHAR2 (32 BYTE)
		GEO_DERIVED_AFTER	VARCHAR2 (32 BYTE)
		GEO_DERIVED_POSTAL_CODE	VARCHAR2 (16 BYTE)
		GEO_DERIVED_STATE_CODE	VARCHAR2 (5 BYTE)
		GEO_DERIVED_CITY_NAME	VARCHAR2 (100 BYTE)
		GEO_DERIVED_COUNTY_NAME	VARCHAR2 (100 BYTE)
		GEO_DERIVED_COUNTY_FIPS	VARCHAR2 (5 BYTE)
		GEO_DERIVED_COUNTRY	VARCHAR2 (100 BYTE)
		GEO_DERIVED_FULL_ADDRESS	VARCHAR2 (1000 BYTE)
		GEO_DERIVED_ADDR_TYPE	VARCHAR2 (50 BYTE)
		GEO_DERIVED_QA_HOUSE_NUMBER	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_STREET_NAME	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_PREFIX	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_SUFFIX	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_STYPE	VARCHAR2 (200 BYTE)
		GEO_DERIVED_QA_CITY	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_POSTAL_CODE	VARCHAR2 (100 BYTE)
		GEO_DERIVED_MULTI_ADDRESS_FLAG	VARCHAR2 (1 BYTE)
		GEO_DERIVED_PLACENAME	VARCHAR2 (200 BYTE)
		GEO_DERIVED_GEOCODER_MESSAGE	VARCHAR2 (1000 BYTE)
		STD_NAME	VARCHAR2 (150 CHAR)
		STD_LOC_ADDRESS	VARCHAR2 (150 BYTE)
		STD_PARSED_STREET_NAME	VARCHAR2 (240 BYTE)
		STD_PARSED_STREET_NUMBER	VARCHAR2 (15 BYTE)
		STD_PARSED_PRE_DIR_CODE	VARCHAR2 (6 BYTE)
		STD_PARSED_STREET_SUFFIX	VARCHAR2 (12 BYTE)
		STD_PARSED_POST_DIR_CODE	VARCHAR2 (6 BYTE)
		STD_ADDR_TYPE	VARCHAR2 (50 BYTE)
		STD_POSTAL_CODE	VARCHAR2 (16 BYTE)
		STD_STATE_CODE	VARCHAR2 (5 BYTE)
		STD_CITY_NAME	VARCHAR2 (60 BYTE)
		STD_COUNTY_NAME	VARCHAR2 (35 BYTE)
		STD_COUNTRY	VARCHAR2 (100 BYTE)
		STD_FULL_ADDRESS	VARCHAR2 (1000 BYTE)
		LINK_MTHD	VARCHAR2 (20 BYTE)
		LOCATION_DESCRIPTION	VARCHAR2 (256 BYTE)
		SENSITIVE_IND	CHAR (1 BYTE)
		USER_COMMENT	VARCHAR2 (240 BYTE)
	*	PUBLIC_IND	CHAR (1 BYTE)
		REFRESH_DATE	DATE
		SMALL_BUS_IND	CHAR (1 BYTE)
		ENV_JUSTICE_CODE	VARCHAR2 (3 BYTE)
		STAND_ALONE_FLAG	VARCHAR2 (1 BYTE)
	*	SOURCE_OF_DATA	VARCHAR2 (25 BYTE)
		LAST_REPORTED_DATE	DATE
	*	CREATE_DATE	DATE
		UPDATE_DATE	DATE
	*	USER_ID	VARCHAR2 (160 BYTE)
		DAYS_SINCE_UPDATE	NUMBER
		TRIBAL_LAND_NAME	VARCHAR2 (350 BYTE)
		PORTABLE_SOURCE_FLAG	VARCHAR2 (1 BYTE)
		POTW_FLAG	VARCHAR2 (1 BYTE)
		START_DATE	DATE
		END_DATE	DATE
		FACILITY_MANAGEMENT_TYPE_CODE	VARCHAR2 (20 BYTE)
		COUNTRY_FIPS_CODE	VARCHAR2 (2 BYTE)
		STD_STATE_NAME	VARCHAR2 (35 BYTE)
	*	REGISTRY_TYPE	VARCHAR2 (40 BYTE)
		AIR_LCON_DESC	VARCHAR2 (100 BYTE)
		PROCESS_IND	VARCHAR2 (5 BYTE)
		COUNTRY_ISO_3166_1_ALPHA_2	VARCHAR2 (2 CHAR)
		OPERATING_STATUS_DATE	DATE
		OPERATING_STATUS	VARCHAR2 (100 BYTE)
		OPERATING_STATUS_YEAR	NUMBER (4)
		FACILITY_OWNER_TYPE	VARCHAR2 (40 BYTE)
		FACILITY_SOURCE_SYS_PGM_CODE	VARCHAR2 (20 BYTE)
		OFFSHORE_FLAG	VARCHAR2 (1 BYTE)
		FEDERAL_FACILITY_DOCKET_IND	VARCHAR2 (1 BYTE)
		SEMS_ID	VARCHAR2 (30 BYTE)
		FEDERAL_LAND_IND	VARCHAR2 (1 BYTE)

- FFP_PK1 (PGM_SYS_ID, PGM_SYS_ACRNM)
- FPF_PGM_SYS_ACRNM_FK (PGM_SYS_ACRNM)
- FRS_FACILITY_TYPE_FK (FACILITY_TYPE_NAME)
- FRS_REGISTRY_TYPE_FK (REGISTRY_TYPE)
- FPC_REGISTRY_ID_IDX (REGISTRY_ID)
- FPF_CTX_PRIMARY (STD_NAME)
- FPF_IDX1 (PGM_SYS_ACRNM)
- FPF_IDX2 (PGM_SYS_ACRNM, PRIMARY_NAME, LOCATION_ADDRESS, CITY_NAME, STATE_CODE, SUBSTR(TRIM("POSTAL_CODE"),1,5))
- FPF_IDX_PUBLIC_IND (PUBLIC_IND)
- FPF_IDX_RP (EPA_REGION_CODE, PUBLIC_IND)
- FPF_PGMID_I (PGM_SYS_ID)
- FPF_PK1 (PGM_SYS_ID, PGM_SYS_ACRNM)
- FPF_POSTAL_CODE_I2 (POSTAL_CODE)
- FPF_PUBLIC_IND_IDX (NVL("PUBLIC_IND",'x'))
- FPF_REGISTRY_TYPE_IDX (REGISTRY_TYPE)
- FPF_UK2 (PGM_SYS_ACRNM)
- FRP_IDX20 (GEO_DERIVED_FULL_ADDRESS, STATE_CODE)
- FRP_IDX21 (LOCATION_ADDRESS, CITY_NAME, STATE_CODE)
- FRP_IDX22 (STD_LOC_ADDRESS, STD_CITY_NAME, STD_STATE_CODE)
- IBM_FRS_PROGRAM_FACILITY2 (PROCESS_IND)

FRSPRD_D2.FRS_PROGRAM_ALT_ID

UF	*	PGM_SYS_ACRNM	VARCHAR2 (20 BYTE)
UF	*	PGM_SYS_ID	VARCHAR2 (30 BYTE)
	*	REGISTRY_TYPE	VARCHAR2 (40 BYTE)
U	*	ALTERNATIVE_ID	VARCHAR2 (150 BYTE)
U	*	ALTERNATIVE_ID_TYPE	VARCHAR2 (250 BYTE)
	*	CREATE_SOURCE_OF_DATA	VARCHAR2 (25 BYTE)
		LAST_REPORTED_DATE	DATE
	*	CREATE_DATE	DATE
		UPDATE_DATE	DATE
	*	USER_ID	VARCHAR2 (160 BYTE)
		SENSITIVE_IND	CHAR (1 BYTE)
		PUBLIC_IND	CHAR (1 BYTE)
		START_DATE	DATE
		END_DATE	DATE
		REFRESH_DATE	DATE
		UPDATE_SOURCE_OF_DATA	VARCHAR2 (25 BYTE)
		REFRESH_SOURCE_OF_DATA	VARCHAR2 (25 BYTE)
		RESP_AGENCY_FLAG	VARCHAR2 (1 BYTE)
U		PGM_SUB_SYS_ID	VARCHAR2 (36 BYTE)
		RESPONSIBLE_AGENCY	VARCHAR2 (200 BYTE)

- FRS_PGM_ALT_ID_UK (PGM_SYS_ACRNM, PGM_SYS_ID, ALTERNATIVE_ID, ALTERNATIVE_ID_TYPE, PGM_SUB_SYS_ID)
- FRS_PGM_ALT_ID_FK (PGM_SYS_ID, PGM_SYS_ACRNM)
- FPAID_IDX (PGM_SUB_SYS_ID)
- FRS_PGM_ALT_ID_IDX (ALTERNATIVE_ID, ALTERNATIVE_ID_TYPE)
- FRS_PGM_ALT_ID_UK (PGM_SYS_ACRNM, PGM_SYS_ID, ALTERNATIVE_ID, ALTERNATIVE_ID_TYPE, PGM_SUB_SYS_ID)

FRSPRD_D2.FRS_PROGRAM_ORG

U	*	ORG_ID	VARCHAR2 (12 BYTE)
UF	*	PGM_SYS_ID	VARCHAR2 (30 BYTE)
UF	*	PGM_SYS_ACRNM	VARCHAR2 (20 BYTE)
U		PGM_SUB_SYS_ID	VARCHAR2 (30 BYTE)
U	*	AFFILIATION_TYPE	VARCHAR2 (60 BYTE)
		START_DATE	DATE
		END_DATE	DATE
		ORG_NAME	VARCHAR2 (150 BYTE)
		STD_ORG_NAME	VARCHAR2 (150 BYTE)
		DISPLAY_ORG_NAME	VARCHAR2 (150 BYTE)
	*	ORG_TYPE	VARCHAR2 (40 BYTE)
		DUNS_NUMBER	VARCHAR2 (9 BYTE)
		DIVISION_NAME	VARCHAR2 (50 BYTE)
		PHONE_NUMBER	VARCHAR2 (30 BYTE)
		ALTERNATE_PHONE	VARCHAR2 (30 BYTE)
		FAX_NUMBER	VARCHAR2 (30 BYTE)
		EMAIL_ADDRESS	VARCHAR2 (120 BYTE)
		EIN	VARCHAR2 (14 BYTE)
		STATE_BUSINESS_ID	VARCHAR2 (30 BYTE)
U		ADDRESS_ID	VARCHAR2 (12 BYTE)
		MAILING_ADDRESS	VARCHAR2 (100 BYTE)
		STD_MAIL_ADDRESS	VARCHAR2 (150 BYTE)
		SUPPLEMENTAL_ADDRESS	VARCHAR2 (100 BYTE)
		STD_SUPPLEMENTAL_ADDRESS	VARCHAR2 (150 BYTE)
		CITY_NAME	VARCHAR2 (30 BYTE)
		STD_CITY_NAME	VARCHAR2 (60 BYTE)
		STATE_CODE	VARCHAR2 (5 BYTE)
		STATE_NAME	VARCHAR2 (35 BYTE)
		POSTAL_CODE	VARCHAR2 (14 BYTE)
		COUNTRY_NAME	VARCHAR2 (44 BYTE)
	*	SOURCE_OF_DATA	VARCHAR2 (25 BYTE)
		LAST_REPORTED_DATE	DATE
		SENSITIVE_IND	CHAR (1 BYTE)
	*	PUBLIC_IND	CHAR (1 BYTE)
		SUP_PGM_SYS_ACRNM	VARCHAR2 (20 BYTE)
		SUP_PGM_SYS_ID	VARCHAR2 (30 BYTE)
		SUP_INTEREST_ID	NUMBER
		USER_ID	VARCHAR2 (160 BYTE)
		OWNER_PERCENT	NUMBER
		REFRESH_DATE	DATE
		GEO_DERIVED_LOC_ADDRESS	VARCHAR2 (250 BYTE)
		GEO_DERIVED_HOUSE_NUMBER	VARCHAR2 (20 BYTE)
		GEO_DERIVED_STREET_NAME	VARCHAR2 (80 BYTE)
		GEO_DERIVED_BASE_NAME	VARCHAR2 (64 BYTE)
		GEO_DERIVED_PREFIX	VARCHAR2 (32 BYTE)
		GEO_DERIVED_SUFFIX	VARCHAR2 (32 BYTE)
		GEO_DERIVED_STYPE_BEFORE	VARCHAR2 (32 BYTE)
		GEO_DERIVED_AFTER	VARCHAR2 (32 BYTE)
		GEO_DERIVED_POSTAL_CODE	VARCHAR2 (16 BYTE)
		GEO_DERIVED_STATE_CODE	VARCHAR2 (5 BYTE)
		GEO_DERIVED_CITY_NAME	VARCHAR2 (100 BYTE)
		GEO_DERIVED_COUNTY_NAME	VARCHAR2 (100 BYTE)
		GEO_DERIVED_COUNTY_FIPS	VARCHAR2 (5 BYTE)
		GEO_DERIVED_COUNTRY	VARCHAR2 (100 BYTE)
		GEO_DERIVED_FULL_ADDRESS	VARCHAR2 (1000 BYTE)
		GEO_DERIVED_ADDR_TYPE	VARCHAR2 (50 BYTE)
		GEO_DERIVED_QA_HOUSE_NUMBER	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_STREET_NAME	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_PREFIX	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_SUFFIX	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_STYPE	VARCHAR2 (200 BYTE)
		GEO_DERIVED_QA_CITY	VARCHAR2 (100 BYTE)
		GEO_DERIVED_QA_POSTAL_CODE	VARCHAR2 (100 BYTE)
		GEO_DERIVED_MULTI_ADDRESS_FLAG	VARCHAR2 (1 BYTE)
		GEO_DERIVED_PLACENAME	VARCHAR2 (200 BYTE)
		GEO_DERIVED_GEOCODER_MESSAGE	VARCHAR2 (1000 BYTE)
		STD_PARSED_STREET_NAME	VARCHAR2 (240 BYTE)
		STD_PARSED_STREET_NUMBER	VARCHAR2 (15 BYTE)
		STD_PARSED_PRE_DIR_CODE	VARCHAR2 (6 BYTE)
		STD_PARSED_STREET_SUFFIX	VARCHAR2 (12 BYTE)
		STD_PARSED_POST_DIR_CODE	VARCHAR2 (6 BYTE)
		STD_ADDR_TYPE	VARCHAR2 (50 BYTE)
		STD_POSTAL_CODE	VARCHAR2 (16 BYTE)
		STD_STATE_CODE	VARCHAR2 (5 BYTE)
		STD_COUNTY_NAME	VARCHAR2 (35 BYTE)
		STD_COUNTRY	VARCHAR2 (100 BYTE)
		STD_FULL_ADDRESS	VARCHAR2 (1000 BYTE)
	*	CREATE_DATE	DATE
		UPDATE_DATE	DATE
		COUNTRY_FIPS_CODE	VARCHAR2 (2 BYTE)
		PHONE_NUM_EXTENSION	VARCHAR2 (30 BYTE)
		STD_PHONE_NUMBER	VARCHAR2 (30 BYTE)
		STD_EMAIL_ADDRESS	VARCHAR2 (120 BYTE)
		REGISTRY_TYPE	VARCHAR2 (40 BYTE)
		COMMENTS	VARCHAR2 (1000 BYTE)
		CONFIDENCE_LEVEL	VARCHAR2 (25 BYTE)
		DATA_QUALITY_CODE	VARCHAR2 (20 BYTE)
		EMPLOYEE_COUNT	NUMBER
		MAJOR_BUSINESS	VARCHAR2 (200 BYTE)
		STATE_OF_INCORP	VARCHAR2 (2 BYTE)
		STD_DUNS_NUMBER	VARCHAR2 (9 BYTE)
		WEBSITE_URL	VARCHAR2 (200 BYTE)
		STD_STATE_NAME	VARCHAR2 (35 BYTE)

- FRS_PROGRAM_ORG_UK (ORG_ID, ADDRESS_ID, PGM_SUB_SYS_ID, AFFILIATION_TYPE, PGM_SYS_ID, PGM_SYS_ACRNM)
- FPO_ADDRESS_ID_FK (ADDRESS_ID)
- FPO_ORG_ID_FK (ORG_ID)
- FRS_PROG_ORG_ACRNMID_FK (PGM_SYS_ID, PGM_SYS_ACRNM)
- FPO_IDX (NVL("PUBLIC_IND",'X'))
- FRS_PROGRAM_ORG_ADDRESS (ADDRESS_ID)
- FRS_PROGRAM_ORG_IDX2 (PGM_SYS_ACRNM, PGM_SYS_ID, ORG_ID, NVL("ADDRESS_ID",'!@#'), NVL("PGM_SUB_SYS_ID",'!@#'), NVL("AFFILIATION_TYPE",'!@#'))
- FRS_PROGRAM_ORG_ORGID (ORG_ID)
- FRS_PROGRAM_ORG_UK (ORG_ID, ADDRESS_ID, PGM_SUB_SYS_ID, AFFILIATION_TYPE, PGM_SYS_ID, PGM_SYS_ACRNM)
- FRS_PROGRAM_PGM_IDACRNM (PGM_SYS_ID, PGM_SYS_ACRNM)

FRSPRD_D2.FRS_PROGRAM_NAICS

UF	*	PGM_SYS_ID	VARCHAR2 (30 BYTE)
UF	*	PGM_SYS_ACRNM	VARCHAR2 (20 BYTE)
U		PGM_SUB_SYS_ID	VARCHAR2 (20 BYTE)
U	*	REGISTRY_TYPE	VARCHAR2 (40 BYTE)
U	*	NAICS_CODE	VARCHAR2 (6 BYTE)
	*	PRIMARY_INDICATOR	VARCHAR2 (10 BYTE)
	*	SOURCE_OF_DATA	VARCHAR2 (25 BYTE)
		LAST_REPORTED_DATE	DATE
		SENSITIVE_IND	CHAR (1 BYTE)
	*	PUBLIC_IND	CHAR (1 BYTE)
		USER_ID	VARCHAR2 (160 BYTE)
		CREATE_DATE	DATE
		UPDATE_DATE	DATE
		START_DATE	DATE
		END_DATE	DATE

- FRS_PROGRAM_NAICS_UK (NAICS_CODE, PGM_SYS_ID, PGM_SYS_ACRNM, PGM_SUB_SYS_ID, REGISTRY_TYPE)
- FRS_PROG_NAICS_ACRNMID_FK (PGM_SYS_ID, PGM_SYS_ACRNM)
- FRS_PROGRAM_NAICS_IDX1 (PGM_SYS_ACRNM, PGM_SYS_ID)
- FRS_PROGRAM_NAICS_UK (NAICS_CODE, PGM_SYS_ID, PGM_SYS_ACRNM, PGM_SUB_SYS_ID, REGISTRY_TYPE)

FRSPRD_D2.FRS_PROGRAM_CONTACT

UF	*	PGM_SYS_ID	VARCHAR2 (30 BYTE)
UF	*	PGM_SYS_ACRNM	VARCHAR2 (20 BYTE)
U	*	AFFILIATION_TYPE	VARCHAR2 (40 BYTE)
		START_DATE	DATE
		END_DATE	DATE
	*	FULL_NAME	VARCHAR2 (70 BYTE)
	*	STD_FULL_NAME	VARCHAR2 (100 BYTE)
		TITLE	VARCHAR2 (40 BYTE)
		DIVISION_NAME	VARCHAR2 (50 BYTE)
		PHONE_NUMBER	VARCHAR2 (30 BYTE)
		PHONE_NUM_EXTENSION	VARCHAR2 (30 BYTE)
		ALTERNATE_PHONE	VARCHAR2 (30 BYTE)
		FAX_NUMBER	VARCHAR2 (30 BYTE)
		EMAIL_ADDRESS	VARCHA