Name And Vendor	ESB Lists ¹	Location Availability/ Space Requirements	Technology Type/Process	History and/or applicability With M6	Destruction Efficiency	Nature Of Residue And Recycle/ Disposal	Nature Of Emissions And Monitoring, Capturing, Testing	Capacity And Throughput					
General DDESB Staff comment.	with the	None of these systems have specifically been tested for large-scale M6 destruction. For the scale being considered, testing systems to be used with the actual material is the right thing to do. From a throughput and capacity perspective, these systems are simply not designed for the large scale industrial-type operation required to address the Minden problem.											
	event for require	or the quantities e d to destroy the M	ned for large-scale de nvisioned. Even if a s l6 would far exceed the signed specifically for	ystem existed that e stabilizer life of t	was designed speci he propellant. In the	fically for this typ DDESB's Staff's	e of large-scale o opinion the time i						
Army JPEO's Project Manager Demilmilitarization (Chemical Systems) TNT Equivalent	be used the stat safety is months	I at all. The techn e. Safe handling ssues. Finally, no).	ologies proposed will of the propellant and c	require modification design of an effection	on, sy <mark>stem</mark> testing an ve means for deliver	nd certification, a ring propellant to	RCRA permit and the destruction sy						
Industrial Waste Processor (IWP) and Caffee Road Thermal Decontamination Area (CRTDA)	AE	Indian Head, MD			Processes explosives contaminated materials from an initial "trace explosives- contaminated" to a final "releasable to the public" condition		Emission factors for this technology were not available at least in literature reviewed for M6. Ambient and	Net Explosive Weight (NEW) for the IWP is 2 to 10 lbs NEW for the CRTDA is 1 lb.					

Name And Vendor	ESB Lists ¹	Location Availability/ Space Requirements	Technology Type/Process	History and/or applicability With M6	Destruction Efficiency	Nature Of Residue And Recycle/ Disposal	Nature Of Emissions And Monitoring, Capturing, Testing	Capacity And Throughput
							would be recommended.	



Ammunition Peculiar Equipment (APE)- 1236 Rotary Kiln Incinerator (Deactivation Furnace) (Ref 7)	AE	CAAA(Crane), TEAD (Tooele), MCAAP (McAlester), HWAD (Hawthorne) El Dorado Engineering (Explosive Waste Incinerator Rotary Kiln) Not available for use.	An explosive waste rotating incinerator with afterburner and baghouse located at the discharge end Developed specifically for conventional end- item munitions	DRE >99.99% for 2,4-DNT & HCB Army: The Army's Program Executive Office - Ammunition (PEO Ammo) indicated the APE (Ammunition Peculiar Equipment) 1236 is not a mobile system. It would take significant construction to emplace a new system (6 – 12 months), and possibly longer to deconstruct a system, move and emplace it at a new location.	Emission factors for this technology were not available at least in literature reviewed for M6. Ambient and direct plume monitoring would be recommended.	DDESB and Army: Up to 600 lbs/hour for certain propellants p explosives, and pyrotechnics (PEP) (Bulk High Explosives – Comp B, TNT, Tetryl, Octyl, Black Powder, etc.; Bulk Single & double based propellants and composites; Bulk Pyrotechnics - signal flares, illuminating candles.) The type material determines the actual feed rate. On average the feed rate approximates 250 lbs/hour. The weight of the material processed is not limited to the net explosives weight (i.e., it includes other materials, such as metal parts.) A heavily modified kiln, which is not the current APE 1236 system configuration, could potentially
						system configuration,

Static Detonation	AE	Anniston,	Designed for thermal	Army: The SDC	Gasses are	Army: The SDC has
Chamber (SDC)	2/12	Alabama	decomposition/controlled	can process	largely	very limited
1200 CM			deflagration and burning	propellants and	destroyed by	throughput - the
			reactions of high	can process M6	explosive	maximum detonable
Vendor is UXB			explosives and	propellant.	effects and	quantity allowed
under the Dynasafe			propellants (Ref 1)		pyrolysis in the	inside at any one time
nam e				Not	main chamber.	is 5.29 lbs of TNT
				recommended for	Remaining	equivalent material
				large quantities	pyrolysis	(approximately 11
				(millions of	products and	pounds of M-6).
				pounds) given the	gasses from	• •
				time and money	the explosives	The SDC cannot
				required to	are further	process extremely
				process it.	treated to	large amounts of
					remove	propellant (M6). For
					pollutants.	example, the
					p =	Anniston SDC could
						process (rough
						estimate) 325,000
					Emission	pounds of propellant
					factors for this	annually.
					technology	annaanyr
					were not	Has very limited
					available at	throughput because the
					least in	maximum detonable
					literature	quantity allowed inside
					reviewed for	at any one time is 5.29
					M6.	lbs of TNT equivalent
					IVIU.	material.
					Ambient and	material.
						(D = f 4)
					direct plume	(Ref 1)
					monitoring	
					would be	
					recommended.	

Vacuum	AE	Blue Grass AD,	Designed for	Destruction	Uses detonation	This is a	The DV65 system has
Integrated	2/12	KY;	fragmenting munitions	Technologies	as a means for	vacuum	a 65 kg capacity (31 kg
Chamber		Pueblo CD, CO	and solid rocket motors;	for Specific	Destruction.	detonation	TNT equivalents), of
(DA VINCH DV -			method used for	Munitions at		followed by	which only the fraction
60)			destruction by	the Blue	Is not intended	cold plasma.	8.8/22.2 (40%) was the
			detonation. (Ref 1)	Grass and	for the	No emission	subject material for
Vendor is Kobe				Pueblo	destruction of	factors were	destruction, the rest
Steel under the DA			Is an explosive	Chemical	bulk propellants.	available in	being an explosive
VINCH DV -60			destruction	Agent		literature	donor material. (Ref 1)
name			technology (EDT)	Destruction		reviewed for	
			system.	Pilot Plants		 M6.	DoD did a test on HD
Capable of				(2009).			projectiles and it was
destroying							successful; 9 projectiles
chemical							per 10 hour day would
munitions – not							take up to 5.3 years to
DDESB approved							process 15,000
for such.							projectiles.
							Disposal of 1,200
							bombs in 3 years.
							Stated capacity of 65
							kg TNT equivalent per
							batch.
							Capacity for M6 not
							available.
1							(Ref 3)

Explosives	AE	Various	Designed for chemical	The U.S.	Army: Not	Emission	The containment
Destruction		locations	munitions destruction	Army	suitable for	factors for this	vessels is designed to
System (EDS)			by external	Chemical	destruction of M6	technology	handle munitions
Phase 1 and		Not available	(implosion) detonation	Materials	or other bulk	were not	containing a TNT-
Phase 2 Units			(Agency's	propellants.	available at	equivalent of
Phase 2 (Retrofit)		Phase 2		(CMA) Non-	propenants.	least in	explosives as listed
		(Retrofit is at	EDS are capable of	Stockpile		literature	below:
		Pueblo	treating chemical	Chemical		reviewed for	below.
		Chemical	munitions with a	Material		M6.	Phase 1 = 1.5 lbs
		Depot).		Project		IVIO.	Phase 2 = 4.8 lb
		Depoty.	variety of different fills	(NSCMP)		Ambient and	Phase 2 (Retrofit) = 9
			(e.g., treat Mustard,	designed the		direct plume	lbs
			Phosgene, G-series agents, VX, Lewisite,	Explosive		monitoring	
				Destruction		would be	Phase 1 can
			Cyanogen Chloride,	System		recommended	processes three items
			Hydrogen Cyanide,	(EDS) with		recommended	at once including: 4.2-
			and Chloropicrin.)	Sandia			inch mortars, 75 mm
				National			artillery shells, livens
				Laboratories			projectiles and
				to provide			bomblets.
				on-site			Phase 2 and Phase 2
				treatment of			(Retrofit) can
				chemical			processes six
				warfare			munitions at one time,
				material.			including: 4.2-inch
							mortars, 75 mm
				Successfully			-
				completed			artillery shells, 105
				missions at			mm projectiles, 155
				Aberdeen			mm projectiles and 8-
				Proving			inch projectiles.
				Ground, Md.,			(Ref 5)
				Spring			\ <i>1</i>
				Valley,			
				Washington,			
				D.C., Dover			
				Air Force			
				Base, Del.,			

DRAFT - FOR DR	3003						
				Former Camp Sibert, Ala., Pine Bluff Arsenal, Ark., Rocky Mountain Arsenal, Colo., and Redstone Arsenal, Ala. Testing for the EDS was conducted at Porton Down, United Kingdom and Aberdeen Proving Ground, Md. (Ref 5)			
Tactical Missile Demilitarization (TMD)	AE	Letterkenny Army Depot	System used to section and destroy large tactical missiles ; Recover high value energetics from propellant and warhead feedstocks (Ref 2)			Emission factors for this technology were not available at least in literature reviewed for M6. Ambient and direct plume monitoring would be recommended	Disposal of up to 10,000 lbs. of ammunition per day through demilitarization, burning, or processing through a deactivation furnace. (Ref 6)



Controlled	2/12		Systems are self-	Not suitable for	Emission	Varies based on type
Detonation	<i>L</i> / 1 <i>L</i>	Hill/Demil	contained and mobile.	destruction of M6	factors for this	munition and CDC
Chamber (also		International	Have been used to	or other bulk	technology	used.
referred to a		International	destroyed conventional	propellants as	were not	uscu.
Donovan			munitions and explosive	designed and	available at	Example: T-10 used at
Chambers)			components.	approved.	least in	Fort Hunter Liggett,
onamberaj			componento.	appioveu.	literature	Mare Island, Seal
Transportable			Each system is		reviewed for	Beach, and Camp
Controlled			approved for various net		M6.	Roberts. 28,858
Detonation			explosive weights.)		10.	munitions of explosive
Chambers-					Ambient and	concern and code H
(Models T-10,			Demonstrated the ability		direct plume	munitions destroyed in
T-25, T-30 and			to destroy 105mm HE		monitoring	15 days. Typical
T-60)			munitions. (Ref 4)		would be	throughput is 25
,					recommended	munitions per day.
			T-10 - 13 pounds TNT			
			equivalency (up to			Systems are
			81mm mortar)			transportable. (Ref 4)
			T-25 – 16.7 lbs TNT			
(T60C is approved			equivalency (up to 4.2			System intended for
for use for			in mortar or 4.5 in			emergency use and
destruction of			rocket)			not a production
certain chemical						environment
munitions)			T-30 – 40 lb TNT			
			equivalency (up to 155			
			mm projectile)			
			T-60 - 40 lb TNT			
			equivalency (up to 155			
			mm projectile			
			DDESB approved for			
			use at Schofield			
			Barracks, HI, for the			
			destruction of certain			
			chemical munitions.			

Super Critical Water Oxidation Vendor is General Atomics	2/12	There is a system currently at Camp Minden, also McAlester AAP, OK	Water at conditions above its thermodynamic critical point of 374°C (705°F) and 3,206 psi (pounds per square inch), allowing complete oxidation of organic materials (Ref 1)	M6 would need a preparation step such as grinding or alkaline hydrolysis to prepare aqueous waste stream			CO2, H2O, and salts, with NOX, SOX, and particulate concentrations at or below detection limits, all without any post-treatment	
FDHS - Field Deployable Hydrolysis System (FDHS)	2/12	Edgewood, MD Army: Can be up and running within 10 days of arriving on a site.	Destroys chemical warfare agents in bulk and can be up and running within 10 days of arrival on site.		Army: Not suitable for M6. Designed to destroy chemical warfare agents in bulk	Possible liquid waste stream		Army - FDHS is not configured to handle flammable liquids or explosive mixtures. Additionally, M6 propellant is made up of relatively insoluble solids; therefore, is unsuitable for a process which relies on being able to mix the intended destruction material with an aqueous liquid.
Humic Acid Processing Vendor is Arctech under the Actodemil name	2/12	Could be placed on site.	Humic Acid reacts with hazardous chemicals in a reaction vessel at 160 to 180° F. (Ref 1)	Has been tested on M6		Neutralized material available for disposal or reuse	No emissions according to manufacturer	Pre-designed units of 100, 200 or 500 pounds per batch. Batches take between 2 and 4 hours.

Open Burning	Site	Industrial-level burns	Used	Extremely		Varies by site.
	specific	are normally a RCRA-	extensively for	efficient. (Will		
	approval	permitted process.	demilitarization	have to get a		Quantity to be
			of excess,	definitive answer		processed generally
		Operations are	obsolete or	based on testing		restricted by permit,
		governed by DoD	unserviceable	and experience		approved operating
		explosives safety	propellants	estimate, but		procedures, and
		criteria (DoD 6055.9M	and other	expect in the 95 +		DDESB-approved
		Vol 1 to 8, DoD	energetic	% range)		site plan
		Ammunition and	material.			
		Explosives Safety				
		Standards:				

NOTES

1. AE denotes the DDESB approved system for ammunition and explosives. 2/12 identifies technologies that were shared at the 2/12 dialogue meeting as from a chemical weapons process, but we are still seeking an official list designation for these technologies.

Manufacturer websites (incomplete list; provided as reference only; no endorsement implied)

SWCO: www.ga.com/supercritical-water-oxidation

Humic Acid Processing: www.arctech.com/actodemil.html

Rotary Kiln (APE 1236): www.eldoradoengineering.com, General Dynamics (http://www.gd-ots.com/munitions/company.html)

CDC: CH2M Hill (http://www.ch2m.com/corporate/markets/environmental/munitions.asp), http://demilinternational.com

SDC: UXB International (http://uxb.com/pages/demil.html)

Department of Defense Explosives Safety Board (DDESB)

The DDESB's role in the review of AE demilitarization systems is defined by DoD policy and limited to validating that:

(1) Personal protection criteria are met; and

(2) A system may be used in lieu of 100-percent independent dual inspections to determine whether material to be demilitarized may be documented as safe prior to its transfer within or release from DoD control.

b. The DDESB does not evaluate systems for other types of feasibility (economic, environmental, etc.).

PRELIMINARY LIST OF POTENTIAL TECHNOLOGIES FOR THE DESTRUCTION OF M6 AT CAMP MINDEN, draft 2/26/15 DRAFT – FOR DISCUSSION PURPOSES ONLY DDESB REVIEW AND APPROVAL PROCESS

A. Review of Demilitarization Systems for Personnel Protection

The DDESB's role in the review of systems that may be used to support AE demilitarization operations is limited to the explosives safety aspects of those systems (vice an evaluation of whether the system will ensure an item has been adequately demilitarized). For a given quantity of AE to be processed in a system at a given time, the DDESB reviews and approves safety distances and compensatory measures associated with the system.

The DDESB will review U.S. Military Component submissions of AE demilitarization systems in accordance with DoDI 6055.161 that meet the requirements of DoDM 6055.092 for personnel protection from thermal, blast and fragmentation effects. Criteria are established based on accidental or intentional detonations or burns of the AE and the associated safety distances. A DoD Component may submit for review and approval systems that have demonstrated (e.g., by testing) that the proposed system meets DoD criteria for personnel protection.

B. DDESB Review of Systems for Material Documented as Safe (MDAS)

DoDI 4140.623 requires that material to be transferred within or released from DoD control must be assessed and documented as either safe or as having a known or suspected explosive hazards based on the following two conditions:

- (1) After 100-percent inspection and an independent 100-percent reinspection.
- (2) After processing by a DDESB-approved means with an appropriate post-processing inspection.

A DoD Component may propose a system to the DDESB, with appropriate justification, to indicate material processed through the system does not require the inspections specified in (1) above. The justification must show that over its lifetime the system will achieve a commensurate level of safety without the need for costly or potentially hazardous 100-percent inspection and independent reinspection. This type of approval would apply to, among other materials, AE where energetic material (e.g., the explosive fill) is removed from the material.

¹ Department of Defense Instruction (DoDI) 6055.16, "Explosives Safety Management Program", July 29, 2008, Incorporating Change 1, December 8, 2011

² Department of Defense Manual (DoDM) 6055.09, "DoD Ammunition and Explosives Safety Standards", date varies by volume.

³ Department of Defense Instruction (DoDI) 4140.62, "Material Potentially Presenting an Explosives Hazard", November 25, 2008, Incorporating Change 1, February 19, 2014

References:

- 1. Preliminary List of Potential Technologies/Evaluation Framework, draft 2/22/15
- 2. Defense Explosives Safety Board's Role in Approving Demilitarization Technology for Ammunition and Explosives Information Paper, January 23, 2015
- 3. Evaluation of Monitoring Emissions, and Modeling Technologies Proposed for Camp Minden, LA site
- 4. Current Status of Transportable Controlled Detonation Chambers, CH2MHill Demilitarization, Inc., May 2007
- 5. Explosive Destruction System Overview Fact Sheet, U.S. Army Chemical Materials Agency
- 6. GlobalSecurity.org website (Letterkenny Army Depot)
- 7. "Results of Trial Test Burns on Army Deactivation Furnaces Upgraded to Meet RCRA" (DDESB seminar paper), August 1992, Tooele Army Depot.

"General Instructions for Demilitarization/Disposal of Conventional Munitions", TM 9-1300-277, March 1982 (rev. March 2001), Dept. of the Army.

Hazardous Waste Incinerator APE 1236M2 promotional flyer, Tooele Army Depot (www. Tooele.army.mil).

McAlester Army Ammunition Plant (MCAAP) Munitions Deactivation Furnace (APE 1236M2), Permit No. 2005-301-TV, with Evaluation of Permit Application, Oklahoma Department of Environmental Quality Air Quality Division, October 31, 2006.