



Finasol OSR 52 IBC

Volume **1000** liters
Net weight **990** kg
Gross weight **1054** kg

Oil Spill Dispersant type 2/3 For use from ships, boats and aircraft

Pure or diluted in sea water

Danger:

Contains Sodium Docusate

Causes skin irritation. Causes serious eye damage.

Wash hands, forearms and face thoroughly after handling. Wear eye protection, face protection, impermeable protective gloves.

If on skin: Wash with plenty of water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. Specific treatment (see Section 4.1 of SDS or information on this label).

If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.



Not Classified as hazardous for transport

Storage conditions:

Store in original packaging in a clean and dry room, away from direct light exposure, preferably between 5°C and 35°C. It is recommended to limit as much as possible amplitude of temperature variations.

Always consult the Safety Data Sheet and technical data sheet prior to use

Product main components:

More than 30% non-ionic surfactants

More than 20% anionic surfactant

Hydrocarbon and Propylene Glycol solvents

Instruction to users:

Diluted in Sea water: 10% solution of dispersant in seawater to 2 to 3 parts oils. From ships and boats.

Pure: Low treatment rate 3 to 5% dispersant as volume of spilled oil. From Aircraft, ships, boats.

Dispersants should only be used as part of approved contingency plan.

⚠ WARNING: Not to be mixed with any other dispersant

Disclaimer:

FINASOL OSR 52 IBC is listed on the National Contingency Plan (NCP) Product Schedule. This listing does NOT mean that EPA approves, recommends, licenses, or certifies the use of FINASOL OSR 52 IBC on an oil discharge. This listing means only that data have been submitted to EPA as required by Subpart J of the NCP. Only a Federal On-Scene Coordinator (OSC) may authorize use of this product in accordance with Subpart J of the NCP in response to an oil discharge.

TotalEnergies Petrochemicals & Refining USA, Inc.

P O Box 674411

Houston, TX 77267-4411

Tel 713-483-5000 / Tel Emergency : CHEMTREC: 1-800-424-9300 / 703-527-3887 - TotalEnergies Petrochemicals & Refining USA, Inc.: 1-800-322-3462

Batch number: **XXXX**

Date of manufacturing: **YYY**

Date of expiry: **ZZZ (= YYY + 5 years - 1 day)**

Retest recommendation:

For efficiency after 5 years