

**Commonwealth of Kentucky
Energy and Environment Cabinet
Department for Environmental Protection
Division for Air Quality
300 Sower Boulevard, 2nd Floor
Frankfort, Kentucky 40601
(502) 564-3999**

Proposed

**AIR QUALITY PERMIT
Issued under 401 KAR 52:020**

Permittee Name: Polyair Corporation
Mailing Address: 300 Spencer Mattingly Lane
Bardstown, KY 40004

Source Name: Polyair Packaging
Mailing Address: 300 Spencer Mattingly Lane
Bardstown, KY 40004

Source Location: same as above

Permit: V-21-013 R1
Agency Interest: 39476
Activity: APE20240002
Review Type: Title V, Operating
Source ID: 21-179-00050

Regional Office: Frankfort Regional Office
300 Sower Blvd., 1st Floor
Frankfort, KY 40601
(502) 564-3358

County: Nelson

Application
Complete Date: March 1, 2022
Issuance Date: July 22, 2022
Revision Date:
Expiration Date: July 22, 2027

**For Michael J. Kennedy, P.E.
Director
Division for Air Quality**

TABLE OF CONTENTS

SECTION	ISSUANCE	PAGE
A. PERMIT AUTHORIZATION	Renewal	1
B. EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS	Revision 1	2
C. INSIGNIFICANT ACTIVITIES	Revision 1	7
D. SOURCE EMISSION LIMITATIONS AND TESTING REQUIREMENTS	Renewal	8
E. SOURCE CONTROL EQUIPMENT REQUIREMENTS	Renewal	9
F. MONITORING, RECORDKEEPING, AND REPORTING REQUIREMENTS	Renewal	10
G. GENERAL PROVISIONS	Revision 1	13
H. ALTERNATE OPERATING SCENARIOS	Renewal	19
I. COMPLIANCE SCHEDULE	Renewal	19

Permit	Permit Type	Activity#	Complete Date	Issuance Date	Summary of Action
V-21-013	Renewal	APE20210001	3/1/2022	7/22/2022	Permit Renewal, removal of Foam Laminators EUs 010(1) and (2)
V-21-013 R1	Revision	APE20240002	1/14/2025		Add 1 previously installed Makeup Air Handling Unit (MAU) (EU 011); Add previously installed insignificant heaters and MAUs (EU 012)

SECTION A - PERMIT AUTHORIZATION

Pursuant to a duly submitted application the Kentucky Energy and Environment Cabinet (Cabinet) hereby authorizes the operation of the equipment described herein in accordance with the terms and conditions of this permit. This permit was issued under the provisions of Kentucky Revised Statutes (KRS) Chapter 224 and regulations promulgated pursuant thereto.

The permittee shall not construct, reconstruct, or modify any affected facilities without first submitting a complete application and receiving a permit for the planned activity from the permitting authority, except as provided in this permit or in 401 KAR 52:020, Title V Permits.

Issuance of this permit does not relieve the permittee from the responsibility of obtaining any other permits, licenses, or approvals required by the Cabinet or any other federal, state, or local agency.

SECTION B - EMISSION POINTS, EMISSION UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

EMISSION UNIT	DESCRIPTION	MAXIMUM OPERATING RATE
002	Foam Extruder Line #01 Installation Date: April 1995 Collection System: Floor-Vents-to-Roof Exhaust	530 lb/hr
003	Curing Rooms Installation Date: April 1995 Collection System: Floor-Vents-to-Roof Exhaust	78 lb/hr
004	Foam Extruder Line #02 Installation Date: April 1995 Collection System: Floor-Vents-to-Roof Exhaust	470 lb/hr

APPLICABLE REGULATIONS:

401 KAR 50:012, General application

1. Operating Limitations:

Pursuant to 401 KAR 50:012, Section 1(2), in the absence of a standard specified in these administrative regulations, all major air contaminant sources shall as a minimum apply control procedures that are reasonable, available, and practical.

- a. The permittee shall maintain the VOC blowing agent at no more than 0.6 pounds of VOC per cubic foot of foam (lb VOC/ft³) on a monthly basis for each Foam Extruder Line #01 and Foam Extruder Line #02 [RAP Analysis Determination approved on November 12, 2014].
- b. The permittee shall maintain preventative maintenance program for all solvent delivery system elements and components including the following safety control procedures [RAP Analysis Determination approved on November 12, 2014]:
 - i. Maintaining safe room LEL levels by vapor venting to the atmosphere,
 - ii. Maintaining high humidity for spark prevention, and
 - iii. Maintaining multiple LEL monitors in the rooms of the Foam Extruder Line #01 and Foam Extruder Line #02.

Compliance Demonstration Method:

- i. For compliance with **1. Operating Limitations**, a., refer to **4. Specific Monitoring Requirements**, **5. Specific Recordkeeping Requirements** and **6. Specific Reporting Requirements**.
- ii. For compliance with **1. Operating Limitations**, b., refer to **5. Specific Recordkeeping Requirements** and **6. Specific Reporting Requirements**.

2. Emission Limitations:

- a. To preclude 401 KAR 51:017, the volatile organic compounds (VOC) emissions from line 1 and line 2 (including curing rooms) shall not exceed 180.5 and 173 tons per year (tpy), respectively plus a combined increase for both lines 1 and 2 (including curing rooms) shall be less than 36 tpy.
- b. The increase of 36 tpy of VOC can be split as permittee wishes between lines 1 and 2 (including curing rooms).

SECTION B - EMISSION POINTS, EMISSION UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

- c. To preclude 401 KAR 51:017, the total VOC emissions from line 1 (including curing rooms) shall not exceed 216.5 tpy and the line 2 (including curing rooms) shall not exceed 209.0 tpy, and the combined lines 1 and 2 (including curing rooms) shall not exceed 389.5 tpy.

Compliance Demonstration Method:

- i. The permittee shall operate at all times a floor-vent-to-roof-exhaust-stack collection system that will collect VOC emissions from the extruder line process equipment.
- ii. The permittee shall operate at all times a floor-vent-to-roof-exhaust-stack collection system that will collect VOC emissions from the curing room.
- iii. Monthly VOC emission from the above affected facilities shall be calculated and shall be used to calculate the annual emission rate:

Emissions from each line = Emissions from extruder line + Curing room emissions

Monthly VOC emission in tons from each extruder line =

[lb/hr VOC containing material (Isobutane, Propane or a mixture thereof) used] x [actual monthly hours of operation of each line / 2000]

Monthly VOC emission in tons from curing room =

[Monthly VOC emissions in tons from each line] x [capture efficiency] x [emission factor]

3. Testing Requirements:

Pursuant to 401 KAR 50:045, Section 1, testing shall be conducted at such times as may be requested by the Cabinet.

4. Specific Monitoring Requirements:

Pursuant to 401 KAR 52:020, Section 10, the permittee shall monitor the following:

- a. Monthly usage of each VOC containing material (Isobutane, Propane or a mixture thereof) at each line.
- b. Daily hours of operations of each line.
- c. Monthly usage of the VOC blowing agent for each Foam Extruder Line #01 and Foam Extruder Line #02 in terms of lb VOC/ft³ of foam.

5. Specific Recordkeeping Requirements:

Pursuant to 401 KAR 52:020, Section 10, the permittee shall keep the following records:

- a. At the end of each month, VOC emissions in tons shall be calculated and recorded.
- b. The annual VOC emissions for each calendar year for each extruder line (including curing rooms) and the total for both lines shall be calculated and kept available at the plant site.
- c. The records listed above, as well as purchase orders and invoices for all VOC (Isobutane, Propane or a mixture thereof) containing materials, shall be made available for inspection upon request by duly authorized representatives of the Division.
- d. The permittee shall keep a log of all routine and non-routine maintenance.

SECTION B - EMISSION POINTS, EMISSION UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

- e. The permittee shall keep a log of all time periods when the collection system is not operating and reasons for not operating.
- f. The permittee shall maintain records of the monthly VOC blowing agent usage rates in terms of lb VOC/ft³ for each Foam Extruder Line #01 and Foam Extruder Line #02.
- g. The permittee shall record and report of any deviations from the preventative maintenance program.

6. Specific Reporting Requirements:

Pursuant to 401 KAR 52:020, Section 10, reporting of the following shall be done on a semi-annual basis:

- a. Any deviations from the requirements of Section B shall be reported.
- b. The VOC emissions for each month in the semi-annual period shall be reported.
- c. The rolling 12-month total of VOC emissions during each month in the semi-annual period shall be reported.
- d. The VOC blowing agent usage rates in terms of lb VOC/ft³ for each Foam Extruder Line #01 and Foam Extruder Line #02 on a monthly basis.

SECTION B - EMISSION POINTS, EMISSION UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)**Emission Unit 011: Makeup Air Handling Unit #1 (MAU #1)**

Capacity Heat Input: 3.51 MMBtu/hr

Fuel: Natural Gas

Installation Date: January 1, 2018

Controls: None

APPLICABLE REGULATIONS:

401 KAR 59:015, New indirect heat exchangers

STATE ORIGIN REQUIREMENT:

401 KAR 63:020, Potentially hazardous matter or toxic substances.

1. Operating Limitations:

- a. Persons responsible for a source from which hazardous matter or toxic substances may be emitted shall provide the utmost care and consideration, in the handling of these materials, to the potentially harmful effects of the emissions resulting from such activities. No owner or operator shall allow any affected facility to emit potentially hazardous matter or toxic substances in such quantities or duration as to be harmful to the health and welfare of humans, animals and plants. Evaluation of such facilities as to adequacy of controls and/or procedures and emission potential will be made on an individual basis by the cabinet. [401 KAR 63:020, Section 3]

Compliance Demonstration Method:

Based upon the emission rates of toxics and hazardous air pollutants determined by the Cabinet using information provided in the application and supplemental information submitted by the source, the Cabinet determines the affected facility to be in compliance with 401 KAR 63:020.

- b. During a startup period or shutdown period, the permittee shall comply with the work practice standards established in 401 KAR 59:015, Section 7. [401 KAR 59:015, Section 7]
 - i. The permittee shall comply with 401 KAR 50:055, Section 2(5); [401 KAR 59:015, Section 7(1)(a)]
 - ii. The frequency and duration of startup periods or shutdown periods shall be minimized by the affected facility; [401 KAR 59:015, Section 7(1)(b)]
 - iii. All reasonable steps shall be taken by the permittee to minimize the impact of emissions on ambient air quality from the affected facility during startup periods and shutdown periods; [401 KAR 59:015, Section 7(1)(c)]
 - iv. The actions, including duration of the startup period, of the permittee during startup and shutdown periods, shall be documented in signed, contemporaneous logs or other relevant evidence; [401 KAR 59:015, Section 7(1)(d)]
 - v. Startups and shutdowns shall be conducted according to either: [401 KAR 59:015, Section 7(1)(e)]
 - 1) The manufacturer's recommended procedures; or [401 KAR 59:015, Section 7(1)(e)1.]

SECTION B - EMISSION POINTS, EMISSION UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

- 2) Recommended procedures for a unit of similar design, for which manufacturer's recommended procedures are available, as approved by the cabinet based on documentation provided by the permittee. [401 KAR 59:015, Section 7(1)(e)2.]

2. Emission Limitations:

- a. The permittee shall not cause emissions of particulate matter in excess of 0.56 lb/MMBtu actual heat input. [401 KAR 59:015, Section 4(1)(a)]
- b. The permittee shall not cause emissions of particulate matter in excess of 20 percent opacity, except: [401 KAR 59:015, Section 4(2)]
 - i. A maximum of 40 percent opacity shall be allowed for a maximum of 6 consecutive minutes in any 60 minutes during fire box cleaning or soot blowing; and [401 KAR 59:015, Section 4(2)(b)]
 - ii. For emissions from an affected facility caused by building a new fire, emissions during the period required to bring the boiler up to operating conditions shall be allowed, if the method used is recommended by the manufacturer and the time does not exceed the manufacturer's recommendations. [401 KAR 59:015, Section 4(2)(c)]
- c. The permittee shall not cause emissions of gases that contain sulfur dioxide in excess of 3.0 lb/MMBtu actual heat input. [401 KAR 59:015, Section 5(1)(a)1.]

Compliance Demonstration Method:

Compliance with the 401 KAR 59:015 emission standards is assumed while burning natural gas.

3. Testing Requirements:

Testing shall be conducted at such times as may be requested by the Cabinet. [401 KAR 50:045, Section 1, and 401 KAR 59:005, Section 2(2)]

4. Specific Monitoring Requirements:

The permittee shall monitor the amount of natural gas combusted, in MMscf, on an annual basis. [401 KAR 52:040, Section 10]

5. Specific Recordkeeping Requirements:

- a. The permittee shall maintain records of the amount of natural gas combusted, in MMscf, on an annual basis. [401 KAR 52:020, Section 10]
- b. The permittee shall keep records of the manufacturer's recommended procedures for startup and shutdown, any instance in which the recommended procedures were not followed, and any corrective action taken. [401 KAR 52:040, Section 10]

6. Specific Reporting Requirements:

None

SECTION C - INSIGNIFICANT ACTIVITIES

The following listed activities have been determined to be insignificant activities for this source pursuant to 401 KAR 52:020, Section 6. Although these activities are designated as insignificant the permittee must comply with the applicable regulation. Process and emission control equipment at each insignificant activity subject to an opacity standard shall be inspected monthly and a qualitative visible emissions evaluation made. Results of the inspection, evaluation, and any corrective action shall be recorded in a log.

<u>Description</u>	<u>Generally Applicable Regulations</u>
1. Recycling Material Recycler	401 KAR 59:010
2. (Isobutane, Propane or a Mixture thereof) Storage Tank Storage Capacity: 18,000 gallons	None
3. Isobutane Storage Tank Storage Capacity: 10,000 gallons	None
4. Ten (10) Insignificant Heaters & MAU #2	401 KAR 59:010 401 KAR 63:020

SECTION D - SOURCE EMISSION LIMITATIONS AND TESTING REQUIREMENTS

1. As required by Section 1b of the *Cabinet Provisions and Procedures for Issuing Title V Permits* incorporated by reference in 401 KAR 52:020, Section 26; compliance with annual emissions and processing limitations contained in this permit, shall be based on emissions and processing rates for any twelve (12) consecutive months.
2. VOC emissions, measured by applicable reference methods, or an equivalent or alternative method specified in 40 C.F.R. Chapter I, or by a test method specified in the state implementation plan shall not exceed the respective limitations specified herein.

SECTION E - SOURCE CONTROL EQUIPMENT REQUIREMENTS

Pursuant to 401 KAR 50:055, Section 2(5), at all times, including periods of startup, shutdown and malfunction, owners and operators shall, to the extent practicable, maintain and operate any affected facility including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on information available to the Division which may include, but is not limited to, monitoring results, opacity observations, review of operating and maintenance procedures, and inspection of the source.

SECTION F - MONITORING, RECORDKEEPING, AND REPORTING REQUIREMENTS

1. Pursuant to Section 1b-IV-1 of the *Cabinet Provisions and Procedures for Issuing Title V Permits* incorporated by reference in 401 KAR 52:020, Section 26, when continuing compliance is demonstrated by periodic testing or instrumental monitoring, the permittee shall compile records of required monitoring information that include:
 - a. Date, place as defined in this permit, and time of sampling or measurements;
 - b. Analyses performance dates;
 - c. Company or entity that performed analyses;
 - d. Analytical techniques or methods used;
 - e. Analyses results; and
 - f. Operating conditions during time of sampling or measurement.
2. Records of all required monitoring data and support information, including calibrations, maintenance records, and original strip chart recordings, and copies of all reports required by the Division for Air Quality, shall be retained by the permittee for a period of five (5) years and shall be made available for inspection upon request by any duly authorized representative of the Division for Air Quality [Sections 1b-IV-2 and 1a-8 of the *Cabinet Provisions and Procedures for Issuing Title V Permits* incorporated by reference in 401 KAR 52:020, Section 26].
3. In accordance with the requirements of 401 KAR 52:020, Section 3(1)h, the permittee shall allow authorized representatives of the Cabinet to perform the following during reasonable times:
 - a. Enter upon the premises to inspect any facility, equipment (including air pollution control equipment), practice, or operation;
 - b. To access and copy any records required by the permit;
 - c. Sample or monitor, at reasonable times, substances or parameters to assure compliance with the permit or any applicable requirements.Reasonable times are defined as during all hours of operation, during normal office hours; or during an emergency.
4. No person shall obstruct, hamper, or interfere with any Cabinet employee or authorized representative while in the process of carrying out official duties. Refusal of entry or access may constitute grounds for permit revocation and assessment of civil penalties.
5. Summary reports of any monitoring required by this permit shall be submitted to the Regional Office listed on the front of this permit at least every six (6) months during the life of this permit, unless otherwise stated in this permit. For emission units that were still under construction or which had not commenced operation at the end of the 6-month period covered by the report and are subject to monitoring requirements in this permit, the report shall indicate that no monitoring was performed during the previous six months because the emission unit was not in operation [Sections 1b-V-1 of the *Cabinet Provisions and Procedures for Issuing Title V Permits* incorporated by reference in 401 KAR 52:020, Section 26].

SECTION F - MONITORING, RECORDKEEPING, AND REPORTING REQUIREMENTS (CONTINUED)

6. The semi-annual reports are due by January 30th and July 30th of each year. All reports shall be certified by a responsible official pursuant to 401 KAR 52:020, Section 23. If continuous emission and opacity monitors are required by regulation or this permit, data shall be reported in accordance with the requirements of 401 KAR 59:005, General Provisions, Section 3(3). All deviations from permit requirements shall be clearly identified in the reports.
7. In accordance with the provisions of 401 KAR 50:055, Section 1, the owner or operator shall notify the Regional Office listed on the front of this permit concerning startups, shutdowns, or malfunctions as follows:
 - a. When emissions during any planned shutdowns and ensuing startups will exceed the standards, notification shall be made no later than three (3) days before the planned shutdown, or immediately following the decision to shut down, if the shutdown is due to events which could not have been foreseen three (3) days before the shutdown.
 - b. When emissions due to malfunctions, unplanned shutdowns and ensuing startups are or may be in excess of the standards, notification shall be made as promptly as possible by telephone (or other electronic media) and shall be submitted in writing upon request.
8. The permittee shall promptly report deviations from permit requirements, including those attributable to upset conditions as defined in the permit, the probable cause of such deviations, and any corrective actions or preventive measures taken shall be submitted to the Regional Office listed on the front of this permit. Where the underlying applicable requirement contains a definition of prompt or otherwise specifies a time frame for reporting deviations, that definition or time frame shall govern. Where the underlying applicable requirement does not identify a specific time frame for reporting deviations, prompt reporting, as required by Sections 1b-V, 3 and 4 of the *Cabinet Provisions and Procedures for Issuing Title V Permits* incorporated by reference in 401 KAR 52:020, Section 26, shall be defined as follows:
 - a. For emissions of a hazardous air pollutant or a toxic air pollutant (as identified in an applicable regulation) that continue for more than an hour in excess of permit requirements, the report must be made within 24 hours of the occurrence.
 - b. For emissions of any regulated air pollutant, excluding those listed in F.8.a., that continue for more than two hours in excess of permit requirements, the report must be made within 48 hours.
 - c. All deviations from permit requirements, including those previously reported, shall be included in the semiannual report required by F.6.
9. Pursuant to 401 KAR 52:020, Title V permits, Section 21, the permittee shall annually certify compliance with the terms and conditions contained in this permit, by completing and returning a Compliance Certification Form (DEP 7007CC) (or an alternative approved by the regional office) to the Regional Office listed on the front of this permit and the U.S. EPA in accordance with the following requirements:
 - a. Identification of the term or condition;
 - b. Compliance status of each term or condition of the permit;
 - c. Whether compliance was continuous or intermittent;

SECTION F - MONITORING, RECORDKEEPING, AND REPORTING REQUIREMENTS (CONTINUED)

- d. The method used for determining the compliance status for the source, currently and over the reporting period.
- e. For an emissions unit that was still under construction or which has not commenced operation at the end of the 12-month period covered by the annual compliance certification, the permittee shall indicate that the unit is under construction and that compliance with any applicable requirements will be demonstrated within the timeframes specified in the permit.
- f. The certification shall be submitted by January 30th of each year. Annual compliance certifications shall be sent to the following addresses:

Division for Air Quality
Frankfort Regional Office
300 Sower Blvd, 1st Floor
Frankfort, KY 40601

U.S. EPA Region 4
Air Enforcement Branch
Atlanta Federal Center
61 Forsyth St. SW
Atlanta, GA 30303-8960

- 10. In accordance with 401 KAR 52:020, Section 22, the permittee shall provide the Division with all information necessary to determine its subject emissions within 30 days of the date the Kentucky Emissions Inventory System (KYEIS) emissions survey is mailed to the permittee.

SECTION G - GENERAL PROVISIONS

1. General Compliance Requirements

- a. The permittee shall comply with all conditions of this permit. Noncompliance shall be a violation of 401 KAR 52:020, Section 3(1)(b), and a violation of Federal Statute 42 USC 7401 through 7671q (the Clean Air Act). Noncompliance with this permit is grounds for enforcement action including but not limited to termination, revocation and reissuance, revision or denial of a permit [Section 1a-3 of the *Cabinet Provisions and Procedures for Issuing Title V Permits* incorporated by reference in 401 KAR 52:020, Section 26].
- b. The filing of a request by the permittee for any permit revision, revocation, reissuance, or termination, or of a notification of a planned change or anticipated noncompliance, shall not stay any permit condition [Section 1a-6 of the *Cabinet Provisions and Procedures for Issuing Title V Permits* incorporated by reference in 401 KAR 52:020, Section 26].
- c. This permit may be revised, revoked, reopened and reissued, or terminated for cause in accordance with 401 KAR 52:020, Section 19. The permit will be reopened for cause and revised accordingly under the following circumstances:
 - (1) If additional applicable requirements become applicable to the source and the remaining permit term is three (3) years or longer. In this case, the reopening shall be completed no later than eighteen (18) months after promulgation of the applicable requirement. A reopening shall not be required if compliance with the applicable requirement is not required until after the date on which the permit is due to expire, unless this permit or any of its terms and conditions have been extended pursuant to 401 KAR 52:020, Section 12;
 - (2) The Cabinet or the United States Environmental Protection Agency (U.S. EPA) determines that the permit must be revised or revoked to assure compliance with the applicable requirements;
 - (3) The Cabinet or the U. S. EPA determines that the permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the permit;
 - (4) New requirements become applicable to a source subject to the Acid Rain Program.

Proceedings to reopen and reissue a permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of the permit for which cause to reopen exists. Reopenings shall be made as expeditiously as practicable. Reopenings shall not be initiated before a notice of intent to reopen is provided to the source by the Division, at least thirty (30) days in advance of the date the permit is to be reopened, except that the Division may provide a shorter time period in the case of an emergency.

- d. The permittee shall furnish information upon request of the Cabinet to determine if cause exists for modifying, revoking and reissuing, or terminating the permit; or to determine compliance with the conditions of this permit [Sections 1a- 7 and 8 of the *Cabinet Provisions and Procedures for Issuing Title V Permits* incorporated by reference in 401 KAR 52:020, Section 26].

SECTION G - GENERAL PROVISIONS (CONTINUED)

- e. Emission units described in this permit shall demonstrate compliance with applicable requirements if requested by the Division [401 KAR 52:020, Section 3(1)(c)].
- f. The permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to the permitting authority [401 KAR 52:020, Section 7(1)].
- g. Any condition or portion of this permit which becomes suspended or is ruled invalid as a result of any legal or other action shall not invalidate any other portion or condition of this permit [Section 1a-14 of the *Cabinet Provisions and Procedures for Issuing Title V Permits* incorporated by reference in 401 KAR 52:020, Section 26].
- h. The permittee shall not use as a defense in an enforcement action the contention that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance [Section 1a-4 of the *Cabinet Provisions and Procedures for Issuing Title V Permits* incorporated by reference in 401 KAR 52:020, Section 26].
- i. All emission limitations and standards contained in this permit shall be enforceable as a practical matter. All emission limitations and standards contained in this permit are enforceable by the U.S. EPA and citizens except for those specifically identified in this permit as state-origin requirements. [Section 1a-15 of the *Cabinet Provisions and Procedures for Issuing Title V Permits* incorporated by reference in 401 KAR 52:020, Section 26].
- j. This permit shall be subject to suspension if the permittee fails to pay all emissions fees within 90 days after the date of notice as specified in 401 KAR 50:038, Section 3(6) [Section 1a-10 of the *Cabinet Provisions and Procedures for Issuing Title V Permits* incorporated by reference in 401 KAR 52:020, Section 26].
- k. Nothing in this permit shall alter or affect the liability of the permittee for any violation of applicable requirements prior to or at the time of permit issuance [401 KAR 52:020, Section 11(3) b.].
- l. This permit does not convey property rights or exclusive privileges [Section 1a-9 of the *Cabinet Provisions and Procedures for Issuing Title V Permits* incorporated by reference in 401 KAR 52:020, Section 26].
- m. Issuance of this permit does not relieve the permittee from the responsibility of obtaining any other permits, licenses, or approvals required by the Cabinet or any other federal, state, or local agency.
- n. Nothing in this permit shall alter or affect the authority of U.S. EPA to obtain information pursuant to Federal Statute 42 USC 7414, Inspections, monitoring, and entry [401 KAR 52:020, Section 11(3) d.].

SECTION G - GENERAL PROVISIONS (CONTINUED)

- o. Nothing in this permit shall alter or affect the authority of U.S. EPA to impose emergency orders pursuant to Federal Statute 42 USC 7603, Emergency orders [401 KAR 52:020, Section 11(3) a.].
- p. This permit consolidates the authority of any previously issued PSD, NSR, or Synthetic Minor source preconstruction permit terms and conditions for various emission units and incorporates all requirements of those existing permits into one single permit for this source.
- q. Pursuant to 401 KAR 52:020, Section 11, a permit shield shall not protect the owner or operator from enforcement actions for violating an applicable requirement prior to or at the time of permit issuance. Compliance with the conditions of this permit shall be considered compliance with:
 - (1) Applicable requirements that are included and specifically identified in the permit; and
 - (2) Non-applicable requirements expressly identified in this permit.

2. Permit Expiration and Reapplication Requirements

- a. This permit shall remain in effect for a fixed term of five (5) years following the original date of issue. Permit expiration shall terminate the source's right to operate unless a timely and complete renewal application has been submitted to the Division at least six (6) months prior to the expiration date of the permit. Upon a timely and complete submittal, the authorization to operate within the terms and conditions of this permit, including any permit shield, shall remain in effect beyond the expiration date, until the renewal permit is issued or denied by the Division [401 KAR 52:020, Section 12].
- b. The authority to operate granted shall cease to apply if the source fails to submit additional information requested by the Division after the completeness determination has been made on any application, by whatever deadline the Division sets [401 KAR 52:020, Section 8(2)].

3. Permit Revisions

- a. A minor permit revision procedure may be used for permit revisions involving the use of economic incentive, marketable permit, emission trading, and other similar approaches, to the extent that these minor permit revision procedures are explicitly provided for in the State Implementation Plan (SIP) or in applicable requirements and meet the relevant requirements of 401 KAR 52:020, Section 14(2).
- b. This permit is not transferable by the permittee. Future owners and operators shall obtain a new permit from the Division for Air Quality. The new permit may be processed as an administrative amendment if no other change in this permit is necessary, and provided that a written agreement containing a specific date for transfer of permit responsibility coverage and liability between the current and new permittee has been submitted to the permitting authority within ten (10) days following the transfer.

SECTION G - GENERAL PROVISIONS (CONTINUED)**4. Construction, Start-Up, and Initial Compliance Demonstration Requirements**

No construction authorized by this permit V-21-013 R1.

5. Testing Requirements

- a. Pursuant to 401 KAR 50:045, Section 2, a source required to conduct a performance test shall submit a completed Compliance Test Protocol form, DEP form 6028, or a test protocol a source has developed for submission to other regulatory agencies, in a format approved by the cabinet, to the Division's Frankfort Central Office a minimum of sixty (60) days prior to the scheduled test date. Pursuant to 401 KAR 50:045, Section 7, the Division shall be notified of the actual test date at least thirty (30) days prior to the test.
- b. Pursuant to 401 KAR 50:045, Section 5, in order to demonstrate that a source is capable of complying with a standard at all times, any required performance test shall be conducted under normal conditions that are representative of the source's operations and create the highest rate of emissions. If [When] the maximum production rate represents a source's highest emissions rate and a performance test is conducted at less than the maximum production rate, a source shall be limited to a production rate of no greater than 110 percent of the average production rate during the performance tests. If and when the facility is capable of operation at the rate specified in the application, the source may retest to demonstrate compliance at the new production rate. The Division for Air Quality may waive these requirements on a case-by-case basis if the source demonstrates to the Division's satisfaction that the source is in compliance with all applicable requirements.
- c. Results of performance test(s) required by the permit shall be submitted to the Division by the source or its representative within forty-five days or sooner if required by an applicable standard, after the completion of the fieldwork.

6. Acid Rain Program Requirements

- a. If an applicable requirement of Federal Statute 42 USC 7401 through 7671q (the Clean Air Act) is more stringent than an applicable requirement promulgated pursuant to Federal Statute 42 USC 7651 through 7651o (Title IV of the Act), both provisions shall apply, and both shall be state and federally enforceable.
- b. The permittee shall comply with all applicable requirements and conditions of the Acid Rain Permit and the Phase II permit application (including the Phase II NO_x compliance plan and averaging plan, if applicable) incorporated into the Title V permit issued for this source. The source shall also comply with all requirements of any revised or future acid rain permit(s) issued to this source.

SECTION G - GENERAL PROVISIONS (CONTINUED)**7. Emergency Provisions**

- a. Pursuant to 401 KAR 52:020, Section 24(1), an emergency shall constitute an affirmative defense to an action brought for the noncompliance with the technology-based emission limitations if the permittee demonstrates through properly signed contemporaneous operating logs or relevant evidence that:
 - (1) An emergency occurred and the permittee can identify the cause of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During an emergency, the permittee took all reasonable steps to minimize levels of emissions that exceeded the emissions standards or other requirements in the permit; and
 - (4) Pursuant to 401 KAR 52:020, 401 KAR 50:055, and KRS 224.01-400, the permittee notified the Division as promptly as possible and submitted written notice of the emergency to the Division when emission limitations were exceeded due to an emergency. The notice shall include a description of the emergency, steps taken to mitigate emissions, and corrective actions taken.
 - (5) This requirement does not relieve the source of other local, state or federal notification requirements.
- b. Emergency conditions listed in General Condition G.7.a above are in addition to any emergency or upset provision(s) contained in an applicable requirement [401 KAR 52:020, Section 24(3)].
- c. In an enforcement proceeding, the permittee seeking to establish the occurrence of an emergency shall have the burden of proof [401 KAR 52:020, Section 24(2)].

8. Ozone Depleting Substances

- a. The permittee shall comply with the standards for recycling and emissions reduction pursuant to 40 CFR 82, Subpart F, except as provided for Motor Vehicle Air Conditioners (MVACs) in Subpart B:
 - (1) Persons opening appliances for maintenance, service, repair, or disposal shall comply with the required practices contained in 40 CFR 82.156.
 - (2) Equipment used during the maintenance, service, repair, or disposal of appliances shall comply with the standards for recycling and recovery equipment contained in 40 CFR 82.158.
 - (3) Persons performing maintenance, service, repair, or disposal of appliances shall be certified by an approved technician certification program pursuant to 40 CFR 82.161.
 - (4) Persons disposing of small appliances, MVACs, and MVAC-like appliances (as defined at 40 CFR 82.152) shall comply with the recordkeeping requirements pursuant to 40 CFR 82.166
 - (5) Persons owning commercial or industrial process refrigeration equipment shall comply with the leak repair requirements pursuant to 40 CFR 82.156.
 - (6) Owners/operators of appliances normally containing 50 or more pounds of refrigerant shall keep records of refrigerant purchased and added to such appliances pursuant to 40 CFR 82.166.

SECTION G - GENERAL PROVISIONS (CONTINUED)

- b. If the permittee performs service on motor (fleet) vehicle air conditioners containing ozone-depleting substances, the source shall comply with all applicable requirements as specified in 40 CFR 82, Subpart B, *Servicing of Motor Vehicle Air Conditioners*.

9. Risk Management Provisions

- a. The permittee shall comply with all applicable requirements of 401 KAR Chapter 68, Chemical Accident Prevention, which incorporates by reference 40 CFR Part 68, Risk Management Plan provisions. If required, the permittee shall comply with the Risk Management Program and submit a Risk Management Plan to U.S. EPA using the RMP* eSubmit software.
- b. If requested, submit additional relevant information to the Division or the U.S. EPA.

SECTION H - ALTERNATE OPERATING SCENARIOS

None

SECTION I - COMPLIANCE SCHEDULE

None