

NCP SUBPART J TECHNICAL NOTEBOOK A COMPANION TO THE NCP PRODUCT SCHEDULE

**NOVEMBER 2025
(11/17/2025)**

FOREWORD

The Environmental Protection Agency's (EPA) Office of Emergency Management (OEM) Regulations Implementation Division (RID) compiled the National Oil and Hazardous Substances Pollution Contingency Plan (NCP) Product Schedule Technical Notebook as a companion to the NCP Product Schedule. The NCP Product Schedule Technical Notebook contains a compilation of Subpart J required data, information, and testing results of listed products provided by product submitters.

For more information, please review Subpart J of the National Oil and Hazardous Substances Pollution Contingency Plan; Product Schedule Listing and Authorization of Use Requirements final rule effective December 11, 2023, located at <https://www.federalregister.gov/documents/2023/06/12/2023-11904/national-oil-and-hazardous-substances-pollution-contingency-plan-product-schedule-listing-and->.

On May 31, 2023, EPA finalized the amendments to Subpart J of the NCP. The regulatory amendments published on June 12, 2023 (88 FR 38280) provide a process to transition listed products from the current NCP Product Schedule to the new NCP Product Schedule. From December 11, 2023, Subpart J product submitters will have two years to retest their product and resubmit an application for listing. The 24-month transition period provides time to prepare and submit new packages according to amended testing and listing requirements and for EPA to review and make listing determinations. The transition period also allows for the continued availability of listed products to be accessible for planning and response activities.

All products listed on the NCP Product Schedule as of December 11, 2023, will remain conditionally listed until December 12, 2025, at which time all products that have not been submitted and listed on the NCP Product Schedule based on the amended test and listing criteria will be removed. Products will be transitioned from the current NCP Product Schedule to the new NCP Product Schedule prior to December 12, 2025, provided a new complete package is submitted in accordance with § 300.955(b), and EPA makes a determination to list the product on the new NCP Product Schedule.

Products listed on the NCP Subpart J Product Schedule prior to December 11, 2023, for which a new submission is not received or that do not meet the revised listing criteria will be removed from the NCP Subpart J Product Schedule at the end of the 24-month transition period on December 12, 2025.

Updates to the NCP Product Schedule Technical Notebooks, such as the addition of new products, or modifications and/or deletions of Product Schedule listed products, are indicated in **bold**.

NCP Product Schedule Technical Notebook users can navigate to all product data and information summaries, including all product's name(s), brand(s), and/or trademark(s), by category type, alphabetically, or categorically by product. For products conditionally listed through December 12, 2025, users can navigate to the product bulletins by category type (i.e., Bioremediation Agents, Dispersants, Miscellaneous Oil Spill Control Agents, Surface Collecting Agents, Surface Washing Agents). For products that have transitioned or listed under the new NCP Product Schedule, users can navigate to the product bulletins by category type (i.e., Bioremediation Agents, Dispersants, Herding Agents, Solidifiers, Surface Collecting Agents, Surface Washing Agents). Note: Under the new Subpart J rule, Miscellaneous Oil Spill Control Agent category was removed; and the Surface Collecting Agent category was renamed "Herding Agents." In addition, the new Subpart J rule includes the category Solidifiers.

For additional information, please leave a message on EPA's NCP Subpart J Information Line at (202) 260-2342.

Written requests may be mailed to:

Attention: NCP Product Schedule Manager
U.S. Environmental Protection Agency
1200 Pennsylvania Avenue NW
Mail Code: 5104-A, Room 1448K
William Jefferson Clinton North Building
Washington, DC 20460

Disclaimer: [PRODUCT NAME] is listed on the National Contingency Plan (NCP) Product Schedule. This listing does NOT mean that EPA approves, recommends, licenses, or certifies the use of [PRODUCT NAME] on an oil discharge. This listing means only that data have been submitted to EPA as required by Subpart J of the NCP. Only a Federal On-Scene Coordinator (OSC) may authorize use of this product in accordance with Subpart J of the NCP in response to an oil discharge.

NCP Product Schedule Products by Category

Products Conditionally Listed through December 12, 2025

Product Category	Number of Products
Bioremediation Agents (B)	29
Dispersants (D)	18
Miscellaneous Oil Spill Control Agents (M)	18
Surface Collecting Agents (S)	2
Surface Washing Agents (SW)	62
Total Products	129

New and Transitioned Products

Product Categories	Number of Products
Bioremediation Agents (B)	0
Dispersants (D)	4
Herding Agents (H)	0
Solidifiers (SO)	0
Surface Washing Agents (SW)	0
Total Products	4

All changes and additions to the NCP Product Schedule Technical Notebook are indicated in bold under the applicable product listing.

Changes to the Product Bulletins

New listing for Finasol OSR 52 (2025-D-004) under the final testing, listing, and authorization of use regulatory amendments for Subpart J of the NCP that were published in the Federal Register on June 12, 2023 ([88 FR 38280](#)) and effective on December 11, 2023.

Product Bulletin Changes Pending EPA Verification:

STEP ONE (B-43); SHAMANTRA GREEN (B-68); OIL SOLUTIONS POWDER (M-25); SIMPLE GREEN® (Water Based) (SW-15); PREMIER 99 (SW-12); and EO ALL PURPOSE SOAP-LAVENDER (SW-50).

Contact Information Could Not Be Verified (last attempt dates noted on product bulletin):

WMI-2000 (B-19); SYSTEM E.T. 20 (B-45); BET BIOPETRO (B-48); LAND AND SEA RESTORATION PRODUCT 001 (VELITE) (B-55); JE1058BS (B-58); PRO-ACT (B-62); DUALZORB® (B-65); ERGOFIT MICRO MIX AQUA (B-67); NEOS AB3000 (D-2); MARE CLEAN 200 (D-3); JD-109 (D-6); JD-2000™ (D-7); BIODISPERS (D-9); SAF-RON GOLD (D-12); ZI-400 (D-13); FFT-SOLUTION® (D-17); CIAGENT (M-17); WASTE-SET #3200® (M-19); WASTE-SET #3400® (M-20); RAPIDGRAB 2000™ (M-24); ELASTOL (M-26); NORSOREX® APX (M-30); CAS 100© (M-31); CN-110 (SW-9); DE-SOLV-IT INDUSTRIAL FORMULA (SW-11); NATURE'S WAY HS (SW-18); PETROTECH 25 (SW-21); DO-ALL #18 (SW-24); BG-CLEAN™ 401 (SW-32); E-SAFE© (SW-

33); SHEEN-MAGIC© (SW-34); PROCLEANS (SW-35); G-CLEAN OSC-1809 (SW-39); GREEN BEAST™ OIL SPILL & ODOR REMEDIATOR (SW-40); SOC-10 (SW-45); ENVIRONMENTAL 1 CRUDE OIL CLEANER (SW-47); SANDKLENE 950 (SW-48); DE-SOLV-IT CLEAN AWAY APC SUPER CONCENTRATE (SW-49); VERU-SOLVE™ MARINE 200 HP (SW-52); JEP-MARINE CLEAN (SW-52); ETHOS CLEAN (SW-58); OSR-10 (SW-59); EPA OIL FIELD SOLUTION™ (SW-61); and FORMULA 206-1x BIO-WASH™ (SW-66).

Note: Products are numbered as they are listed. For products conditionally listed through December 12, 2025, product numbering convention includes, for example, “B” for Bioremediation Agents and the sequential order of listing “19” or B-19. For products conditionally listed through December 12, 2023, numbering may not be consecutive when products are removed from the NCP Product Schedule. For example, Bioremediation Agents begin with B-19. Products numbered B-1 through B-18 were removed from the NCP Product Schedule.

Updated: 11/17/2025

NCP PRODUCT SCHEDULE TECHNICAL NOTEBOOK
TABLE OF CONTENTS: LISTING BY PRODUCT CATEGORY

TABLE OF CONTENTS: LISTING BY PRODUCT CATEGORY	v
BIOREMEDIATION AGENTS: TECHNICAL NOTEBOOK BULLETINS	1
WMI-2000.....	2
OPPENHEIMER FORMULA	5
MICRO-BLAZE® EMERGENCY LIQUID SPILL CONTROL	8
VB591™, VB997™, BINUTRIX®	12
STEP ONE	16
SYSTEM E.T. 20.....	20
BET BIOPETRO	24
OIL SPILL EATER II (OSE II).....	27
LAND AND SEA RESTORATION PRODUCT 001 (VELITE)	32
S-200C	35
SPILLREMEDI (MARINE)®	39
JE1058BS.....	42
BIOWORLD BIOREMEDIATION TREATMENT PRODUCTS (BIOWORLD BHTP).....	45
MUNOX SR®	49
SOIL RX	53
PRO-ACT	57
BIOREM-2000 OIL DIGESTER™.....	61
DRYLET™ MB BIO.....	65
DUALZORB®	68
REMEDIADE™	72
ERGOFIT MICROMIX AQUA	76
SHAMANTRA GREEN.....	81
SUMP SAFE BIO-RECLAIM.....	85
WASTE AWAY®	89
ACT TERRA FIRMA.....	93
PETROCLEAN™	98
ECOBIOCLEAN® 100 COSW.....	102
SPILL GENIE™ 3T	107
GHG ORGANIC.....	111
DISPERSANTS: TECHNICAL NOTEBOOK BULLETINS	115
COREXIT™ EC9527A	116
NEOS AB3000.....	120
MARE CLEAN 200.....	123
COREXIT™ EC9500A	126
DISPERSIT SPC 1000™.....	130
JD-109.....	133
JD-2000™	136
NOKOMIS 3-F4	139
BIODISPERS.....	142
SEA BRAT #4	145

SAF-RON GOLD	148
ZI-400	151
NOKOMIS 3-AA.....	154
ACCELL CLEAN® DWD	158
FFT-SOLUTION®	162
MARINE D-BLUE CLEAN™	166
COREXIT™ EC9500B	169
CHIMEC CHIMSPERSE 6000	173
ACCELL CLEAN® DWD 2.0	176
DASIC ECOSAFE OSD.....	184
FINASOL OSR 52 IBC	194
FINASOL OSR 52.....	203
MISCELLANEOUS OIL SPILL CONTROL AGENTS: TECHNICAL NOTEBOOK	
BULLETINS.....	212
PES-51	213
CIAGENT	218
ZYME-FLOW.....	221
WASTE-SET #3200®	224
WASTE-SET #3400®	227
PX-700®	230
ALSOCUP	233
RAPIDGRAB 2000™	236
OIL SOLUTIONS POWDER.....	239
ELASTOL.....	242
OIL BOND®	245
AQUAFLEX® (Open-Cell Elastomeric Sorbents)	248
GELCO 200	251
NORSOREX® APX.....	255
CAS 100©	260
S-200 OILGONE®	263
HYDRO-BOND™.....	266
AQUAPAL® (Open-Cell polyolefin foam Sorbent).....	269
HERDING AGENTS (formerly known as surface collecting agents): TECHNICAL	
NOTEBOOK BULLETINS	272
THICKSLICK 6535.....	273
SILTECH OP-40.....	276
SURFACE WASHING AGENTS: TECHNICAL NOTEBOOK BULLETINS.....	
TOPSALL #30 (aka, SUPERALL #38).....	280
CN-110.....	283
COREXIT™ EC9580A	286
DE-SOLV-IT INDUSTRIAL FORMULA.....	289
PREMIER 99	292
SIMPLE GREEN®	295
AQUACLEAN.....	298

NATURE’S WAY HS	301
CYTOSOL	304
BIOSOLVE® PINKWATER®	308
PETROTECH 25	311
PETRO-CLEAN	314
DO-ALL #18.....	317
SC-1000®	320
GOLD CREW SW	323
NALE-IT	326
F-500	329
ENVIROCLEAN	332
BG-CLEAN™ 401	335
E-SAFE®	338
SHEEN-MAGIC®	341
PROCLEANS	344
SPILLCLEAN.....	347
TXCHEM HE-1000™	351
NOKOMIS 5-W.....	354
G-CLEAN OSC-1809.....	357
GREEN BEAST™ OIL SPILL & ODOR REMEDIATOR.....	360
TULXA	363
MARINE GREEN CLEAN™	366
MARINE GREEN CLEAN PLUS™	369
CLEANGREEN® PLANET WASH.....	372
SOC 10 (SURFACE OIL CLEANER).....	375
BIOGRASS EXTRA®	378
ENVIRONMENTAL 1 CRUDE OIL CLEANER	381
SANDKLENE 950.....	384
DE-SOLV-IT CLEAN AWAY APC SUPER CONCENTRATE	387
EO ALL PURPOSE SOAP-LAVENDER.....	390
DYNAMIC GREEN™	393
VERU-SOLVE™ MARINE 200 HP	396
NATURAMA G3 A-5	399
SAFE KLEEN.....	402
CORIBA 700 SR	405
CORIBA 713 SR	408
JEP-MARINE CLEAN.....	411
ETHOS CLEAN	414
OSR-10	417
ACCELL CLEAN® SWA.....	420
EPA OIL FIELD SOLUTION™	423
PETROMAX PSC 3	426
GREEN TECHNOLOGIES SOLUTIONS-OIL RECOVERY (GTS-OR).....	429
SIMPLE GREEN® 2013 Reformulation.....	432
NONTOX™ SURFACE WASHING AGENT	435

FORMULA 206-1x BIO-WASH™.....	438
RHAMNOWASH 10.....	441
ADP-7.....	444
WATER WORKS™ HEAVY DUTY DEGREASER CONCENTRATE.....	447
X4JH2000.....	450
TASMANIA C-CLENZ.....	453
GOLD CREW® TC.....	457
DE-OIL-IT INDUSTRIAL STRENGTH CONCENTRATE.....	460
ECOGREEN.....	463
ABLUOL OSASA H/C.....	466

BIOREMEDIATION AGENTS: **TECHNICAL NOTEBOOK BULLETINS**

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**9/07/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #B-19
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JUNE 18, 1990
REVISED LISTING DATE: JANUARY 11, 1996
“WMI-2000”

I. NAME, BRAND, OR TRADEMARK

WMI-2000

Type of Product: Biological Additive

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

WMI International, Inc.

2104 Brentwood Drive

Houston, TX 77019

Phone: updated information required

Mobile: updated information required

Fax: updated information required

E-mail: updated information required

or teri@oxygenorchard.com

(Mr. Joseph F. Jennings, President)

Mailing Address

WMI International, Inc.

P.O. Box 130583

Houston, TX 77219

(Mr. Joseph F. Jennings, President)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

WMI International, Inc.

2104 Brentwood Drive

Houston, TX 77019

Phone: updated information required

Mobile: updated information required

Fax: updated information required

E-mail: updated information required

or teri@oxygenorchard.com

(Mr. Joseph F. Jennings, President)

Mailing Address

WMI International, Inc.

P.O. Box 130583

Houston, TX 77219

(Mr. Joseph F. Jennings, President)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: WMI-2000 is non-flammable.

2. Ventilation: Avoid breathing dust or aerosol due to possibility of sensitization. Use adequate ventilation.

3. Skin and eye contact; protective clothing; treatment in case of contact: Minimize contact with eyes, skin, and clothing. Wash hands thoroughly after handling culture.

4.a. Maximum storage temperature: 100°F

4.b. Minimum storage temperature: 35°F

4.c. Optimum storage temperature range: 45°F - 90°F

Store in a cool, dry location. Keep partially-used containers tightly closed. Prolonged exposure

to high temperature and humidity, may lower activity of product.
 4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

The shelf life of WMI-2000 is 2 years if stored at ambient temperatures

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: The culture should be activated for 2 hours in water, when applicable. Conditions for use vary depending on substrate concentration and type, pH, temperature, availability of nutrients, oxygen content, and liquid medium (static or flowing).
2. Concentration/Application Rate: Inoculation concentration is 5-9 billion spores per gram.
3. Conditions for Use: Temperature requirements are between 35°F and 100°F. The optimum dissolved oxygen content is 2 ppm at the sludge-to-water interface. Nitrogen and phosphorous are key nutrients which promote cultural growth, and should be maintained at concentrations of 15-20 ppm and 2.5-5 ppm, respectively. The optimum pH range is between 7.0 and 8.0.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATIC S (ppm)	28 DAYS
0	CONTROL	2626.7	0	1850.0	0
	NUTRIENT	2763.3	0	2030.0	0
	WMI-2000	2453.3	0	1880.0	0
7	CONTROL	2246.7	0	1823.3	0
	NUTRIENT	1920.0	0	1666.7	0
	WMI-2000	1243.3	0	1456.7	0
28	CONTROL	2240.0	14.7	1866.7	-0.9
	NUTRIENT	1210.0	56.2	1480.0	27.0
	WMI-2000	973.3	60.3	1253.0	33.3

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Nutrient</u>	<u>Product (WMI-2000)</u>
0%	25%	44%

b. Toxicity: NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentage in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additives:

Optimum pH: 7.0

Optimum temperature: 45°F - 90°F

Optimum salinity: Fresh water to sea water

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: 6.0 - 8.0

Temperature: 40°F - 120°F

Salinity range: Fresh to sea water

4. Special nutrient requirements: None

5. Test results regarding the determination of the following:

Salmonella - Negative

Fecal Coliform - Negative

Shigella - Negative

Staphylococcus Coagulase positive - Negative

Beta hemolytic Streptococcus - Negative

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN #B-36
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 17, 1991
REVISED LISTING DATE: OCTOBER 6, 1996
“OPPENHEIMER FORMULA”
(aka, THE OPPENHEIMER FORMULA I, MICROSORB SC)

I. NAME, BRAND, OR TRADEMARK
OPPENHEIMER FORMULA
(aka, THE OPPENHEIMER FORMULA I, MICROSORB SC)
Type of Product: Biological Additive

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Oppenheimer Biotechnology, Inc.
P.O. Box 1490
Pflugerville, TX 78691-1490
Phone: (512) 474-1016
E-mail: jen.neve@obio.com
Website: www.obio.com
(Ms. Jen Neve)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Oppenheimer Biotechnology, Inc.
P.O. Box 1490
Pflugerville, TX 78691-1490
Phone: (512) 474-1016
E-mail: jen.neve@obio.com
Website: www.obio.com
(Ms. Jen Neve)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable
2. Ventilation: Special ventilation is not required. Treat product as an hygroscopic powder. In closed spaces use dust protective measures.
3. Skin and eye contact; protective clothing; treatment in case of contact: The application of the dry powder requires the usual precautions of a dust irritant to membranes. The material is easily removed by washing or flushing, and in confined areas or use, a protective mask and eye glasses are recommended.
- 4.a. Maximum storage temperature: 130°F
- 4.b. Minimum storage temperature: 32°F
- 4.c. Optimum storage temperature range: 82°F

V. SHELF LIFE

The shelf life of the product is approximately 5 year.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Optimal application is by powder seeding directly at the source of oil contamination. Application over larger areas of water surface can be accomplished by aerial powder dusting, spraying a water mixture of nutrients/formula over the oil area, or by dusting with mechanical powder pumps.
2. Concentration/Application Rate: The application rate at the source oil slick is 1 pound per cubic yard of oil. In the open sea slick, the basic application rate is 10 pounds per acre, but this may vary in different situations related to speed of clean up. In estuaries, a larger biomass is recommended and may be at a rate of up to 100 pounds per acre, depending on the oil type and concentration. Heavier oils may require a higher biomass than light oils.
3. Conditions for Use: THE OPPENHEIMER FORMULA may be used in a wide range of environmental conditions of temperature and salinities, ranging from fresh to 100 ppt salts. The formula is especially valuable in grass flats, marshes and the open sea. It has also proved effective in soil and fresh water oil clean up and municipal waste treatment, septic tanks and grease traps.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATIC S (ppm)	28 DAYS
0	CONTROL	29965.2	0	5620.5	0
	NUTRIENT	31494.8	0	6660.2	0
	OPPENHEIMER	31140.6	0	5528.2	0
7	CONTROL	30101.5	0	5610.1	0
	NUTRIENT	8073.9	0	5086.6	0
	OPPENHEIMER	5019.7	0	4338.9	0
28	CONTROL	28785.6	3.9	5512.7	1.9
	NUTRIENT	706.2	97.8	4863.7	27.0
	OPPENHEIMER	3396.8	89.1	3417.8	38.2

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Nutrient</u>	<u>Product (Oppenheimer)</u>
- 6.4 %	50.9 %	10.4 %

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentage in the composition:

Natural, ubiquitous, hydrocarbon-oxidizing, microorganisms for use in removing hydrocarbons and organic materials from soils, fresh and salt waters by natural oxidative pathways.

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 7.6

Temperature: 82°F

Salinity: Fresh water to 20 percent salts

Optimal: 0.5 to 3.5%

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: 5.5-11

Temperature: 32°F-140°F

Salinity: Fresh to 15%

4. Special nutrient requirements: NA

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: <90/100 ml

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS OF HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN #B-41
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: DECEMBER 18, 1991
REVISED LISTING DATE: JANUARY 21, 1997
“MICRO-BLAZE® EMERGENCY LIQUID SPILL CONTROL”

I. NAME, BRAND, OR TRADEMARK
MICRO-BLAZE® EMERGENCY LIQUID SPILL CONTROL
Type of Product: Biological Additive

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Verde Environmental, Inc.
9223 Eastex Freeway
Houston, TX 77093
Phone: (713) 691-6468
(800) 626-6598
Fax: (713) 691-2331
Website: www.micro-blaze.com
E-mail: bscogin@micro-blaze.com
(Mr. William L. Scogin)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Verde Environmental, Inc.
9223 Eastex Freeway
Houston, TX 77093
Phone: (713) 691-6468
(800) 626-6598
Fax: (713) 691-2331
Website: www.micro-blaze.com
E-mail: bscogin@micro-blaze.com
(Mr. William L. Scogin)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable
2. Ventilation: Normal room ventilation
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid eye contact. Wear protective gloves, and wash hands with soap and water after handling the product. Wash contaminated clothing and footwear before reuse.
4. Optimum Storage Conditions:
 - 4.a. Maximum storage temperature: 120°F
 - 4.b. Minimum storage temperature: 35°F
 - 4.c. Optimum storage range temperature: NA
 - 4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

Minimum 10 years, with proper storage, in original containers. Freezing will not kill these microbes; however, extreme heat (over 180°F) for long periods of time will kill the microbes.

VI. RECOMMENDED APPLICATION PROCEDURE

MICRO-BLAZE® EMERGENCY LIQUID SPILL CONTROL is a liquid formulation of several microbial strains, surfactants, and nutrients designed to bioremediate organics and hydrocarbons in soil and water as well as control odors.

1. Application Method: Use normal spray equipment, fire or response equipment, eductor setups, water trucks, etc. as methods of application. Mix MICRO-BLAZE® EMERGENCY LIQUID SPILL CONTROL/water mixture with contaminated soils and liquids thoroughly for maximum contact. Pick up treated contamination after volatile hazard has been negated per local regulatory parameters.

For general bioremediation: For in-situ soils, mix MICRO-BLAZE® EMERGENCY LIQUID SPILL CONTROL/water mixture can be tilled into the contaminated area. For shallower contamination, areas can be over sprayed with normal spray equipment, eductor setups, water trucks, etc. For deeper contamination, application can be applied through underground setups using perforated piping per regulatory recommendations. For wastewater and other operational by-product sludges and soils extracted from contaminated areas, a bioslurry or bioreactor can be setup using MICRO-BLAZE® EMERGENCY LIQUID SPILL CONTROL and water in the process.

2. Concentration/Application Rate: For more viscous or less hazardous contamination, apply MICRO-BLAZE® EMERGENCY LIQUID SPILL CONTROL at a 3% solution mixed with water (3 parts MICRO-BLAZE® EMERGENCY LIQUID SPILL CONTROL, 97 parts water). When bioremediating soils, generally, per every 10 cubic yards of contaminated soils, use one gallon of concentrate, diluted with water according to contamination type.

3. Conditions for Use: Water Salinity: Can be mixed with any fresh, brackish or brine. However, brine reduces the effectiveness by 10%.

Water Temperature: 35°F - 180°F

pH: 4 to 11.5

Temperature: 32°F - 120°F

Nutrient Requirements: Nutrients for microbes are included in product. However, for longer-term bioremediation projects, additional applications of bio-catalyst may be added to boost microbial activity.

Type and Ages of Pollutants: For use on organics and hydrocarbon-based materials. These strains of bacteria provide the capability of biodegrading various straight chained, branched chained, aromatic and polynuclear aromatic hydrocarbons found in diesel and other fuels. Age of contamination is not a factor as much as its density. Tar-like substances may need to be cut for timely remediation.

VII. TOXICITY AND EFFECTIVENESS

Non-toxic, naturally-occurring spore-forming microorganisms common to soil and water. Non-pathogenic, certified by count; will not mutate.

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300,900) Federal Register September 15, 1994.

Microbiological Results - Average

Day 0 - 1.7×10^9 Day 7 - 8.43×10^8 Day 28 - 5.2×10^7

The organisms in this product convert to a spore state (dormant) to survive an unfavorable environment and will reactivate upon favorable conditions. Documentation available from Verde Environmental.

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REP/PROD	ALKANES (ppm)	28 DAYS	AROMATIC S (ppm)	28 DAYS
0	CONTROL	31258.6	0	973	0
	NUTRIENT	28251.8	0	976.6	0
	PRODUCT	29548.9	0	1081.2	0
	CONTROL	31401.73	0	990.5	0
7	NUTRIENT	20728.3	26.6	619.1	36.6
	PRODUCT	12870.5	56.4	496.3	54.1
	CONTROL	32465.8	0	925.7	0
28	NUTRIENT	1787.2	93.7	722.6	26.0
	PRODUCT	1758.2	94.1	566.9	47.6

Alkanes showed significant reductions with aromatic components less dramatic but still significant.

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Nutrient</u>	<u>Product (MICRO-BLAZE®)</u>
<1%	17.6%	12%

CONCLUSIONS: The MICRO-BLAZE® EMERGENCY LIQUID SPILL CONTROL product shows an initial rapid consumption of all measured hydrocarbons at seven (7) days. This rate apparently slows over 28-day period in a closed environment which may be due to a change in the environment of the flask due to the rapid degradation rates. Because of the high microbial population at the end of the test, it is to be assumed that the quantity of metabolites might account for the increased weight as determined by the gravimetric analysis.

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentage in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, salinity ranges for use of the additive:

pH: 7.5

Temperature: 45°F - 105°F

Salinity: 0-10%

3. Minimum and maximum pH, temperature, salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: <5.9, >9.0

Temperature: <32°F, >180°F

Salinity: <0%, 10%

4. Special nutrient requirements: None

5. Test results regarding the determination of the presence of the following:

Product is determined to be free of gram negative contamination.

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS OF HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN #B-42
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JANUARY 3, 1992
REVISED LISTING DATE: FEBRUARY 5, 1997
UPDATED LISTING LETTER: OCTOBER 7, 2020
“VB591™, VB997™, BINUTRIX®”

I. NAME, BRAND, OR TRADEMARK

VB591™, VB997™, BINUTRIX®

Type of Product: Biological Additive (patented, partial encapsulated oleophilic (oil-loving) nutrient; a nutrient additive that contains no microorganisms)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

BioNutraTech Inc.

13647 Pemberwick Park Lane

Houston, TX 77070

Phone: (800) 567-5432

Phone: (281) 354-5900

E-mail: shruza@bionutratech.com

Website: www.bionutratech.com

(Ms. Sandra L. Hruza)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

BioNutraTech Inc.

13647 Pemberwick Park Lane

Houston, TX 77070

Phone: (800) 567-5432

Phone: (281) 354-5900

E-mail: shruza@bionutratech.com

Website: www.bionutratech.com

(Ms. Sandra L. Hruza)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable

2. Ventilation: Normal ventilation is adequate.

3. Skin and eye contact; protective clothing; treatment in case of contact: Normal precautions and protective equipment for handling any type of powder, such as dust protectors and eye shield. Avoid contact with eyes and do not take internally. Upon contact with eyes, flush with water immediately for a minimum of 15 minutes. If redness or irritation continues, contact a physician. Avoid breathing dust.

4.a. Maximum storage temperature: >140°F

4.b. Minimum storage temperature: NA

4.c. Optimum storage temperature range: 50°F to 80°F

4.d. Temperature phase separations and chemical changes: NA

V. SHELF LIFE

The shelf life is approximately three years if kept dry. Store in dry location and avoid contact with moisture. Prolonged storage may result in the formation of soft clumps, which are easily broken by mechanical disruption.

VI. RECOMMENDED APPLICATION PROCEDURE

VB591™, VB997™, BINUTRIX® is a powder, and can be applied using conventional powder spraying equipment. No pre-mixing or dilution is required.

1. Application Method: Application for localized spills can be done using hand-held pressurized dust blowers. For inland waterways, ship channels, marinas or coastal wetlands, large dust blowers mounted on barges or ships can be employed to apply the product. Application by aircraft using conventional dust spraying systems is recommended for treatment of large uncontained spreading spills or spills in open waters or at sea.

2. Concentration/Application Rate: Recommended initial application rate is 5 to 15 pounds of VB591™, VB997™, BINUTRIX® per barrel of spilled oil. Follow-up applications at 48 to 72 hour intervals should be adjusted to allow for reduction in oil due to clean-up activities and natural loss by evaporation, droplet formation and dispersion and microbial activity. Applications should not exceed 250 pounds per acre per application.

3. Conditions for Use: VB591™, VB997™, BINUTRIX® should be applied to spilled oil as soon as possible following spillage to stimulate natural oil utilizing microbial populations to maximize biodegradation activity. Application of VB591™, VB997™, BINUTRIX® to spilled oil does not significantly alter the physical consistency of the spilled oil, and as such will not adversely affect conventional cleanup activities, nor will conventional and removal activities adversely affect the activity of VB591™, VB997™, BINUTRIX®. Dispose of waste in accordance with local, state, and federal regulations. Information regarding use of VB591™, VB997™, BINUTRIX® in conjunction with chemical dispersing agents is at present not available.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	31041.7	0	973.1	0
	NUTRIENT	28251.8	0	976.6	0
	VB591™, VB997™, BINUTRIX®	28813.8	0	932.8	0

7	CONTROL	31436.33	0	990.5	0
	NUTRIENT	20728.3	26.6	619.1	36.6
	VB591™, VB997™, BINUTRIX®	14637.4	49.2	733.1	21.4
28	CONTROL	32465.8	0	925.7	0
	NUTRIENT	1787.2	93.7	722.6	26.0
	VB591™, VB997™, BINUTRIX®	937.97	96.8	290.8	73.1

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Nutrient</u>	<u>Product</u>
<1%	17.6%	18.0%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

VB591™, VB997™, BINUTRIX® is an oleophilic nutrient additive and contains no preserved natural or mutated microorganisms of any type.

1. Listing of all microorganisms by species and percentage in the composition: None
2. Optimum pH, temperature, and salinity ranges for use of the additive: VB591™, VB997™, BINUTRIX® may be used under any conditions where natural populations of oil-degrading microbes are active.

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: NA

Temperature: NA

Salinity: NA

4. Special nutrient requirements: None

5. Test results regarding the determination of the presence of the following:

Salmonella: NA

Fecal coliform: NA

Shigella: NA

Staphylococcus coagulase positive: NA

Beta hemolytic Streptococci: NA

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS OF HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS
NA

LISTING CHANGES PENDING;
VERIFICATION BY MANUFACTURER AND EPA REQUIRED

TECHNICAL PRODUCT BULLETIN #B-43
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: MARCH 12, 1992
REVISED LISTING DATE: MARCH 21, 1997
“STEP ONE”
(aka, B&S INDUSTRIAL)

I. NAME, BRAND, OR TRADEMARK
STEP ONE
(aka, B&S INDUSTRIAL)
Type of Product: Biological Additive

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
B&S Research, Inc.
4345 Highway 21
Embarrass, MN 55732
Phone: (218) 984-3757
Fax: (218) 984-3212
E-mail: farmforprofit@frontier.com
(Mr. H. W. Lashmett)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS	
B&S Research, Inc.	Bioremediation International
4345 Highway 21	4345 Highway 21
Embarrass, MN 55732	Embarrass, MN 55732
Phone: (218) 984-3757	Phone: (218) 984-3757
Fax: (218) 984-3212	Fax: (218) 984-3212
E-mail: farmforprofit@frontier.com	E-mail: farmforprofit@frontier.com
(Mr. H. W. Lashmett)	(Mr. H. W. Lashmett)

Farm for Profit Research and Development
4345 Highway 21
Embarrass, MN 55732
Phone: (800) 232-7692
Fax: (218) 984-3212
E-mail: farmforprofit@frontier.com
(Mr. H. W. Lashmett)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: None
2. Ventilation: Normal ventilation is adequate
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid contact with

skin, especially when there are open wounds. In case of skin contact, wash with soapy water. The use of protective gloves is recommended. Avoid contact with eyes. In case of eye contact, immediately flush eyes with plenty of water continuously for at least 15 minutes. Consult a physician. The use of protective goggles is recommended. Avoid inhalation and ingestion. It is recommended that workers wear dust mask and not eat or smoke while handling the product(s).

4.a. Maximum storage temperature: 90°F

4.b. Minimum storage temperature: -30°F

4.c. Optimum storage temperature range: 32°F to 70°F

4.d. Temperature phase separations and chemical changes: NA

V. SHELF LIFE

Over 3 years

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Components of the product STEP ONE (BC101) and STEP ONE (MSE2.5) are only sold together. B&S Research will make application recommendations based on contamination and ppm of contamination at time of purchase order and employ specified application methods (spray, plowing, agitation, etc.) appropriate for a particular situation.

2. Concentration/Application Rate: Nominally, the STEP ONE water mixture can be used on most hydrocarbons, including crude and refined petroleum products, pesticides, etc., on land, fresh water or ocean water. Laboratory tests also indicate effectiveness in destruction of PCB's. In certain circumstances, B&S Research, Inc. may require laboratory soil and water contamination tests before the product may be used (see VI 1. above).

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED %	TOTAL MEAN	RED %
	3 REPS/PROD.	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	29959.5		5391.8	
	NUTRIENT	29008.5		5163.0	
	STEP ONE	30477.8		5499.8	
7	CONTROL	33471.3		5720.9	
	NUTRIENT	22723.7		5050.1	
	STEP ONE	24196.8		3110.2	
28	CONTROL	30997.4	0.0 %	5388.9	0.0 %
	NUTRIENT	1103.9	96.19%	4582.4	11.23%

DAYS	PRODUCT	TOTAL MEAN	RED %	TOTAL MEAN	RED %
	3 REPS/PROD.	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
	STEP ONE	17059.4	44.03%	2501.9	54.51%

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Nutrient</u>	<u>Product (STEP ONE)</u>
0%	19%	51%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentages in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 6-8

Temperature: 70°F to 90°F

Salinity: Fresh or salt (ocean <110 ppm) water, land or dry surfaces

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: <5 or <9, (apply neutralizing agents -- lime or P205)

Temperature: <50°F or >135°F

Salinity: <0 or >110 ppm

4. Special nutrient requirements: None

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

1. Flash Point: >212°F

2. Pour Point: -7°F

3. Viscosity: 2.8 cSt @ 50°F

3.5 cSt @ 32°F

5.9 cSt @ -4°F

4. Specific Gravity: 1.03 @ 59°F

5. pH: 7.2 (1:2.5:80 BC101:MSE2.5:water mixture)

6. Chemical Name and Percentage by Weight of the Total Formulation: CONFIDENTIAL

7. Surface Active Agents: Noedal

8. Solvents: None

9. Additives: Phosphoric acid as P205

3% emulsifier <.5% by weight

10. Solubility: Infinite

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration</u>
Arsenic	<0.0200
Cadmium	<0.0030
Chromium	0.0859
Copper	0.0177
Lead	0.0090
Mercury	0.0002
Nickel	<0.0080
Zinc	0.0602
Cyanide	0.2830
Chlorinated Hydrocarbons	<0.0050

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**8/09/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #B-45
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JANUARY 28, 1993
REVISED LISTING DATE: NOVEMBER 14, 1995
“SYSTEM E.T. 20”

**I. NAME, BRAND, OR TRADEMARK
SYSTEM E.T. 20**

Type of Product: Biological Additive
(formerly MCW.B 20)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Environmental Restoration Services

9211 Lakewood Drive
Windsor, CA 95492
E-mail: ERS.BTI@gmail.com
Phone: (619) 253-0664
(Mr. John Chase)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Environmental Restoration Services

14384 Highland Valley Road
Escondido, CA 92025
E-mail: ERS.BTI@gmail.com
Phone: (619) 253-0664
(Mr. John Chase)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: SYSTEM E. T. 20 is non-flammable
2. Ventilation: No special ventilation is required under normal use.
3. Skin and eye contact; protective clothing; treatment in case of contact: In its primary form, no special handling or storage is required. Avoid excessive inhalation, and protect the nose and mouth with a dust protection mask. Wear protective gloves, and wash hands with soap and water after handling the product.
- 4.a. Maximum storage temperature:
- 4.b. Minimum storage temperature:
- 4.c. Optimum storage temperature range: 4°C - 20°C (39°F - 68°F). Place in a dry area, shaded from sunlight.
- 4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

2 years if maintained at 4°C (39°F).

VI. RECOMMENDED APPLICATION PROCEDURE

SYSTEM E. T. 20 can be used on a broad range of hydrocarbon compounds (including PAH's) found in open and closed water systems (salt or fresh) or in soil (beach, sands, or inland soil types). SYSTEM E.T. 20 protocols can be used with indigenous and introduced bacteria. SYSTEM E.T. 20 is an oleophilic, non-water soluble nutrient, which releases nitrogen and phosphorous enzymatically, thus allowing SYSTEM E.T. 20 to be used in water and soil applications including: conditions requiring fast degradation rates due to regulations, limited space or cost; under conditions where weathered or heavy oils, sludges or PAH's exist that require consistently high populations of hydrocarbon degrading bacteria to metabolize these long or more complex carbon chains; tropical or sub-tropical conditions that support large, indigenous, non-beneficial bacterial populations that would otherwise dilute the effectiveness of standard bioaugmentation approaches; aqueous conditions in which soluble or time release nutrient compounds would be washed away or diluted, i.e., beaches, frequent rains, floods, streams, stream banks, estuaries and areas affected by tides; sensitive environmental conditions that demand low or no toxicity; toxicity in soil or water during bioremediation may be stimulated by adding broadly available nutrients which may activate disease carrying bacilli or pathogens; controlled nutrient release to SYSTEM E. T. 20 bacteria prevents over-nitrification; conditions requiring the elimination of oil discoloration caused by the presence of polar fractions; and conditions where salt water conditions exist or where only salt water is available for bacteria application.

1. Application Methods:

Biopile	Land farm	Pump and Treat
Bioreactor	Bio slurry	
In situ	Windrow	

Topical application to discolored rocks or soil.

Topical application to beaches.

2. Concentration/Application Rate: Concentration and rate of application will vary from site to site depending upon the type of contaminant and the area contaminated. Contact QET for specific information.

3. Conditions for Use: Before applying SYSTEM E. T. 20, QET recommends that the site be evaluated for its physical and chemical soil characteristics (i.e., pH, salinity, conductivity, physical parameters, moisture content, hydrocarbon type and concentration, nitrogen content, etc.), and toxicity of both the soil and the contaminant, by biological screening tests.

Basic biological requirements of SYSTEM E. T. 20, site conditions and SYSTEM E. T. 20 capabilities dictate the appropriate procedures for application of SYSTEM E. T. 20.

Biological requirements for SYSTEM E. T. 20 bacteria are nutrients, adequate oxygen supply, hydrocarbon food source, neutral pH and a 15% minimum moisture level for soil remediation applications.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATIC S (ppm)	28 DAYS
0	CONTROL	29959.5	0	5391.8	0
	NUTRIENT	29008.5	0	5163.0	0
	SYSTEM E.T. 20	30476.1	0	5311.3	0
7	CONTROL	33471.3	0	5720.9	0
	NUTRIENT	22723.7	0	5050.1	0
	SYSTEM E.T. 20	3837.1	0	2928.8	0
28	CONTROL	30997.4	0	5383.9	0.2
	NUTRIENT	1103.9	96.2	4582.4	11.2
	SYSTEM E.T. 20	261.9	99.1	1188.0	77.0

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control
0%

Nutrient
19%

Product (SYSTEM E.T. 20)
18%

b. Toxicity:
NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentage in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 7.5, (6.5 to 8.5)

Temperature: 4°C to 35°C (39°F to 95°F)

Salinity: Fresh to 2.5% (average ocean salt level)

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: <6.5 and >8.5

Temperature: <5°C and >35°C (<41°F and >95°F)

Salinity: >3%

4. Special nutrient requirements: Recommendation is for a non-soluble nutrient. The specific types of nutrients will be dependent on the site requirements.

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative
Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES
NA

X. ANALYSIS OF HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS
NA

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**5/18/2006
7/27/2022**

TECHNICAL PRODUCT BULLETIN #B-48
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: NOVEMBER 10, 1993
REVISED LISTING DATE: AUGUST 31, 2000
“BET BIOPETRO”

**I. NAME, BRAND, OR TRADEMARK
BET BIOPETRO**

Type of Product: Biological Additive
(formerly BET BIOPETRO HEAVY)

**II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
BioEnviroTech**

ADDRESS: updated information required
PHONE: updated information required
(Mr. Warren Butler)

**III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
BioEnviroTech**

ADDRESS: updated information required
PHONE: updated information required
(Mr. Warren Butler)

**IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD
APPLICATION**

1. Flammability: Non-Flammable
2. Ventilation: Normal ventilation
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid eye and skin contact. In case of eye contact, flush eyes with water or eyewash, and refrain from rubbing. For skin contact, wash with mild soap and apply hand cream if itching or redness occurs. Avoid inhalation. In case of inhalation, seek fresh air. Repeated inhalation has been associated with respiratory allergy in some persons. Such allergic individuals should wear protective clothing and eye goggles. In enclosed buildings, workers should wear single use nuisance dust masks appropriate for fine particulate dust. In outdoor field applications, no dust mask is required.
- 4.a. Maximum storage temperature: 105°F
- 4.b. Minimum storage temperature: 32°F
- 4.c. Optimum storage temperature range: 50°F to 75°F
- 4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

More than 3 years in unopened original shipping container, stored in cool dry area.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: BET BIOPETRO is a powder containing granules of bacterial product formulated to provide performance in the bioremediation of heavy refined and crude hydrocarbon contaminants in both soil and water environments.

Application procedure and treatment schedule will vary with specific environmental conditions and bioremediation requirements. Contact BET for specific technical advice.

2. Concentration/Application Rate: Dosage will vary with specific environmental conditions and bioremediation requirements. Contact BET for specific technical advice.

3. Conditions for Use: BET BIOPETRO should be used at temperatures in the range of 45°F to 100°F, pH range of 5.5 to 8.5, and dissolved oxygen level of 3 to 5 mg/l. The product is effective in both salt and fresh waters. However, where extreme salinity is projected, testing and evaluation of the bacteria in bioremediation are advised. BET BIOPETRO cultures exhibit some resistance to toxic shocks from strong chemicals. Nonetheless, highly chlorinated compounds, acids, caustics, disinfectants, germicides, and chlorine will render the cultures ineffective, just like other bacteria. Where such chemicals are anticipated, testing and evaluation of the bacteria in bioremediation are advised.

BET BIOPETRO cultures require supplemental nutrients for optimum performance (See section VIII. 4).

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	29965.2	0	5620.5	0
	NUTRIENT	31494.8	0	6660.2	0
	BET BIOPETRO	25914.5	0	5569.1	0
	CONTROL	30101.5	0	5610.1	0
7	NUTRIENT	8073.9	0	5086.6	0
	BET BIOPETRO	373.0	0	1220.0	0
	CONTROL	28785.6	4.0	5512.7	2.0
	NUTRIENT	706.2	98.0	4863.7	27.0

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
28	BET BIOPETRO	350.3	99.0	1882.9	67.0

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Nutrient</u>	<u>Product (BET BIOPETRO)</u>
0%	51%	30%

b. Toxicity:
NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentage in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive

pH: 6.6 to 7.4

Temperature: 70°F to 95°F

Salinity: Fresh to Salt water

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity.

pH: <5.5 and >8.5

Temperature: <45°F and >105°F

Salinity: Extreme salinity

4. Special nutrient requirements: BioEnviroTech, Inc. recommends nutrient supplements for optimum performance of the product in bioremediation application. The required nutrients are dependent upon hydrocarbon contamination levels. Contact BET for specific nutrient dosing requirements.

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS OF HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN #B-53
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: AUGUST 26, 1996
REMOVAL DATE: AUGUST 16, 2005
RELISTING DATE: SEPTEMBER 18, 2009
“OIL SPILL EATER II (OSE II)”

I. NAME, BRAND, OR TRADEMARK

OIL SPILL EATER II (OSE II)

Type of Product: Bioremediation Agent (Biological Enzyme Additive [previously listed as a Nutrient Additive])

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
OSEI Corporation (Formerly Sky Blue Chems)

P.O. Box 515429

Dallas, TX 75251-5429

Phone: (972) 669-3390

E-mail: oseicorp@msn.com

Website: www.osei.us

(Mr. Steven Pedigo, Chairman, CEO, Inventor)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
OSEI Corporation (Formerly Sky Blue Chems)

P.O. Box 515429

Dallas, TX 75251-5429

Phone: (972) 669-3390

E-mail: oseicorp@msn.com

Website: www.osei.us

(Mr. Steven Pedigo, Chairman, CEO, Inventor)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Water-based, non-flammable
2. Ventilation: Needs no ventilation; aqueous-based product; does not emit hazardous vapors
3. Skin and eye contact; protective clothing; treatment in case of contact: OSE II is not a primary dermal irritant. Avoid eye contact, and wear goggles if possible for the spray to come in direct contact with eyes. Facilities for quick and copious eye flushing should be provided and prompt medical attention should be sought if exposure and irritation persists. Protective rubber gloves are suggested during handling. Before mixing the product has a smell of fermentation. The product does not give off any harmful vapors.
- 4.a. Maximum storage temperature: 120°F
- 4.b. Minimum storage temperature: None; OSE II can freeze and thaw without adverse effects
- 4.c. Optimum storage temperature range: 72°F
- 4.d. Temperatures of phase separations and chemical changes: 120°F

V. SHELF LIFE

OSE II has a recommended shelf life of 5 years. After 5 years at optimum storage temperature, there is an approximate 10% decrease per year in product capability.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method:

- A. Use surface spray apparatus, such as small hand held tanks, back pack, large mixing tanks with mechanical pumping devices, vessels with booms for spraying wide paths, or spray devices on airplanes or helicopters.
- B. OSE II can be applied by eductor systems from vessels, fire trucks, etc. Set the eductor system to 2% and apply 1 gallon of mixed OSE II to each spilled gallon of hydrocarbon.

2. Concentration/Application Rate:

General – OSE II generally takes 3 to 30 minutes to penetrate the molecular walls of hydrocarbons. However, once you spray OSE II on the hydrocarbons, OSE II attaches itself and will eventually engulf the hydrocarbons regardless of where the hydrocarbons may spread on the surface of salt or fresh water. Additionally, once you spray OSE II, the hydrocarbons cannot attach itself to the shoreline, rocks, or any equipment in its path. OSE II breaks down the adhesion properties of hydrocarbons and causes hydrocarbons to float, thereby, eliminating secondary contamination of the water column or any other areas, and holding the contaminated area to the water's surface, the original contaminated area.

- If OSE II is to be used on ocean spills or on intertidal zones OSE II should be mixed with ocean water.
- If OSE II is to be used on lakes, rivers, streams, ponds, or on land mix the product with water from a lake, stream, or pond.
- If you are performing a cleanup, make sure the water used to mix with OSE II, and the water used to keep the area saturated, is the type of water normally associated with that area.
- If you use fresh water in an area normally contacted with salt water or vice versa, the different types of bacteria and competition could occur, not to mention the problems with salinity for fresh water organisms.

[Note: Do not mix tap water with OSE II if possible: Chlorine in tap water slows bacterial enhancement]

Spills on Water:

Dilute each gallon of OSE II with 50 gallons of fresh, brackish, or salt water – depending on the water associated with the area that has been impacted by the spill. Apply OSE II at a ratio of 1 gallon mixed OSE II to each gallon of hydrocarbon spilled. Apply using hand held sprayers, tank sprayers, booms from vessels, helicopters, or airplanes; by spraying the perimeter first then working toward the middle of the spilled area. Next spray the entire surface of the spill. If the spill is very heavy (more than 2 inches thick) it is recommended that OSE II be applied every day until you have met a 1:1 ratio of OSE II and water mixture to spilled oil/hydrocarbons.

- Use 1 gallon OSE II for every 50 gallons of hydrocarbons.
- Use 1 drum of OSE II for every 2,750 gallons of hydrocarbons.
- If you know gallons of hydrocarbons spilled, multiply gallons of hydrocarbons by 0.02 to get amount of OSE II needed [gallons of hydrocarbons x 0.02 = gallons of OSE II].
- If you know barrels of crude oil spilled, multiply barrels of crude oil by 0.015 to get drums

of OSE II needed [barrels of crude oil x 0.015 = drums of OSE II].

- If you do not know gallons of hydrocarbons or barrels of crude oil, multiply size of spill by 0.0023 to get drums of OSE II needed or by 0.12 to get gallons of OSE II needed [(yards long x yards wide x inches thick) x 0.0023 = drums of OSE II or (yards long x yards wide x inches thick) x 0.015 = gallons of OSE II].

Intertidal Zone:

Mix each 55 gallon drum of OSE II with 2,750 gallons of fresh, brackish, or salt water. The water used is determined by the type of water associated with the site. OSE II should be applied as the tide recedes (if there is a tide) and once the tide comes in the application should cease until the tide recedes again. Additional applications should only be warranted if spill has been allowed time to percolate into the depths of the soil.

If there is no tide, but waves have pushed the spill into the intertidal zone, then there will be direct access to the spill at all times. If possible use string or stakes to grid off the beach or intertidal zone area, and then you can calculate how much premixed OSE II to apply to a given area. If unable to grid off an area then calculate how much OSE II to apply and then determine how much premixed OSE II will flow through a nozzle (gallons per minute) then let application technician know how many gallons to apply in a given area and this can be determined by applying product for a certain time period to get the correct amount of OSE II applied to gain the 1:1 ratio.

Note: If the intertidal zone is associated with the sea then mix OSE II with salt water. If the spill area is in an area of brackish water then mix OSE II with brackish water. If the intertidal zone is associated with fresh water such as lakes, rivers, streams, ponds, creeks, aquifers, or drinking water wells then use fresh water to mix OSE II.

3. Conditions for Use:

- OSE II can remediate hydrocarbon-based material including chlorinated hydrocarbons, PCB's, dioxins, and some pesticides.
- As the age of spilled hydrocarbons increases, the time necessary for bioremediation increases. In general, fresh crude, gasoline or BTEX takes from 72 hours to 30 days to completely bioremediate.
- Variations of sea water salinity should have no effect, but as long as microbial life can exist, then OSE II will be effective.
- OSE II bioremediation slows somewhat at temperatures below 40°F. OSE II however, will continue to work at any liquid water temperature that will sustain microbial life.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	43,170	-	11,435	-
	NUTRIENT	40,569	-	11,785	-
	OSE II	41,730	-	12,155	-
7	CONTROL	39,250	9.1	10,355	9.4
	NUTRIENT	34,815	14.2	9,898	16.0
	OSE II	26,316	36.9	8,072	33.6
28	CONTROL	35,797	17.1	9,534	16.6
	NUTRIENT	26,507	34.7	8,938	24.2
	OSE II	4,273	89.8	1,268	89.6

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Nutrient</u>	<u>Product</u>
16.5%	52.0%	85.4%

b. Toxicity: NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of each component of the total formulation, other than enzymes, by chemical name and percentage by weight: CONFIDENTIAL
2. Enzyme Names: CONFIDENTIAL
3. I.U.B.: CONFIDENTIAL
4. Source of Enzymes: Fermentation process
5. Units: No less than 1% and no more than 50% by weight
6. Specific Gravity: 1.05
7. Optimum Conditions:
 - a. pH: 7.0
 - b. Temperature: 72°F
 - c. Salinity Ranges: Fresh water to salt water
 - d. Maximum and Minimum pH: 3.5 – 8.0
 - e. Maximum and Minimum Temperature: 28°F – 128°F

- f. Maximum and Minimum Salinity Levels – Salinity level above that will support microbial activity will adversely affect OSE II's performance
- g. Enzyme Shelf Life: Up to 5 years when properly stored
- h. Enzyme Optimal Storage Conditions: 72°F is optimal, enzyme range is freezing to 120°F, never leave OSE II in direct sunlight for more than a couple of hours

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**4/02/2007
7/27/2022**

TECHNICAL PRODUCT BULLETIN B-55
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: SEPTEMBER 10, 1999
“LAND AND SEA RESTORATION PRODUCT 001 (VELITE)”

I. NAME, BRAND, OR TRADEMARK
LAND AND SEA RESTORATION PRODUCT 001 (VELITE)
Type of Product: Bioremediation Agent (Nutrient Additive)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Land and Sea Restoration LLC
ADDRESS: updated information required
PHONE: updated information required
(Mr. T. Shawn Parker)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Land and Sea Restoration LLC
ADDRESS: updated information required
PHONE: updated information required
(Mr. T. Shawn Parker)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Flash Point 250°C (482°F)
2. Ventilation: Normal ventilation
3. Skin and eye contact; protective clothing; treatment in case of contact: Protective clothing and glasses. In case of eye contact, flush eyes with water or eyewash and refrain from rubbing. For skin contact, wash with mild soap and apply cream if itching or redness occurs. Avoid inhalation. In case of inhalation, seek fresh air. Wear protective clothing and eye goggles. Workers should wear single use nuisance dust masks appropriate for fine particulate dust.
- 4.a. Maximum storage temperature: 65°C (150°F)
- 4.b. Minimum storage temperature: 0°C (32°F)
- 4.c. Optimum storage temperature range: 0°C to 65°C (32 to 150°F)
- 4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

More than 5 years in unopened original shipping container, store in a cool, dry place. Avoid moisture prior to use.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: On water, spread over contaminated area at 1 to 3 ratios. On soil, blend to depth equivalent to contamination level. On hard surfaces, spread over contaminated area.

Make sure the spill is completely absorbed. For best results agitate with broom. (Will not damage cured asphalt if used as an absorbent for spills.) Remove and dispose of in accordance with all state and federal laws, after absorption is complete.

2. Concentration/Application Rate:

1 part 001 to 3 parts hydrocarbon.

3. Conditions for Use:

NA

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	13.8239	0	0.0443	0
	001	13.5856	0	0.0509	0
7	CONTROL	14.3292	0	0.0473	0
	001	10.1005	29.52	0.0437	0
28	CONTROL	14.4675	0	0.0401	0
	001	8.2629	42.92	0.0273	31.92

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control

0%

Product (001)

25.18%

b. Toxicity: NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentages in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 6 to 8

Temperature: 25°C to 30°C (77°F to 86°F)

Salinity: Fresh to salt water

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: NA

Temperature: NA

Salinity: NA

4. Special nutrient requirements: The product “001” is a nutrient, therefore no nutrients are required.

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: <3

Shigella: Negative

Staphylococcus Coagulase positive: <10

Beta hemolytic Streptococci: 1,100

IX. PHYSICAL PROPERTIES

1. Flash Point: 250°C (482°F)

2. Pour Point: NA

3. Viscosity: NA

4. Specific Gravity: NA

5. pH: NA

6. Surface Active Agents: NA

7. Solvents: NA

8. Additives: NA

9. Solubility in Water: NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN B-56
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JULY 24, 2002
“S-200C”

I. NAME, BRAND, OR TRADEMARK

S-200C

Type of Product: Bioremediation Agent (Nutrient Additive)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

RBL Environmental, LLC*

1311 Dorothy Avenue

Phoenixville, PA 19460

Phone: (610) 520-7665

E-mail: jim.lynn@iepusa.com

(Mr. James Lynn)

*(*RBL Environmental, LLC is the manufacturer and marketer for International Environmental Products)*

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

RBL Environmental, LLC

1311 Dorothy Avenue

Phoenixville, PA 19460

Phone: (610) 520-7665

E-mail: jim.lynn@iepusa.com

(Mr. James Lynn)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.
2. Ventilation: Ventilation of the work place is not necessary.
3. Skin and eye contact; protective clothing; treatment in case of contact: In case of contact with skin or eyes, wash with plenty of water.
- 4.a. Maximum storage temperature: 132°F
- 4.b. Minimum storage temperature: 32°F
- 4.c. Optimum storage temperature range: 55°F - 85°F
- 4.d. Temperatures of phase separations and chemical changes: <32°F and >140°F

V. SHELF LIFE

The recommended shelf life of S-200C is 10 years if kept in the unopened, original container.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: S-200C is a light amber liquid, and as such can be sprayed with traditional liquid spraying equipment, such as pressurized sprayers or backpack sprayers.
2. Concentration/Application Rate: The recommended application rate is approximately 10% by of the S-200C as compared to the hydrocarbon being remediated. In other words, use 1 pound of S-200C for every 10 pounds of hydrocarbon you are remediating. For applications on soil contaminated below 1 foot, the soil is turned and the material is applied. This allows air to circulate and thereby maintains an aerobic condition. On a surface application, the amount to use is approximately 0.1 to 1 pound of S-200C for every square yard of surface area. The amount sprayed is dependent on the amount of hydrocarbon on the surface you are spraying. To remediate a sheen on water, the same application ratio for a surface application is used.
3. Conditions for Use: S-200C is a bioremediation accelerator used for the remediation of hydrocarbon spills or leaks. It is a non-intrusive, cost effective remedy for the cleanup of these hydrocarbons. These hydrocarbons include but are not limited to gasoline, No. 2 up to No. 6 diesel fuel, jet fuels, kerosene, lubricating oils, hydraulic oils, and crude oils.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	27666	0	5600	0
	S-200C	29333	0	5666	0
7	CONTROL	21333	0	4333	0
	S-200C	11000	0	4400	0
28	CONTROL	18771	32	5597	0.05
	S-200C	660	98	5073	10.4

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control

-18.57%

Product (001)

27.82%

b. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
S-200C	Menidia beryllina	39.69 96-hr
	Mysidopsis bahia	21.33 48-hr
No. 2 Fuel Oil	Menidia beryllina	35.36 96-hr
	Mysidopsis bahia	35.36 48-hr
S-200C & No. 2 Fuel Oil (1:10)	Menidia beryllina	25.33 96-hr
	Mysidopsis bahia	17.67 48-hr
Reference Toxicant (SDS)	Mysidopsis bahia	22.96 48-hr

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentages in the composition:

S-200C is a nutrient bioremediation accelerator and does not contain bacterial cultures or amendments. However, with the addition of S-200C, the microbiological data shows a continued viability of microbial incubations over time.

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 7.0

Temperature: 86°F

Salinity: Fresh to salt water

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: 4.5 - 10.0

Temperature: 50°F - 120°F

Salinity: 0% - 10%

4. Special nutrient requirements: NA

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

1. Flash Point: >212°F

2. Pour Point: 40°F

3. Viscosity: 100cp@70°F

4. Specific Gravity: 0.996

5. pH: 4.5

6. Surface Active Agents: NA

7. Solvents: NA

8. Additives: NA

9. Solubility in Water: Dispersible

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

S-200C does not contain any heavy metals, cyanide, or chlorinated hydrocarbons.

TECHNICAL PRODUCT BULLETIN B-57

USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION

LISTING DATE: JANUARY 8, 2007

“SPILLREMEDIATION (MARINE)®”

(aka, AGROREMEDIATION, HYDROREMEDIATION, SPILLREMEDIATION (INDUSTRIAL), VAPORREMEDIATION)

I. NAME, BRAND, OR TRADEMARK

SPILLREMEDIATION (MARINE)®

(aka, AGROREMEDIATION, HYDROREMEDIATION, SPILLREMEDIATION (INDUSTRIAL), VAPORREMEDIATION)

Type of Product: Bioremediation Agent (Biological Additive: Microbiological Culture)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Sarva Bio Remed, LLC

25 Marianne Drive, Suite ‘B’

York, PA 17406

Phone: (717) 779-0040

Phone : (877) 717-2782

E-mail: sales@sarvabioremed.com

Website: www.sarvabioremed.com

(Mr. Satya Ganti)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Sarva Bio Remed, LLC

25 Marianne Drive, Suite ‘B’

York, PA 17406

Phone: (717) 779-0040

Phone : (877) 717-2782

E-mail: sales@sarvabioremed.com

Website: www.sarvabioremed.com

(Mr. Satya Ganti)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.

2. Ventilation: No special ventilation required.

3. Skin and eye contact; protective clothing; treatment in case of contact: On contact with product, wash with plenty of water and for eye contact consult your physician. Use of gloves and eye protection is recommended during field application to protect eyes from spray.

4.a. Maximum storage temperature: 100°F

4.b. Minimum storage temperature: 32°F

4.c. Optimum storage temperature range: Ambient

4.d. Temperatures of phase separations and chemical changes: <32°F and >100°F

V. SHELF LIFE

The recommended shelf life is one year.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method:

SPILLREMED (MARINE)[®] is a ready to use liquid product. It can be sprayed undiluted over the spill in open water conditions.

2. Concentration/Application Rate:

SPILLREMED (MARINE)[®] is applied in a product to oil ratio of 1:10. Rate of application is one gallon per 10 minutes.

3. Conditions for Use:

SPILLREMED (MARINE)[®] is a marine salt formulation and is not effective in fresh water conditions. Optimal effectiveness is in the salinity range of 10 to 35 ppt.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	48,963.31		13,467.59	
	NUTRIENT	46,963.33		13,779.24	
	SPILLREMED (MARINE) [®]	52,063.18		14,143.06	
7	CONTROL	47,606.78		11,262.98	
	NUTRIENT	40,853.28		11,329.01	
	SPILLREMED (MARINE) [®]	43,236.67		11,076.99	
28	CONTROL	45,467.28	7	12,560.37	7
	NUTRIENT	7,210.06	98	9,927.87	28
	SPILLREMED (MARINE) [®]	1,310.09	97	7,442.71	47

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Nutrient</u>	<u>Product</u>
6.00%	76%	85%

b. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
SPILLREMEDI (MARINE) [®]	Menidia beryllina	392.30 96-hr
	Mysidopsis bahia	343.80 48-hr
No. 2 Fuel Oil	Menidia beryllina	40.50 96-hr
	Mysidopsis bahia	17.40 48-hr
SPILLREMEDI (MARINE) [®] & No. 2 Fuel Oil (1:10)	Menidia beryllina	37.50 96-hr
	Mysidopsis bahia	22.40 48-hr
Reference Toxicant (SDS)	Menidia beryllina	8.00 96-hr
	Mysidopsis bahia	15.90 48-hr

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentages in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 7.6

Temperature: 55°F

Salinity: 30 ppt

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: 6.5 – 6.9

Temperature: 40°F – 90°F

Salinity: 10 ppt – 35 ppt

4. Special nutrient requirements: None

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**3/22/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN B-58
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: DECEMBER 3, 2007
“JE1058BS”

I. NAME, BRAND, OR TRADEMARK

JE1058BS

Type of Product: Bioremediation Agent (Nutrient Additive)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Japan Energy Corporation

Business Development Department, Bio Research Center

3-17-35 Niizo-Minami

Toda-shi, Saitama 335-8502

Japan

Phone: updated information required

Fax: updated information required

E-mail: updated information required

(Hisashi Saeki)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Japan Energy Corporation

Business Development Department, Bio Research Center

3-17-35 Niizo-Minami

Toda-shi, Saitama 335-8502

Japan

Phone: updated information required

Fax: updated information required

E-mail: updated information required

(Hisashi Saeki)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.

2. Ventilation: Use adequate ventilation. Treat product as a hygroscopic powder.

3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid contact with eyes and do not take internally. Upon contact with eyes, flush with plenty of fresh water. Avoid breathing dust. Normal protective equipment for handling of powder, such as a dust mask and eye shield can be used.

4.a. Maximum storage temperature: 105°F

4.b. Minimum storage temperature: NA

4.c. Optimum storage temperature range: 0°F - 68°F

4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

The shelf life of the product is approximately 2 years if stored in a cool dry area.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method:

JE1058BS contains biosurfactant and has an ability to stimulate the biodegradation of oil by indigenous microorganisms. JE1058BS, which is a powder, can be applied using conventional spraying equipment, for example a powder mist duster attached with boom type multi-hole head.

2. Concentration/Application Rate:

JE1058BS is applied in a product:oil ratio of 1:10. No pre-mixing or dilution by water is required.

3. Conditions for Use:

JE1058BS may be used in a wide range of environmental conditions of temperature and salinities where natural populations of oil-degrading microbes are active. The mechanical removal of as much oil as possible should be done before the product is introduced to the slick.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	48,213		11,413	
	NUTRIENT	51,833		13,056	
	JE1058BS	52,280		13,211	
7	CONTROL	48,030		11,108	
	NUTRIENT	33,423		11,755	
	JE1058BS	13,453		10,188	
28	CONTROL	48,257	0	10,429	8.6
	NUTRIENT	16,953	67.3	11,837	9.3
	JE1058BS	3,854	92.6	8,061	39.0

Results of Gravimetric Analysis: DATA MISSING
 Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Nutrient</u>	<u>Product</u>
5.9%	60.0%	81.8%

b. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
JE1058BS	Menidia beryllina	91.70 96-hr
	Mysidopsis bahia	72.09 48-hr
No. 2 Fuel Oil	Menidia beryllina	5.56 96-hr
	Mysidopsis bahia	2.19 48-hr
JE1058BS & No. 2 Fuel Oil (1:10)	Menidia beryllina	8.68 96-hr
	Mysidopsis bahia	2.44 48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.23 96-hr
	Mysidopsis bahia	11.70 48-hr

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentages in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive: NA

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

Store in dry location and avoid contact with moisture

4. Special nutrient requirements: NA

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN B-59

USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION

LISTING DATE: NOVEMBER 24, 2008

“BIOWORLD BIOREMEDIATION TREATMENT PRODUCTS (BIOWORLD BHTP)”

I. NAME, BRAND, OR TRADEMARK

BIOWORLD BIOREMEDIATION TREATMENT PRODUCTS (BIOWORLD BHTP)

Type of Product: Bioremediation Agent (Microbiological Additive)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

BioWorld USA, Inc.

6734B W Pershing Ave

Visalia, CA 93291

Phone: (559) 651-2042

Fax: (559) 651-9041

E-mail: support@bioworldusa.com

Website: www.bioworldusa.com

(Ms. Diane R. Barnes)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

BioWorld USA, Inc.

6734B W Pershing Ave

Visalia, CA 93291

Phone: (559) 651-2042

Fax: (559) 651-9041

E-mail: support@bioworldusa.com

Website: www.bioworldusa.com

(Mr. Donald E. Damschen)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-hazardous.

2. Ventilation: Use adequate ventilation. Treat dry product as a hygroscopic powder and avoid ventilation.

3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid contact with eyes and do not take internally. Upon contact with eyes, flush with plenty of fresh water. Avoid breathing dust. Normal protective equipment for handling of powder, such as a dust mask and eye shield are recommended to be used. Wash hands and body contacted areas with soap and water.

4.a. Maximum storage temperature: 110°F

4.b. Minimum storage temperature: 34°F – containers may break if frozen

4.c. Optimum storage temperature range: 34°F - 90°F

4.d. Temperatures of phase separations and chemical changes: <32°F and > 140°F

V. SHELF LIFE

The recommended shelf life exceeds 3 years when stored properly in cool, dry place out of direct sun light.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method:

BioWorld BHTP is a two part product 1) Bioremediation Enhancer liquid and 2) Hydrocarbon Digesting Microbes in a dry form. Prior to use the microbes are rehydrated in 100°F water for 10 to 300 minutes.

Example for small volume applications – best results are obtained by applying Bioremediation Enhancer first followed by the rehydrated Hydrocarbon Microbe solution in the same location.

Example for large volume applications – the two parts of BioWorld BHTP can be mixed with additional water and applied together to spray over the perimeter and over the top of the spill.

Example for soil and groundwater applications – evenly apply to soils and mix with till or discing equipment. Oxygen additions are periodically used in certain situations and can be applied with mechanical generation and/or by using oxygen release compound products.

2. Concentration/Application Rate:

BioWorld BHTP is applied at an approximate rate of 40 gallons Bioremediation Enhancer liquid and 4 pounds Hydrocarbon Microbes per surface acre treated. Increased quantities and multiple applications may be required to meet shorter cleanup time constraints and desired results.

3. Conditions for Use:

BioWorld BHTP can be used in freshwater conditions, wetlands, rock or sand shorelines, contaminated soil areas, salt marshes and salt water conditions (up to 60 ppt salinity).

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	61,234		9,395	
	NUTRIENT	64,803		8,873	
	BioWorld BHTP	63,192		9,220	
7	CONTROL	57,907	5	7,290	22
	NUTRIENT	49,747	14	5,956	18
	BioWorld BHTP	41,480	28	4,405	40

28	CONTROL	49,364	19	6,499	31
	NUTRIENT	21,490	67	5,259	41
	BioWorld BHTP	1,948	97	1,078	88

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Nutrient</u>	<u>Product</u>
21%	64%	96%

b. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
BioWorld BHTP	Menidia beryllina	8,848.70 96-hr
	Mysidopsis bahia	7,348.70 48-hr
No. 2 Fuel Oil	Menidia beryllina	4.50 96-hr
	Mysidopsis bahia	3.21 48-hr
BioWorld BHTP & No. 2 Fuel Oil (1:10)	Menidia beryllina	13.90 96-hr
	Mysidopsis bahia	7.10 48-hr
Reference Toxicant (SLS)	Menidia beryllina	15.00 96-hr
	Mysidopsis bahia	15.90 48-hr

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentages in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 6-8

Temperature: 80°F-100°F

Salinity: 0-1 for use of the additive

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: 3-10

Temperature: 33°F-120°F

Salinity: >5

Use under any conditions where indigenous populations of oil-degrading microbes are/are not present

4. Special nutrient requirements: Some sites may benefit with various nutrients added depending on project variables

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: <2

Shigella: Negative

Staphylococcus Coagulase positive: <10

Beta hemolytic Streptococci: <10

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN: B-60
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: OCTOBER 28, 2010
“MUNOX SR®”

I. NAME, BRAND, OR TRADEMARK

MUNOX SR®

Type of Product: Bioremediation Agent (Microbiological Culture)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Osprey Biotechnics, a division of Phibro Animal Health Corporation

1845 57th Street

Sarasota, FL 34243

Phone: (941) 351-2700

Fax: (941) 351-0026

E-mail: troy.smith@pahc.com

(Mr. Troy Smith, Sr. VP Technical Operations)

E-mail: thomas.baldeschieler@pahc.com

(Mr. Thomas Baldeschieler, Regulatory)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Osprey Biotechnics a division of Phibro Animal Health Corporation

1845 57th Street

Sarasota, FL 34243

Phone: (941) 351-2700

Fax: (941) 351-0026

E-mail: rafael.bortoleto@pahc.com

(Mr. Rafael Bortoleto, Sr. Director – Microbial Operations)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable

2. Ventilation: No special ventilation is required under normal use.

3. Skin and eye contact; protective clothing; treatment in case of contact: No special handling necessary. In case of skin contact, wash with soap and water. In case of eye contact, flush with water. In case of eye contact, flush with water. Wear protective gloves and wash hands with soap and water after handling.

4.a. Maximum storage temperature: 100°F

4.b. Minimum storage temperature: 32°F

4.c. Optimum storage temperature range: 35°F to 95°F. Store in a cool, dry location.

4.d. Temperatures of phase separations and chemical changes: <32°F and >212°F

V. SHELF LIFE

MUNOX SR® is stable for over one year when stored at temperatures from 35°F to 95°F.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method:

MUNOX SR[®] is a consortium of robust organisms that tolerate the natural salinity of seawater up to approximately 5% and water temperatures below 100°F. MUNOX SR[®] is effective on fresh and weathered crude oil and refined products because the metabolic pathways of the organisms are based on beta oxidation that is effective on a wide range of constituents of petroleum including aromatic, aliphatic and polyaromatic compounds. MUNOX SR[®] is provided with a microbial density of 1×10^8 cfu/mL in stabilized liquid form or after the freeze-dried form is hydrated. The target population for effective treatment is 2.5×10^5 cfu/mL.

One unit consists of one 55-gallon drum of hydrated MUNOX SR[®] or the amount of freeze-dried powder to mix with 55-gallons of water to formulate the equivalent hydrated microbial solution. Based on this formulation and treatment ratio, one unit of MUNOX SR[®] will treat approximately 22,000 gallons of impacted water.

Apply using in situ, hand sprayer, pump, pressure washer, etc. Product is ready to use and does not require dilution of additional formulation.

2. Concentration/Application Rate:

Surface water: MUNOX SR[®] provides organisms that can be effective in the destruction and removal of petroleum hydrocarbons in surface water. It is best applied in areas where vertical water mixing is minimal in order to maintain high microbial density in the vicinity of floating hydrocarbons and near the water surface where there is a maximal oxygen concentration..

Beach application: The best application on the beach is by mixing the microbes in the beach between the tide marks. Assuming the contractor will be mixing the microbes to a depth of 12 inches and there is 30% porosity, 5 drums per acres will provide sufficient MUNOX SR[®] microbes for treatment.

Marsh or wetland application: This application of MUNOX SR[®] provides the greatest value because it is the treatment approach that will not cause more damage to the wetlands. The microbes will be sprayed on the oiled wetland from a boat or aircraft so the vegetation is not disturbed. The recommended volume of MUNOX SR[®] will provide enough microbes to degrade a moderate oiling level to acceptable levels. This application rate will treat the oil in surface water, attached to vegetation, and on the soil surface. Assuming the wetland is submerged to a depth of six inches during high tide, an application rate of 8 units per acre will provide sufficient microbes for treatment.

3. Conditions for Use:

MUNOX SR[®] is formulated for the bioremediation and metabolism of a wide range of petroleum hydrocarbons including crude oil and refined fuels. Because petroleum in all of its forms is made up of a wide variety of components, the dosage and application of MUNOX SR[®] will depend on the type of hydrocarbon, degree of weathering, and environmental conditions.

Heavy petroleum compounds such as crude oil and refined products, such as bunker fuel, with a high proportion of complex aliphatics will require a high dosage than lighter petroleum compounds such as gasoline. The dosage will be site specific and will be determined with the assistance of CL Solutions at no cost to the U.S. EPA or the user.

MUNOX SR® will tolerate a wide range of environmental conditions; however, some conditions may reduce the effectiveness of MUNOX SR®. MUNOX SR® is most effective at a neutral pH, but can tolerate a pH range from 5 to 8.5. The salinity of water should be less than 5%. MUNOX SR® will also be most effective at moderately high temperatures from 70°F to 100°F. MUNOX SR® will tolerate low temperatures and will become dormant at freezing temperatures. However, MUNOX SR® will not tolerate temperatures above 105°F.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	1,003	0	3,609	0
	NUTRIENT	1,096	0	4,661	0
	MUNOX SR®	806	0	4,063	0
7	CONTROL	1,039	0	3,932	0
	NUTRIENT	815	0	3,172	0
	MUNOX SR®	199	0	3,292	0
28	CONTROL	847	15.5	3,578	0.85
	NUTRIENT	832	24	3,674	21.2
	MUNOX SR®	41	94.9	996	75.5

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Nutrient</u>	<u>Product</u>
0.2%	9.9%	14.3%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentages in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 6-8

Temperature: 4°C-35°C

Salinity: Fresh water to salt water, <110 ppm

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: <6.0 and >8.0

Temperature: <4°C->35°C

Salinity: >110 ppm

4. Special nutrient requirements: None required. In application, MUNOX SR® may be supplemented with the following Nutrient Mix at a ratio up to 1:10.

Nutrient Mix Composition:

Soy Peptone – 2.2%

Yeast Extract – 2.2%

Dextrose – 0.2%

Sodium Nitrate – 0.2%

Di-potassium Phosphate – 0.2%

Sodium Thiosulfate – 0.01%

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative.

Fecal coliform: Negative.

Shigella: Negative.

Staphylococcus Coagulase positive: Negative.

Beta hemolytic Streptococci: Negative.

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN: B-61
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: NOVEMBER 17, 2010
“SOIL RX”
(aka, BIO-REGEN HYDROCARBON)

I. NAME, BRAND, OR TRADEMARK
SOIL RX

(aka, BIO-REGEN HYDROCARBON)

Type of Product: Bioremediation Agent (Microbiological Culture, Nutrient Additive)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

3 Tier Technologies LLC

Worldwide Headquarters

413 W 13th Street

Sanford, FL 32771

Phone: (877) 226-7498

Fax: (877) 570-0072

E-mail: dburdette@3tierotech.com

Website: www.3tierotech.com

(Daniel J. Burdette, President)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Direct Sales

3 Tier Technologies LLC

Worldwide Headquarters

413 W 13th Street

Phone: (877) 226-7498

Fax: (877) 570-0072

E-mail: dburdette@3tierotech.com

Website: www.3tierotech.com

(Daniel J. Burdette, President)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable

2. Ventilation: Normal ventilation is adequate.

3. Skin and eye contact; protective clothing; treatment in case of contact: Ingestion: No effect if ingested in small amounts. A single dose of this product is rarely toxic by ingestion. Irritation of the mouth, pharynx, esophagus and stomach can develop. Give two glasses of water. Do not induce vomiting. Contact physician if needed. Eyes: Avoid eye contact. This material may cause eye irritation. Immediately flush with water for 15 minutes. Contact physician if needed. Skin: Slight redness on hands and forearms if individual has a history of dermal allergic reactions. Dermatitis and skin sensitization can develop after repeated and/or prolonged contact. Remove contaminated clothing and footwear. Wash with soap and water.

Always consult a physician if needed. Respirators are not required for recommended uses. Rubber gloves are not required, but recommended. Safety glasses are not required, but recommended. Wash hands with soap and water after handling product. Wash contaminated clothing and footwear before reuse.

4.a. Maximum storage temperature: 120°F

4.b. Minimum storage temperature: 34°F – do not allow product to freeze

4.c. Optimum storage temperature range: 45°F to 95°F.

4.d. Temperatures of phase separations and chemical changes: NA, stable.

V. SHELF LIFE

Shelf life exceeds 2 years when properly stored in the unopened original container.

VI. RECOMMENDED APPLICATION PROCEDURE

SOIL RX (aka, BIO-REGEN HYDROCARBON) is a concentrated liquid formulation of activated humic acid, highly concentrated hydrocarbon-oxidizing bacteria, and a readily biodegradable natural amino acid complex consisting of a nutrient-rich extract with a broad-spectrum package of identifiable amino acids, surfactants, and other proteins. This product is designed to digest organics and hydrocarbons in soil and water.

1. Application Method: SOIL RX (aka, BIO-REGEN HYDROCARBON) is a liquid concentrate that must be diluted prior to use. The product can be sprayed after dilution using standard spray application equipment, including but not limited to hand sprayers, mechanical sprayers, water trucks, fire or emergency response equipment, pressure washers, etc. Mix or saturate concentrate/water mixture with contaminated soils thoroughly for maximum performance. For shallow/surface contamination, drench affected areas with enough dilution to fully saturate the soil using normal spray equipment and water trucks. For general contamination less than two feet, contaminated soil may require tilling or excavation to properly mix concentrate/water dilution into soils. For deeper contamination greater than two feet, product application can be applied through boring the area and using perforated piping per regulatory recommendations or excavate the material and treat while land farming or bio-piling. For contaminated water, such as marshes, shoreline and open water with floating hydrocarbons, apply dilution directly to the contaminated areas using appropriate spray equipment and water cannons.

2. Concentration/Application Rate: SOIL RX (aka, BIO-REGEN HYDROCARBON) must be diluted using 1 part concentrate to 10 parts clean water prior to use. Product can be diluted up to 100 parts water as directed for specific applications. Application rates are determined by level of contamination, area of application, and speed required for cleanup. Specific application rates are determined prior to sale by the manufacturer and the distributor. A normal application rate for contaminated soil is on gallon 10:1 diluted product per cubic yard of soil. Normal application rate for water applications is three gallons 10:1 diluted product per 1000 square feet of contaminated surface area.

3. Conditions for Use: SOIL RX (aka, BIO-REGEN HYDROCARBON) is safe for application in ocean and fresh water, all soil types, and shoreline treatments.

Water Salinity: Product should be diluted with fresh, clean water. Use of brackish or brine water may be used if fresh water is not available. It should be noted that the use of brine water may slightly reduce product performance or increase overall remediation time.

Water Temperature: Water must be between 42° to 110°F for normal product performance.

pH: Optimum water pH ranges between 4 to 8.

Temperature: Temperatures are below 32° and above 120°F may decrease product performance.

Nutrient Requirements: None. Nutrients required are in the product.

Type and Age of Pollutants: For use on most organic based contaminants and hydrocarbon based materials like gasoline, jet fuels, diesel fuels, grease, tar, motor oils, crude oils, solvents, etc. Age of contamination is not a factor as much as level of contamination, depth of contamination, and length of time required for the remediation process. For materials that have hardened and are tar-like, additional procedures may be required for effective remediation.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	34908.9	0	6051.3	0
	NUTRIENT	34863.3	0	6047.4	0
	SOIL RX	34993.0	0	6069.0	0
7	CONTROL	35206.2	+0.08	5720.9	5.45
	NUTRIENT	32894.1	5.64	5745.8	4.98
	SOIL RX	24446.0	30.14	3219.2	46.96
28	CONTROL	34287.8	1.779	5892.7	2.621
	NUTRIENT	32610.0	6.463	5205.1	13.928
	SOIL RX	17597.0	49.713	1600.1	73.635

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control

8.01%

Nutrient

7.43%

Product

30.14%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentages in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 4-8

Temperature: 42°F-100°F

Salinity: NA

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: 2-10

Temperature: 34°F-125°F

Salinity: NA

4. Special nutrient requirements: None

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**2/04/2020
7/27/2022**

TECHNICAL PRODUCT BULLETIN: B-62
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: DECEMBER 15, 2010
“PRO-ACT”
(aka, OILCLEAN w/ACTIVATOR)

**I. NAME, BRAND, OR TRADEMARK
PRO-ACT**

(aka, OILCLEAN w/ACTIVATOR)

Type of Product: Bioremediation Agent (Biological Additive: Microbiological Culture w/
Nutrient Additive)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Pro-Act Biotech a Unit of LLG.LLC

64 Church Street

Warren, RI 02885

Phone: (401) 245-7004

Fax: (401) 633-6270

E-mail: bill@proactbiotech.com

Website: www.oil-clean.net

(Mr. William Campion)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Pro-Act Biotech a Unit of LLG.LLC

64 Church Street

Warren, RI 02885

Phone: (401) 245-7004

Fax: (401) 633-6270

E-mail: bill@proactbiotech.com

Website: www.oil-clean.net

(Mr. William Campion)

**IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD
APPLICATION**

1. Flammability: Non-flammable

2. Ventilation: No special requirements.

3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing is required in the handling, storage and field application of this product. For skin and eye contact, wear goggles. If eye or skin irritation occurs, flush with plenty of fresh water.

4.a. Maximum storage temperature: 110°F, up to 5 days

4.b. Minimum storage temperature: 35°F, do not freeze

4.c. Optimum storage temperature range: 40°F to 90°F

V. SHELF LIFE

One year as packaged.

VI. RECOMMENDED APPLICATION PROCEDURE

PRO-ACT (aka, OILCLEAN w/ACTIVATOR) consists of two parts: liquid microbes and activator (i.e., nutrient additive). As part of the Product Schedule, training on the proper use of PRO-ACT (aka, OILCLEAN w/ACTIVATOR) will be provided by Pro-Act Microbial, Inc. certified personnel.

1. Application Method: Site (water and/or soil) testing is highly recommended prior to product application. The testing is designed to assess the nutrient status of the contaminated site. The desired nitrogen and phosphorus concentrations are in the range of 0.5 to 2.5 mg N/L for nitrogen and 0.05 to 0.3 mg P/L for phosphorus. If there are inadequate nutrients in the water/soil, the activator portion will be needed to bring the nutrients in line with product specification. The activator portion can be applied directly to the site for treatment or it can be mixed in with the diluted liquid microbes first. Nutrient levels need to be maintained for optimal microbial action. Thus, depending on the nature of water/soil and the results of on site monitoring, activator may need to be applied more than once. It is recommended that physical methods such as skimming should be employed to recover as much oil as possible. PRO-ACT (aka, OILCLEAN w/ACTIVATOR) should be used to breakdown the residual oil after the physical methods have been used.

2. Concentration/Application Rate: Liquid microbes are to be diluted with the non-chlorinated, non-ozonated water or with the water to be treated (1:10 liquid microbe/water ratio) and applied with a sprayer, either pump or pneumatic. The amount of PRO-ACT (aka, OILCLEAN w/ACTIVATOR) needed depends on the amount of oil to be treated. One gallon undiluted liquid microbes can treat up to 1000 square feet, assuming there is less than ¼ inch of oil on surface. For example, one gallon undiluted liquid microbes is good for up to 5 gallons of spilled oil. A second application of Pro-Act (aka OilClean w/Activator) is beneficial to speed up the bioremediation process.

3. Conditions for Use: Monitoring of dissolved oxygen levels is recommended. If needed, a mechanical aeration device should be deployed to maintain DO levels above 3 mg/L. PRO-ACT (aka, OILCLEAN w/ACTIVATOR) works with fresh oil as well as weathered oil. Oil toxicity (especially from easily dissolved shorter chain hydrocarbons in the fresh oil) should not be a problem as long as physical methods are used first following a spill. The product is ideal for salt water, brackish water and fresh water, with no limitations as to usage within optimum temperature range of 20 to 40°C.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	41277	0	6100	0
	NUTRIENT	41670	0	6140	0
	PRO-ACT	43193	0	6460	0
7	CONTROL	41393	0	5705	0
	NUTRIENT	26370	0	3640	0
	PRO-ACT	302	0	1979	0
28	CONTROL	42451	-2.766	4546	25.475
	NUTRIENT	3654	91.231	1968	67.948
	PRO-ACT	59	99.863	378	94.149

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control

12.624%

Nutrient

55.670%

Product

65.516%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentages in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 7.0

Temperature: 30°C

Salinity: 0.2 to 4%

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: <6.0 or >9.0

Temperature: <15°C or >45°C

Salinity: <0.02% or >5%

4. Special nutrient requirements: PRO-ACT (aka, OILCLEAN w/ACTIVATOR)

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN: B-63
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: DECEMBER 15, 2010
“BIOREM-2000 OIL DIGESTER™”

I. NAME, BRAND, OR TRADEMARK
BIOREM-2000 OIL DIGESTER™

Type of Product: Bioremediation Agent (Biological Additive: Microbiological Culture)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Clift Industries, Inc.

P.O. Box 471578

Charlotte, NC 28247

Customer Service:

Phone: (800) 996-9901

Product Management:

Phone: (704) 752-0031

Fax: (704) 544-2532

E-mail: matt@cliftindustries.com

(Mr. Matt Barnhill)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Clift Industries, Inc.

P.O. Box 471578

Charlotte, NC 28247

Customer Service:

Phone: (800) 996-9901

Product Management:

Phone: (704) 752-0031

Fax: (704) 544-2532

E-mail: matt@cliftindustries.com

(Mr. Matt Barnhill)

X-Cel Chemical Specialties

921 Rosewood Street

Jenison, MI 49428

Office: (616) 581-4324

Fax: (616) 777-0022

E-mail: larry.hewitt@xcelchemical.com

(Mr. Larry Hewitt, Primary Contact)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable

2. Ventilation: No special requirements.

3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing is required in the handling, storage and field application of this product. For skin and eye contact, wear gloves and goggles.

4.a. Maximum storage temperature: 140°F

4.b. Minimum storage temperature: 35°F

4.c. Optimum storage temperature range: 85°F

V. SHELF LIFE

The shelf life of the product is two (2) years when stored within the storage temperature range in the original container.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Spray from boats, aircraft, fire eductor systems on boats, helicopter buckets, hand-held or backpack sprayers, or from hoses attached to small pumps, water trucks and aerial spray, including typical spreading systems.

2. Concentration/Application Rate:

Shoreline Treatment:

To treat beaches, coarse sand, rocks, rip rap, sea walls, cobble shorelines and rocky shores, oiled pilings and piers use one (1) part BIOREM-2000 OIL DIGESTER™ diluted with five (5) parts water. Use one (1) gallon per 1,500 square feet of contaminated area.

Treating Marine Vegetation/Wetlands:

Dilute one (1) part BIOREM-2000 OIL DIGESTER™ with five (5) parts water and apply with non-pressure, non-impact spraying equipment onto reeds, grasses, trees, and rocks in marsh areas and vegetated wetlands. Use one (1) gallon per 1,500 square feet of contaminated area.

For Treating Water:

Do not dilute BIOREM-2000 OIL DIGESTER™ and apply directly spraying onto the surface of oil.

Small Applications:

BIOREM-2000 OIL DIGESTER™ may be applied with hand sprayers or portable pumps to spray the product directly onto oiled surfaces. Dose rates will vary with the type and amount of petroleum spilled, the extent of weathering, and other site-specific conditions, including temperature, porosity of surface, and residence time available to let the product contact the oil.

3. Conditions for Use: Effective at temperatures above 40°F.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	43163	0	6001	0
	NUTRIENT	36643	0	4813	0

7	BIOREM-2000 OIL DIGESTER™	36492	0	4634	0
	CONTROL	39249	9.0	5067	15.5
	NUTRIENT	2946	91.9	3832	20.0
	BIOREM-2000 OIL DIGESTER™	5390	85.2	4114	11.0
	CONTROL	33961	21.0	3812	36.0
	NUTRIENT	106	99.7	729	84.0
28	BIOREM-2000 OIL DIGESTER™	64	99.8	1324	71.0

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control

10.7%

Nutrient

68.9%

Product

67.0%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentages in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 7.0

Temperature: 85°F

Salinity: <10%

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: 3.0 or 11.5

Temperature: <35°F or >125°F

Salinity: >40%

4. Special nutrient requirements: None

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN: B-64
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: FEBRUARY 22, 2011
“DRYLET™ MB BIO”

I. NAME, BRAND, OR TRADEMARK

DRYLET™ MB BIO

Type of Product: Bioremediation Agent (Biological Additive: Microbiological Culture)
(formerly DRYLET™ MB BIOREMEDIATION)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Drylet, Inc.

8300 FM 1960 West

Suite #450

Houston, TX 77070

Phone: (346) 980-9570

E-mail: sales@drylet.com

(Mr. Scott Conley)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Drylet, Inc.

8300 FM 1960 West

Suite #450

Houston, TX 77070

Phone: (346) 980-9570

E-mail: sales@drylet.com

(Mr. Scott Conley)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: No special requirements. In closed spaces, uses dust protective measures.
3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing is required; however, goggles and dust mask are recommended. Applying dry powder may cause irritation to membranes. If eye or skin irritation occurs, flush with plenty of water.
- 4.a. Maximum storage temperature: 120°F continuous
- 4.b. Minimum storage temperature: 35°F
- 4.c. Optimum storage temperature range: 40°F to 120°F

V. SHELF LIFE

Minimum 5 years, with proper storage, in original packaging. Freezing does not harm shelf life; however, extreme heat (over 180°F) for long periods of time can shorten shelf life.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Apply DRYLET™ MB BIO directly to oil contamination. DRYLET™ MB BIO may be applied by the usual methods of aerial or manual broadcast spreading. For smaller spills, manual broadcast will deliver the best results. Larger spills in open water, marsh, wetlands, or estuary areas should be treated by aerial powder dusting or dusting with mechanical powder pumps.

2. Concentration/Application Rate: Apply DRYLET™ MB BIO directly on the spill. Apply 0.4 pounds of product per cubic yard of soil, or 50 pounds per acre of open water slick. In marsh, wetlands, and estuaries application rates may be up to 75 pounds per acre depending on the oil type and contamination level.

3. Conditions for Use: Water salinity: can be used in fresh or salt water. pH: 4 to 11.5. Temperature: 32°F – 120°F. Water Temperature: 35°F - 170°F. Nutrient Requirements: Nutrients are included with the product. However, for longer term project, additional nutrients may be added to increase microbial activity. Types and Ages of Contamination: For use on organic and hydrocarbon-based contamination. Tar like contamination may require mechanically breaking the structure to obtain timely results.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	60871	0	8729	0
	NUTRIENT	61995	0	8170	0
	PRODUCT	61459	0	8790	0
7	CONTROL	56197	0	6224	0
	NUTRIENT	42501	0	4833	0
	PRODUCT	12303	0	4140	0
28	CONTROL	27314	55.0	5030	42.4
	NUTRIENT	47	99.9	533	93.5
	PRODUCT	820	98.6	1305	85.1

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Nutrient</u>	<u>Product</u>
0.30%	50.0%	84.8%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentages in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 6.0-8.0

Temperature: 85°F to 110°F

Salinity: 0.5-4.0

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: 4.0 or 11.5

Temperature: 35°F or 180°F

Salinity: 0.5 or 5.0 (above 4.5 reduces effectiveness by half)

4. Special nutrient requirements: None

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**3/17/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN: B-65
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: MAY 18, 2011
“DUALZORB®”
(aka, TRAILZORB, WHITZORB)

**I. NAME, BRAND, OR TRADEMARK
DUALZORB®**

(aka, TRAILZORB, WHITZORB)

Type of Product: Bioremediation Agent (Biological Additive: Microbiological Culture)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

LBI Renewable

P.O. Box 637

22 Plains Drive

Buffalo, WY 82834

CUSTOMER SERVICE:

Phone: updated information required

Fax: updated information required

E-mail: updated information required

(Mr. Aaron Larsen)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

DUALZORB® and TRAILZORB:

LBI Renewable

P.O. Box 637

22 Plains Drive

Buffalo, WY 82834

CUSTOMER SERVICE:

Phone: updated information required

Fax: updated information required

E-mail: updated information required

(Mr. Aaron Larsen)

WHITZORB:

Whitmore Manufacturing Co.

930 Whitmore Drive

Rockwall, TX 75032

CUSTOMER SERVICE:

Phone: (972) 771-1000, ext. 241

Fax: (972) 722-4561

E-mail: mkellis@whitmores.com

(Ms. Mary Kathryn Ellis)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: DUALZORB® is classified as non-flammable by DOT regulations (49 CFR 173.124)

2. Ventilation: DUALZORB® is not volatile and does not require ventilation.

3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid eye contact due to mechanical abrasion. In case of eye contact, immediately flush eyes with large amounts of water until particles are evacuated. Goggles are recommended during use.

- 4.a. Maximum storage temperature: 200°F continuous
- 4.b. Minimum storage temperature: NA
- 4.c. Optimum storage temperature range: 32°F to 100°F
- 4.d. Temperatures of phase separation and chemical changes: DUALZORB® should be stored out of the weather and should not be exposed to direct sun light for extended periods of time.

V. SHELF LIFE

Guaranteed shelf life of unopened product is 5 years if not exposed to weather or direct sunlight.

VI. RECOMMENDED APPLICATION PROCEDURE

DUALZORB® is a dehydrated product that must be hydrated for maximum effectiveness to bioremediate hydrocarbons in soil and water. Hydration can be accomplished with fresh or sea water. Additionally, it can be applied on a surface and hydrated with natural precipitation.

1. **Application Method:** This product can be applied by hand, mechanical spreaders, portable mixer or blown onto a surface using an air conveyor. Mix hydrated DualZorb® with oil contaminated soil, sand, or rocks by either hand, shovel or till into the soil with power equipment. DUALZORB® will absorb approximately 80% of the oil from soil and sand in the first 2 hours of application, with continued bioremediation of oil. The bioremediation effect of this product is not affected by water salinity, temperature, or oil type and age. However, the oil absorption capacity is reduced in the presence of salt water as it will also absorb salts. For hard surface stains and cleanup, hydrated product can be rubbed by hand over the surface until it will no longer absorb oil. Place the spent product in an approved, labeled container in accordance with local, state, federal, international, or country specific regulations. Depending upon the compound(s) absorbed, this product may be disposed in a landfill, incinerated, or land farmed. This product has a heat value of 8421Btu/pound and an ash content of 0.35%. For in situ applications, the hydrated DUALZORB® can be tilled into the contaminated soil.

2. **Concentration/Application Rate:** DUALZORB® is packaged in a dehydrated form and expands three times its original volume when rehydrated with either fresh or 1.5 times with salt water. This product should be mixed on a 1:1 volume basis with hydration water. For every 1 gallon of oil, 4 pounds of DUALZORB® is recommended. For in situ applications, 50 pounds of hydrated DUALZORB® is recommended per cubic yard of soil.

3. **Conditions for Use:** DUALZORB® is manufactured for land use and will absorb hydrocarbon, waste oil, and fuel spills. DUALZORB® is not affected by cold water but may require additional contact time.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	255,568	0	10,816	0
	NUTRIENT	255,414	0	10,821	0
	PRODUCT	248,869	0	12,738	0
7	CONTROL	244,841	0	10,290	0
	NUTRIENT	79,688	0	9,963	0
	PRODUCT	14,254	0	11,168	0
28	CONTROL	215,169	15.8	7,908	26.9
	NUTRIENT	2,407	99.1	9,393	13.2
	PRODUCT	1,545	99.4	950	92.5

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control

0.4%

Nutrient

15.4%

Product

30.0%

b. Toxicity:

Materials TestedSpeciesLC50 (ppm)

DUALZORB®

Menidia beryllina

1,414.21 96-hr

Mysidopsis bahia

1,096.05 48-hr

No. 2 Fuel Oil

Menidia beryllina

7.08 96-hr

Mysidopsis bahia

1.13 48-hr

DUALZORB® &

Menidia beryllina

8.43 96-hr

No. 2 Fuel Oil (1:10)

Mysidopsis bahia

2.70 48-hr

Reference Toxicant (SLS)

Menidia beryllina

12.25 96-hr

Mysidopsis bahia

11.71 48-hr

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of all microorganisms by species and percentages in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 6.5-7.5

Temperature: 60°F to 100°F

Salinity: 0-10%

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: 5.5-9.0

Temperature: 45°F and 105°F

Salinity: 0-10%

4. Special nutrient requirements: LBI Renewable recommends nutrient supplement s of maximum performance for bioremediation or in-situ applications. Contact LBI Renewable for project specific nutrient dosing.

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

1. Flash Point: NA

2. Pour Point: NA

3. Viscosity: NA

4. Specific Gravity: 2.25 g/mL

5. pH: NA

6. Surface Washing Agents: NA

7. Solvents: NA

8. Additives: None

9. Solubility: NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.185
Cadmium	0.185
Chromium	0.500
Copper	0.537
Lead	<0.185
Mercury	<0.00303
Nickel	<0.463
Zinc	9.35
Cyanide	<0.060
Chlorinated Hydrocarbons	<0.024

TECHNICAL PRODUCT BULLETIN: B-66
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JUNE 08, 2011
“REMEDIADE™”
(aka, SP 7010)

I. NAME, BRAND, OR TRADEMARK
REMEDIADE™
(aka, SP 7010)

Type of Product: Bioremediation Agent (Nutrient Additive)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
GrowMate International, LLC
17150 Butte Creek Drive, Suite 100
Houston, TX 77090
Phone: (281) 866-9042
Fax: (281) 866-9714
E-mail: victor@growmateintl.com
Website: www.growmateintl.com
(Mr. Victor J. Cardenas)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS	
GrowMate International, LLC	VariChem International, Inc.
17150 Butte Creek Drive, Suite 100	78330 HiWay 35 North
Houston, TX 77090	Bay City, TX 77414
Phone: (281) 866-9042	Phone: (979) 245-7278
Fax: (281) 866-9714	Fax: (979) 245-0612
E-mail: victor@growmateintl.com	E-mail: Gordon@varichemusa.com
Website: www.growmateintl.com	Website: www.varichemusa.com
(Mr. Victor J. Cardenas)	(Mr. Gordon Winfrey)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: No special requirements
3. Skin and eye contact; protective clothing; treatment in case of contact: As defined by OSHA’s Hazard Communication Standard, this product is non-hazardous with no evidence of adverse effects. Use safety glasses when handling for eye protection. Store in a cool dry place. Flush eyes and wash skin if contacted. In the event of contact with skin, wash with water. In the event of contact with eyes, rinse with water. In the event of contact with clothing or surfaces such as floors or counter tops, rinse with water and dry. In the event of spilling onto land or water, no handling or rinsing requirements are needed. No other safety or handling precautions need to be adhered to in the event of contact or spills.
- 4.a. Maximum storage temperature: 115°F continuous
- 4.b. Minimum storage temperature: 32°F

4.c. Optimum storage temperature range: 40°F to 98°F

4.d. Temperatures of phase separation and chemical changes: NA

V. SHELF LIFE

Shelf life of product unopened is 2 years. If the container has been opened, but uncontaminated and is resealed properly, the shelf life is 1 year after initial opening.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Product may be applied to any surface for removal of hydrocarbons. For treatment of large areas, properly diluted product may be applied by spraying with a pressure washer, portable fire pump or any other suitable pump with non-chlorinated fresh water or salt water. Application can also be made with normal spray equipment via a 1" or larger hose and a spray nozzle, similar to a fire nozzle. Eductor setups, water trucks as well as fire or other emergency response equipment may be used. Aircraft application is also effective in covering large areas or contaminated water.

2. Concentration/Application Rate: For in-situ soils, till the REMEDIADE™/water mixture onto the contaminated area. Soil treatment rate guidelines are 1 gallon of concentrate for 30 cubic yards of soil for each 20,000 TPH contamination level. Example: 40,000 TPH level would be 2 gallons per 30 cubic yards. Clay soils may take more product and sandy soils may take less. After the treatment rate is established, apply 1/3rd of the product mixture on the first day, wait 5 to 7 days and apply the second 1/3rd of the product mixture, wait another 5 to 7 days and apply the final 1/3rd of the product mixture. During each of the three applications apply 1/2 of the product mixture to the affected soil. Till or blade in this application before applying the second 1/2 of the product mixture. This will help the product get good coverage and disperse well into the soil.

In the event of oil spills on water, treatment guidelines are 1 gallon of concentrate per 30 square foot of surface area. After the treatment rate is established, apply 1/3rd over the area and wait 5 to 7 days and apply the second treatment. Then wait 2 to 5 days and apply the third treatment. Light gravity oils may take more. When spraying the product over oil, good agitation of the contaminant with the product can only help. This helps add to surface contact and aids in the bioremediation process. Salinity of the water will not make a difference in the effectiveness of the product.

3. Conditions for Use: Product must be mixed with non-chlorinated water, but it can be used with fresh, salt or brackish water. Reapplication may be necessary in severely contaminated areas. Be sure to apply the product on three separate days, allowing time in between the days, this helps keep bacteria counts up at a more consistent level through the process. Adding all the product in one treatment will only prove to waste product and slow the effectiveness of the overall remediation process.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	255,568	0	10,822	0
	NUTRIENT	255,414	0	10,821	0
	PRODUCT	245,168	0	10,816	0
7	CONTROL	244,841	0	10,920	0
	NUTRIENT	215,169	0	9,963	0
	PRODUCT	79,688	0	9,393	0
28	CONTROL	21,469	91.6	9,067	16.2
	NUTRIENT	4,198	98.4	7,908	26.9
	PRODUCT	2,404	99.0	607	94.4

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control

0.0%

Nutrient

17.8%

Product

36.0%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

The product is a nutrient additive and does not contain microbiological cultures or enzyme additives.

1. Listing of each component of the formulation by chemical name and percentage by weight:

CONFIDENTIAL

2. Optimum storage conditions:

Temperature: 40°F to 98°F

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS
NA

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**4/16/2017
7/27/2022**

TECHNICAL PRODUCT BULLETIN: B-67
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JULY 27, 2011
“ERGOFIT MICROMIX AQUA”

I. NAME, BRAND, OR TRADEMARK

ERGOFIT MICROMIX AQUA

Type of Product: Bioremediation Agent (Microbiological Culture, Enzyme Additive, Nutrient Additive)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Evadine Technologies, LLC

217 Deborah Drive

New Braunfels, TX 78130

Phone: updated information required

E-mail: updated information required

(Mr. Warren Russell)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Evadine Technologies, LLC

217 Deborah Drive

New Braunfels, TX 78130

Phone: updated information required

E-mail: updated information required

(Mr. Warren Russell)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Water-based, Non-flammable

2. Ventilation: Needs no ventilation; aqueous-based organic product; does not emit hazardous vapors. Some CO₂ may build up.

3. Skin and eye contact; protective clothing; treatment in case of contact: ERGOFIT MICROMIX AQUA is not a dermal irritant. Avoid eye contact, and wear goggles when using product. Eyewash for quick and copious eye flushing should be available on site. Seek prompt medical attention should contact occur and if irritation persists. Protective rubber gloves are suggested during handling. ERGOFIT MICROMIX AQUA has a smell of fermentation and yeast. The product does not give off harmful vapors. Long storage will cause build up of CO₂ in water vapor.

4.a. Maximum storage temperature: 104°F

4.b. Minimum storage temperature: 32°F

4.c. Optimum storage temperature range: 57°F to 97°F

4.d. Temperatures of phase separation and chemical changes: above 113°F

V. SHELF LIFE

ERGOFIT MICROMIX AQUA has a recommended shelf life of 5 years. After 5 years at optimum storage in cool temperature there is an approximate 10% decrease per year in product effectiveness. Shelter from direct sunlight or extreme cold or heat source. In the event of fire, wash with water.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: ERGOFIT MICROMIX AQUA can be applied with any commercially available spray apparatus, such as small hand held tanks, back packs, large mixing tanks with mechanical pumping devices, vessels with booms for spraying wide paths, or liquid spray devices on crop duster airplanes or helicopters. ERGOFIT MICROMIX AQUA can also be applied by eductor systems from vessels, fire trucks, or any other outfitted vehicle.

2. Concentration/Application Rate: ERGOFIT MICROMIX AQUA generally takes 5 to 50 minutes to penetrate the molecular walls of hydrocarbons. Warmer conditions favor faster biological action whereas colder conditions may reduce the speed of decomposition. Once ERGOFIT MICROMIX AQUA is applied to the targeted areas, the microbes will attach themselves to the hydrocarbons and start to attack their carbon structure and metabolize into natural organic substances from the humus family. Aquatic plants and animal life will feed on this nutrient. Within hours odor will be negligent and changes will be noticeable in seven days, depending on the temperature. ERGOFIT MICROMIX AQUA will also break down the adhesive properties of the hydrocarbons, preventing oils from attaching to animals, vegetation, rocks, and earth.

Dilution Rates: ERGOFIT MICROMIX AQUA should always be mixed with the native water of the affected area. Note: Do not use city water that has been treated with chlorine with ERGOFIT MICROMIX AQUA. This means that if you are treating an affected saltwater area, then saltwater should be used as your base carrier for the product. Likewise if you are treating a lake or river, then that carrier water would be the freshwater from that source. For general applications and light oil films, dilute each gallon of ERGOFIT MICROMIX AQUA with source water (e.g., fresh, brackish, or saltwater) at a ratio of 1:50. For oil mousse like formation in intertidal zones, use a dilution of 1:30. If the spill is very heavy and the oil layer is thick (more than 1 inch) it is recommended that ERGOFIT MICROMIX AQUA be applied at a lower ratio of 1:20. On land not involving water bodies, it is recommended that an organic absorbent be applied prior to using ERGOFIT MICROMIX AQUA to treat oil spills to remediate the C1 and C35 Petroleum Hydrocarbons. This is to increase the contact surface area for ERGOFIT MICROMIX AQUA to convert spills oil and absorbent to organic humus.

Application on Coastal Water: Apply the mixed solution using hand held sprayers, tank sprayers, booms from vessels, helicopters, or airplanes. First, start by spraying the outer perimeter of the spill and systematically work towards the middle of the affected area, making sure to cover the entire surface area of the spill. Use 1.5 gallons of ERGOFIT MICROMIX AQUA concentrate for every 1000 gallons of hydrocarbons spilled. Dilute it with 30 gallons of seawater per gallon of concentrate for spraying. [To calculate gallons of ERGOFIT MICROMIX AQUA required, multiply estimated gallons of hydrocarbons by 0.0015.] For denser hydrocarbons, like in the case of crude oil, multiply barrels of crude oil by 42 to get gallons of crude and apply above ratios. If

you do not know gallons of hydrocarbons or barrels of crude oil, estimate size of spill by (1000 square yards x 2 inch average thickness) to arrive at gallons of oil spilled. Use 10 kg/22 lbs of ERGOFIT MICROMIX AQUA diluted to 50 gallons in water to cover this area. As a rule, 2 kg/4.4 lbs ERGOFIT MICROMIX AQUA is required per metric ton of oil spilled. Dilution varies depending on oil thickness or simple sheen floating on water surface.

Application for Intertidal Zones: ERGOFIT MICROMIX AQUA should be applied at low tide, when the affected areas are exposed to the elements, allowing the product to securely attach to the hydrocarbons. Cease application if the tide rises and resume once the water level has receded again. Continue application cycle until the entire affected area has been coated. The recommended mix ratio is 1:30. In areas where a combination of high tide and waves have pushed the contamination beyond the intertidal zone, oil rag layer looking like chocolate mousse, cordon off the area and start spraying ERGOFIT MICROMIX AQUA diluted at a ratio of 1:20 in water. The objective is to get an application rate of between 1 to 2 gallons of concentrated ERGOFIT MICROMIX AQUA sprayed per 1000 gallons of hydrocarbons spilled.

3. Conditions for Use: ERGOFIT MICROMIX AQUA acts on all organic hydrocarbons on sea, fresh water, and land. As the age of spilled hydrocarbons increases, so does the time necessary for bioremediation. In general, fresh crude, gasoline of BTEX takes anywhere from 30 days to 12 months to completely bioremediate depending on weather conditions and density of spill. However, the remediation process will be noticeable throughout the process. Variations in seawater salinity, has no effect, as long as microbial life can exist, then ERGOFIT MICROMIX AQUA will be effective in salt and brackish water with a maximum salinity of 4.9 percent. ERGOFIT MICROMIX AQUA bioremediation slows somewhat at temperatures below 40°F. However, it will continue to work in any water temperatures that will sustain microbial life. Decreasing the amount of ERGOFIT MICROMIX AQUA per square yard from recommended dosage rates lengthens the remediation time. When nitrogen and carbon is added to ERGOFIT MICROMIX AQUA the initiation of bacterial-enzymatic activity is enhanced many fold to begin bioremediation within 2 hours of application.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	239,235	0	16,502	0
	PRODUCT	239,686	0	17,431	0
	CONTROL	217,023	9.30	10,942	33.70

7	PRODUCT	17,819	92.6	9,606	44.90
28	CONTROL	188,379	21.3	8,989	45.50
	PRODUCT	2,216	99.10	3,100	82.20

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Product</u>
1.7%	45.6%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

Microbiological Culture:

1. Listing of all microorganisms by species and percentage in the composition:

CONFIDENTIAL

2. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 6.5 to 7.5.

Temperature: 57°F to 97°F.

Salinity: The maximum permissible salinity is up to 4.9% sodium by solution

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: Lower than 4.5 or higher than 8.5 reduces the product efficiency by 50 percent.

Temperature: Lower than 32°F or higher than 104°F reduces the product efficiency by 50 percent.

Salinity: The maximum permissible salinity is up to 4.9% sodium by solution

4. Special nutrient requirements: NA

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta Hemolytic Streptococci: Negative

Enzyme Additive:

1. Listing of each component of the total formulation, other than enzymes, by chemical name and percentage by weight: CONFIDENTIAL

2. Enzyme Names: CONFIDENTIAL

3. I.U.B.: CONFIDENTIAL

4. Source of Enzymes: Plant or Fungi/Fermentation process

5. Units: No less than 1% and no more than 50% by weight

6. Specific Gravity: 1.00

7. Optimum Conditions:

- a. pH: 7.0
- b. Temperature: 72°F
- c. Salinity Ranges: Fresh water to salt water up to 4.9%
- d. Minimum and Maximum pH: 4.5 – 8.5
- e. Minimum and Maximum Temperature: 32°F – 104°F
- f. Minimum and Maximum Salinity Levels: Salinity level that will support microbial activity will not adversely affect ERGOFIT MICROMIX AQUA performance
- g. Enzyme Shelf Life: Up to 5 years when properly stored
- h. Enzyme Optimal Storage Conditions: 72°F is optimal, enzyme range is freezing to 104°F, never leave ERGOFIT MICROMIX AQUA in direct sunlight for more than a couple of hours

Nutrient Additive:

1. Listing of each component of the formulation by chemical name and percentage by weight:

CONFIDENTIAL

2. Optimum storage conditions:

Temperature: 32°F to 104°F

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

LISTING CHANGES PENDING;
VERIFICATION BY MANUFACTURER AND EPA REQUIRED

TECHNICAL PRODUCT BULLETIN: B-68
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: AUGUST 8, 2011
“SHAMANTRA GREEN”
(aka, SHAMANTRA BIO)

I. NAME, BRAND, OR TRADEMARK
SHAMANTRA GREEN
(aka, SHAMANTRA BIO)
Type of Product: Bioremediation Agent (Nutrient Additive)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Molecular Mediation LLC
C/- Molecular Mediation Pty Ltd
Level 3, Suite 405
152 Bunnerong Road
Eastgardens 2036
Australia
Phone: +612-9659-4553
E-mail: info@molecularmediation.com
E-mail: mark@molecularmediation.com
(Mr. Mark Pilgrim, Manager)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Molecular Mediation PTY LTD
Level 3, Suite 405
152 Bunnerong Road
Eastgardens 2036
Australia
Phone: +612-9659-4553
E-mail: info@molecularmediation.com
E-mail: mark@molecularmediation.com
(Mr. Mark Pilgrim, Manager)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: No special requirements
3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing required, however goggles are recommended. If eye or skin irritation occurs, flush with plenty of fresh water.
- 4.a. Maximum storage temperature: 200°F
- 4.b. Minimum storage temperature: None

- 4.c. Optimum storage temperature range: 40°F to 140°F
- 4.d. Temperatures of phase separation and chemical changes: Stable

V. SHELF LIFE

>3 years when stored in sealed silos, polydrums, poly bags or totes.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method:

Recommended Uses and Product Description

Shamantra Green is recommended for use on water and near shoreline oil spills. Shamantra Green is a natural product made using humic acid. The product has been processed to have a strong affinity for collecting natural oils. The process makes applying and removing the product to/from the environment easy and safe.

Water Applications

For small scale spills on fresh or salt water, Shamantra Green can be broadcast directly onto the spill by hand or a hand held spreader. Agitation is not necessary when using Shamantra Green on small scale spills. Shamantra Green can also be used in booms, sacks, and pillows.

For large spills on fresh or salt water, Shamantra Green can be deployed into the spill using an air or water stream.

Shamantra Green will remove oils and other hazardous hydrocarbon based materials from both salt and fresh water very effectively using an encapsulation process on the spilled oil. Once encapsulated into the carbon matrix of Shamantra Green, the spilled oil will not leach out, even under pressure. The humic acid then acts as a nutrient to stimulate microbial activity and enhance the bioremediation of the spilled oil.

Any encapsulated residue can be removed from the water with hand vacuums, vacuum barges, commercial nets, centrifuges, etc. Encapsulated materials can be sent to landfill or used as a fuel source for generating heat ensuring that any material disposed of is in accordance with all applicable federal, state, and local regulations.

Shoreline Applications

For spills on shorelines, Shamantra Green would be applied in the same manner and ratios as with the water applications. The product can also be applied by sand-blasting equipment, fire hoses or pneumatic spreading equipment. Agitation is not necessary for most applications.

To recover encapsulated oil or hazardous materials from spills on land, the encapsulated product can be collected and removed efficiently and effectively using a variety of manual and mechanical methods including picking up by hand, using brooms, rakes and shovels to remove and pick up encapsulated petroleum waste product. Mechanical means include using hand held vacuums, portable vacuum units, and vacuum vehicles.

Once the Shamantra Green has been saturated with oil or hazardous materials, it will not leach

the contaminants, even under pressure, so any encapsulated materials can be disposed of appropriately or used as a fuel source for generating heat ensuring that any material disposed of is in accordance with all applicable federal, state, and local regulations.

Proper precautions, including testing as necessary to identify the characteristics of wastes encapsulated by Shamantra Green should be taken to determine the safe and legally required means of recovering, handling, storing, transporting, treating, recycling, or disposing of materials on land in accordance with all applicable federal, state, and local regulations.

2. Concentration/Application Rate:

Shamantra Green is usually applied at a ratio of 1:5–1:30 to waste by weight to remediate light, medium, and heavy hydrocarbons. Shamantra Green can also be used very effectively on heavier crudes including Bunker C using the aforementioned application ratios. The specific ratio will depend on many factors including the composition of the waste, the ambient temperatures, pH of the contaminated water and age of the waste spill. Optimum application ratios should be determined on a case by case basis.

3. Conditions for Use:

Shamantra Green initially behaves like a synthetic sorbent, then encapsulates the oil through a chemical and physical process. Once encapsulated, the spilled oil is captured within the pore matrix contained within the carbon structure.

Shamantra Green is effective in all environments and under a broad range of weather conditions. Depending upon the age, viscosity, and composition of the spilled material, varying amounts of Shamantra Green may be required to obtain complete remediation. Any encapsulated residue can be recovered and disposed of in accordance with all applicable federal, state, and local regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	43,457	0	6,451	0
	NUTRIENT	43,047	0	6,263	0
	PRODUCT	43,153	0	6,262	0

7	CONTROL	40,943	0	5,283	0
	NUTRIENT	214	0	2,389	0
	PRODUCT	9,859	0	1,338	0
28	CONTROL	39,066	10.1	4,429	31.3
	NUTRIENT	76	99.8	685	89.1
	PRODUCT	122	99.7	297	95.3

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control

14.4%

Nutrient

0.0%

Product

25.4%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

Nutrient Additive:

No special requirements are required other than the product can be stored in dry conditions with an optimum storage temperature of 40°F to 140°F and a maximum storage temperature of 200°F.

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN: B-69
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: OCTOBER 13, 2011
“SUMP SAFE BIO-RECLAIM”

I. NAME, BRAND, OR TRADEMARK

SUMP SAFE BIO-RECLAIM

Type of Product: Bioremediation Agent (Biological Additive/Microbiological Culture)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

F4 Environmental, Inc.

P.O. BOX 2506

Stony Plain, Alberta, Canada

T7Z 1X9

Mobile: (780) 238-2741

E-mail: marlin@f4environmental.ca

(Mr. Marlin Rudolph)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Long Chain Reclaim

960 Boulder Blvd

Stony Plain, Alberta, Canada

T7Z 0E6

Phone: (780) 886-2024

Email: mmyshak@lcreclaim.com

(Mr. Mike Myshak)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: No special requirements
3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing required, however goggles are recommended. If eye or skin irritation occurs, flush with plenty of fresh water.
- 4.a. Maximum storage temperature: 110°F maximum, must be used within 24 hours from constitution
- 4.b. Minimum storage temperature: 45°F
- 4.c. Optimum storage temperature range: 60°F to 90°F
- 4.d. Temperatures of phase separation and chemical changes: Stable

V. SHELF LIFE

The material must be used within 24-48 hours of constitution of the powdered bacteria portion in water. The dry material must be kept at -20°C and is stable for two years at this temperature. Once sent to the field, the material may be stored on ice for up to two weeks prior to constitution.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Product may be applied by the usual methods. For smaller spills a drum pump with sprayer may be used, mixing with fresh water typically. The concentrate is used at 25:1 dilution rate with water and is typically applied at a rate of 6 gallons per cubic meter of soil. It is important that the soil be broken up into small clumps (rototilling is acceptable) to ensure effective application. The soil is left and biodegradation is expected to complete in approximately 12 weeks. Analysis using approved sampling procedures is performed to confirm biodegradation.

For larger volume projects, any auger based soil homogenizer is employed to break up large clumps of soil, which are dug out from the contaminated area using a standard hoe. The broken up soil is taken up a conveyor and has the diluted concentrate (25:1) at a rate of 6 gallons per cubic meter of soil. Piles up to 20 feet high may be formed. The soil is left and biodegradation is expected to be complete in approximately 12-18 weeks. Analysis using approved sampling procedures is performed to confirm biodegradation. Proper safety rules must be employed to ensure that any holes dug out are not accessible to employees or unauthorized personnel.

For oil spills on open water, it is recommended that a 25:1 dilution of the product be applied via spraying. In this way, the bacteria can contact the floating oil and immediately begin to form a bio-film. The spray would also be applied on any soil contaminated on banks, etc. It is important to ensure complete coverage of the water/oily surface and soil during spray application. Degradation will be visible visually and can be confirmed by Fats, Oil and Grease (FOG) analysis.

For smaller, contained volumes of oily water (typically emulsified, white water), it is recommended that sufficient concentrate be added to the contaminated water such that it results in a 2.5% concentration of the concentrate in the contaminated water. Preferably, aeration can be performed, using even a small, fish tank aeration unit. Visual evidence of biodegradation should be apparent within one week or less and can be confirmed by FOG analysis.

2. Concentration/Application Rate: The concentrate is used at 25:1 dilution rate with water and is typically applied at a rate of 6 gallons per cubic meter of soil.

3. Conditions for Use: The product can be used in fresh or salt water and may be applied at temperatures between 40°F and 120°F. However, the product is most effective when applied at water temperatures between 70°F-90°F. Further, the product is effective on fresh spills or aged hydrocarbons. Note for preparation of the product to be applied while in the field: all components listed in the product are packaged as a complete unit and are applied as such. The microbial portion of the product is supplied in bags which are either drum (55 gallon) or pail (5 gallon) sizes. Fresh water, if available, is added to fill the bag (bags are placed in pails or open headed drums) to 55 gallon or 5 gallons respectively. Depending upon which of these are being constituted with water, a high-density polyethylene (HDPE) bottle with the appropriate quantity of surfactant is added into the container (bottles are labeled Bio-Reclaim Surfactant – Drum Size (or Pail Size)). In the same way, HDPE containers with appropriate amounts of sodium nitrite are added and are labeled Bio-Reclaim Salt – Drum Size (or Pail Size)).

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	40770	0	5229	0
	NUTRIENT	41329	0	5326	0
	PRODUCT	40609	0	5384	0
7	CONTROL	37530	0	4824	0
	NUTRIENT	21788	0	4634	0
	PRODUCT	38354	0	5298	0
28	CONTROL	31456	22.8	3692	24.2
	NUTRIENT	502	98.8	3052	42.7
	PRODUCT	21356	47.4	3742	49.0

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control

6.36%

Nutrient

33.00%

Product

3.00%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of each component of the total formulation, other than microorganisms, by chemical name and percentage by weight: CONFIDENTIAL

2. Listing of all microorganisms by species and percentages of each species in the composition of the additive: CONFIDENTIAL

3. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 6-8

Temperature: 90°F

Salinity: Not applicable

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: 4.8 – 9

Temperature: 59°F – 104°F

Salinity: Not applicable

4. Special nutrient requirements: A combination of 70 percent live active yeast mixed with 30 percent fine ground corn cob is used as a nutrient. In a 55 gallon drum of concentrate, approximately 1.1 kg of this mix will be found (relative to the 1.1 kg, the actual bacteria represent the negligible mass of several grams). There are no storage requirements for the nutrient portion of the formula; however, as they are in a homogenous mixture with the bacteria, they must be stored as described in Part V of this bulletin.

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN: B-70
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: FEBRUARY 7, 2013
“WASTE AWAY®”

I. NAME, BRAND, OR TRADEMARK
WASTE AWAY®

Type of Product: Bioremediation Agent (Biological Additive/Microbiological Culture)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
CXI (Chem-X International, LLC)
1100 East Sandy Lake Road
Coppell, Texas 75019
Phone: (972) 471-7775
Fax: (972) 393-2011
E-mail: dhowardcxi@outlook.com
Website: www.cxinternational.com
(Mr. David Howard)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Prime-Dirt

20810 Avenue 332
Woodlake, California 93286
Phone: (555) 787-7278
Fax: (555) 787-8560
E-mail: james@prime-dirt.com
Website: www.prime-dirt.com
(Mr. James Henderson)

Microbial Matrix

33935 Highway 99E, Suite B
Tangent, Oregon 97389
Phone: (541) 967-0554
E-mail: lrogers@microbialmatrix.com
Website: www.microbialmatrix.com
(Ms. Lynn Rogers)

Back-To-Nature Compost

P.O. Box 190
5407 Slaton Highway
Slaton, Texas 79364
Phone: (888) 282-2000
Phone: (806) 745-1170
E-mail: greg@backtonaturecompost.com or
bj@backtonaturecompost.com
Website: www.backtonaturecompost.com
(Mr. Greg Schilling)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: No special requirements
3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing required; however, gloves and goggles are recommended. If eye or skin irritation

occurs, flush with plenty of fresh water. If ingested, may cause nausea or vomiting, seek medical attention. Do not induce vomiting. In case of spills, disperse with water, treat like a surfactant or soap spill.

4.a. Maximum storage temperature: 100°F continuous, 120°F up to 5 days

4.b. Minimum storage temperature: 35°F

4.c. Optimum storage temperature range: 50°F to 100°F

4.d. Temperatures of phase separation and chemical changes: Stable

V. SHELF LIFE

Two years when product remains in sealed bottles, poly drums, or totes (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Product may be applied by any type of liquid delivery system (i.e., boom sprayers, spray pumps). For smaller spills a drum pump with sprayer may be used, mixing with fresh or salt water as required depending on the type and viscosity of oil being treated. Typically containment is not necessary.

2. Concentration/Application Rate:

a. On heavy oils: use product directly on the spill, or up to approximately a 1:10 dilution ratio (product:water). Lighter oils will require a 1:10 to 1:30 product to water ratio. Warmer waters (greater than 78 °F) and/or good agitation during application will require less product.

b. Lagoon application: 2 gallons per surface acre of lagoon or 16 ounces per 3,000 cubic feet. Maintain daily at 50 percent initial application. Use spray applicator for even distribution.

c. Shoreline application: 1 gallon per 10 cubic yards of contaminated soil applied at 3 percent concentration. Maintain weekly with 50 percent initial application. Use spray applicator for even distribution. Till soil after application or use gravity fed drip system.

3. Conditions for Use: Effective in salt water or fresh water, with no limitations as to usage within optimum temperature parameters (application may be made at or above 35°F, with optimum above 48°F). Product may be used on any age crude and any type. Optimum salinity range is from fresh water to salt water of 110 ppt.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	99715	0	11056	0
	NUTRIENT	94558	0	10228	0
	PRODUCT	98187	0	10270	0
7	CONTROL	54816	0	9690	0
	NUTRIENT	48670	0	9329	0
	PRODUCT	51534	0	6019	0
28	CONTROL	46847	53.0	6452	40.8
	NUTRIENT	3581	96.2	6136	40.0
	PRODUCT	776	99.2	4038	60.7

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control
6.41%

Nutrient
50.91%

Product
49.95%

b. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
WASTE AWAY®	Menidia beryllina	552,762.06 96-hr
	Mysidopsis bahia	353,302.46 48-hr
No. 2 Fuel Oil	Menidia beryllina	10.22 96-hr
	Mysidopsis bahia	2.11 48-hr
WASTE AWAY® & No. 2 Fuel Oil (1:10)	Menidia beryllina	12.54 96-hr
	Mysidopsis bahia	2.11 48-hr
Reference Toxicant (SLS)	Menidia beryllina	11.87 96-hr
	Mysidopsis bahia	13.29 48-hr

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of each component of the total formulation, other than microorganisms, by chemical name and percentage by weight: CONFIDENTIAL
2. Listing of all microorganisms by species and percentages of each species in the composition of

the additive: CONFIDENTIAL

3. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: 7.5, range 6.0 to 8.0

Temperature: 72°F, range 60°F to 60°F

Salinity: 40 ppt, range 0 to 110 ppt

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: 4.0 – 11.0

Temperature: 40°F – 125°F

Salinity: 0 – 110

4. Special nutrient requirements: Not applicable

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN: B-71
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: APRIL 7, 2014
“ACT TERRA FIRMA”
(aka, ACT-TF)

I. NAME, BRAND, OR TRADEMARK

ACT TERRA FIRMA

(aka, ACT-TF)

Type of Product: Bioremediation Agent (Biological Additive/Microbiological Culture)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Franssen Enterprises, Inc.

511 N. McKinley Avenue

Fort Lupton, CO 80621

Phone: (303) 833-5393

Fax: (303) 833-2872

E-mail: actcleaners@comcast.net

Website: www.actcleaners.com

(Mr. Todd Franssen)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

American Cleaning Technologies, Inc.

(ACT BioRemediation Products)

511 N. McKinley Avenue

Fort Lupton, CO 80621

Phone: (303) 833-5393

Phone: (866) 919-2872

Fax: (303) 833-2872

E-mail: actcleaners@comcast.net

Website: www.actcleaners.com

(Mr. Todd Franssen)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)

2. Ventilation: Standard industrial hygiene ventilation practices should be used to control human exposures to this product. Respiratory protection equivalent to either N100 or the older HEPA filter (APR with a DFM (purple) cartridge) will provide adequate protection.

3. Skin and eye contact; protective clothing; treatment in case of contact: Recommendations are guidelines and may not apply to every situation. To prevent skin contact, standard work clothing and standard work or latex gloves will provide adequate protection. To prevent eye contact, standard safety glasses with side shields are recommended.

4.a. Maximum storage temperature: 48°C continuous, 60°C up to 5 days

4.b. Minimum storage temperature: -45°C

4.c. Optimum storage temperature range: 4°C to 38°C

4.d. Temperatures of phase separation and chemical changes: Stable

V. SHELF LIFE

Store product in a dry area. If kept in a sealed container with desiccant bag the shelf life is 5 years.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Apply ACT TERRA FIRMA directly to surfaces by broadcasting product with a scoop or grass seed drop spreader. DO NOT add fertilizers or nutrients.

2. Concentration/Application Rate:

Hard Surface with Limited Permeability (e.g., concrete, asphalt, stone, etc.): Apply a small amount of ACT TERRA FIRMA with a scoop or grass seed drop spreader to the surface. Using a soft bristle broom spread ACT TERRA FIRMA over the surface. If desired results are not achieved within two weeks repeat application. DO NOT sweep or wash cleaner off. ACT TERRA FIRMA will dissipate over time. One pound covers approximately 100 square feet. DO NOT add fertilizers or nutrients. Prior to application, appropriate containment mechanisms should be used deployed to prevent runoff of the product/oil mixture.

Permeable Surfaces (e.g., packed sand, gravel, or soil; loose, bulk material that may be excavated and stockpiled for treatment): Apply ACT TERRA FIRMA product directly to surfaces by broadcasting product using a scoop or grass seed drop spreader over the contaminated area. Check the contamination levels every 15 days, reapplying as needed. Tilling may be needed for contamination 12 inches or deeper. One pound covers approximately 50 square feet. DO NOT add fertilizers or nutrients. Prior to application, appropriate containment mechanisms should be deployed to prevent runoff of the product/oil mixture.

Applications to Water: ACT TERRA FIRMA is recommended for use in conditions where the water is not actively flowing. Apply to water surface at a rate of one pound over approximately a 200 square foot surface area. Using a scoop or a handheld broadcast spreader to ensure that ACT TERRA FIRMA is dispersed evenly. DO NOT add fertilizers or nutrients.

Conditions for Use: Product usage is not affected by salinity. Water temperature range should be -2°C to 46°C and can be used on frozen water in temperatures as low as -65°C. ACT TERRA FIRMA is best used on contamination levels of 3% to 5% TPH. Contact Act BioRemediation Products for usage on higher contamination levels.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	29,969	0	9,018	0
	NUTRIENT	29,102	0	8,582	0
	ACT TERRA FIRMA	27,685	0	8,240	0
7	CONTROL	24,289	0	6,974	0
	NUTRIENT	18,132	0	6,377	0
	ACT TERRA FIRMA	2,614	0	3,306	0
28	CONTROL	18,909	36.9	4,426	50.8
	NUTRIENT	1,465	94.9	5,609	34.6
	ACT TERRA FIRMA	113	99.6	475	94.2

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control

0.0%

Nutrient

17.0%

ACT Terra Firma

9.7%

b. Toxicity:

Material Tested

ACT TERRA FIRMA

No. 2 Fuel Oil

ACT TERRA FIRMA & No.

2 Fuel Oil (1:10)

Reference Toxicant (SLS)

Species

Menidia beryllina

Mysidopsis bahia

Menidia beryllina

Mysidopsis bahia

Menidia beryllina

Mysidopsis bahia

Menidia beryllina

Mysidopsis bahia

LC50 (ppm)

223.60 96-hr

74.10 48-hr

4.24 96-hr

1.99 48-hr

2.61 96-hr

1.19 48-hr

12.25 96-hr

12.27 48-hr

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of each component of the total formulation, other than microorganisms, by chemical name and percentage by weight: CONFIDENTIAL
2. Listing of all microorganisms by species and percentages of each species in the composition of the additive: CONFIDENTIAL
3. Optimum pH, temperature, and salinity ranges for use of the additive:
pH: range 4.0 to 9.0
Temperature: range -20°C to 52°C
Salinity: Freshwater 0 to 500 ppm; Ocean Saltwater 35,000 ppm
3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:
pH: 3.0 and 13.0
Temperature: -50°C and 65°C
Salinity: Freshwater and 45,000 ppm
4. Special nutrient requirements: Not applicable. DO NOT add fertilizers or nutrients.
5. Test results regarding the determination of the presence of the following:
Salmonella: Negative
Fecal coliform: Negative
Shigella: Negative
Staphylococcus Coagulase positive: Negative
Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

1. Flash Point: NA
2. Pour Point: NA
3. Viscosity: NA
4. Specific Gravity: 0.8 g/cm³
5. pH: 7.0 – 12.0
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: NA
8. Additives: CONFIDENTIAL
9. Solubility: <5% (estimated)

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.13
Barium	1.30
Cadmium	0.077
Chromium	0.17
Copper	NA
Lead	<0.25
Mercury	<0.00010
Selenium	0.67
Silver	<0.030

Zinc	NA
Cyanide	NA
Chlorinated Hydrocarbons	NA

TECHNICAL PRODUCT BULLETIN: B-72
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: APRIL 2, 2018
“PETROCLEAN™”

I. NAME, BRAND, OR TRADEMARK

PETROCLEAN™

Type of Product: Bioremediation Agent (Biological Additive/Microbiological Culture)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Green Earth Naturally, L.L.C.

2314 Ridgefield Street NE

Roanoke, VA 24102

Phone: (540) 362-5636

Fax: (540) 362-9447

E-mail: chale@greeneearthnaturally.com

Website: www.GreenEarthNaturally.com

(Mr. Carroll Hale III)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Green Earth Naturally, L.L.C.

2314 Ridgefield Street NE

Roanoke, VA 24102

Phone: (540) 362-5636

Fax: (540) 362-9447

E-mail: chale@greeneearthnaturally.com

Website: www.GreenEarthNaturally.com

(Mr. Carroll Hale III)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: Use combination of general dilution ventilation and local exhaust ventilation to keep exposure as low as possible.
3. Skin and eye contact; protective clothing; treatment in case of contact: Prevent skin and eye contact by wearing appropriate personal protective equipment. If eye or skin irritation occurs, flush with plenty of fresh water. Coveralls or other suitable protective garments should be worn with suitable footwear for application and working conditions. Chemical safety goggles or glasses and impervious gloves are recommended.
- 4.a. Maximum storage temperature: below 120°F
- 4.b. Minimum storage temperature: above freezing
- 4.c. Optimum storage temperature range: 55°F to 100°F. Avoid storage in areas of extreme heat or extreme cold. Store in tightly closed containers, and away from children.
- 4.d. Temperatures of phase separation and chemical changes: Stable

V. SHELF LIFE

Three to six months in sealed 1 gallon containers, 5 gallon buckets and 55 gallon drums or totes (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURE

PETROCLEAN™ is effective in bioremediating petroleum contaminated soils and is not designed for use in open waters. There are no limitations to usage within optimum temperature parameters.

1. Application Method:
 - a. Surficial spraying of PETROCLEAN™ may be applied by any type of liquid delivery system.
 - i. Soils and gravels can be treated with PETROCLEAN™ using a conventional yard sprayer. Repetition may be needed.
 - ii. PETROCLEAN™ can be applied to secondary containment areas, the key factor in cleaning the contaminated substrate, whether gravel or soil, is residence time for the microbes, moisture, and oxygen.
 - b. Subsurface application can vary by location. Soil type becomes a contingent factor in dilution rates and method of application. When bioremediating soils, cleaning the contaminated substrate, whether gravel or soil, is affected by residence time for the microbes, moisture, and oxygen.
 - i. For in-situ soils, mix PETROCLEAN™ with water to the desired concentration and dispense inoculated fluids in the subsurface, adjacent infrastructure, and the surface.
 - ii. For ex-situ soils and longer term bioremediation projects, additional applications of nutrients and oxygen releasing compounds may be required to maintain or boost microbial activity.
2. Concentration/Application Rate: Rates will vary based upon the type of soil and amount of petroleum spilled, the extent of weathering, and other site-specific conditions, including soil profiles, proximity to surface waters and wells. Heavy petroleum compounds such as crude oil and bunker fuel, with a higher proportion of complex aliphatics, will require a higher concentration of PETROCLEAN™ than lighter petroleum compounds such as gasoline.
 - a. Hydrocarbon types: PETROCLEAN™ can be applied on any hydrocarbon compound (including crude, diesel, gasoline, aviation fuel, bunker fuels, etc.) found in soils.
 - b. Most frequent applications include any petroleum contamination around AST's and USTs and containment pits requiring rehabilitation.
 - c. Concentration Rate: on heavy oils, apply PETROCLEAN™ directly on the spill area following absorption of free product, utilize a 1:10 dilution ratio (product to water). Lighter oils will require a 1:30 (product to water) dilution ratio.
3. Conditions for Use: Bioremediation slows at temperatures below 40°F. No limitations as to usage within optimum temperature parameters have been observed.
 - a. Monitoring of dissolved oxygen levels is recommended. If needed, a mechanical aeration device should be deployed or the use of Oxygen Releasing Compounds (ORC) should be encouraged to maintain dissolved oxygen levels above 3 mg/L.
 - b. Additional nutrients may be required to increase microbial activity over time if intrinsic nutrients are depleted. The application of 10% nitrogen, 10% phosphorus, and 10%

potassium fertilizer can be used in-situ or ex-situ as situations warrant to boost microbial activity and enhance co-metabolic digestion of petroleum.

- c. Prevent spill run-off from entering surface water bodies.
- d. Eliminate all source of ignition.
- e. Dispose of used absorbent materials according to all local, regional, and federal regulations.

II. TOXICITY AND EFFECTIVENESS

b. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	57,032	0	12,547	0
	NUTRIENT	55,231	0	12,458	0
	PETROCLEAN™	58,148	0	12,141	0
7	CONTROL	55,126	0	12,091	0
	NUTRIENT	47,951	0	11,599	0
	PETROCLEAN™	34,095	0	8,640	0
28	CONTROL	50,608	11.2%	10,766	14.2%
	NUTRIENT	34,291	37.9%	9,574	23.1%
	PETROCLEAN™	14,854	74.4%	4,711	61.1%

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control

7.83%

Nutrient

41.50%

PETROCLEAN™

60.93%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

1. Listing of each component of the total formulation, other than microorganisms, by chemical name and percentage by weight: CONFIDENTIAL

2. Listing of all microorganisms by species and percentages of each species in the composition of the additive: CONFIDENTIAL

3. Optimum pH, temperature, and salinity ranges for use of the additive:

pH: range 6.3 to 7.3

Temperature: range 55°F to 100°F

Salinity: 0 to 5%

3. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:

pH: 6.0 and 8.0

Temperature: >32°F and <120°F

Salinity: no minimum and 10%

4. Special nutrient requirements: NA

5. Test results regarding the determination of the presence of the following:

Salmonella: Negative

Fecal coliform: Negative

Shigella: Negative

Staphylococcus Coagulase positive: Negative

Beta hemolytic Streptococci: Negative

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN: B-73
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: MAY 21, 2019
“ECOBIOCLEAN® 100 COSW”

I. NAME, BRAND, OR TRADEMARK

ECOBIOCLEAN® 100 COSW

Type of Product: Bioremediation Agent (Microbiological Culture, Enzyme Additive, Nutrient Additive)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
JACOR, LLC

1000 Brown Street, Suite 208

Wauconda, IL 60084

Phone: (847) 865-3189

Fax: (847) 865-3287

E-mail: info@ecobioclean.com or janetangel@ecobioclean.com

Website: www.ecobioclean.com

(Dr. Janel Angel, CEO, Inventor)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
JACOR, LLC

1000 Brown Street, Suite 208

Wauconda, IL 60084

Phone: (847) 865-3189

Fax: (847) 865-3287

E-mail: info@ecobioclean.com or janetangel@ecobioclean.com

Website: www.ecobioclean.com

(Dr. Janel Angel, CEO, Inventor)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable

2. Ventilation: Special ventilation is not required. Use standard industrial hygiene ventilation practices. Use of a dust mask for respiratory protection in line with NIOSH standards such as N100 (3M) quality or comparable products will provide adequate protection from non-oil-based dust particles.

3. Skin and eye contact; protective clothing; treatment in case of contact: To protect skin from contact, standard work clothing and standard work or latex gloves will provide adequate protection. In case of skin contact, wash with soap and water. To prevent eye contact, standard safety glasses with side shields are recommended. In case of eye contact, flush with plenty of water.

4.a. Maximum storage temperature: 120°F (48°C) continuous up to 5 days.

4.b. Minimum storage temperature: 32°F (0.00 °C)

4.c. Optimum storage temperature range: 40°F (4.44°C) to 120°F (48°C).

4.d. Temperatures of phase separation and chemical changes: Stable

V. SHELF LIFE

Store product in a dry area. If kept in sealed container such as drums or totes (as delivered) at temperatures below 100 °F, shelf life is 4-5 years.

VI. RECOMMENDED APPLICATION PROCEDURE

4. Application Method: ECOBIOCLEAN® 100 COSW is a multi-faceted bioremediation product that may be applied directly in powder form or diluted with non-chlorinated water to initiate degradation of crude oil (hydrocarbons) at the source of contamination such as on shorelines, vegetation, or land. For powder treatment, apply directly to contamination site via crop dusting implements, farm fertilizer apparatus, and planes for larger areas. For smaller spills where powder form is desired, use fertilizer distributors, hand sprinklers, or other dry nutrient delivery system. For liquid applications and after dilution, apply with any commercially available spray apparatus, such as hand held tanks, back packs, and large mixing tanks with pumping devices. In addition, ECOBIOCLEAN® 100 COSW may be applied via educator systems from vessels, fire trucks, or any other appropriately outfitted vehicle. Spraying/applying to the outer edges of contamination site first and then working inward will help control spreading of spill.
5. Concentration/Application Rate: Concentration rates will vary based upon the type of crude oil spilled, the type of substrate and the amount of contamination spilled, the weathering process, and environmental conditions. ECOBIOCLEAN® 100 COSW contains billions of active hydrocarbon consuming microbes (MC) per gram along with a supporting proprietary complex of nutrients (NA) and enzymes (EA), which together are bio-catalyzing elements that stimulate bioremediation. ECOBIOCLEAN® 100 COSW may be applied to shorelines or land in full strength powder form or diluted using native water supplies as required depending upon the location of environmental contamination (do not use municipal/chlorinated water for mixing). Product may be applied immediately after mixing or within 12 hours via hoses or other spray devices or systems. Dilute 1:10 to 1:30 (1 pound product to 10-30 gallons native water) depending upon the type of contamination. For example, heavy petroleum compounds such as crude oil or bunker fuel will require higher dose of ECOBIOCLEAN® 100 COSW and lighter petroleum compounds will require less. Nutrient additives are not necessary. Within minutes ECOBIOCLEAN® 100 COSW should begin to penetrate the molecular walls initiating bioremediation. ECOBIOCLEAN® 100 COSW provides an inoculum that insures bacterial colonies consume hydrocarbons throughout the remediation process. Within 3-7 days, there should be a noticeable reduction of crude oil contamination and odor while population of microbial strains continue to proliferate. Weathered oils may require longer treatment times. Diluted product can be sprayed from a boat or aircraft to degrade surface oils on soil, beach/sand surface, or vegetation. When dry application is preferred, such as in or around UST/AST and containment pits, ECOBIOCLEAN® 100 COSW can be applied via powder distribution implements as with seeding/fertilizing equipment or dry sprayers and then tilled for more complete distribution of product to contaminant. Be certain to cover the entire contaminated area for thorough treatment starting with perimeter and working to center. Product will quickly begin to break the hydrocarbon structure into organic nutrient substances that aquatic

and ground life can feed upon. In some circumstances (such as above) tilling of the ground is advisable to insure higher oxygenation and that product is reaching offending chemical. Within hours, odors should be greatly reduced, as may the hydrocarbon bonding properties helping to prevent adhesion to vegetation, rocks, soil/earth, and wildlife. (Use only non-chlorinated water for dilution.) Estimate area needing treatment. Use 1 pound of product (dilute 1:10 to 1:25 product to gallons of water) per cubic yard of heavy crude oil spilled, or 10 pounds of product per acre of land depending upon the oil type, penetration depth and concentration. Heavier oils may need greater biomass than lighter oils or fuels.

6. Conditions for Use: Product is effective in salt water or fresh water ecosystems including marshlands, rocks, vegetation, sand, and soil (shorelines/land) with no limitations as to usage within temperature parameters above 35°F and below 100°F. For greater immediate activity, water temperature for optimal mixing is between 60-80°F, though you may mix with warmer or colder non-chlorinated water between 45-105°F if need exists. Water salinity is not a factor as ECOBIOCLEAR® 100 COSW works well with all forms of water. Weathered crude/hydrocarbon contamination or tar-like substances may need to be agitated or tilled/cut for shorter remediation time prior to or with application. For heavy oils use product directly on the spill or up to approximately a 1:10 dilution ratio (1 pound product to 10 gallons of water). Lighter oils would require a 1:10 to 1:30 product to water dilution ratio. In warmer waters and in good agitation during application less product may be required. ECOBIOCLEAR® 100 COSW will work more quickly when adequate oxygen levels exist at contamination site but is viable wherever microbial life can be sustained.

II. TOXICITY AND EFFECTIVENESS

c. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	65064	0	7360	0
	NUTRIENT	57799	0	6452	0
	PRODUCT	59661	0	6731	0
7	CONTROL	60375	0	5788	0
	NUTRIENT	47685	0	5309	0
	PRODUCT	33684	0	3888	0
28	CONTROL	55425	14.80	5874	20.20
	NUTRIENT	27944	57.10	4041	45.10

PRODUCT	6479	90.00	1789	75.70
---------	------	-------	------	-------

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

<u>Control</u>	<u>Nutrient</u>	<u>ECOBIOCLEAN® 100 COSW</u>
8.90%	51.50%	60.93%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

Microbiological Cultures:

1. Listing of each component of the total formulation, other than microorganisms, by chemical name and percentage by weight: CONFIDENTIAL
2. Listing of all microorganisms by species and percentages of each species in the composition of the additive: CONFIDENTIAL
3. Optimum pH, temperature, and salinity ranges for use of the additive:
pH: range 6.5 to 7.5
Temperature: range 75°F to 85°F
Salinity: 0.5 to 15.0%
4. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity:
pH: 5.5 and 11.0
Temperature: 32°F and 120°F
Salinity: maximum permissible salinity is up to 20% by solution
5. Special nutrient requirements: NA
6. Test results regarding the determination of the presence of the following:
Salmonella: Negative
Fecal coliform: Negative
Shigella: Negative
Staphylococcus Coagulase positive: Negative
Beta hemolytic Streptococci: Negative

Enzyme Additives:

1. Listing of each component of the total formulation, other than enzymes, by chemical and percentage by weight: CONFIDENTIAL
2. Enzyme(s): CONFIDENTIAL
3. International Union of Biochemistry (I.U.B.) number(s): CONFIDENTIAL
4. Source of enzyme: CONFIDENTIAL
5. Units: No less than 1% and no more than 25% by weight.
6. Specific Activity: CONFIDENTIAL
7. Optimum Conditions:
pH: 7.0
Temperature: CONFIDENTIAL

Salinity ranges for use of the additive: CONFIDENTIAL

Minimum and maximum pH: 4.5 to 8.5

Minimum and maximum temperature: CONFIDENTIAL

Minimum and maximum salinity levels above or below which the effectiveness of the additive is reduced to half its optimum capacity: CONFIDENTIAL

8. Enzyme shelf life: Up to 5 years if unopened and stored properly
9. Enzyme optimum storage conditions: Low moisture environment at temperatures between 40°F and 115°F

Nutrient Additives:

1. Listing of each component of the total formulation by chemical name and percentage by weight: CONFIDENTIAL
2. Nutrient additive optimum storage conditions: Store product in sealed containers and dry area at temperatures between 40°F and 120°F.

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN: B-74
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: AUGUST 6, 2020
“SPILL GENIE™ 3T”
(aka, SG 3T)

I. NAME, BRAND, OR TRADEMARK
SPILL GENIE™ 3T
(aka, SG 3T)

Type of Product: Bioremediation Agent (Biological Additive)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Product Owner/Primary Contact:

Spill Genie, LLC
401 East Jackson Street (SunTrust Financial
Center), Suite 2340
Tampa, FL 33602
Phone: (352) 515-3861
Fax: (813) 807-3036
E-mail: rstotts@spill-genie.com
Website: www.sg3t.com
(Mr. Rick Stotts, President)

Product Manufacturer:

Seatex Corporation
445 Texas Highway 36
Rosenberg, TX 77417
Phone: (713) 357-5300
E-mail: kaimes@seatexcorp.com
Website: www.seatexcorp.com
(Mr. Kelly Aimes)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Spill Genie, LLC
401 East Jackson Street (SunTrust Financial Center), Suite 2340
Tampa, FL 33602
Phone: (352) 515-3861
Fax: (813) 807-3036
E-mail: rstotts@spill-genie.com
Website: www.sg3t.com
(Mr. Rick Stotts, President)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-Hazardous)
2. Ventilation: Recommended, ventilator in confined areas.
3. Skin and eye contact; protective clothing; treatment in case of contact: Wear eye protection and impervious gloves. Wash face, hands and any exposed skin thoroughly after handling. If eye contact, wash eyes thoroughly for 15 minutes; including upper and lower lids and seek medical attention. For skin contact, irritation is possible, wash with soap and water for 15 minutes. If irritation persists, seek medical attention.
- 4.a. Maximum storage temperature: Below 95°F.
- 4.b. Minimum storage temperature: Above 32°F.
- 4.c. Optimum storage temperature range: 55°F to 90°F. Avoid storage in extreme heat and

extreme cold.

4.d. Temperatures of phase separation and chemical changes: Stable within storage temperature ranges.

V. SHELF LIFE

One year in the original unopened container, as delivered, under optimum storage conditions. It is not recommended to store in open containers. Unused product stored in a properly sealed or air tight container will have a diminished shelf life of less than one year.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Surficial spraying of Spill Genie™ 3T may be applied by a conventional liquid delivery system used in the bioremediation industry.
 - a. Spill Genie™ 3T is designated for use on soils, sandy or gravel applications. In-situ and situ application can vary based on soil and surface composition. Spill Genie™ 3T is pre-mixed into water and sprayed directly onto the hydrocarbon contaminants on soils, sandy or gravel areas. Spill Genie™ 3T should be applied using recommended dilution rates and utilizing a conventional sprayer or water dispensing cannon (recommend application above 35°F, with optimum above 48°F). Reapplication may be required to achieve desired results.
 - b. When bioremediating contaminated substrate, whether sand, gravel or soil, additional applications of nutrients, oxygen releasing compounds and or aeration may be required to maintain or boost microbial activity.
2. Concentration/Application Rate:
 - a. Typical dilution is 1 gallon of Spill Genie™ 3T with 9 gallons of water (approximately 1:10 dilution ratio, product to water). For lighter hydrocarbons, a dilution ratio of up to 1:30, product to water). Apply 0.5 gallons of stock solution of Spill Genie™ 3T to one cubic yard of contaminated soil. Agitate to slurry by mixing thoroughly with contaminated soil. Application rate may vary due to level of hydrocarbon contamination or type and density of treatable substrate.
 - b. Hydrocarbon types: Spill Genie™ 3T can be applied on hydrocarbon compounds including, but not limited to, crude, diesel, gasoline, aviation fuel, light oils, and bunker fuels.
 - c. Aged or asphaltic contaminants may be more resistant to remediation efforts and may require multiple applications.
 - d. Application rates of Spill Genie™ 3T may vary widely based on unknown extent and depth of contamination.
3. Conditions for Use:
 - a. Most frequent applications include petroleum contamination around ASTs and USTs (Above and Underground Storage Tanks) and containment pits requiring rehabilitation.
 - b. Optimum application temperature of Spill Genie™ 3T is above 48°F.
 - c. Aeration of treated medium is recommended as it will increase oxygen levels within the treated area allowing microbial reproductions and remediation activity to thrive.
 - d. Additional nutrients may be required to increase microbial activity over time if intrinsic nutrients are depleted. An application of nitrogen, phosphorus, and

- potassium fertilizer can be used in-situ or situ to boost microbial activity and enhance co-metabolic digestion of petroleum.
- e. After treatment, solid asphaltic residue should be collected, removed from the site and disposed of in accordance with applicable local, state and federal regulations. Collection process and disposal of any excess washing solution, should comply with applicable local, state and federal regulations.
 - f. Prevent spill run-off from entering surface and sub-surface water bodies.
 - g. Expected results in TPH (Total Petroleum Hydrocarbon) reduction have been observed between 7 and 28 days.

II. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	46495	0	14656	0
	NUTRIENT	43232	0	14090	0
	PRODUCT	45979	0	13652	0
7	CONTROL	43141	0	12848	0
	NUTRIENT	40276	0	12538	0
	PRODUCT	33679	0	10128	0
28	CONTROL	37497	19.3%	12332	15.9%
	NUTRIENT	22732	47.4%	10686	24.2%
	PRODUCT	14482	68.5%	7538	44.4%

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control
14.5%

Nutrient
35.0%

SPILL GENIE™ 3T
57.0%

b. Toxicity:
NA

VIII. MICROBIOLOGICAL ANALYSIS

Microbiological Cultures:

1. Listing of each component of the total formulation, other than microorganisms, by chemical name and percentage by weight: CONFIDENTIAL
2. Listing of all microorganisms by species and percentages of each species in the composition of the additive: CONFIDENTIAL
3. Optimum pH, temperature, and salinity ranges for use of the additive: CONFIDENTIAL
4. Minimum and maximum pH, temperature, and salinity levels below or above which the effectiveness of the additive is reduced to half its optimum capacity: CONFIDENTIAL
5. Special nutrient requirements: NA
6. Test results regarding the determination of the presence of the following:
 Salmonella: Negative
 Fecal coliform: Negative
 Shigella: Negative
 Staphylococcus Coagulase positive: Negative
 Beta hemolytic Streptococci: Negative

Enzyme Additives:

1. Listing of each component of the total formulation, other than enzymes, by chemical and percentage by weight: CONFIDENTIAL
2. Enzyme(s): CONFIDENTIAL
3. International Union of Biochemistry (I.U.B.) number(s): CONFIDENTIAL
4. Source of enzyme: CONFIDENTIAL
5. Units: CONFIDENTIAL.
6. Specific Activity: CONFIDENTIAL
7. Optimum Conditions: CONFIDENTIAL
8. Enzyme shelf life: CONFIDENTIAL
9. Enzyme optimum storage conditions: CONFIDENTIAL

Nutrient Additives: NA

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

NA

TECHNICAL PRODUCT BULLETIN: B-75
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: NOVEMBER 08, 2021
“GHG ORGANIC”

I. NAME, BRAND, OR TRADEMARK

GHG ORGANIC

Type of Product: Bioremediation Agent (Nutrient Additive)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Bucheus Investments LLC

4320 NW 72nd Avenue

Miami, FL 33166

Phone: +56-9-79128229 (WhatsApp Phone Number)

Phone: (786) 521-0074 (Christian Alonso)

Phone: (786) 436-9498 (Rene Mendoza)

E-mail: asrojas1261@gmail.com

(Mr. Alberto Rojas P., CEO)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Bucheus Investments LLC

4320 NW 72nd Avenue

Miami, FL 33166

Phone: +56-9-79128229 (WhatsApp Phone Number)

Phone: (786) 521-0074 (Cristian Alonso)

Phone: (786) 436-9498 (Rene Mendoza)

E-mail: asrojas1261@gmail.com

(Mr. Alberto Rojas P., CEO)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.

2. Ventilation: Wearing masks with filter for fine dust under MESH 200 is recommended.

3. Skin and eye contact; protective clothing; treatment in case of contact: Wear goggles for eye protection, impervious gloves, and normal work clothing. Contact may cause mild irritation. Wash face, hands, and any exposed skin thoroughly after handling. For eye contact, wash eyes thoroughly with clean water until irritation disappears. For skin contact and in case of redness or rash, wash the affected area with clean water until irritation disappears. If irritation persists, seek medical attention.

4.a. Maximum storage temperature: 140°F.

4.b. Minimum storage temperature: -10°F.

4.c. Optimum storage temperature range: -4°F to 104°F.

4.d. Temperatures of phase separation and chemical changes: Stable in powder form under all conditions. GHG ORGANIC in its natural states does not agglomerate or bind due to moisture. It does not require any type of additive to preserve its properties.

V. SHELF LIFE

Five years in open container; and four years in pressurized containers. Pressurized containers include portable extinguisher with N2 gas at 25 pounds working pressure 100 psi with metal anticorrosive valve made of 1/16-inch-thick carbon steel. Store in closed and dry places (e.g., containers, closed metal/wooden warehouses). Keep in manufacturers closed containers and store in height according to the resistance that bagged containers or pallets indicate, not to have a column with more than 2,000 pounds. Do not store volumes greater than 20,000 pounds in bulk in closed warehouses less than 1,000 yards from the vicinity of swamps of stagnant waters.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: GHG ORGANIC is a homogenous powder that is applied directly to oil contaminated solid surfaces (e.g., soil, sand, shorelines, and vegetation). Apply directly from container, product should not be diluted in water or mixed with other substances or solvents. Distribute GHG ORGANIC directly and uniformly on the spilled oil from containers (such as buckets and maxi bags) on the solid surface. For remote areas, apply using pressurized extinguishers with N2 gas (manual extinguishers from 2 pounds to 100 pounds) on solid surfaces. Means of application:
 - a. From all terrain trucks, distribute GHG ORGANIC using 50-yard x 1 inch rubber hose of medium pressure (8 bar) coupled with:
 - i. ≤5,000-pound tank mounted on pressurized pickup with N2 gas at 200 psi.
 - ii. Compressed air 250 CFM and 8 bar working pressure mounted on a truck to pull product directly from open containers using a VENTURI so that GHG ORGANIC is projected onto the spilled oil on the solid surface.
 - b. For difficult to access environments such as edges of islets and cliffs, recommend distributing GHG ORGANIC:
 - i. From boats using 50-yard x 1-inch-long rubber hoses of medium pressure (8 bar) coupled to a compressed air compressor. 250 CFM and 8 bar working pressure is used to pull product directly from open containers using a VENTURI.
 - ii. From planes and helicopters, GHG ORGANIC is available in plastic tanks that discharge the compound by gravity from gravitational sprinklers mounted on the discharge pipes outside the equipment. The application rate of the compound will be defined based on the surface affected by the spill.
2. Concentration/Application Rate: Applied at a ratio of 2 pounds product per square yard of oil; or 8,800 pounds of product per acre of oil.
3. Conditions for Use: Time of bioremediation is dependent upon oil density and ambient temperature. For light oils, bioremediation is 30 days. For heavy fuel oils, bioremediation is 90 days. A second application may be necessary in areas of accumulation. In case of oil seepage to the subsoil due to old spills in permeable soils and to accelerate the bioremediation process, the manufacturer recommends removing the contaminated soil and mixing GHG ORGANIC using vibratory screens and industrial blending machines.

VII. TOXICITY AND EFFECTIVENESS

a. Effectiveness:

Bioremediation Agent Effectiveness Test (40 CFR 300.900), Federal Register September 15, 1994:

Summary Data Table

DAYS	PRODUCT	TOTAL MEAN	RED%	TOTAL MEAN	RED%
	3 REPS/PROD	ALKANES (ppm)	28 DAYS	AROMATICS (ppm)	28 DAYS
0	CONTROL	39682	0	5055	0
	NUTRIENT	38370	0	5578	0
	PRODUCT	38358	0	4699	0
7	CONTROL	38159	0	4797	0
	NUTRIENT	36956	0	5575	0
	PRODUCT	31488	0	4270	0
	CONTROL	37517	5.5%	4871	3.6%
28	NUTRIENT	29986	21.8%	4822	13.5%
	PRODUCT	13599	64.7%	3074	34.6%

Results of Gravimetric Analysis:

Percentage (%) Decrease in Weight of Oil on Day 28

Control

7.0%

Nutrient

15.1%

GHG ORGANIC

52.5%

b. Toxicity:

NA

VIII. MICROBIOLOGICAL ANALYSIS

The product is a nutrient additive and does not contain microbiological cultures or enzyme additives.

1. Listing of each component of the formulation by chemical name and percentage by weight:

CONFIDENTIAL

2. Optimum storage conditions:

Temperature: -4.0°F to 104°F

IX. PHYSICAL PROPERTIES

NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS
NA

DISPERSANTS: TECHNICAL **NOTEBOOK BULLETINS**

TECHNICAL PRODUCT BULLETIN #D-1
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: MARCH 10, 1978
REVISED LISTING DATE: DECEMBER 18, 1995
“COREXIT™ EC9527A”

I. NAME, BRAND, OR TRADEMARK
COREXIT™ EC9527A
Type of Product: Dispersant
(formerly COREXIT 9527)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Corexit Environmental Solutions LLC
11177 South Stadium Drive
Sugar Land, TX 77478
Product Management:
Phone: (281) 632-8827
E-mail: corexitinfo@corexit.com
(Mr. Huw Jones)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Corexit Environmental Solutions LLC
11177 South Stadium Drive
Sugar Land, TX 77478
Product Management:
Phone: (281) 632-8827
E-mail: corexitinfo@corexit.com
(Mr. Huw Jones)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: COREXIT™ EC9527A is not classified as flammable by either DOT or IMO regulations.
2. Ventilation: Avoid prolonged breathing of vapors. Use with ventilation equal to unobstructed outdoors in moderate breeze.
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid eye contact. In case of eye contact, immediately flush eyes with large amounts of water for at least 15 minutes. Get prompt medical attention. Avoid contact with skin and clothing. In case of skin contact, immediately flush with large amounts of water, and soap if available. Remove contaminated clothing, including shoes, after flushing has begun. If irritation persists, seek medical attention. For open systems where contact is likely, wear long sleeve shirt, chemical resistant gloves, and chemical protective goggles.
- 4.a. Maximum storage temperature: 170°F
- 4.b. Minimum storage temperature: -30°F
- 4.c. Optimum storage temperature range: 40°F to 100°F

4.d. Temperatures of phase separations and chemical changes: COREXIT™ EC9527A is not adversely affected by changes in storage temperature unless evaporation is allowed to occur.

V. SHELF LIFE

The shelf life of unopened drums of COREXIT™ EC9527A is unlimited. Containers should always be capped when not in use to prevent contamination and evaporation of solvents.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: COREXIT™ EC9527A is most effectively applied by aircraft, however, application with boat spray booms, boat fire monitors, and by hand held sprayers and back packs has been successfully done on a number of spills and trials.

Aerial Spraying – Aircraft provide the most rapid method of applying dispersants to an oil spill and a variety of aircraft can be used for spraying. For aerial spraying, COREXIT™ EC9527A is applied undiluted. Typical application altitudes of 30 to 50 feet have been used, although higher altitudes may be effective under certain conditions. Actual effective altitudes will depend on the application equipment, weather and aircraft. Careful selection of spray nozzles is critical to achieve desired dose levels, since droplet size must be controlled. Many nozzles used for agricultural spraying are of low capacity and produce too fine a spray. A quarter-inch open pipe may be all that is necessary if the aircraft travels at 120 mph (104 knots) or more, since the air shear at these speeds will be sufficient to break the dispersant into the proper sized droplets.

Boat Spraying – COREXIT™ EC9527A may be applied by workboats equipped with spray booms mounted ahead of the bow wake or as far forward as possible. The preferred and most effective method of application from a workboat is to use a low-volume, low-pressure pump so the chemical can be applied undiluted. Spray equipment designed to provide a five to ten percent diluted dispersant solution to the spray booms can also be used. COREXIT™ EC9527A should be applied as droplets, not fogged or atomized. Natural wave or boat wake action usually provides adequate mixing energy to disperse the oil.

Recent tests have indicated that a fire monitor modified with a screen cap for droplet size may also be useful for applying COREXIT™ EC9527A. Due to the increased volume output and the greater reach of the fire monitor, significantly more area can be covered in a shorter period of time.

System Calibration – Spray systems should be calibrated at temperatures anticipated to insure successful application and dosage control.

2. Concentration/Application Rate: A treatment rate of about 2 to 10 U.S. gallons per acre, or a dispersant to oil ratio of 1:50 to 1: 10 is recommended. This rate varies depending on the type of oil, degree of weathering, temperature, and thickness of the slick.

3. Conditions for Use: As with all dispersants, timely application ensures the highest degree of success. Early treatment with COREXIT™ EC9527A, even at reduced treat rates, can reduce the “mousse” forming tendencies of the spilled oil. COREXIT™ EC9527A is useful on oil spills in salt water.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
COREXIT™ EC9527A	Menidia beryllina	14.57 96-hr
	Mysidopsis bahia	24.14 48-hr
No. 2 Fuel Oil	Menidia beryllina	10.72 96-hr
	Mysidopsis bahia	16.12 48-hr
COREXIT™ EC9527A & No. 2 Fuel Oil (1:10)	Menidia beryllina	4.49 96-hr
	Mysidopsis bahia	6.60 48-hr
Reference Toxicant (DSS)	Menidia beryllina	7.07 96-hr
	Mysidopsis bahia	9.82 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	37.4
South Louisiana Crude	63.4
Average of Prudhoe Bay and South Louisiana Crudes	50.4

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 163°F
2. Pour Point: < - 40°F
3. Viscosity: 160 cSt at 32°F
4. Specific Gravity: 0.98 - 1.02
5. pH: 6.1
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: Water, Propylene Glycol, 2-Butoxyethanol
8. Additives: CONFIDENTIAL
9. Solubility: Complete

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.005
Cadmium	<0.01
Chromium	1.0
Copper	<0.2
Lead	<0.1
Mercury	<0.003
Nickel	<0.1
Zinc	0.1
Cyanide	<0.01
Chlorinated Hydrocarbons	<0.01

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**3/18/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #D-2
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: APRIL 22, 1985
REVISED LISTING DATE: JANUARY 26, 1996
“NEOS AB3000”

I. NAME, BRAND, OR TRADEMARK
NEOS AB3000

Type of Product: Dispersant (Hydrocarbon Solvent Based)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
NEOS Company Limited
Daisan Kendai Building
1-2, 3-chome Isobedori
Chuo-ku, Kobe, 651-0084 Japan
Phone: updated information required
E-mail: updated information required
(Mr. T. Ishii, Manager)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
NEOS Company Limited
Daisan Kendai Building
1-2, 3-chome Isobedori
Chuo-ku, Kobe, Japan
Phone: updated information required
E-mail: updated information required
(Mr. T. Ishii, Manager)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: NEOS AB3000 is flammable; keep away from open flame.
2. Ventilation: Special ventilation is not required; however, natural ventilation is recommended.
3. Skin and eye contact; protective clothing; treatment in case of contact: Contact may cause skin and eye irritation. Goggles and rubber clothing are recommended during application.
In case of contact with skin or eye, flush with copious amounts of fresh water. If severe, consult a doctor.
- 4.a. Maximum storage temperature: 158°F
- 4.b. Minimum storage temperature: 32°F
- 4.c. Optimum storage temperature range: 50°F to 140°F
- 4.d. Temperatures of phase separations and chemical changes: Phase separation and chemical changes do not appear between the temperature range of 32°F to 158°F.

V. SHELF LIFE

The shelf life is five (5) years.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Spray neat concentrate on the oil slick in atomized form by means of a manual pump, or spray with a pump system incorporating an ejector system for drawing concentrate from the drum or stock tank.

For aerial application, use a spray boom with pressure nozzles or rotating atomizers mounted on helicopters or airplanes.

2. Concentration/Application Rate: The application rate is 65 gallons of dispersant per ton of oil. Five (5) to fifteen (15) parts of dispersant to suctioned water is recommended for ejector systems.

For aerial application, 75 to 125 gallons per ton of oil is recommended.

3. Conditions for Use: NEOS AB3000 can be used in salt water. It is effective with crude and residual heavy oil. The dispersant is also effective at controlling volatile emissions from the oil.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
NEOS AB3000	Menidia beryllina	91.1 96-hr
	Mysidopsis bahia	33.0 48-hr
No. 2 Fuel Oil	Menidia beryllina	201.8 96-hr
	Mysidopsis bahia	11.5 48-hr
NEOS AB3000 & No. 2 Fuel Oil (1:10)	Menidia beryllina	57.0 96-hr
	Mysidopsis bahia	25.0 48-hr
Reference Toxicant (DSS)	Menidia beryllina	1.5 96-hr
	Mysidopsis bahia	9.3 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	19.7
South Louisiana Crude	89.8
Average of Prudhoe Bay and South Louisiana Crudes	54.8

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: No flash point to 212°F

2. Pour Point: Less than 32°F
3. Viscosity: 30.7 cSt at 104°F
4. Specific Gravity: 0.924 at 59°F
5. pH: 8.0 (5wt % aq., at 77°F)
6. Surface Active Agents: Nonionic and Cationic surfactants
7. Solvents: Paraffin
8. Additives: None
9. Solubility: NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.1
Cadmium	<0.1
Chromium	0.26
Copper	<0.05
Lead	0.21
Mercury	<0.001
Nickel	0.076
Zinc	1.1
Cyanide	<0.05
Chlorinated Hydrocarbons	<0.10

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**3/22/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #D-3
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: FEBRUARY 23, 1988
REVISED LISTING DATE: JANUARY 26, 1996
“MARE CLEAN 200”

I. NAME, BRAND, OR TRADEMARK
MARE CLEAN 200
Type of Product: Dispersant (Solvent-Based)
(formerly MARE CLEAN 505)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Ichinen Chemicals Co., Ltd
Mita Twin Building, East Wing 8F
4-2-8 Shibaura, Minato-ku,
Tokyo, Japan 108-0023
Phone: updated information required
Fax: updated information required
E-mail: updated information required
(Mr. Tsuyoshi Imai)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Ichinen Chemicals Co., Ltd
Mita Twin Building, East Wing 8F
4-2-8 Shibaura, Minato-ku
Tokyo, Japan 108-0023
Phone: updated information required
Fax: updated information required
E-mail: updated information required
(Mr. Tsuyoshi Imai)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: The flash point is 212°F @ 20°F
2. Ventilation: Is required. Use in closed room is not recommended.
3. Skin and eye contact; protective clothing; treatment in case of contact: Use protective goggles to avoid eye contact. In case of eye contact, wash immediately with plenty of water and consult with physician.
- 4.a. Maximum storage temperature: 122°F
- 4.b. Minimum storage temperature: 21°F
- 4.c. Optimum storage temperature range: 32°F to 86°F
- 4.d. Temperatures of phase separations and chemical changes: Phase separation does not relate to temperatures. Chemical changes may occur at temperatures above 194°F.

V. SHELF LIFE

The shelf life of MARE CLEAN 200 is 10 years when stored indoors. (Container will deteriorate before contents.)

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Sprinkle the dispersant on the oil spill, then 5-10 minutes later stir the surface intensively. For convenience, MARE CLEAN 200 may be diluted with water if desired.
2. Concentration/Application Rate: Use 53-66 gallons of MARE CLEAN 200 per ton of oil
3. Conditions for Use: The performance of MARE CLEAN 200 is not affected by water salinity. At temperatures below 40°F or in case of heavy crude oil spill, MARE CLEAN 200 should be used without dilution. MARE CLEAN 200 is an effective dispersant for any liquid hydrocarbon.

VII. TOXICITY AND EFFECTIVENESS

1. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
MARE CLEAN 200	Menidia beryllina	1996.00 96-hr
	Mysidopsis bahia	938.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	10.72 96-hr
	Mysidopsis bahia	16.12 48-hr
MARE CLEAN 200 and No. 2 Fuel Oil (1:10)	Menidia beryllina	42.00 96-hr
	Mysidopsis bahia	9.84 48-hr
Reference Toxicant (SDS)	Menidia beryllina	7.07 96-hr
	Mysidopsis bahia	9.82 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OILS

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	63.97
South Louisiana Crude	84.14
Average of Prudhoe Bay and South Louisiana Crudes	74.06

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 212°F @ 20°F
2. Pour Point: 14 @ 10°F
3. Viscosity: 2.4 @ 5 cSt at 104°F
4. Specific Gravity: 0.95 @ 0.03 at 77°F
5. pH: 7.7 @ 1.0 (10% solution)

6. Surface Active Agents: A mixture of sorbitan fatty acid esters, polysorbates, and polyoxyethylene fatty acid esters.
7. Solvents: Paraffinic hydrocarbons (CAS 74664-93-0)
8. Additives: None
9. Solubility: NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.50
Cadmium	<0.100
Chromium	<0.500
Copper	<0.250
Lead	<2.50
Mercury	<0.0200
Nickel	<0.250
Zinc	0.611
Cyanide	<0.01
Chlorinated Hydrocarbons	<0.10

TECHNICAL PRODUCT BULLETIN #D-4
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: APRIL 13, 1994
REVISED LISTING DATE: DECEMBER 18, 1995
“COREXIT™ EC9500A”

I. NAME, BRAND, OR TRADEMARK

COREXIT™ EC9500A

Type of Product: Dispersant
(formerly COREXIT 9500)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Corexit Environmental Solutions LLC

11177 South Stadium Drive

Sugar Land, TX 77478

Product Management:

Phone: (281) 632-8827

E-mail: corexitinfo@corexit.com

(Mr. Huw Jones)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Corexit Environmental Solutions LLC

11177 South Stadium Drive

Sugar Land, TX 77478

Product Management:

Phone: (281) 632-8827

E-mail: corexitinfo@corexit.com

(Mr. Huw Jones)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: IMO – Non-flammable; DOT - Non-hazardous.
2. Ventilation: Use with ventilation equal to unobstructed outdoors in moderate breeze.
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid eye contact. In case of eye contact, immediately flush eyes with large amounts of water for at least 15 minutes. Get prompt medical attention. Avoid contact with skin and clothing. In case of skin contact, immediately flush with large amounts of water, and soap if available. Remove contaminated clothing, including shoes, after flushing has begun. If irritation persists, seek medical attention. For open systems where contact is likely, wear long sleeve shirt, chemical resistant gloves, and chemical protective goggles.
- 4.a. Maximum storage temperature: 170°F
- 4.b. Minimum storage temperature: -30°F
- 4.c. Optimum storage temperature range: 40°F to 100°F
- 4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

The shelf life of unopened drums of COREXIT™ EC9500A is unlimited. Containers should always be capped when not in use to prevent contamination and evaporation of solvents.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: COREXIT™ EC9500A contains the same surfactants present in COREXIT™ EC9527A and a new improved oleophilic solvent delivery system.

Aerial Spraying – Aircraft provide the most rapid method of applying dispersants to an oil spill and a variety of aircraft can be used for spraying. For aerial spraying, COREXIT™ EC9500A is applied undiluted. Typical application altitudes of 30 to 50 feet have been used, although higher altitudes may be effective under certain conditions. Actual effective altitudes will depend on the application equipment, weather and aircraft. Careful selection of spray nozzles is critical to achieve desired dose levels, since droplet size must be controlled. Many nozzles used for agricultural spraying are of low capacity and produce too fine a spray. A quarter-inch open pipe may be all that is necessary if the aircraft travels at 120 mph (104 knots) or more, since the air shear at these speeds will be sufficient to break the dispersant into the proper sized droplets.

Boat Spraying – COREXIT™ EC9500A may also be applied by workboats equipped with spray booms mounted ahead of the bow wake or as far forward as possible. The preferred and most effective method of application from a workboat is to use a low-volume, low-pressure pump so the chemical can be applied undiluted. Spray equipment designed to provide a five to ten percent diluted dispersant solution to the spray booms can also be used. COREXIT™ EC9500A should be applied as droplets, not fogged or atomized. Natural wave or boat wake action usually provides adequate mixing energy to disperse the oil.

Recent tests have indicated that a fire monitor modified with a screen cap for droplet size control may also be useful for applying COREXIT™ EC9500A. Due to the increased volume output and the greater reach of the fire monitor, significantly more area can be covered in a shorter period of time.

System Calibration – Spray systems should be calibrated at temperatures anticipated to insure successful application and dosage control. Application at sub-freezing temperatures may require larger nozzle, supply lines and orifices due to higher product viscosity.

2. Concentration/Application Rate: A treatment rate of about 2 to 10 U.S. gallons per acre, or a dispersant to oil ratio of 1:50 to 1:10 is recommended. This rate varies depending on the type of oil, degree of weathering, temperature, and thickness of the slick.

3. Conditions for Use: As with all dispersants, timely application ensures the highest degree of success. Early treatment with COREXIT™ EC9500A, even at reduced treat rates, can also counter the “mousse” forming tendencies of the spilled oil. COREXIT™ EC9500A is useful on oil spills in salt water.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
COREXIT™ EC9500A	Menidia beryllina	25.20 96-hr
	Mysidopsis bahia	32.23 48-hr
No. 2 Fuel Oil	Menidia beryllina	10.72 96-hr
	Mysidopsis bahia	16.12 48-hr
COREXIT™ EC9500A & No. 2 Fuel Oil (1:10)	Menidia beryllina	2.61 96-hr
	Mysidopsis bahia	3.40 48-hr
Reference Toxicant (SDS)	Menidia beryllina	7.07 96-hr
	Mysidopsis bahia	9.82 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OILS

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	45.3
South Louisiana Crude	54.7
Average of Prudhoe Bay and South Louisiana Crudes	50.0

VIII. MICROBIOLOGICAL PROPERTIES

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 181.4°F
2. Pour Point: <-71°F
3. Viscosity: 22.5 cSt at 104°F
4. Specific Gravity: 0.95 at 60°F
5. pH: 6.2
6. Chemical Name and Percentage by Weight of the Total Formulation: CONFIDENTIAL
7. Surface Active Agents: CONFIDENTIAL
8. Solvents: CONFIDENTIAL
9. Additives: None
10. Solubility: Miscible

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.16
Cadmium	ND
Chromium	0.03
Copper	0.10
Lead	ND
Mercury	ND
Nickel	ND
Zinc	ND
Cyanide	ND
Chlorinated hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #D-5

USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION

ORIGINAL LISTING DATE: APRIL 22, 1999

“DISPERSIT SPC 1000™”

(aka, SEACARE E.P.A. (ECOSPERSE™ POLLUTION ABATEMENT))

I. NAME, BRAND, OR TRADEMARK

DISPERSIT SPC 1000™

(aka, SEACARE E.P.A. (ECOSPERSE™ POLLUTION ABATEMENT))

Type of Product: Dispersant (Water Based)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

U.S. Polychemical Corp.

584 Chestnut Ridge Road

Chestnut Ridge, NY 10977

Phone: (845) 356-5530

Fax: (845) 356-6656

E-mail: bruceg@uspoly.com

(Mr. Bruce Gebhardt)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

U.S. Polychemical Corp.

584 Chestnut Ridge Road

Chestnut Ridge, NY 10977

Phone: (845) 356-5530

Fax: (845) 356-6656

E-mail: bruceg@uspoly.com

(Mr. Bruce Gebhardt)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: IMO: Non-flammable; DOT: Non-hazardous

2. Ventilation: None normally required. Adequate to maintain fume levels below the TLV.

3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid prolonged contact with skin and eyes. Flush eyes with plenty of water for at least 15 minutes. Get medical attention. Wear long sleeve shirt, chemical resistant gloves, and chemical protective goggles in case of exposure to mist.

4.a. Maximum storage temperature: 180°F

4.b. Minimum storage temperature: -25°F

4.c. Optimum storage temperature range: 40°F to 140°F

4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

The shelf life of DISPERSIT SPC 1000™ is unlimited in unopened containers. Containers must be kept closed when not in use to prevent contamination.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: The dispersant may be applied by any conventional methods such as 1) aerial spraying and 2) boat spraying to accommodate weather conditions.
2. Concentration/Application Rate: A dispersant to oil ratio ranging from 1 part dispersant to 50 parts oil to 1 part dispersant to 10 parts oil; or an application rate of about 2-10 gallons (7.6 liters- 37.9 liters) per acre (4840 square meters) is suggested. These rates will be dependent on the type of oil, degree of weathering, temperature and extent of oil slick.
3. Conditions for Use: Timely application ensures the highest degree of successful dispersion of the oil spill.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
DISPERSIT SPC 1000™	Menidia beryllina	3.5 96-hr
	Mysidopsis bahia	16.6 48-hr
No. 2 Fuel Oil	Menidia beryllina	11.6 96-hr
	Mysidopsis bahia	11.7 48-hr
DISPERSIT SPC 1000™ & No. 2 Fuel Oil (1:10)	Menidia beryllina	7.9 96-hr
	Mysidopsis bahia	8.2 48-hr
Reference Toxicant (SDS)	Menidia beryllina	6.3 96-hr
	Mysidopsis bahia	11.7 48-hr

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	40
South Louisiana Crude	105
Average of Prudhoe Bay and South Louisiana Crudes	73

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point, ASTM D-56-87: 208°F
2. Pour Point, ASTM D-97-87: <-20°C
3. Viscosity, ASTM D-445-88: 144CPS, @ 68°F
4. Specific Gravity, ASTM D-1298-85(90): 0.995, @ 68°F
5. pH, ASTM D-1293-84(90): 10.0
6. Surface Active Agents: Anionic and non-ionic, proprietary, surfactants
7. Solvents: Proprietary, non-petroleum based
8. Additives: None

9. Solubility in Water: Complete

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<1.00
Cadmium	<2.00
Chromium	<2.00
Copper	<2.00
Lead	<1.00
Mercury	<0.04
Nickel	<10.00
Zinc	<2.00
Cyanide	<2.00
Chlorinated Hydrocarbons	<5.00

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**3/22/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #D-6
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: SEPTEMBER 20, 2000
“JD-109”

I. NAME, BRAND, OR TRADEMARK

JD-109

Type of Product: Dispersant

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

GlobeMark Resources Ltd.

1312 Mill Creek Drive

Salado, TX 76571

Mobile: (254) 231-2251

E-mail: fiddler656@gmail.com

Website: www.globemarkresources.com

(Ms. Joannie Docter)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

GlobeMark Resources Ltd.

1312 Mill Creek Drive

Salado, TX 76571

Mobile: (254) 231-2251

E-mail: fiddler656@gmail.com

Website: www.globemarkresources.com

(Ms. Joannie Docter)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: IMO - Nonflammable; DOT - Nonhazardous
2. Ventilation: Use with ventilation equal to unobstructed outdoors in a moderate breeze.
3. Skin and eye contact, protective clothing, treatment in case of contact: Avoid skin and clothing contact. If skin contact occurs, immediately wash with large amounts of soap and water (if possible). Remove any contaminated clothing and shoes. Launder before reusing. If irritation persists, seek medical assistance. For areas where contact is likely, wear long sleeve shirt, chemical resistant gloves, and chemical resistant goggles.
- 4.a. Maximum storage temperature: 120°F
- 4.b. Minimum storage temperature: - 4°F
- 4.c. Optimum storage temperature range: 32°F to 90°F
- 4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

The shelf life of unopened drums of JD-109 is unlimited. Containers should be capped when not being used to prevent contamination and evaporation.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: The most rapid and effective method of applying JD-109 to a oil spill is by spraying. Temperature ranges for application should not drop below 32°F or exceed 120°F.

Aerial Spraying - Typical application altitudes of 30 to 50 feet are advised although higher altitudes may be used if conditions warrant. Spray nozzle should be about ¼ inches in diameter flying at 104 knots or more to create enough water shear sufficient to break the dispersant into proper sized droplets. A ½ inch diameter nozzle may be needed for temperatures below 50°F.

Boat Spraying - JD-109 can also be applied by workboats with spray booms mounted as far forward as possible of the bow or wake. The most effective application from a workboat is a low-volume, low-pressure pump.

2. Concentration/Application Rate: A treatment rate of about 2 to 10 US gallons (7.6 to 37.9 liters) per acre (4,840 square meters) or a dispersant to oil ratio of 1:50 to 1:10 is recommended. The rate may vary depending on the type of oil, degree of weathering, temperature and thickness of slick.

3. Conditions for Use: As with any oil related spill, timely application of a dispersant will ensure the highest degree of success. Timely treatment with JD-109, even at low application rates, can counter the “mousse” forming effect of the spilled oil.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
JD-109	Menidia beryllina	1.90 96-hr
	Mysidopsis bahia	1.18 48-hr
No. 2 Fuel Oil	Menidia beryllina	9.35 96-hr
	Mysidopsis bahia	3.13 48-hr
JD-109 & No. 2 Fuel Oil (1:10)	Menidia beryllina	3.84 96-hr
	Mysidopsis bahia	3.51 48-hr
Reference Toxicant (SRT)	Menidia beryllina	2.63 96-hr
	Mysidopsis bahia	8.06 48-hr

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	26
South Louisiana Crude	91
Average of Prudhoe Bay and South Louisiana Crudes	58.5

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point, ASTM D3278-89: 93°C
2. Pour Point, ASTM D97-87: -19°C
3. Viscosity, ASTM D445-88: 202.9 cSt
4. Specific Gravity, ASTM D1298-85 (90): 1.02
5. pH, ASTM D1293-84 (90): 9.45
6. Surface Active Agents: Anionic and nonionic, proprietary, surfactants
7. Solvents: Proprietary, ester based
8. Additives: None
9. Solubility in Water: Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<10
Cadmium	<10
Chromium	<10
Copper	<10
Lead	<10
Mercury	<1
Nickel	<10
Zinc	<10
Cyanide	<0.5
Chlorinated Hydrocarbons	<1.4

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**5/18/2006
7/27/2022**

TECHNICAL PRODUCT BULLETIN #D-7
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: AUGUST 06, 2001
“JD-2000™”

I. NAME, BRAND, OR TRADEMARK
JD-2000™
Type of Product: Dispersant

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
GlobeMark Resources Ltd.
1312 Mill Creek Drive
Salado, TX 76571
Mobile: (254) 231-2251
E-mail: fiddler656@gmail.com
Website: www.globemarkresources.com
(Ms. Joannie Docter)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
GlobeMark Resources Ltd.
1312 Mill Creek Drive
Salado, TX 76571
Mobile: (254) 231-2251
E-mail: fiddler656@gmail.com
Website: www.globemarkresources.com
(Ms. Joannie Docter)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: IMO - Non-flammable. This product is not regulated by DOT when shipped domestically by land.
2. Ventilation: Use with ventilation equal to unobstructed outdoors in a moderate breeze.
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid skin and clothing contact. If skin contact occurs, immediately wash with large amounts of soap and water (if possible). Remove any contaminated clothing and shoes. Launder before reusing. If irritation persists, seek medical assistance. For areas where contact is likely, wear long sleeve shirt, chemical resistant gloves, and chemical resistant goggles.
- 4.a. Maximum storage temperature: 120°F
- 4.b. Minimum storage temperature: -30°F
- 4.c. Optimum storage temperature range: 30°F to 90°F
- 4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

The shelf life of unopened drums of JD-2000™ is unlimited. Containers should be capped when not being used to prevent contamination and evaporation. Opened container should be used within 1 year for optimal performance. Poly containers are recommended for storage near wet environments, i.e., ships, harbors, ports, etc.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: JD-2000™ is free of phosphates, aromatic chlorinated solvents, branched ethoxylated alcohols, and hydrotreated distillates. Optimum temperature for application is above 30°F.

Aerial Spraying - Typical application altitudes of 30 to 50 feet are advised although higher altitudes may be used if conditions warrant. Spray nozzle should be about ¼ inch in diameter flying at 104 knots or more to create enough air shear sufficient to break the dispersant into proper sized droplets. A ½ inch diameter nozzle may be needed for temperatures from 30°F to 30°F.

Boat Spraying - JD-2000™ can also be applied by workboats with spray booms mounted as far forward as possible of the bow or wake. The most effective application from a workboat is a low-volume, low-pressure pump.

2. Concentration/Application Rate: JD-2000™ is an oil spill dispersant concentrate that may be diluted by 5 to 10 percent with water if needed. A treatment rate of about 2 to 10 U.S. gallons (7.6 to 37.9 liters) per acre (4,840 square meters) or a dispersant to oil ratio of 1:50 to 1:10 is recommended. The rate may vary depending on the type of oil, degree of weathering, temperature, and thickness of slick.

3. Conditions for Use: As with any oil related spill, timely (preferably within 48 hours) application of a dispersant will ensure the highest degree of success. Timely treatment with JD-2000™, even at low application rates, can counter the “mousse” forming effect of the spilled oil.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
JD-2000™	Menidia beryllina	407.00 96-hr
	Mysidopsis bahia	90.50 48-hr
No. 2 Fuel Oil	Menidia beryllina	8.39 96-hr
	Mysidopsis bahia	2.58 48-hr
JD-2000™ & No. 2 Fuel Oil (1:10)	Menidia beryllina	3.59 96-hr
	Mysidopsis bahia	2.19 48-hr
Reference Toxicant (SDS)	Menidia beryllina	2.22 96-hr
	Mysidopsis bahia	10.50 48-hr

2. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	60.4
South Louisiana Crude	77.8
Average of Prudhoe Bay and South Louisiana Crudes	69.1

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point (SW1010): 212°F
2. Pour Point (ASTM D97): -36°F
3. Viscosity (ASTM D445): 65.2 cSt
4. Specific Gravity 60/60 (ASTM D287): 0.99
5. pH (EPA 150.1): 7.54
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL
8. Additives: None
9. Solubility in Water: Dispersible in fresh and salt water. Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.24
Cadmium	<0.10
Chromium	<0.10
Copper	<0.10
Lead	0.43
Mercury	<0.10
Nickel	<0.10
Zinc	0.11
Cyanide	<0.20
Chlorinated Hydrocarbons	<2.00

TECHNICAL PRODUCT BULLETIN #D-8
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: MARCH 04, 2002
“NOKOMIS 3-F4”

I. NAME, BRAND, OR TRADEMARK

NOKOMIS 3-F4

Type of Product: Dispersant

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Mar-Len Supply, Inc.

23159 Kidder Street

Hayward, CA 94545

Phone: (510) 782-3555

Fax: (510) 782-2032

E-mail: marlensupply@yahoo.com

(Mrs. Shirley Winter or Mr. Curt Winter)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Mar-Len Supply, Inc.

23159 Kidder Street

Hayward, CA 94545

Phone: (510) 782-3555

Fax: (510) 782-2032

E-mail: marlensupply@yahoo.com

(Mrs. Shirley Winter or Mr. Curt Winter)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (water based)

2. Ventilation: No special requirements

3. Skin and eye contact; protective clothing; treatment in case of contact: In case of eye contact, flush with water; in case of skin contact, wash with water; and if swallowed, drink water to dilute and induce vomiting.

4.a. Maximum storage temperature: 212°F

4.b. Minimum storage temperature: 32°F

4.c. Optimum storage temperature range: 50°F

4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

15 years or more if stored correctly in plastic drums.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Application of the product may be made directly from 33 and 35 gallon drums (marketing sizes) by fitting the drum with a "T" connection and pumping fresh or salt water across the junction, which will pull the dispersant from the drum into the water stream and onto the oil spill.
2. Concentration/Application Rate: For heavy concentrations of crude or Bunker C oil, apply the product undiluted. Where lighter fractions of petroleum are involved, the product can be diluted up to one part dispersant to 30 parts water.
3. Conditions for Use: Effective in salt water, and can be used on water of any temperature.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
NOKOMIS 3-F4	Menidia beryllina	29.80 96-hr
	Mysidopsis bahia	32.20 48-hr
No. 2 Fuel Oil	Menidia beryllina	100.00 96-hr
	Mysidopsis bahia	72.70 48-hr
NOKOMIS 3-F4 & No. 2 Fuel Oil (1:10)	Menidia beryllina	100.00 96-hr
	Mysidopsis bahia	58.40 48-hr
Reference Toxicant (DSS)	Menidia beryllina	159.60 96-hr
	Mysidopsis bahia	267.70 48-hr

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	62.20
South Louisiana Crude	64.90
Average of Prudhoe Bay and South Louisiana Crudes	63.55

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: None
2. Pour Point: 28°F
3. Viscosity: 290 cps at 20°C (68°F)
4. Specific Gravity: 1.0065g/cc at 20°C (68°F)
5. pH: 10.3 (at room temperature)
6. Surface Active Agents: Confidential
7. Solvents: None
8. Additives: None
9. Solubility: Completely water soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.30
Cadmium	<5.00
Chromium	<10.00
Copper	<10.00
Lead	<10.00
Mercury	<0.05
Nickel	<10.00
Zinc	<10.00
Cyanide	<2.00
Chlorinated Hydrocarbons	<1.00

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**7/19/2021
7/27/2022**

TECHNICAL PRODUCT BULLETIN #D-9
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JUNE 28, 2002
“BIODISPERS”

**I. NAME, BRAND, OR TRADEMARK
BIODISPERS**

Type of Product: Dispersant
(formerly PETROBIODISPERS)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Petrotech America Corporation
130 William Street, Suite 802
New York, NY 10038
Phone: (212)933-9071, ext. 7001
Fax: (877) 226-4028
E-mail: Info@helpenvironmental.com
(Mr. Lawrence Gallo)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Petrotech America Corporation	<u>Manufacturing Plant:</u>
130 William Street, Suite 802	Clariant Corp.
New York, NY 10038	Charlotte, NC
Phone: (212)933-9071, ext. 7001	
Fax: (877) 226-4028	
E-mail: Info@helpenvironmental.com	
(Mr. Lawrence Gallo)	

H.E.L.P. Environmental
926 3rd Avenue
Brooklyn, NY 11232

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable
2. Ventilation: Use general ventilation to minimize exposure to vapor or mist.
3. Skin and eye contact; protective clothing; treatment in case of contact: Skin contact – immediately flush with copious amounts of water. Remove and wash contaminated clothing and shoes. If irritation persists, see a doctor. Eye contact – may cause eye irritation. In case of contact, immediately flush eyes with plenty of water. If irritation persists, immediately see a doctor. Hygienic practices – wear safety glasses. Wear gloves in accordance with routine laboratory safety precautions.

- 4.a. Maximum storage temperature: >70°C
- 4.b. Minimum storage temperature: -25°C
- 4.c. Optimum storage temperature range:
- 4.d. Temperatures of phase separations and chemical changes: No phase or chemical separation observed.

V. SHELF LIFE

The product has unlimited shelf life.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Recommended application is by aircraft, fireboat monitors or similar apparatus.
2. Concentration/Application Rate: Concentration varies with spilled material - Solvents at 5%, light oils at 10%, medium oils at 10%, and heavy oils at 10%.
3. Conditions for Use: Data is for water temperature of 40°F to 65°F. There are no known application restrictions.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
BIODIPSERS	Menidia beryllina	13.46 96-hr
	Mysidopsis bahia	78.90 48-hr
No. 2 Fuel Oil	Menidia beryllina	12.42 96-hr
	Mysidopsis bahia	2.82 48-hr
BIODIPSERS &	Menidia beryllina	5.95 96-hr
No. 2 Fuel Oil (1:10)	Mysidopsis bahia	2.66 48-hr
Reference Toxicant (SDS)	Menidia beryllina	11.84 96-hr
	Mysidopsis bahia	21.81 48-hr

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	51.0
South Louisiana Crude	63.0
Average of Prudhoe Bay and South Louisiana Crudes	57.0

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point, ASTM Method D56: 193°F
2. Pour Point, ASTM Method D97: - 26°F
3. Viscosity at 40°C, ASTM Method D445: Initial boil point 104.2°C, at 50 mL 109°C, at 70 mL 111°C, at 80 mL 113.7°C, final temperature 307.1°C)
4. Specific Gravity: 0.965

5. pH: 7
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: Water
8. Additives: None
9. Solubility: Product is 100% soluble in water.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<2.50
Cadmium	<0.75
Chromium	<0.75
Copper	<0.50
Lead	<5.00
Nickel	<1.20
Zinc	<0.50
Cyanide	3.90*
Chlorinated Hydrocarbons	<5.00

*During the analysis of cyanide on sample #V202057-01 (Petrotech Dispersant) analyst encountered interferences due to the matrix of sample. Soapy residue created a false positive for cyanide. Sample showed no traces of cyanide. Value related to the soap film turbidity.

TECHNICAL PRODUCT BULLETIN #D-10
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: NOVEMBER 26, 2002
“SEA BRAT #4”

I. NAME, BRAND, OR TRADEMARK

SEA BRAT #4

Type of Product: Dispersant

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

B.R.A.T. Microbial Products Inc.

208 Cinnabar Bay Court

League City, TX 77573

Phone: (713) 724-9226

E-mail: alabastercorp@gmail.com

(Mr. John Sheffield)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

B.R.A.T. Microbial Products Inc.

208 Cinnabar Bay Court

League City, TX 77573

Phone: (713) 724-9226

E-mail: alabastercorp@gmail.com

(Mr. John Sheffield)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable

2. Ventilation: Normal.

3. Skin and eye contact; protective clothing; treatment in case of contact:

Wear safety glasses or goggles, gloves, and rubber boots. Wash after each shift. Remove and wash contaminated clothing before reuse. No respiratory protection is required. Local exhaust is desirable. Mechanical exhaust is helpful in congested areas. Skin contact – flush with water. Seek medical attention if irritation persists. Eye contact – flush with water using eye cup or fountain for 15 minutes. Seek medical attention if irritation persists. Ingestion - seek medical attention. Inhalation – no medical attention is required with inhalation.

4.a. Maximum storage temperature: 120°F

4.b. Minimum storage temperature: 35°F

4.c. Optimum storage temperature range: NA

4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

Indefinite when stored properly.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Spray affected area with a high pressure pump. Always apply in

compliance with federal, state, and local laws.

2. Concentration/Application Rate: Dilution ratios of 1 part SEA BRAT #4 to 9 parts water for a 10 percent solution.

3. Conditions for Use: May be applied to the coastal waters of the U.S. It is designed for hydrocarbon spills on water temperatures between 50°F and 90°F. It is best applied with nozzle pressure of between 80 psi and 100 psi, with a direct hard spray and continuously moving the stream of water over the entire surface.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
SEA BRAT #4	Menidia beryllina	30.00 96-hr
	Mysidopsis bahia	14.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	16.00 96-hr
	Mysidopsis bahia	14.00 48-hr
SEA BRAT #4 &	Menidia beryllina	23.00 96-hr
No. 2 Fuel Oil (1:10)	Mysidopsis bahia	18.00 48-hr
Reference Toxicant (DSS)	Menidia beryllina	1.14 96-hr
	Mysidopsis bahia	0.98 48-hr

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL
VENDOR LAB REPORT:

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	53.55
South Louisiana Crude	60.65
Average of Prudhoe Bay and South Louisiana Crudes	57.10

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point, ASTM Method D56: 200°F
2. Pour Point, ASTM Method D97: 4°F
3. Viscosity (furol seconds): 380 at 77°F
4. Specific Gravity (g/cc): 0.994 at 70°F
5. pH: 9.45
6. Surface Active Agents: Surfactants
7. Solvents: Propylene glycol
8. Additives: None
9. Solubility: Soluble in all ratios.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.05
Cadmium	<0.05
Chromium	<0.05
Copper	<0.05
Lead	<0.05
Mercury	<0.0002
Nickel	<0.05
Zinc	0.215
Cyanide	<0.05
Chlorinated Hydrocarbons	<0.05

TECHNICAL PRODUCT BULLETIN #D-12
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JANUARY 3, 2005
“SAF-RON GOLD”
(aka, SF-GOLD DISPERSANT)

I. NAME, BRAND, OR TRADEMARK
SAF-RON GOLD
(aka, SF-GOLD DISPERSANT)
Type of Product: Dispersant

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Sustainable Environmental Technologies Inc.
55 Ivan Allen Jr. Boulevard, Suite 850
Atlanta, GA 30308
Customer Service:
Phone: (404) 946-3585
24-hour Emergency Number:
Phone: updated information required
E-mail: updated information required
Website: updated information required
(Mr. Bruce Richards)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Sustainable Environmental Technologies Inc.
55 Ivan Allen Jr. Boulevard, Suite 850
Atlanta, GA 30308
Customer Service:
Phone: (404) 946-3585
24-hour Emergency Number:
Phone: updated information required
E-mail: updated information required
Website: updated information required
(Mr. Bruce Richards)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.
2. Ventilation: Special ventilation is not required.
3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment required; however, goggles are recommended. Skin contact - if irritation occurs flush with water; seek medical attention if irritation persists. Eye contact - flush with plenty of water; seek medical attention if irritation persists.
- 4.a. Maximum storage temperature: 120°F
- 4.b. Minimum storage temperature: 32°F

- 4.c. Optimum storage temperature range: 40 - 120°F
 4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

The shelf life is unlimited in unopened containers.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Sprayer, Boat, Aircraft.
2. Concentration/Application Rate: A dispersant to oil ratio ranging from 1:50 to 1:10 is recommended. For heavy high-viscosity oils - 8 gallons of SAF-RON GOLD will disperse approximately 70 gallons of crude oil or bunker C. Also for use with heavy high viscosity oils, SAF-RON GOLD can be used as a concentrate or diluted at a dispersant to water ratio of 1:10. For lighter oils, SAF-RON GOLD can be diluted at mixtures of 1:20 to 1:100. A recommended dispersant to water ratio of 1:40 can be used for most spills. Ratios are dependent upon type of oil and weather conditions.
3. Conditions for Use: Any applicable condition determined by authorities for dispersant use.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
SAF-RON GOLD	Menidia beryllina	29.43 96-hr
	Mysidopsis bahia	63.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	16.76 96-hr
	Mysidopsis bahia	5.93 48-hr
SAF-RON GOLD	Menidia beryllina	9.25 96-hr
No. 2 Fuel Oil (1:10)	Mysidopsis bahia	3.04 48-hr
Reference Toxicant (SLS)	Menidia beryllina	15.94 96-hr
	Mysidopsis bahia	9.83 48-hr

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL
 VENDOR LAB REPORT:

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	84.80
South Louisiana Crude	53.80
Average of Prudhoe Bay and South Louisiana Crudes	69.30

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point, ASTM D-56: >100°C
2. Pour Point, ASTM D-97: -2.5°C
3. Viscosity @40°C, ASTM Method D-445: 1.42 cSt
4. Specific Gravity @60°F/60°F, ASTM Method D-287: 1.014
5. pH: 8.8

6. Surface Active Agents: Proprietary blend of surface-active agents.
7. Solvents: None.
8. Additives: None.
9. Solubility: Fully water soluble.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.01
Cadmium	<0.005
Chromium	0.140
Copper	0.324
Lead	<0.005
Mercury	<0.020
Nickel	<0.005
Zinc	0.0671
Cyanide	<0.20
Chlorinated Hydrocarbons	<0.80

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**3/18/2019
7/27/2022**

TECHNICAL PRODUCT BULLETIN #D-13
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JUNE 16, 2005
“ZI-400”
(aka, ZI-400 OIL SPILL DISPERSANT)

I. NAME, BRAND, OR TRADEMARK
ZI-400
(aka, ZI-400 OIL SPILL DISPERSANT)
Type of Product: Dispersant

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Z.I. Chemicals
340 S Lemon Avenue #5358
Walnut, CA 91789
Phone: updated information required
E-mail: updated information required
Website: www.zichemicals.com
(Ms. Annie Mack)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Z.I. Chemicals
340 S Lemon Avenue #5358
Walnut, CA 91789
Phone: updated information required
E-mail: updated information required
Website: www.zichemicals.com
(Ms. Annie Mack)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-Hazardous).
2. Ventilation: No special requirements.
3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing required; however, goggles are recommended. If eye or skin irritation occurs, flush with plenty of water.
- 4.a. Maximum storage temperature: 120°F continuous, 140°F up to 5 days
- 4.b. Minimum storage temperature: 35°F
- 4.c. Optimum storage temperature range: 40 - 120°F
- 4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE
Unlimited in sealed polydrums of totes (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: ZI-400 may be applied by the usual method of aerial or boat spraying. For smaller spills a drum pump with sprayer may be used, mixing with water as required depending on the type and viscosity of oil being treated.
2. Concentration/Application Rate: On heavy oils use ZI-400 directly on the spill, or up to approximately a 1:10 dilution ratio (product:water). Lighter oils will require a 1:10 to 1:30 product to water dilution ratio. Warmer waters (greater than 78°F) and/or good agitation during application will require less product.
3. Conditions for Use: No limitations as to usage within optimum temperature parameters (application may be made at or above 35°F, with optimum above 48°F).

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
ZI-400	Menidia beryllina	31.76 96-hr
	Mysidopsis bahia	20.96 48-hr
No. 2 Fuel Oil	Menidia beryllina	18.05 96-hr
	Mysidopsis bahia	2.66 48-hr
ZI-400	Menidia beryllina	8.35 96-hr
No. 2 Fuel Oil (1:10)	Mysidopsis bahia	1.77 48-hr
Reference Toxicant (SLS)	Menidia beryllina	16.13 96-hr
	Mysidopsis bahia	27.80 48-hr

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL
VENDOR LAB REPORT:

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	50.10
South Louisiana Crude	89.80
Average of Prudhoe Bay and South Louisiana Crudes	69.90

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point, ASTM D-56: >93°C
2. Pour Point, ASTM D-97: 12.6°F
3. Viscosity, ASTM D-445: 18.80 cSt @ 40°C
4. Specific Gravity, ASTM D-1298: 1.026 @ 60°F
5. pH, ASTM D-1293: 10.9
6. Surface Active Agents: Proprietary
7. Solvents: Proprietary
8. Additives: None.
9. Solubility: Miscible in oil, water, and solvents.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<10
Cadmium	<10
Chromium	<10
Copper	<10
Lead	<10
Mercury	<1
Nickel	<10
Zinc	<10
Cyanide	<0.5
Chlorinated Hydrocarbons	<1.0

TECHNICAL PRODUCT BULLETIN #D-14
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 31, 2008
“NOKOMIS 3-AA”

I. NAME, BRAND, OR TRADEMARK

NOKOMIS 3-AA

Type of Product: Water-Based Dispersant

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Mar-Len Supply, Inc.

23159 Kidder Street

Hayward, CA 94545

Phone: (510) 782-3555

Fax: (510) 782-2032

E-mail: marlensupply@yahoo.com

(Mrs. Shirley Winter or Mr. Curt Winter)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Mar-Len Supply, Inc.

23159 Kidder Street

Hayward, CA 94545

Phone: (510) 782-3555

Fax: (510) 782-2032

E-mail: marlensupply@yahoo.com

(Mrs. Shirley Winter or Mr. Curt Winter)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (water based)

2. Ventilation: No special requirements

3. Skin and eye contact; protective clothing; treatment in case of contact: In case of eye contact, flush with water; in case of skin contact, wash with water; and if swallowed, drink water to dilute and induce vomiting.

4.a. Maximum storage temperature: 160°F

4.b. Minimum storage temperature: 32°F

4.c. Optimum storage temperature range: 32 - 140°F

4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

In excess of 24 months or more if stored correctly in plastic drums.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method:

Aerial applied dispersant – spray from an aircraft flying with a controllable speed at altitudes of 30 to 50 feet. Spray nozzles should be sized to cover an area using 5 gallons per surface acre.

Spray from boat: NOKOMIS 3-AA can be applied by ships or workboat with spray booms mounted as far forward as possible. NOKOMIS 3-AA will generally be marketed in 55 gallon plastic drums. Application of the products may be made directly from the drum. By using a direct connection from pump to drum NOKOMIS 3-AA can be applied at full strength to the oil spill. The determination of whether to use NOKOMIS 3-AA at full strength or diluted with water must be determined by observations and evaluations made on-site at the oil spill. Portable engine powered centrifugal water pumps are a satisfactory means of moving the dispersant from the container to the spill's surface. Diesel-powered larger capacity pump may also be used. If the spill is confined to a small area, a hand-pump connected directly to the 55 gallon drum can be used. Hose diameters and lengths will relate to capacities required for the specific situation and distances from the pump to container and the spill. Fire hose has been successfully used, and with hand pumps small diameter hose is adequate. Fog nozzles on the dispersing end of the hose provide a fine spray of NOKOMIS 3-AA full strength or diluted as appropriate. Any type of hose nozzle can be used, but preferable one with the ability to produce a spray rather than a coarse stream.

2. Concentration/Application Rate: NOKOMIS 3-AA may be applied to oil spills at full strength, or diluted with sea water. Where large areas of water may be covered with heavy concentrations of crude or Bunker C oil, it may be advantageous to apply NOKOMIS 3-AA at full strength. Where lighter fractions of petroleum are involved it is possible that dilutions of up to one part NOKOMIS 3-AA to 30 parts water may be applicable. Approximately 5 gallons of NOKOMIS 3-AA can be used for one surface acre of oil spill.

3. Conditions for Use: Once NOKOMIS 3-AA is applied to the water's surface, to obtain the most efficient emulsification of the oil it is necessary to agitate and mix dispersant, oil, and water thoroughly. In open unconfined areas, the use of ship propellers has been determined a practical way of accomplishing this purpose. By passing over the spill area on a grid system, the vessel's propellers will churn the water, causing the needed mixing. For a large spill, two or more vessels may be needed to apply the product and agitate the water. In and around piers and similar confined areas it is necessary to apply the product from small boats, the shore, or pier itself. Where it is impossible or impractical to supply agitation with propellers of a vessel it is necessary to use pumps and a hose, applying salt water in the coarse stream and under sufficient pressure to cause surface turbulences and subsequent mixing.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
NOKOMIS 3-AA	Menidia beryllina	34.22 96-hr
	Mysidopsis bahia	20.16 48-hr
No. 2 Fuel Oil	Menidia beryllina	22.50 96-hr
	Mysidopsis bahia	11.07 48-hr
NOKOMIS 3-AA &	Menidia beryllina	7.03 96-hr
No. 2 Fuel Oil (1:10)	Mysidopsis bahia	5.56 48-hr
Reference Toxicant (CuSO ₄)	Menidia beryllina	5.36 96-hr
	Mysidopsis bahia	7.83 48-hr

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	63.20
South Louisiana Crude	65.70
Average of Prudhoe Bay and South Louisiana Crudes	64.50

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: None
2. Pour Point: 25 °F
3. Viscosity: 72.3 sus at 100°F
4. Specific Gravity: 1.031 at 60°F
5. pH: 9.0
6. Surface Active Agents: Confidential
7. Solvents: Propylene glycol and Water
8. Additives: None
9. Solubility: Completely water soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.12
Cadmium	<0.25
Chromium	<0.25
Copper	<0.25
Lead	<0.12
Mercury	<0.0016
Nickel	<0.25
Zinc	<1.0
Cyanide	0.034
Chlorinated Hydrocarbons	<0.10

TECHNICAL PRODUCT BULLETIN #D-16
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 18, 2011
“ACCELL CLEAN® DWD”

I. NAME, BRAND, OR TRADEMARK

ACCELL CLEAN® DWD

Type of Product: Dispersant

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Advanced BioCatalytics Corporation

18010 Skypark Circle, #130

Irvine, California 92614-6456

Office Phone: (949) 771-0209

General E-mail: info@abiocat.com

Website: www.abiocat.com

Product Management:

Mobile: (949) 981-6510

E-mail: cpodella@abiocat.com

(Mr. Carl Podella)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Advanced BioCatalytics Corporation

18010 Skypark Circle, #130

Irvine, California 92614-6456

Office Phone: (949) 771-0209

General E-mail: info@abiocat.com

Website: www.abiocat.com

Product Management:

Mobile: (949) 981-6510

E-mail: cpodella@abiocat.com

(Mr. Carl Podella)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Combustible as defined by DOT and USCG.

2. Ventilation: Use in well ventilated areas.

3. Skin and eye contact; protective clothing; treatment in case of contact: Protective clothing is recommended. Avoid eye contact. In case of eye contact, immediately flush with large amounts of water for at least 15 minutes. Get prompt medical attention. Avoid direct contact with skin and clothing. In case of skin contact, immediately flush with large amounts of water. Remove contaminated clothing, including shoes, after flushing has begun. If irritation persists, seek medical attention. For open systems where contact is likely, wear long sleeve shirt, chemical resistant gloves, and protective chemical goggles.

4.a. Maximum storage temperature: 130°F/55°C

- 4.b. Minimum storage temperature: 30°F/-1°C
- 4.c. Optimum storage temperature range: 40°F to 100°F/4°C to 38°C
- 4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

The shelf life of unopened drums of ACCELL CLEAN® DWD is unlimited. Containers should always remain capped when not in use to prevent contamination and evaporation.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Aircrafts provide the most rapid method of applying dispersants to an oil spill and a variety of aircraft can be used for spraying. For aerial spraying, ACCELL CLEAN® DWD is applied undiluted. Typically application altitudes of 30 to 50 feet are recommended, although higher altitudes may be effective under certain conditions. Actual effective altitudes will depend on the application equipment, weather and aircraft. Careful selection of spray nozzles is critical to achieve desired dose levels, since droplet size must be controlled. A quarter-inch open pipe may be all that is necessary if the aircraft travels at 120 mph (104 knots) or more, since the air shear at these speeds will be sufficient to break the dispersant into the proper sized droplets. Agricultural spray delivery systems may not be suitable because of too fine of spray and too little delivery of ACCELL CLEAN® DWD to the affected area.

Boat Spraying: ACCELL CLEAN® DWD may also be applied from boats equipped with spray booms mounted ahead of the bow wake or as far forward as possible. The most effective method of application from a boat is to apply ACCELL CLEAN® DWD using a low-volume, low-pressure pump so the ACCELL CLEAN® DWD can be applied undiluted. ACCELL CLEAN® DWD should not be fogged or atomized. Natural wave or boat wake action usually provides adequate mixing energy to disperse the oil. Application at sub-freezing temperatures may require larger nozzle, supply lines and orifices due to higher product viscosity.

2. Concentration/Application Rate: A treatment rate of about 10 gallons per acre, or a dispersant to oil ratio of 1:10 is optimal. The rate varies depending on the type of oil, degree of weathering, temperatures, and thickness of the slick.

3. Conditions for Use: For optimal results, ACCELL CLEAN® DWD early treatment of oil-contaminated waters is beneficial. ACCELL CLEAN® DWD can be used on weathered oils.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Materials Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
ACCELL CLEAN [®] DWD	Menidia beryllina	5.66	96-hr
	Mysidopsis bahia	2.07	48-hr
No. 2 Fuel Oil	Menidia beryllina	11.10	96-hr
	Mysidopsis bahia	1.68	48-hr
ACCELL CLEAN [®] DWD & No. 2 Fuel Oil (1:10)	Menidia beryllina	8.05	96-hr
	Mysidopsis bahia	1.32	48-hr
Reference Toxicant (DDS)	Menidia beryllina	6.60	96-hr
	Mysidopsis bahia	30.80	48-hr

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	58.70
South Louisiana Crude	96.03
Average of Prudhoe Bay and South Louisiana Crudes	77.37

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 130°F/55°C
2. Pour Point: -20.2°F/-29°C
3. Viscosity: 130 SUS @100°F
4. Specific Gravity: 1.0329 @60°F
5. pH: 5.8
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL
8. Additives: CONFIDENTIAL
9. Solubility: Miscible

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND
Cadmium	ND
Chromium	ND
Copper	ND
Lead	ND
Mercury	ND
Nickel	ND
Zinc	ND
Cyanide	ND
Chlorinated Hydrocarbons	ND

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**7/23/2021
7/27/2022**

TECHNICAL PRODUCT BULLETIN #D-17
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: NOVEMBER 01, 2011
“FFT-SOLUTION®”

I. NAME, BRAND, OR TRADEMARK
FFT-SOLUTION®
Type of Product: Dispersant

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Fog Free Technologies, LLC
4365 Dorchester Road
Building 300, Suite 301
North Charleston, SC 29405
Product Management:
Office Phone: (843) 735-6626
Mobile: (478) 697-2588
E-mail: updated information required
Website: www.fogfreetechnologies.com
(Mr. William Knight)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Fog Free Technologies, LLC
4365 Dorchester Road
Building 300, Suite 301
North Charleston, SC 29405
Product Management:
Office Phone: (843) 735-6626
Mobile: (478) 697-2588
E-mail: updated information required
Website: www.fogfreetechnologies.com
(Mr. William Knight)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: IMO: Non-Flammable, DOT: Non-Hazardous
2. Ventilation: Lowest level of skin protection is acceptable, but no special ventilation is required.
3. Skin and eye contact; protective clothing; treatment in case of contact: Lowest level of skin protection is acceptable. Avoid eye contact. In case of eye contact, immediately flush eyes with large amounts of water for at least 15 minutes. Avoid contact with skin. In case of skin contact, immediately flush with water and soap if available. For open systems where contact is likely, wear long sleeve shirt, chemical resistant gloves and chemical goggles.

Dispersants

- 4.a. Maximum storage temperature: 170°F
- 4.b. Minimum storage temperature: 30°F
- 4.c. Optimum storage temperature range: 40°F to 105°F
- 4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

The shelf life of unopened drums of FFT-Solution® is limited to 60 months. Storage should be in a semi-controlled warehouse, out of direct sunlight.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Aerial Spraying – Aircraft provide the most rapid method of applying dispersants to an oil spill and a variety of aircraft can be used for spraying. For aerial spraying, FFT-Solution® is applied undiluted. Typical application altitudes of 30 to 50 feet have been used, although higher altitudes may be effective under certain conditions. Actual effective altitudes will depend upon application equipment, weather, and aircraft. Careful selection of spray nozzles is critical to achieve desired dose levels, since droplet size must be controlled. Many nozzles used for agricultural spraying are of low capacity and product fine a spray. A quarter-inch open pipe may be all that is necessary if the aircraft travels at 120 mph (104 knots) or more, since the air shear at these speeds will be sufficient to break the dispersant into the proper sized droplets. Optimal temperatures for application are between 33°F and 105°F.

Boat Spraying – FFT-Solution® may also be applied by workboats equipped with spray booms mounted on the stern of the vessel. (Mounting boom on the stern prevents any over spray from making contact with boat operators.) The preferred and most effective method of application from a workboat is to use a low-volume, low-pressure pump so the chemical can be applied undiluted. Standard agriculture spray equipment is designed to make dosage adjustments or provide different spray tips that effect dosage rates. Natural wave or boat wake action usually provides adequate mixing energy to disperse the oil. A typical agriculture spray boom can be mounted to the stern to get wide coverage. The booms on shrimp boats also can be retrofitted to cover a much wider path during applications. The manufacturer also recommends that in lieu of spray tips on the booms, spray tips be changed into solid tubing for injection of FFT-Solution® 3 to 5 feet below the water surface. This will get the thicker crude slicks injected faster and with better results. FFT-Solution® should be applied as droplets, not fogged or atomized.

2. Concentration/Application Rate: A treatment rate of about 2 to 10 U.S. gallons per acre, or dispersant to oil ratio of 1:50 to 1:10 is recommended. This rate varies depending on the type of oil, degree of weathering, temperature, and thickness of the slick.

3. Conditions for Use: FFT-Solution® can be applied to weathered oil as well as light, medium, or heavy oils. Early treatment even at reduced treatment rates, can also counter the foaming tendencies of the spilled oil in turbulent waters. FFT-Solution® can be used on any type oil spills in salt water.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Materials Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
FFT-SOLUTION®	Menidia beryllina	5.34	96-hr
	Mysidopsis bahia	2.72	48-hr
No. 2 Fuel Oil	Menidia beryllina	40.80	96-hr
	Mysidopsis bahia	5.19	48-hr
FFT-SOLUTION®	Menidia beryllina	5.14	96-hr
& No. 2 Fuel Oil (1:10)	Mysidopsis bahia	2.75	48-hr
Reference Toxicant (SDS)	Menidia beryllina	2.42	96-hr
	Mysidopsis bahia	6.97	48-hr

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	49.97
South Louisiana Crude	48.87
Average of Prudhoe Bay and South Louisiana Crudes	49.42

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 170°F
2. Pour Point: 23°F
3. Viscosity: 450 SUS @100°F
4. Specific Gravity: 1.0302 @60°F
5. pH: 9.96
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: None
8. Additives: None
9. Solubility: Product is 100% soluble in water

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND
Cadmium	ND
Chromium	ND
Copper	ND
Lead	ND
Mercury	ND
Nickel	ND
Zinc	ND
Cyanide	ND
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #D-18
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: APRIL 23, 2012
“MARINE D-BLUE CLEAN™”

I. NAME, BRAND, OR TRADEMARK

MARINE D-BLUE CLEAN™

Type of Product: Dispersant

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

AGS Solutions, Inc.

5647 Nunn Street

Houston, TX 77087

Phone: (713) 645-4933

Fax: (713) 645-4903

E-mail: agssolutionsinc@gmail.com

Website: www.agstx.com

(Mrs. Linda Whiteley)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

AGS Solutions, Inc.

5647 Nunn Street

Houston, TX 77087

Phone: (713) 645-4933

Fax: (713) 645-4903

E-mail: agssolutionsinc@gmail.com

Website: www.agstx.com

(Mrs. Linda Whiteley)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable

2. Ventilation: No special requirements. Drums and similar containers should be kept closed.

Store in steel or plastic containers.

3. Skin and eye contact; protective clothing; treatment in case of contact: In case of contact with eyes, wash thoroughly with plenty of clean water. Seek medical attention if irritation develops. Rubber protective gloves should be used if prolonged use of product is anticipated. Goggles, long sleeve shirt, and rubber gloves are recommended during application.

4.a. Maximum storage temperature: 170°F

4.b. Minimum storage temperature: 32°F

4.c. Optimum storage temperature range: 40°F to 110°F

4.d. Temperatures of phase separations and chemical changes: Marine D-Blue Clean™ has a pour point of 30°F and may cause chemical changes at temperatures >110°F.

V. SHELF LIFE

Marine D-Blue Clean™ has a shelf life of ≥ 2 years, if unopened. Cleaner older than 24 months may still be viable. Ensure product is mixed well and then inspect to confirm the product is suitable for application. The product will not lose effectiveness unless the temperatures in $>140^{\circ}\text{F}$.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Sprayer, boat, aircraft. Marine D-Blue Clean™ is to be used to disperse petroleum-based products in salt water. It may be applied by any conventional methods such as aerial spraying or surface vessel spraying, to accommodate weather conditions. Marine D-Blue Clean™ is to be applied undiluted, for aerial spraying. Timely application provides optimal results. Spray concentrated on the oil slick in atomized form such as with a manual pump or a pump system using moderately coarse droplets rather than a fine mist.

2. Concentration/Application Rate: Marine D-Blue Clean™ can be applied with a variety of spraying equipment, depending upon the type and scale of the water to be cleaned. For heavy concentrations of crude oil spill or temperatures below 40°F , Marine D-Blue Clean™ should be used without dilution in neat form. A dispersant to oil ratio up to 1 part dispersant to 20 parts of oil is suggested. Dose rates may vary depending on type and amount of petroleum spilled, and other site specific conditions such as weather, temperatures and extent of oil slick.

3. Conditions for Use: The performance of Marine D-Blue Clean™ is not affected by water salinity. Marine D-Blue Clean™ is useful on oil spills in salt water. It is effective with crude and residual heavy oil spills.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
MARINE D-BLUE CLEAN™	Menidia beryllina	18.00 96-hr
	Mysidopsis bahia	56.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	18.00 96-hr
	Mysidopsis bahia	18.00 48-hr
MARINE D-BLUE CLEAN™ & No. 2 Fuel Oil (1:10)	Menidia beryllina	32.00 96-hr
	Mysidopsis bahia	18.00 48-hr
Reference Toxicant (DSS)	Menidia beryllina	1.06 96-hr
	Mysidopsis bahia	0.97 48-hr

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OIL

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	45.00
South Louisiana Crude	55.59
Average of Prudhoe Bay and South Louisiana Crudes	50.30

VIII. MICROBIOLOGICAL ANALYSIS
NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >200°F
2. Pour Point: 30°F
3. Viscosity: 17.29 cSt @ 100°C
4. Specific Gravity: 1.035 @70°F
5. pH: 11.89
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL
8. Additives: None
9. Solubility: Completely soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.25
Cadmium	<0.005
Chromium	<0.08
Copper	<0.30
Lead	<0.015
Mercury	<0.0025
Nickel	<0.350
Zinc	<2.015
Cyanide	<0.050
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #D-19
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: AUGUST 1, 2013
“COREXIT™ EC9500B”

I. NAME, BRAND, OR TRADEMARK

COREXIT™ EC9500B

Type of Product: Dispersant

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Corexit Environmental Solutions LLC

11177 South Stadium Drive

Sugar Land, TX 77478

Product Management:

Phone: (281) 632-8827

E-mail: corexitinfo@corexit.com

(Mr. Huw Jones)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Corexit Environmental Solutions LLC

11177 South Stadium Drive

Sugar Land, TX 77478

Product Management:

Phone: (281) 632-8827

E-mail: corexitinfo@corexit.com

(Mr. Huw Jones)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: DOT HazMat Classification – This product meets the criteria for classification as a Class 3 combustible liquid (49 CFR §173.120(b)(1)). However, it does not contain combustion, and, therefore, is not subject to the requirements for the Hazardous Materials Regulations (49 CFR §173.120(b)(3)).
2. Ventilation: Use with adequate ventilation equal to unobstructed outdoors in moderate breeze.
3. Skin and eye contact; protective clothing; treatment in case of contact: Do not get in eyes, on skin, or on clothing. In case of eye contact, rinse immediately with plenty of water and seek medical advice promptly. In case of skin contact, wash immediately with plenty of soap and water. If irritation persists or symptoms develop, seek medical attention. If clothing is contaminated, remove clothing and thoroughly wash the affected area. Do not take internally. In the event of oral ingestion, do not induce vomiting (can cause chemical pneumonia if aspirated into lungs). If conscious, wash out mouth and give water to drink. Get medical attention. If inhaled, remove to fresh air, treat symptomatically. Get medical attention.

For open systems where contact is likely, wear Tyvek, chemical resistant gloves (e.g., nitrile), and chemical splash goggles. Where concentrations in air may be high (e.g., confined area), the use of a half face filter mask or air supplied breathing apparatus is recommended.

4.a. Maximum storage temperature: 170°F

4.b. Minimum storage temperature: 40°F

4.c. Optimum storage temperature range: 40°F to 100°F

4.d. Temperatures of phase separations and chemical changes: No phase changes or chemical reactions are anticipated in the minimum to maximum storage range. Below 40°F, surfactant may slowly precipitate out of the solution, but it will return back into solution when warmed.

V. SHELF LIFE

The shelf life of unopened drums of COREXIT™ EC9500B is potentially unlimited when containers remain capped and sealed to prevent contamination and evaporation of solvents.

Testing of COREXIT™ EC9500B is recommended every five years to ensure it remains fit for its intended purpose.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: For aerial spraying, apply COREXIT™ EC9500B undiluted. Various fixed-wing aircraft or helicopters can be used for spraying over a large area, from an altitude of 30 to 50 feet or even higher, depending on the application equipment and aircraft. Typical application altitudes of 30 to 50 feet have been used, although higher altitudes may be effective under certain conditions. Actual altitudes will depend on the application equipment, weather and aircraft. Careful selection of spray nozzles is critical to achieve desired dose levels, since droplet size must be controlled. Many nozzles used for agricultural spraying are of low capacity and produce too fine a spray. Avoid nozzles that produce a mist or fog. No nozzle may be necessary if the aircraft travels at 120 mph (104 knots) or more, since the air shear at these speeds will be sufficient to break the chemical stream into appropriately-sized droplets.

For boat spraying (spray boom), COREXIT™ EC9500B may also be applied by workboats equipped with spray booms mounted ahead of the bow wake or as far forward as possible. The most effective method of application from a workboat could be the use of a low-volume, low-pressure pump. Spray equipment designed to provide a diluted dispersant solution to the spray booms can also be used. Dispersant concentrations in the 5 to 10 percent range are recommended; lower concentrations may result in significant fall-off in effectiveness.

COREXIT™ EC9500B should be applied as droplets, not fogged or atomized. Natural wave or boat wake action usually provides adequate mixing energy to disperse the oil. Water from a fire hose can also be used for agitation of the treated slick.

For boat spraying (fire monitor), a slightly modified fire monitor may be useful for applying dispersant concentrates such as COREXIT™ EC9500B from a boat. A screen cap is used on the nozzle of the monitor to obtain a uniform spray pattern with the proper sized droplet. Due to the volume output and the greater reach of the fire monitor, significantly more area can be covered in a shorter period of time than using conventional spray booms.

System Calibration – To facilitate successful application and dosage control, calibrate spray systems at the temperatures anticipated. Application at sub-freezing temperatures may require larger nozzle, supply lines and orifices due to higher product viscosity.

2. Concentration/Application Rate: A treatment rate of about 2 to 10 U.S. gallons per acre, or a dispersant to oil ratio of 1:50 to 1:10 is recommended; lower concentrations may also be used. This rate varies depending on the type of oil, degree of weathering, temperature, and thickness of the slick.

3. Conditions for Use: COREXIT™ EC9500B can be used on oil spills in salt waters and at any water temperature. The product can be used on most oils, weathered spills, and “chocolate mousse” (water-oil emulsions). Viscous oil may require higher dosage rates.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

Material Tested	Species	LC50 (ppm)	
COREXIT™ EC9500B	Menidia beryllina	29.13	96-hr
	Mysidopsis bahia	10.00	48-hr
No. 2 Fuel Oil	Menidia beryllina	7.54	96-hr
	Mysidopsis bahia	2.51	48-hr
COREXIT™ EC9500B & No. 2 Fuel Oil (1:10)	Menidia beryllina	4.46	96-hr
	Mysidopsis bahia	2.13	48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.19	96-hr
	Mysidopsis bahia	10.53	48-hr

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OILS

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	57.0
South Louisiana Crude	50.9
Average of Prudhoe Bay and South Louisiana Crudes	53.9

VIII. MICROBIOLOGICAL PROPERTIES

NA

IX. PHYSICAL PROPERTIES

- Flash Point: 164°F
- Pour Point: -44.0°F
- Viscosity: 21.78 cSt at 40°C
- Specific Gravity: 0.9626 at 15°C
- pH: 6.29
- Chemical Name and Percentage by Weight of the Total Formulation: CONFIDENTIAL
- Surface Active Agents: CONFIDENTIAL
- Solvents: CONFIDENTIAL

9. Additives: None

10. Solubility: Miscible

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

Compound	Concentration (ppm)
Arsenic	0.0108
Cadmium	<0.0020
Chromium	<0.0060
Copper	<0.0060
Lead	<0.0040
Mercury	<1.0000 (ug/L)
Nickel	<0.0100
Zinc	<0.0060
Cyanide	<0.0100
Chlorinated hydrocarbons	1.7600

TECHNICAL PRODUCT BULLETIN #D-20
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: NOVEMBER 06, 2019
“CHIMEC CHIMSPERSE 6000”

I. NAME, BRAND, OR TRADEMARK

CHIMEC CHIMSPERSE 6000

Type of Product: Dispersant

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

CHIMEC S.p.A.

Via dell'informatica 5

00071 Pomezia (RM), Italy

Phone: +39-06-91825291

Fax: +39-06-91825225

E-mail: fnanchi@chimec.it

(Mr. Francesco Nanchi, Deputy and
Special Prosecutor for Manufacturing,
Shipping, Safety, and Environment)

CHIMEC Technical Manager and Primary Contact:

Phone: +39-06-91825258

Fax: +39-06-91825262

E-mail: mmantarro@chimec.it

(Mrs. Milena Mantarro)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

CHIMEC S.p.A.

Via dell'informatica 5

00071 Pomezia (RM), Italy

Phone: +39-06-918251

Fax: +39-06-9194170

E-mail: mortolani@chimec.it

(Mrs. Maria Angela Ortolani,
Chairperson and Legal Representative)

CHIMEC Technical Manager and Primary Contact:

Phone: +39-06-91825258

Fax: +39-06-91825262

E-mail: mmantarro@chimec.it

(Mrs. Milena Mantarro)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-Flammable.

2. Ventilation: None under normal conditions. If exposure levels are exceeded or irritation is experienced, wear approved respiratory protection. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known, wear approved respiratory protection (e.g., a mask fit for organic vapors (A1)). If inhaled, go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

3. Skin and eye contact; protective clothing; treatment in case of contact: For skin protection, wear latex or neoprene gloves, and clothing with chemically resistant materials and fabric (e.g., trivalent suit). For eye and face protection, wear chemical safety glasses; or face shield with safety glasses. General first aid measures include never give anything by mouth to an unconscious person. If feeling unwell, see medical advice. After skin contact, remove

contaminated clothing and drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists. In case of eye contact, immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention. If ingested, rinse mouth. DO NOT induce vomiting and obtain medical attention.

- 4.a. Maximum storage temperature: 104°F (40°C) continuous
- 4.b. Minimum storage temperature: -4°F (-20°C)
- 4.c. Optimum storage temperature range: 32°F (0°C) to 80°F (27°C)
- 4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

The shelf life of opened containers is 12 months. If sealed as delivered, shelf life of closed containers is 24 months. Shelf life may be extended to 48 months after analytical checks. According to internal procedures for dispersant products, after 24 months the Chimec Quality Control department checks analytical parameters based on technical specifications before extending shelf life to 48 months.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: CHIMEC CHIMSPERSE 6000 may be applied by the usual methods (e.g., NIMBUS package, the Modular Aerial Spray System (MASS) package, or the Aerial Dispersant Delivery System (ADDS) package). The preferred and most effective method of application from a workboat is to use a low-volume, low-pressure pump.
2. Concentration/Application Rate: CHIMEC CHIMSPERSE 6000 is preferably used undiluted. A typical treatment rate is 10 to 15 L/acre or a DOR (dispersant to oil ratio) of 1:50 to 1:10. However, the treatment rate can vary depending on the type or oil, degree of weathering, temperature, and thickness of oil slick. For heavy oils, a 1:10 dilution ratio (product:water) is recommended. Lighter oils will require a 1:10 to 1:30 (product:water) dilution ratio. Warmer waters (greater than 78°F) and/or good agitation during application will require less product.
3. Conditions for Use: CHIMEC CHIMSPERSE 6000 can be used in salt water, with no limitations as to usage if within optimum temperature parameters (application may be made at or above 35°F, with optimum above 48°F).

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
CHIMSPERSE 6000	Menidia beryllina	2.51 96-hr
	Mysidopsis bahia	3.43 48-hr
No. 2 Fuel Oil	Menidia beryllina	4.48 96-hr
	Mysidopsis bahia	3.26 48-hr
CHIMSPERSE 6000 & No. 2 Fuel Oil (1:10)	Menidia beryllina	3.01 96-hr
	Mysidopsis bahia	1.88 48-hr
Reference Toxicant (SLS)	Menidia beryllina	1.86 96-hr
	Mysidopsis bahia	9.44 48-hr

b. Effectiveness:

SWIRLING FLASK DISPERSANT EFFECTIVENESS TEST WITH SOUTH LOUISIANA (S/L) AND PRUDHOE BAY (P/B) CRUDE OILS

<u>Oil</u>	<u>Effectiveness (%)</u>
Prudhoe Bay Crude	48.30
South Louisiana Crude	58.50
Average of Prudhoe Bay and South Louisiana Crudes	53.40

VIII. MICROBIOLOGICAL PROPERTIES

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >100°F
2. Pour Point: -28°C
3. Viscosity: 26.8 cSt at 40°C
4. Specific Gravity: 0.9987 at 60°F
5. pH: 7.3
7. Surface Active Agents: CONFIDENTIAL
8. Solvents: CONFIDENTIAL
9. Additives: None
10. Solubility: Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	1.24
Cadmium	<0.122
Chromium	0.254
Copper	<0.272
Lead	<0.118
Mercury	<0.0132
Nickel	0.778
Zinc	5.24
Cyanide	1.75
Chlorinated hydrocarbons	<1.80

TECHNICAL PRODUCT BULLETIN #2024-D-001
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: NOVEMBER 18, 2024
ACCELL CLEAN® DWD 2.0

**DISPERSANT DATA SUBMISSION TECHNICAL BULLETIN
FOR § 300.915 DATA AND INFORMATION REQUIREMENTS**

PRODUCT NAME: Accell Clean® DWD 2.0

CATEGORY: DISPERSANT

GENERAL PRODUCT INFORMATION [§ 300.915(a)]

(1) NAME, ADDRESS, EMAIL, AND TELEPHONE NUMBER OF SUBMITTER [§ 300.915(a)(1)]

Advanced BioCatalytics
18010 Skypark Circle, Suite #130
Irvine, California 92614
Email: info@abiocat.com
Phone: 949-442-0880
Martin Carrera (Primary): mcarrera@abiocat.com
Chris Harano (Alternate): charano@abiocat.com

(2) SUBMITTER IDENTIFICATION [§ 300.915(a)(2)]

Submitter identity and documentation of that identity, as the manufacturer of the product; vendor, importer, or distributor of the product; and/or designated agent acting on behalf of the manufacturer provided by the submitter on October 18, 2024.

(3) PRODUCT NAME, BRAND, OR TRADEMARK [§ 300.915(a)(3)]

Accell Clean® DWD 2.0

(4) NAME, ADDRESS, EMAIL, AND TELEPHONE NUMBER OF SUPPLIERS [§ 300.915(a)(4)]

For the United States and all other countries not specifically identified below:

Advanced BioCatalytics
18010 Skypark Circle, Suite #130
Irvine, California 92614
Orders may be submitted by email at: orders@abiocat.com
Phone: 949-442-0880
Contacts:
Martin Carrera, Sr Technical Advisor, mcarrera@abiocat.com
Carl Podella, VP R&D, cpodella@abiocat.com
Chris Harano, President, charano@abiocat.com
Marc Garcia, Financial Controller, mgarcia@abiocat.com

<u>For Singapore, Malaysia, Indonesia:</u> Advanced BioCatalytics Asia Pte Ltd Email: siva@abiocat-asia.com Phone: +60-19-6500 135 Contact: Sivabalan Ponniah	<u>For Brazil:</u> Verus Ambiental Avenida Brigadeiro Faria Lima 1478 Sao Paulo, SP, 01472-900 Brazil renato@versusambiental.com.br Phone: +55-11-3892-7634 Contact: Renato Abucham	<u>For France and other European Union nations:</u> BioTech Nature Business Park des Playes 540 Boulevard de L'Europe 83500 La Seyne-sur-Mer France Email: info@biotechnature.com Phone: +33 06 12 60 35 69 Contact: Mr. Colin Wilcken
---	--	--

(5) SAFETY DATA SHEET (SDS) [§ 300.915(a)(5)]

The Safety Data Sheet for the product provided by the submitter on October 18, 2024.

(6) PRODUCT STORAGE [§ 300.915(a)(6)]

1. Maximum storage temperature (e.g., °F and/or °C): 130°F
2. Minimum storage temperature (e.g., °F and/or °C): 15°F
3. Optimum storage temperature (e.g., °F and/or °C): 30°F to 120°F
4. Humidity (e.g., g/kg): Relative humidity will have no impact on a sealed container of the product. Optimal humidity for chemical storage is between 30% to 95% relative humidity. Relative humidity would only have an effect on the product if the liquid were exposed to the environment for more than 12 hours.
 - Maximum humidity: should not exceed 95%
 - Minimum humidity: should not be lower than 15%
 - Optimal humidity: 75%
5. Other relevant conditions for product storage: The ambient air temperature around the liquid has little effect on the product unless the liquid reaches these minimum or maximum temperatures beyond 12 consecutive hours.
6. Description of the consequences to performance if product is not stored within these limits: If the product were exposed to extreme heat (above 150°F) or extreme cold (below -20°F) the product may exhibit phase separation. In some cases, the product can be reblended or re-agitated to re-establish a homogeneous solution. Advanced BioCatalytics can provide technical support in such an extreme instance to advise and assist on product performance evaluation and the re-blending process if deemed feasible.

(7) SHELF LIFE STORAGE CONDITIONS [§ 300.915(a)(7)]

The product should have a minimum shelf life of 10 years and potentially much longer as long as the original packaging remains sealed. Documentation for this determination was provided by the submitter on October 18, 2024. Advanced BioCatalytics offers lab testing of existing inventory and recertification of material. The testing and recertification will be conducted for a fee. The testing and recertification of the material will require that an aliquot of at least 250ml be sent to the address in (a)(1) of this bulletin. Orders may be submitted by email to: orders@abiocat.com with the SUBJECT: "Testing and Recertification for ACCELL CLEAN DWD 2.0"

(8) PRODUCT LABEL [§ 300.915(a)(8)]

A sample product label for all name(s), brand(s), and/or trademark(s) under which the product is to be sold that includes manufacture and expiration dates, and conditions for storage provided by the submitter on October 18, 2024.

(9) PRODUCT CATEGORY AND PROCESSES [300.915(a)(9)]

Accell Clean® DWD 2.0 Deep Water Dispersant is comprised of a combination of surfactants, solvent and a bio-based Yeast Extract Hydrolysate from *Saccharomyces cerevisiae* that create a proper hydrophilic-lipophilic balance (HLB) that disperses the spilled oil rather than emulsifying the spilled oil. The dispersed oil is comprised of fine oil droplets that are much more bioavailable for degradation than the coarse oil droplets or any emulsified oil. The yeast extract functions as a surfactant synergist by reducing the interfacial tension and critical micelle concentration. This function yields greater surfactancy properties at lower concentrations. Additionally, the yeast extract affects aerobic bacteria to increase their ability to uptake organic material at a faster pace than would be observed for the surfactants alone. The solvent also assists in reducing interfacial tension and dispersing the spilled oil into the water column and remaining dispersed for an increased rate of degradation.

(10) RECOMMENDED PRODUCT USE PROCEDURES [§ 300.915(a)(10)]**1. Application Method:**

- Aerial application: Aircrafts provide the most rapid method of applying dispersants to an oil spill and a variety of aircraft can be used for spraying. For aerial spraying, Accell Clean® DWD 2.0 is applied undiluted. Typically, application altitudes of 30 to 50 feet are recommended, although higher the altitudes may be effective under certain conditions. Actual effective altitudes will depend on the application equipment, weather, and aircraft. Careful selection of spray nozzles is critical to achieve the desired dose levels, since the droplet size must be controlled. A quarter-inch open pipe may be all that is necessary if the aircraft travels at 120 mph (104 knots) or, more, since the air shear at these speeds will be sufficient to break the dispersant into the proper sized droplets. Agricultural spray delivery systems may not be suitable because too fine spray and too little delivery of Accell Clean® DWD 2.0 to affected area. Companies that are considering the use for this product from aircraft or vessels should consult the American Petroleum Institute's Technical Report 1148, *Aerial and Vessel Dispersant Preparedness*; and for subsea use, American Petroleum Institute's Technical Report 4791, *Industry Guidelines on Requesting Regulatory Concurrence for Subsea dispersant Use*, which both describe the process and application of dispersants in a marine environment.
- Boat application: Accell Clean® DWD 2.0 may also be applied from boats equipped with spray booms mounted ahead of the bow wake or as far forward as possible. The most effective method of application from a boat is to apply Accell Clean® DWD 2.0 using a low-volume, low-pressure pump so Accell Clean® DWD 2.0 can be applied undiluted. Accell Clean® DWD 2.0 should not be fogged or atomized. Natural wave or boat wake action usually provides adequate mixing energy to disperse the oil. Application at sub-freezing temperatures may require a larger nozzle, supply lines, and orifices due to higher product viscosity.
- Subsea application: Accell Clean® DWD 2.0 may also be applied subsurface at the well head using submarine equipment.

2. Concentration / Application Rate: A treatment rate of about 5 gallons per acre, or a dispersant to oil ratio of 1:20 is optimal for aerial or vessel application, however, application rates of 1:10-1:50 can be used based on the type of oil, degree of weathering, temperatures, and thickness of the slick. For subsurface application a 1:100 dispersant to oil ratio use has been proven to be an effective ratio.

3. Conditions for Use: Accell Clean® DWD 2.0 can be used in salt water, brackish waters, open ocean or subsurface ocean waters with limitations as specified by the Federal On-Scene Coordinator in consultation with the NOAA Scientific Support Coordinator.

(11) ENVIRONMENTAL FATE OF COMPONENTS [§ 300.915(a)(11)]

The submitter provided available information on environmental fate, including any known measured data, methodologies, and supporting documentation, on the persistence, bioconcentration factor, bioaccumulation factor, and biodegradability of the product and all of its components in the environment on October 18, 2024.

(12) PHYSICAL/CHEMICAL PROPERTIES [§ 300.915(a)(12)]

Analysis	Result	Unit	Method
(i) Physical State and Appearance:	Viscous liquid Amber color		
(ii) Vapor Pressure	0.51	psi @ 100°F	ASTM D5191
(iii) Flash Point	>100	°C	ASTM D-56
(iv) Pour Point	-12	°C	ASTM D-97
(v) Viscosity	41.3	cst @ 40°C	ASTM D-445
(vi) Specific Gravity	1.0157	@ 60°F	ASTM D-287
(vii) Particle Size for Solid Components	NA	NA	NA
(viii) pH	6.86		Probe

(13) IDENTIFICATION AND CONCENTRATION OF PRODUCT COMPONENTS [§ 300.915(a)(13)]

Under § 300.950, you may only claim as Proprietary Business Information (PBI) the concentration, the maximum, minimum, and average weight percent; and the units of each component of the total formulation as identified in § 300.915(a)(13) and (14) and as applicable. All other product information submitted to EPA as required under § 300.915 and § 300.955 will be available for public disclosure upon submission, without further notice to the submitter.

Chemical Name	CAS #	Concentration Percentage by Weight (PBI)	Intended Function
Water and fermentation yeast metabolites	8013-01-2	MAX/MIN/AVG% - PBI	Co-surfactant
Hexylene Glycol	107-41-5	MAX/MIN/AVG% - PBI	Mutual solvent
Benzyl Alcohol	100-51-6	MAX/MIN/AVG% - PBI	Solvent
Dioctyl Sodium Sulfosuccinate	577-11-7	MAX/MIN/AVG% - PBI	Surfactant

Alcohols, C9-11, Ethoxylated	68439-46-3	MAX/MIN/AVG% - PBI	Surfactant
Sorbitan Monooleate	1338-43-8	MAX/MIN/AVG% - PBI	Emulsifier

(14) MICROORGANISMS, ENZYMES AND/OR NUTRIENTS [§ 300.915(a)(14)]

Accell Clean® DWD 2.0 contains no microorganisms, enzymes or nutrients. Although yeast species are used during a proprietary fermentation process to create the hydrolysate, the yeast microorganism itself is subject to thermal lysis which is the breakdown of the cell membrane through a heat shock process. The material is further processed using a combination of centrifugation, filtration, and sterilization methods to remove any remaining solid material. The result is the hydrolysate material, also referred to as yeast metabolite, but without any living microorganisms present. Through HPLC (high precision liquid chromatography) analysis we have also determined there are no enzymes present in the material. There are short chain proteins and amino acids which function as a surfactant synergist or co-surfactant making micelles larger and increasing the functionality of the dispersant. One may characterize short chain proteins as “nutrients,” however, that is not the intended purpose of this material.

(15) DATA, METHODOLOGY AND SUPPORTING DOCUMENTATION FOR LEVELS OF THE FOLLOWING [§ 300.915(a)(15)]:

Analyte	Result (mg/L)	Method
Arsenic	<0.00345	SW846 6020B (ICP/MS)
Barium	<0.00671	SW846 6020B (ICP/MS)
Cadmium	<0.00120	SW846 6020B (ICP/MS)
Chromium	<0.00280	SW846 6020B (ICP/MS)
Copper	<0.0194	SW846 6020B (ICP/MS)
Lead	<0.00184	SW846 6020B (ICP/MS)
Mercury	<0.0000706	SW846 7407° (CVAA)
Nickel	<0.00264	SW846 6020B (ICP/MS)
Selenium	<0.00133	SW846 6020B (ICP/MS)
Silver	<0.000780	SW846 6020B (ICP/MS)
Vanadium	<0.000860	SW846 6020B(ICP/MS)
Zinc	<0.0137	SW846 6020B (ICP/MS)
Cyanide	Non-detect	EPA Method 335.4
Chlorinated hydrocarbons	Non-detect	SW846 8260D (GC/MS)
Pesticides	Non-detect	SW846 8081B (GC)

Polychlorinated biphenyls (PCBs)	Non-detect	SW846 8082 (GC)
Polycyclic aromatic hydrocarbons (PAHs)	Non-detect	SW846 8270E (GC/MS)
(16) PROHIBITED AGENT CERTIFICATION [§ 300.915(a)(16)] Certification including data, methodology and supporting documentation indicating that product does not contain any prohibited agents identified in § 300.910(e) provided by submitter October 18, 2024.		
(17) LABORATORY INFORMATION [§ 300.915(a)(17)] Information about the accredited laboratory that conducted the required tests, including: (i) Name of the laboratory, address, contact, name, email, and phone number; and (ii) the national and/or international accreditations held by the laboratory that are applicable to test(s) performed were provided by the submitter on October 18, 2024.		
(18) LABORATORY TEST DATA AND REPORTS [§ 300.915(a)(18)] All test data and calculations were provided by the submitter on October 18, 2024.		
(19) PRODUCTION VOLUMES [§ 300.915(a)(19)] <u>Annual production volume:</u> 1,560,000 gallons <u>Average amount that could be produced in a day:</u> 3,571 gallons <u>Maximum amount that could be produced in a day:</u> 4,286 gallons <u>Time frame needed to reach that maximum production rate in days:</u> The ramp up time to reach maximum daily production is two months or 60 days.		
(20) DESIGN FOR THE ENVIRONMENT (now Safer Choice) [§ 300.915(a)(20)] Not provided.		
(21) INTERNATIONAL PRODUCT TESTING, DATA, AND/OR CERTIFICATIONS [§ 300.915(a)(21)] Not provided.		

PRODUCT CATEGORY TESTING AND LISTING REQUIREMENTS [§ 300.915(b)]					
DISPERSANT EFFICACY TEST AND LISTING CRITERIA [§ 300.915(b)(1)]					
Listing Criteria: Dispersant must demonstrate for each temperature a Dispersant Effectiveness (DE) at the 95% lower confidence level (LCL95) greater than or equal to:					
<ul style="list-style-type: none">• ≥70% for Strategic Petroleum Reserve Bryan Mound test oil at 5°C; and• ≥75% for Strategic Petroleum Reserve Bryan Mound test oil at 25°C.					
Test Oil	Dispersant Effectiveness Temperature at 5°C			Dispersant Effectiveness Temperature at 25°C	
SPR Bryan Mound	87.7% DE _{LCL95}			90.0% DE _{LCL95}	
DISPERSANT TOXICITY TESTS AND LISTING CRITERIA [§ 300.915(b)(2)]					
Listing Criteria: Dispersant tested alone must demonstrate:					
<ul style="list-style-type: none">• For acute toxicity a median lethal concentration for 50% of the test species (LC50) at the lower 95% confidence interval greater than 10 ppm.• For developmental toxicity the inhibition concentration for 50% of the test species (IC50) at the lower 95% confidence interval greater than 1 ppm; and• For sub-chronic toxicity the No Observed Effect Concentration (NOEC) greater than 1 ppm.					
Acute Toxicity Test Data Summary					
Material Tested	Saltwater Species	LC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant Only	<i>Menidia beryllina</i>	20.37	17.85	23.23	96-hr
	<i>Americamysis bahia</i>	20.39	17.41	23.89	48-hr
Dispersant/Reference Oil Mixture	<i>Menidia beryllina</i>	21.44	18.83	24.42	96-hr
	<i>Americamysis bahia</i>	7.72	7.09	8.41	48-hr
SDS Reference Toxicant	<i>Menidia beryllina</i>	10.10	8.91	11.44	96-hr
	<i>Americamysis bahia</i>	24.98	25.29	26.79	48-hr
Developmental Test Data Summary					
Material Tested	Sea Urchin Species	IC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Strongylocentrotus purpuratus</i>	16.74	16.30	17.14	72-hr
Copper Chloride Reference Toxicant	<i>Strongylocentrotus purpuratus</i>	17.31	16.83	17.66	72-hr
Subchronic Test Data Summary					
Material Tested	Saltwater Species	LC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Menidia beryllina</i>	34.29	31.57	37.25	7-day

	<i>Americamysis bahia</i>	29.26	27.05	31.65	7-day
Material Tested	Saltwater Species	IC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Menidia beryllina</i>	36.00	32.17	38.78	7-day
	<i>Americamysis bahia</i>	32.22	28.55	33.55	7-day
Material Tested	Saltwater Species	IC25 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Menidia beryllina</i>	27.52	8.92	31.12	7-day
	<i>Americamysis bahia</i>	23.46	18.54	30.75	7-day
Material Tested	Saltwater Species	LOEC (ppm)		Duration	
		Survival	Growth		
Dispersant	<i>Menidia beryllina</i>	50.00	50.00	7-day	
	<i>Americamysis bahia</i>	40.00	30.00	7-day	
SDS Reference Toxicant	<i>Menidia beryllina</i>	20.00	15.00	7-day	
	<i>Americamysis bahia</i>	40.00	40.00	7-day	
Material Tested	Saltwater Species	NOEC (ppm)		Duration	
		Survival	Growth		
Dispersant	<i>Menidia beryllina</i>	25.00	25.00	7-day	
	<i>Americamysis bahia</i>	30.00	20.00	7-day	
SDS Reference Toxicant	<i>Menidia beryllina</i>	15.00	10.00	7-day	
	<i>Americamysis bahia</i>	20.00	20.00	7-day	

TECHNICAL PRODUCT BULLETIN #2024-D-002
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: NOVEMBER 18, 2024
DASIC ECOSAFE OSD

**DISPERSANT DATA SUBMISSION TECHNICAL BULLETIN
FOR § 300.915 DATA AND INFORMATION REQUIREMENTS**

PRODUCT NAME: Dasic EcoSafe OSD

CATEGORY: DISPERSANT

GENERAL PRODUCT INFORMATION [§ 300.915(a)]

(1) NAME, ADDRESS, EMAIL, AND TELEPHONE NUMBER OF SUBMITTER [§ 300.915(a)(1)]

Dasic USA, LLC
3500 South Dupont Highway
Dover, DE 19901
E-mail: DasicInfo@Dasic-USA.com
Phone: 832-633-0365
Dr. Tim Nedwed

(2) SUBMITTER IDENTIFICATION [§ 300.915(a)(2)]

Submitter identity and documentation of that identity, as the manufacturer of the product; vendor, importer, or distributor of the product; and/or designated agent acting on behalf of the manufacturer provided by the submitter on October 9, 2024.

(3) PRODUCT NAME, BRAND, OR TRADEMARK [§ 300.915(a)(3)]

Dasic EcoSafe OSD

(4) NAME, ADDRESS, EMAIL, AND TELEPHONE NUMBER OF SUPPLIERS [§ 300.915(a)(4)]

Sole Distributor of Dasic EcoSafe OSD:
Dasic USA, LLC
3500 South Dupont Highway
Dover, DE 19901
E-mail: DasicInfo@Dasic-USA.com
Phone: 832-633-0365
Dr. Tim Nedwed

(5) SAFETY DATA SHEET (SDS) [§ 300.915(a)(5)]

The Safety Data Sheet for the product provided by the submitter on October 9, 2024.

(6) PRODUCT STORAGE [§ 300.915(a)(6)]

1. Maximum storage temperature (e.g., °F and/or °C): 170°F
2. Minimum storage temperature (e.g., °F and/or °C): -30°F
3. Optimum storage temperature (e.g., °F and/or °C): 40°F to 100°F
4. Humidity (e.g., g/kg): External humidity can range from 0-100% if containers are maintained with a nitrogen blanket. Containers stored in humidity >60% may experience corrosion. Prolonged storage of containers in high humidity environments (>60%) require frequent inspection (monthly) to ensure their integrity.
 - Maximum humidity: 100%
 - Minimum humidity: 0%
 - Optimal humidity: 0-60%

5. Other relevant conditions for product storage: Protect from exposure to direct sunlight. Exposing Dasic EcoSafe OSD will cause rapid degradation, however, storing in proper containers prevents this. Containers themselves are subject to UV degradation; and should be protected from long-term exposure to direct sunlight as well.

6. Description of the consequences to performance if product is not stored within these limits: The primary concern with storage of Dasic EcoSafe OSD outside the optimum ranges described above for long periods (over 6 months) is degradation and/or precipitation of one or more components of the product. This could impact product effectiveness. Storage of the product outside the maximum and minimum ranges described above for short periods (48 hours) is likely to have little impact on product effectiveness. If Dasic EcoSafe OSD is stored outside the optimal ranges of temperature and humidity but within the maximum and minimum ranges for >6 months, it is recommended that a Dasic USA, LLC representative perform an evaluation of the product in each container stored outside the optimal ranges and either recertify its quality or replace it. Storage of containers in direct sunlight or in humid environments (>60% humidity) for long periods (>6 months) can result in degradation/corrosion of the container itself. This can result in cracking and eventual failure. A minimum of biannual inspection of all Dasic EcoSafe OSD storage containers is recommended with monthly inspections being ideal. If failure of individual containers is identified (i.e., discoloration, cracking, leaking, excessive warping), it is recommended that a Dasic USA, LLC representative repackage the product and recertify the product integrity.

(7) SHELF LIFE STORAGE CONDITIONS [§ 300.915(a)(7)]

The anticipated shelf life of the product is at least 20 years at the storage conditions described in (a)(6) above. This determination is based on this product being a reformulation of an existing dispersant also owned by Dasic USA, LLC that has proven to have long-term stability when stored properly. It uses the same surfactants and solvents as the existing dispersant and does not add new components. Dispersant effectiveness testing was performed on 20-year samples of the existing dispersant that were stored within the maximum/minimum ranges described in (a)(6). The samples maintained "Excellent" effectiveness without effectiveness degradation over this period. Results of this testing was provided by the submitter on October 9, 2024.

(8) PRODUCT LABEL [§ 300.915(a)(8)]

A sample product label for all name(s), brand(s), and/or trademark(s) under which the product is to be sold that includes manufacture and expiration dates, and conditions for storage provided by the submitter on October 9, 2024.

(9) PRODUCT CATEGORY AND PROCESSES [300.915(a)(9)]

Dasic EcoSafe OSD submitted as a chemical agent under the dispersant category.

The specific process through which the product affects the oil is as follows: Dasic EcoSafe OSD contains a mixture of surfactants in a carrier solvent. It is sprayed onto the surface of an oil floating on a marine environment or directly into a jet of oil escaping to a marine environment from a subsea release point. Once the product contacts the oil, the surfactants in Dasic EcoSafe OSD rapidly locate to the interface between the oil and the water for a subsea oil release or both the air/oil and oil/water interfaces for an oil floating on a marine surface. Once the surfactants reach these interfaces, they change the surface and/or interfacial tension of the oil. This allows the oil to break into droplets that are so small they are essentially neutrally buoyant when Dasic EcoSafe OSD is applied to an oil floating on a marine surface, or it reduces the size of oil droplets resulting from a subsea release by at least an order of magnitude.

The surfactants in Dasic EcoSafe OSD not only reduce the oil's surface/interfacial tension, they also protect the droplets from recoalescence once they are formed. This is important because initially plumes of oil formed after treating oil with Dasic EcoSafe OSD are very concentrated in droplets and because of this they tend to frequently collide with each other. Dasic EcoSafe OSD significantly reduces the efficiency of coalescence resulting from these collisions. Without application of Dasic EcoSafe OSD, oil emanating from a subsea release or oil on a marine surface that is impacted by breaking waves will form small droplets initially, but they can rapidly recoalesce to form large droplets that rapidly resurface or reach the surface.

Note that dispersed oil droplets are positively buoyant until they undergo significant biodegradation. "Essentially neutrally buoyant" means that the droplets become so small that their rise velocity is low enough that they are under the influence of ocean currents and turbulence for long periods. Thus, if they do resurface at some point, they are dispersed widely enough to only form very thin sheens on the surface that are themselves subject to rapid redispersion into the water column after they encounter mixing energy from waves. In contrast, large oil droplets can rapidly resurface in a location with other droplets to reform a thick slick that can weather and emulsify to become persistent. Thin sheens aren't thick enough or persistent enough to form emulsions as they tend to rapidly redisperse in most offshore wave environments.

Applying Dasic EcoSafe OSD to a jet of oil emanating from a subsea release reduces the interfacial tension of the oil in the same way as for a surface oil. The exact size of the resulting droplets depends on the amount of turbulent energy in the jet of oil and properties of the oil itself. It is expected that Dasic EcoSafe OSD will reduce the interfacial tension of oil from subsea releases enough to produce oil droplets that are at least an order of magnitude smaller than they would be without treatment. The benefits, at a minimum, will be a hundred-fold reduction in the average rise velocity of droplets emanating from a subsea release because the rise velocity of oil droplets is approximately directly proportional to the square of the oil droplet radius.

Oil droplets that remain entrained in the water column will be rapidly diluted to concentrations low enough to allow aerobic biodegradation of individual oil droplets by petroleum degrading microorganism without exhausting the nutrients or oxygen available in most open marine environments. Individual droplets are rapidly colonized by petroleum degrading microorganisms once they enter the water column. Half-lives of the oil is expected to be on the order of 2-4 weeks. In addition, petroleum-degrading organisms degrade the most soluble petroleum compounds first and fastest. Many of these compounds tend to be the more toxic components of crude and fuel oils. This results in the oil droplets becoming less toxic as biodegradation continues. Ultimately, biodegradation produces a residue that consists of large insoluble compounds that are recalcitrant and not bioavailable.

Reducing the diameter of the average droplet emanating from a subsea release by an order of magnitude could have the same effect as applying Dasic EcoSafe OSD to a surface oil if the turbulent energy of the release jet is high enough. At a minimum, however, reducing the diameter of oil droplets by an order of magnitude will reduce the rise velocity of these droplets by two orders of magnitude thereby allowing the droplets to remain in the water column for significantly longer period – from maybe just a few hours to many tens of hours. This allows the droplets to drift with ocean currents for longer periods and likely surface large distances from the release point thereby protecting responders tasked with stopping the flow of oil from being inundated by volatiles. Relatively fresh oil surfacing from a subsea release will contain volatile components that will rapidly transfer to the air and potentially produce a hazardous environment for responders. Thus, in many scenarios, application of Dasic EcoSafe OSD to a jet of oil emanating from a subsea release will protect the safety of responders attempting to control the oil flow.

(10) RECOMMENDED PRODUCT USE PROCEDURES [§ 300.915(a)(10)]

1. Application Method:

- Aerial application: Application altitudes exceeding 200 feet are acceptable under certain conditions. Spray nozzle location, spray pressures/flowrates, and nozzle opening diameter are all critical to achieving the desired dosage and droplet size. Design of these aspects of an aerial delivery system all depend on the aerial platform used and the application conditions (e.g., application altitude and speed). Parameters for this equipment cannot be prescribed because of the variability of the aerial delivery platforms used by oil spill response organizations (i.e., they vary from helicopters to 737 aircraft). It is recommended that organizations responsible for aerial dispersant spray operations base the appropriate nozzle configuration, delivery pressure/flowrates, spray altitude, and delivery speed on model predictions using prediction tools such as the BSEE Aerial Dispersant Application Decision Support Tool. This tool uses the specification of the aerial delivery system, the aerial delivery platform, and characteristics of Dasic EcoSafe OSD (e.g., droplet density and size distribution) to predict the mass deposition density of dispersant. This type of model allows completion of a multi-variate analysis of aerial spray systems for specific aerial spray platforms to maximize the dispersant delivery accuracy (i.e., onto floating oil) while maximizing application altitude to increase the safety of crews in aerial delivery aircraft.
- Boat application: Dasic EcoSafe OSD may be applied by boats equipped with spray equipment (e.g., spray systems mounted in a way to apply the dispersant before the boat bow wave pushes the oil away from the spray or specialized spray equipment. Natural wave or boat wake action provides adequate mixing energy to disperse the oil. As with aerial spray delivery systems, operators of boat-based delivery systems need to calibrate their systems to allow the highest efficiency delivery of Dasic EcoSafe OSD to floating oil.
- Subsea application: Dasic EcoSafe OSD may be applied to a subsea well blowout using boats that maintain a supply of the product, appropriate pumps, and appropriate conduits from the boats to the location of the subsea release at the seabed. A simple wand-based system placed as near the release point as possible is recommended to deliver Dasic EcoSafe OSD into the oil jet. Nozzles on these wands can be any of several diameters that allow Dasic EcoSafe OSD to efficiently pass into the oil jet without passing through it. Several organizations have subsea dispersant injection systems that can deliver Dasic EcoSafe OSD.

2. Concentration / Application Rate: Dasic EcoSafe OSD is best applied undiluted. Diluted application can be attempted if application equipment requires higher flow rates. Diluted application may be effective given the appropriate oil and spill conditions. As with any dispersant use, field-based dispersant monitoring should determine if the application is successful. Dasic EcoSafe OSD is applied as high as 1 part dispersant to 10 parts oil to as low as 1 part dispersant to 100 parts oil. The exact ratio depends on many factors during a spill response such as the oil type, the amount of oil weathering/emulsification, the type of spill, and the weather or release conditions.

- For surface application: It is recommended applying Dasic EcoSafe OSD at treatment rates of between 2-10 U.S. gallons per acre to oil floating on the surface. Lower rates are suitable for readily dispersible oils and higher rates or reapplication may be needed for more challenging oils.

- For subsea application: Treatment rates of 1 part dispersant to 100 parts oil or even lower are recommended. These lower treatment rates are possible for subsea application because oils emanating from a release point are fresh and likely significantly more dispersible than the same oil that may have weathered and emulsified on a marine surface for hours to days before treatment. Treatment ratios lower than 1:100 might be used for highly energetic subsea release scenarios that are expected to produce smaller dispersed oil droplets. Actual treatment ratios and rates of Dasic EcoSafe OSD during an actual spill depends on many factors, however, in all cases treatment ratios should be based on field dispersant effectiveness monitoring such as the Special Monitoring of Applied Response Technologies. For subsea dispersant use, a monitoring protocol to assess dispersant effectiveness such as the "Environmental Monitoring for Atypical Dispersant Operations" developed by the US National Response Team is recommended.

3. Conditions for Use:

- Surface oil: Dasic EcoSafe OSD is designed for use in a wide range of surface application conditions from tropical, to temperate, to subarctic, and arctic temperature conditions. Use of Dasic EcoSafe OSD in zero or subzero air temperatures is possible, but it is recommended that the product be stored in containers that maintain temperatures above 40°F to ensure suitable flow characteristics before delivery. In addition, Dasic EcoSafe OSD is designed to be applied through a broad range of wind and wave conditions from flat calm to Beaufort 6 and beyond. The maximum wind/wave conditions will depend on the safety of the crew during delivery operations. Dasic EcoSafe OSD can be applied in flat calm or near flat calm conditions (non-breaking waves) as well. Application in non-breaking wave conditions may not result in immediate dispersion as would occur in breaking wave conditions so monitoring should account for this. In non-breaking waves, effective application of Dasic EcoSafe OSD will force the oil to spread very thin if the oil is in an open water environment. As the oil thins, it will become easier to disperse even in low-energy waves. Monitoring the effectiveness of Dasic EcoSafe OSD for up to 24 hours is recommended in non-breaking waves.
- Subsea oil releases: Dasic EcoSafe OSD is designed to be effective in deepwater subsea salinity and temperature conditions (40°F and 35 ppt salinity). Higher temperatures are not a problem. Salinities significantly above 35 ppt require field-based monitoring to assess effectiveness (e.g., with the Environmental Monitoring for Atypical Dispersant Operations protocol).
- Water salinity: Dasic EcoSafe OSD can work in low salinity environments (e.g., as low as 20 ppt or even lower and up to 35 ppt and higher). The effectiveness of the product in low salinity (below 20 ppt) and high salinity (well above 35 ppt) will depend on the oil and spill conditions. As with any dispersant operation, a field-based monitoring protocol should be used to assess effectiveness of Dasic EcoSafe OSD in conditions of either low or high salinity.

- Types and weathering states for oils: Dasic EcoSafe OSD was developed to treat a broad range of oils from low viscosity fresh oils to highly weathered and emulsified viscous oils. Specific ranges of oil weathering, oil emulsification, or oil viscosity for use of Dasic EcoSafe OSD cannot be specified because of the huge differences in chemistry of various oils and conditions of a specific spill scenario. If effective use of Dasic EcoSafe OSD could mitigate spill impacts, a field-based monitoring protocol used to assess effectiveness of the actual oil encountered during a spill is recommended.

(11) ENVIRONMENTAL FATE OF COMPONENTS [§ 300.915(a)(11)]

The submitter provided available information on environmental fate, including any known measured data, methodologies, and supporting documentation, on the persistence, bioconcentration factor, bioaccumulation factor, and biodegradability of the product and all of its components in the environment on October 09, 2024.

(12) PHYSICAL/CHEMICAL PROPERTIES [§ 300.915(a)(12)]

Analysis	Result	Unit	Method
(i) Physical State and Appearance:	Clear amber liquid		
(ii) Vapor Pressure	<0.05 (<2.6 mmHg)	psi @ 100°F	ASTM D-323
(iii) Flash Point	>100	°C	ASTM D-56
(iv) Pour Point	-46	°C	ASTM D-97
(v) Viscosity	60.4	cst @ 40°C	ASTM D-445
(vi) Specific Gravity	1.0003	@ 60°F	ASTM D-287
(vii) Particle Size for Solid Components	NA	NA	NA
(viii) pH	7.81		Probe

(13) IDENTIFICATION AND CONCENTRATION OF PRODUCT COMPONENTS [§ 300.915(a)(13)]

Under § 300.950, you may only claim as Proprietary Business Information (PBI) the concentration, the maximum, minimum, and average weight percent; and the units of each component of the total formulation as identified in § 300.915(a)(13) and (14) and as applicable. All other product information submitted to EPA as required under § 300.915 and § 300.955 will be available for public disclosure upon submission, without further notice to the submitter.

Chemical Name	CAS #	Concentration Percentage by Weight (PBI)	Intended Function
Sodium Diocetyl Sulfosuccinate	577-11-7	MAX/MIN/AVG% - PBI	Surfactant
Polyoxyethylene (20) Sorbitan Monooleate	9005-65-6	MAX/MIN/AVG% - PBI	Surfactant
Polyoxyethylene (20) Sorbitan Trioleate	9005-70-3	MAX/MIN/AVG% - PBI	Surfactant
Sorbitan Monooleate	1338-43-8	MAX/MIN/AVG% - PBI	Surfactant

Dipropylene Glycol n-Butyl Ether	29911-28-2	MAX/MIN/AVG% - PBI	Solvent
Distillates (petroleum) Hydrotreated Light	64742-47-8	MAX/MIN/AVG% - PBI	Solvent
(14) MICROORGANISMS, ENZYMES AND/OR NUTRIENTS [§ 300.915(a)(14)] Dasic EcoSafe OSD contains no microorganisms, enzymes, or nutrients.			
(15) DATA, METHODOLOGY AND SUPPORTING DOCUMENTATION FOR LEVELS OF THE FOLLOWING [§ 300.915(a)(15)]:			
Analyte	Result (mg/L)	Method	
Arsenic	Non-detect	SW846 6020B (ICP/MS)	
Cadmium	Non-detect	SW846 6020B (ICP/MS)	
Chromium	Non-detect	SW846 6020B (ICP/MS)	
Copper	Non-detect	SW846 6020B (ICP/MS)	
Lead	Non-detect	SW846 6020B (ICP/MS)	
Mercury	Non-detect	SW846 7407A (CVAA)	
Nickel	Non-detect	SW846 6020B (ICP/MS)	
Vanadium	0.00935	SW846 6020B (ICP/MS)	
Zinc	Non-detect	SW846 6020B (ICP/MS)	
Cyanide	Non detect	EPA Method 335.4	
Chlorinated hydrocarbons	Non detect	SW846 8260D (GC/MS)	
Pesticides	Non detect	SW846 8081B (GC)	
Polychlorinated biphenyls (PCBs)	Non detect	SW846 8082 (GC)	
Polycyclic aromatic hydrocarbons (PAHs)	Non detect	SW846 8270E (GC/MS)	
(16) PROHIBITED AGENT CERTIFICATION [§ 300.915(a)(16)] Certification including data, methodology and supporting documentation indicating that product does not contain any prohibited agents identified in § 300.910(e) provided by the submitter on October 9, 2024.			
(17) LABORATORY INFORMATION [§ 300.915(a)(17)] Information about the accredited laboratory that conducted the required tests, including: (i)Name of the laboratory, address, contact, name, email, and phone number; and (ii) the national and/or international accreditations held by the laboratory that are applicable to test(s) performed were provided by the submitter on October 09, 2024.			

(18) LABORATORY TEST DATA AND REPORTS [§ 300.915(a)(18)]

All test data and calculations were provided by the submitter on October 09, 2024.

(19) PRODUCTION VOLUMES [§ 300.915(a)(19)]

Annual production volume: 2.4 million gallons per year

Average amount that could be produced in a day: 6,575 gallons, after a 60 day period to start production of various components and taking into account supply chain limitations.

Maximum amount that could be produced in a day: 30,000 gallons when the production rates of various Dasic EcoSafe OSD components are not rate limiting.

Time frame needed to reach that maximum production rate in days: 60 days

(20) DESIGN FOR THE ENVIRONMENT (now Safer Choice) [§ 300.915(a)(20)]

Not provided.

(21) INTERNATIONAL PRODUCT TESTING, DATA, AND/OR CERTIFICATIONS [§ 300.915(a)(21)]

Not provided.

PRODUCT CATEGORY TESTING AND LISTING REQUIREMENTS [§ 300.915(b)]

DISPERSANT EFFICACY TEST AND LISTING CRITERIA [§ 300.915(b)(1)]

Listing Criteria: Dispersant must demonstrate for each temperature a Dispersant Effectiveness (DE) at the 95% lower confidence level (LCL95) greater than or equal to:

• ≥70% for Strategic Petroleum Reserve Bryan Mound test oil at 5°C; and

• ≥75% for Strategic Petroleum Reserve Bryan Mound test oil at 25°C.

Test Oil	Dispersant Effectiveness Temperature at 5°C	Dispersant Effectiveness Temperature at 25°C
SPR Bryan Mound	82.86% DE _{LCL95}	92.81% DE _{LCL95}

DISPERSANT TOXICITY TESTS AND LISTING CRITERIA [§ 300.915(b)(2)]

Listing Criteria: Dispersant tested alone must demonstrate:

• For acute toxicity a median lethal concentration for 50% of the test species (LC50) at the lower 95% confidence interval greater than 10 ppm.

• For developmental toxicity the inhibition concentration for 50% of the test species (IC50) at the lower 95% confidence interval greater than 1 ppm; and

• For sub-chronic toxicity the No Observed Effect Concentration (NOEC) greater than 1 ppm.

Acute Toxicity Test Data Summary					
Material Tested	Saltwater Species	LC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant Only	Menidia beryllina	306.56	271.10	346.65	96-hr
	Americamysis bahia	171.36	156.90	187.16	48-hr
Dispersant/Reference Oil Mixture	Menidia beryllina	66.34	62.93	69.94	96-hr
	Americamysis bahia	8.43	7.12	9.98	48-hr
SDS Reference Toxicant	Menidia beryllina	7.76	7.18	8.38	96-hr
	Americamysis bahia	28.28	27.57	29.01	48-hr

Developmental Test Data Summary					
Material Tested	Sea Urchin Species	IC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Arabica punctulata</i>	58.68	52.21	64.03	72-hr
Copper Chloride Reference Toxicant	<i>Arabica punctulata</i>	11.62	11.60	11.65	72-hr
Subchronic Test Data Summary					
Material Tested	Saltwater Species	LC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Menidia beryllina</i>	414.80	354.00	486.20	7-day
	<i>Americamysis bahia</i>	137.70	119.50	158.8	7-day
Material Tested	Saltwater Species	IC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Menidia beryllina</i>	471.50	420.40	537.70	7-day
	<i>Americamysis bahia</i>	118.20	88.90	141.50	7-day
Material Tested	Saltwater Species	IC25 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Menidia beryllina</i>	251.30	212.50	279.90	7-day
	<i>Americamysis bahia</i>	62.18	46.48	88.32	7-day
Material Tested	Saltwater Species	LOEC (ppm)		Duration	
		Survival	Growth		
Dispersant	<i>Menidia beryllina</i>	500	250	7-day	
	<i>Americamysis bahia</i>	250	100	7-day	
SDS Reference Toxicant	<i>Menidia beryllina</i>	20	15	7-day	
	<i>Americamysis bahia</i>	20	20	7-day	
Material Tested	Saltwater Species	NOEC (ppm)		Duration	
		Survival	Growth		
Dispersant	<i>Menidia beryllina</i>	250	100	7-day	
	<i>Americamysis bahia</i>	100	10	7-day	
SDS Reference Toxicant	<i>Menidia beryllina</i>	15	10	7-day	
	<i>Americamysis bahia</i>	15	15	7-day	

TECHNICAL PRODUCT BULLETIN #2025-D-003
 USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
 ORIGINAL LISTING DATE: JANUARY 15, 2025
 FINASOL OSR 52 IBC

DISPERSANT DATA SUBMISSION TECHNICAL BULLETIN FOR § 300.915 DATA AND INFORMATION REQUIREMENTS	
PRODUCT NAME: FINASOL OSR 52 IBC CATEGORY: DISPERSANT	
GENERAL PRODUCT INFORMATION [§ 300.915(a)]	
(1) NAME, ADDRESS, EMAIL, AND TELEPHONE NUMBER OF SUBMITTER [§ 300.915(a)(1)] TotalEnergies Petrochemicals & Refining USA, Inc. 1201 Louisiana Street, Suite 1800 Houston, TX 77002 Email: nathan.williams@totalenergies.com Telephone: 713-483-5044 Point of Contact: Nathan Williams	
(2) SUBMITTER IDENTIFICATION [§ 300.915(a)(2)] Submitter identity and documentation of that identity, as the manufacturer of the product; vendor, importer, or distributor of the product; and/or designated agent acting on behalf of the manufacturer provided by the submitter on October 29, 2024.	
(3) PRODUCT NAME, BRAND, OR TRADEMARK [§ 300.915(a)(3)] FINASOL OSR 52 IBC TotalEnergies Petrochemicals & Refining USA, Inc. 1201 Louisiana Street, Suite 1800 Houston, TX 77002 Email: juan.aguirre@totalenergies.com Telephone: 713-826-8434 Point of Contact: Juan Aguirre	
(5) SAFETY DATA SHEET (SDS) [§ 300.915(a)(5)] The Safety Data Sheet for the product provided by submitter on October 29, 2024.	
(6) PRODUCT STORAGE [§ 300.915(a)(6)] 1. <u>Maximum storage temperature (e.g., °F and/or °C):</u> 45°C (113 °F) 2. <u>Minimum storage temperature (e.g., °F and/or °C):</u> -5°C (23°F) 3. <u>Optimum storage temperature (e.g., °F and/or °C):</u> 5-35°C (41-95°F) 4. <u>Humidity (e.g., g/kg):</u> <ul style="list-style-type: none"> Maximum humidity: 90% Minimum humidity: 30% Optimal humidity: 70% 	

5. Other relevant conditions for product storage: Direct sunlight, high humidity and saltwater can cause damage to containers; hence, their exposure should be minimized as far as possible. It is, therefore, preferable to store dispersant indoors (i.e., inside warehouse facilities that provide adequate ventilation). If outdoors storage is unavoidable, adequate shelter/cover should be provided. Exposure to temperature extremes and fluctuations should also be avoided wherever feasible. In locations where high or low ambient temperatures are encountered, the use of climate-controlled facilities may be necessary.

6. Description of the consequences to performance if product is not stored within these limits: Phase separation and/or loss of efficiency may occur if the product is not stored within these limits.

(7) SHELF LIFE STORAGE CONDITIONS [§ 300.915(a)(7)]

The initial shelf life is 5 years when the containers remain capped and sealed to prevent contamination and evaporation of solvents and are stored as per advised storage conditions. After storage, stir the product and ensure homogeneity before use.

FINASOL OSR 52 IBC is a new development derived from FINASOL OSR 52. 96.3 % of their formulation is common, while the remaining 3.7 % of FINASOL OSR 52 IBC formulation is split between components also present in FINASOL OSR 52. It is thus expected that the storage stability will be at least similar for both products.

This 5 years value for initial shelf life derives from a study from French laboratory CEDRE presented at Arctic and Marine Oilspill Program (AMOP) 1997. This study, based on the quality controls carried out on French Navy dispersant stockpiles (including periodic control every 5 years after purchase), concludes that FINASOL OSR 52 is stable and keeps its efficiency in the range 0 to 6 years. Another study conducted at CEDRE laboratory on FINASOL OSR 52 samples aged from 7 to 25 years has showed that the efficiency remained unaffected and still within the range required for marine dispersants in France. This is reasonably assumed to be also applicable to FINASOL OSR 52 IBC. Past this five years period, extended shelf life may be granted upon re-testing of the product efficiency (and toxicity if required). Guidance from IPIECA's support document "Dispersant Storage, Maintenance, Transport and Testing" should be [reviewed during] re-testing process:

- Testing should be performed on samples representative of 10% of stock volume (e.g. 1 IBC tote out of 10 for a same production batch)
- Sampling can be performed with the help of a sampling thief
- Samples should be stored in compatible (glass or HOPE) and distinctly labelled bottles, with reference from the original container
- Tests to be performed and pass criteria are the same as those required for product [listing] on NCP Product Schedule

(8) PRODUCT LABEL [§ 300.915(a)(8)]

A sample product label for all name(s), brand(s), and/or trademark(s) under which the product is to be sold that includes manufacture and expiration dates, and conditions for storage provided by submitter on October 29, 2024.

(9) PRODUCT CATEGORY AND PROCESSES [§ 300.915(a)(9)]

A marine dispersant formulation is essentially a solution of different surfactants in a mineral solvent (dearomatized kerosene cut), as can also be inferred from the product composition. As a consequence, its efficacy derives mostly from the properties of surfactant molecules. On top of being a “thinner” for the (viscous) surfactants to allow for a good operability pumpability/spray ability of the dispersant, the solvent acts as “carrier” for the surfactants to soak into the oil slick as both the solvent and crude oil share similar (low) polarities and thus mutual solubility.

Once brought in contact with the oil slick, the amphiphilic surfactant molecules scatter at the oil/water interface, thus lowering the surface tension between oil and water. This reduces the energy needed to create additional surface between both phases, allowing for the wave movements to bring sufficient energy to create droplets of oil in water, stabilized by the surfactant (oil in water emulsion). This process can repeat iteratively, until the size distribution of the droplets makes them small enough (typically below 45 - 70 µm in diameter) to remain dispersed and diluted in the water column by the waves' energy. Once dispersed, the repulsive interactions between droplets due to the surfactant layer at the water/oil interface prevents the coalescence of oil droplets leading to the re-creation of another oil slick. Ultimately, the combined action of marine currents and agitation will disperse and dilute the droplets into a larger volume of water.

(10) RECOMMENDED PRODUCT USE PROCEDURES [§ 300.915(a)(10)]

1. Application Method: FINASOL OSR 52 IBC is applied effectively by aircraft or helicopter, from boats, or by subsea injection. Its viscosity has been chosen to be adapted to the usual dispensing systems (nozzles, ramps, nozzle canon, SSDI wand, etc.). FINASOL OSR 52 IBC is intended to be used pure, however, it can be prediluted with up to 10% seawater if needed to reduce its viscosity in cold weather conditions.

Spraying must not give too fine or atomized droplets as in fog. It must be done as moderately coarse droplets, with diameters in the range of 500 - 1000 µm, whether application is by surface vessel or aircraft.

2. Concentration / Application Rate: It is generally recommended to use marine dispersants, including FINASOL OSR 52 IBC in particular, with a 1:5 to 1:50 dispersant-to-oil ratio. A 1:20 ratio would correspond approximately to 15 gallons per ton of oil.

However, this recommendation may be adapted according to the nature of the oil, its state of weathering, temperature, thickness of the slick, and other circumstances of the spill, based on in- situ trials on a small scale.

3. Conditions for Use: When treating a spill with FINASOL OSR 52 IBC, it is recommended to start the treatment as early as possible, to avoid a thickening of the slick due to either evaporation of light fractions or formation of water-in-oil emulsion.

Apart from its direct influence on both oil and dispersant viscosities, which are treated separately in

Application Method (above) and Application Restrictions (below), water temperature (and ice coverage if relevant) have not been identified as having a decisive influence on FINASOL OSR 52 IBC efficiency, as can be observed in efficiency results at 5 °C and inferred from extrapolating from results obtained with FINASOL OSR 52 in a study conducted by Arctic Response Technology. Use only receptacles, joints, pipes, etc. which are resistant to hydrocarbons. Do not spray at high pressure (> 3 bar).

Application Restrictions: It is generally considered for marine dispersants in general, including FINASOL OSR 52 IBC in particular, that:

- Use should be restricted to pollutants with a viscosity not higher than 10000 mm²/s, preferably not higher than 5000 mm²/s (at sea temperature at the location of the spill). For pollutants whose viscosity is enclosed between 5000 and 10000 mm²/s, result is uncertain, and testing is recommended before treating a spill.
- Sea conditions must allow sufficient energy for breaking the oil into droplets small enough to be dispersed. Oil spill dispersion is considered difficult if not impossible for sea conditions below Beaufort 3 level. Inversely, high winds and/or rough sea (Beaufort 7 or above level) will make dispersant application difficult if not impossible both by boat or aircraft (this is usually taken into account in the decision matrixes for dispersant use). FINASOL OSR 52 IBC has been optimized to treat spills in salty water. Efficiency may be reduced in case of application in low salinity water (below 20 psu).
- Although this may depend on local policies and On Scene Coordinator appreciation, it is usually recommended to use marine dispersants at sea and not too close from the shore (or from fish/shell farms) and/or in too shallow waters.

Containment, Collection, Recovery, and Disposal: FINASOL OSR 52 IBC is designed to be used as dispersant. As such, it is readily dispersed in sea water and aims at dispersing oil into small droplets and dilute it in sea water. As a consequence, there is no need to consider containment, collection, recovery or disposal for FINASOL OSR 52 IBC after use. Disposal of unused (e.g. expired) product should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Disposal should be made via a licensed waste disposal contractor.

(11) ENVIRONMENTAL FATE OF COMPONENTS [§ 300.915(a)(11)]

The submitter provided available information on environmental fate, including any known measured data, methodologies, and supporting documentation, on the persistence, bioconcentration factor, bioaccumulation factor, and biodegradability of the product and all of its components in the environment on October 29, 2024.

(12) PHYSICAL/CHEMICAL PROPERTIES [§ 300.915(a)(12)]

Analysis	Result	Unit	Method
(i) Physical State and Appearance:	Light yellow liquid at ambient temperature	Visual	Liquid

(ii) Vapor Pressure	0.6	psi @ 100°F	ASTM D-323
(iii) Flash Point	>100	°C	ASTM D-56
(iv) Pour Point	-53	°C	ASTM D-445
(v) Viscosity	31.7	cst @ 40°C	ASTM D-97
(vi) Specific Gravity	1.0260	@ 60°F	ASTM D-287
(vii) Particle Size for Solid Components	NA	NA	NA
(viii) pH	6.88		Probe

(13) IDENTIFICATION AND CONCENTRATION OF PRODUCT COMPONENTS [§ 300.915(a)(13)]

Under § 300.950, you may only claim as Proprietary Business Information (PBI) the concentration, the maximum, minimum, and average weight percent; and the units of each component of the total formulation as identified in § 300.915(a)(13) and (14) and as applicable. All other product information submitted to EPA as required under § 300.915 and § 300.955 will be available for public disclosure upon submission, without further notice to the submitter.

Chemical Name	CAS #	Concentration Percentage by Weight (PBI)	Intended Function
Sorbitan Monooleate (SMO)	1338-43-8	MAX/MIN/AVG% - PBI	Surfactant
Sorbitan Monooleate, ethoxylated (SMO-E)	9005-65-6	MAX/MIN/AVG% - PBI	Surfactant
Sorbitan Trioleate (STO)	26266-58-0	MAX/MIN/AVG% - PBI	Surfactant
Sodium Diocylsulfosuccinate 70% in hydrotreated light aliphatic hydrocarbons (DOSS 70%)	577-11-7 64742-47-8	MAX/MIN/AVG% - PBI	Surfactant
Dipropylene Glycol Methyl Ether	34590-94-8	MAX/MIN/AVG% - PBI	Solvent
Hydrotreated Light Aliphatic Hydrocarbons	64742-47-8	MAX/MIN/AVG% - PBI	Solvent
Demineralized Water	NA	MAX/MIN/AVG% - PBI	Solvent

(14) MICROORGANISMS, ENZYMES AND/OR NUTRIENTS [§ 300.915(a)(14)]

Product name OSD contains no microorganisms, enzymes, or nutrients.

(15) DATA, METHODOLOGY AND SUPPORTING DOCUMENTATION FOR LEVELS OF THE FOLLOWING [§ 300.915(a)(15)]:

Analyte	Result (mg/L)	Method
Arsenic	<0.0345	SW846 6020B (ICP/MS)
Barium	<0.0671	SW846 6020B (ICP/MS)
Cadmium	<0.0120	SW846 6020B (ICP/MS)
Chromium	<0.0280	SW846 6020B (ICP/MS)
Copper	<0.194	SW846 6020B (ICP/MS)
Lead	<0.0184	SW846 6020B (ICP/MS)
Mercury	<0.000070	SW846 7470A (CVAA)
Nickel	0.0437	SW846 6020B (ICP/MS)
Selenium	<0.0133	SW846 6020B (ICP/MS)
Silver	<0.00780	SW846 6020B (ICP/MS)
Vanadium	<0.00860	SW846 6020B (ICP/MS)
Zinc	0.389	SW846 6020B (ICP/MS)
Cyanide	0.0642	EPA Kelada Method (EPA-821-B-01-009)
Chlorinated hydrocarbons [Exception: 1,1,2-Trichloroethane]	< Method Detection Limit [2.80]	SW846 8260C (GC/MS); SW846 8270E (GC/MS)
Pesticides	<Method Detection Limit	SW846 8081B (GC)
Polychlorinated biphenyls (PCBs)	<Method Detection Limit	SW846 8082A (GC)
Polycyclic aromatic hydrocarbons (PAHs)	<Method Detection Limit	SW846 8270E (GC/MS)

(16) PROHIBITED AGENT CERTIFICATION [§ 300.915(a)(16)]

Certification including data, methodology and supporting documentation indicating that product does not contain any prohibited agents identified in § 300.910(e) provided by the submitter on 10/29/2024.

(17) LABORATORY INFORMATION [§ 300.915(a)(17)]

Information about the accredited laboratory that conducted the required tests, including:

(i) Name of the laboratory, address, contact, name, email, and phone number; and (ii) the national and/or international accreditations held by the laboratory that are applicable to test(s) performed were provided by the submitter October 29, 2024; and January 8, 2025.

(18) LABORATORY TEST DATA AND REPORTS [§ 300.915(a)(18)]

All test data and calculations were provided by the submitter on October 29, 2024.

(19) PRODUCTION VOLUMES [§ 300.915(a)(19)]

Annual production volume: 500,000 gallons (= 2,000 m³) per year

Average amount that could be produced in a day: 3,800 gallons after initial batch run (= 14 m³) for routine (“average”) production. Daily production volumes are indicative only as the blending process may extend over one day (in which case daily production values are given as a pro-rata temporis of weekly production volume).

Maximum amount that could be produced in a day: 26,000 gallons (= 100 m³) after initial batch run in case of emergencies. These figures are given assuming that the corresponding raw materials are available in sufficient volume at production site. Timeframe needed to reach max production volume is estimated to be 60 days to allow for sufficient supply of all needed raw materials. Quantity and timeframe for the initial batch run is 6,000 gallons (= 24 m³) in 4 weeks. Weekly production volume after the initial batch run is 19,000 gallons (= 72 m³).

(20) DESIGN FOR THE ENVIRONMENT (now Safer Choice) [§ 300.915(a)(20)]

Not provided.

(21) INTERNATIONAL PRODUCT TESTING, DATA, AND/OR CERTIFICATIONS [§ 300.915(a)(21)]

Used as a marine dispersant in France and Spain based on the below results:

Test	Method	Result	Requirement
Efficiency (IFP “Flow Through” Method)	NF T90-345	77.6%	>60%
Toxicity <i>Palaemonetes varians</i> (marine shrimp)	NF T90-349	LC50 > 10,000 ppm (LC50 Noramium DA 50 = 49 ppm)	LC50 (dispersant) > 10x LC50 (Noramium DA 50 (reference toxicant))
Biodegradability	NF T90-346	>100% (%Theoretical CO2 = 112%) based on CO2 evolution	>50% after 28 days

PRODUCT CATEGORY TESTING AND LISTING REQUIREMENTS [§ 300.915(b)]					
DISPERSANT EFFICACY TEST AND LISTING CRITERIA [§ 300.915(b)(1)]					
Listing Criteria: Dispersant must demonstrate for each temperature a Dispersant Effectiveness (DE) at the 95% lower confidence level (LCL95) greater than or equal to:					
<ul style="list-style-type: none">• ≥70% for Strategic Petroleum Reserve Bryan Mound test oil at 5°C; and• ≥75% for Strategic Petroleum Reserve Bryan Mound test oil at 25°C.					
Test Oil	Dispersant Effectiveness Temperature at 5°C	Dispersant Effectiveness Temperature at 25°C			
SPR Bryan Mound	84.10% DE _{LCL95}	88.4% DE _{LCL95}			
DISPERSANT TOXICITY TESTS AND LISTING CRITERIA [§ 300.915(b)(2)]					
Listing Criteria: Dispersant tested alone must demonstrate:					
<ul style="list-style-type: none">• For acute toxicity a median lethal concentration for 50% of the test species (LC50) at the lower 95% confidence interval greater than 10 ppm.• For developmental toxicity the inhibition concentration for 50% of the test species (IC50) at the lower 95% confidence interval greater than 1 ppm; and• For sub-chronic toxicity the No Observed Effect Concentration (NOEC) greater than 1 ppm.					
Acute Toxicity Test Data Summary					
Material Tested	Saltwater Species	LC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant Only	<i>Menidia beryllina</i>	65.36	60.78	70.28	96-hr
	<i>Americamysis bahia</i>	18.08	16.21	20.17	48-hr
Dispersant/Reference Oil Mixture	<i>Menidia beryllina</i>	14.72	12.48	17.35	96-hr
	<i>Americamysis bahia</i>	16.63	14.66	18.87	48-hr
SDS Reference Toxicant	<i>Menidia beryllina</i>	7.76	7.18	8.38	96-hr
	<i>Americamysis bahia</i>	28.28	27.57	29.01	48-hr
Developmental Test Data Summary					
Material Tested	Sea Urchin Species	IC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Arabica punctulata</i>	15.19	14.56	15.63	72-hr
Copper Chloride Reference Toxicant	<i>Arabica punctulata</i>	11.62	11.60	11.65	72-hr
Subchronic Test Data Summary					
Material Tested	Saltwater Species	LC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Menidia beryllina</i>	28.28	23.78	33.64	7-day
	<i>Americamysis bahia</i>	22.66	19.97	25.72	7-day

Material Tested	Saltwater Species	IC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Menidia beryllina</i>	27.20	23.04	40.98	7-day
	<i>Americamysis bahia</i>	18.15	15.56	19.97	7-day
Material Tested	Saltwater Species	IC25 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Menidia beryllina</i>	16.13	13.47	19.84	7-day
	<i>Americamysis bahia</i>	12.29	6.12	14.87	7-day
Material Tested	Saltwater Species	LOEC (ppm)		Duration	
		Survival	Growth		
Dispersant	<i>Menidia beryllina</i>	25	10	7-day	
	<i>Americamysis bahia</i>	25	10	7-day	
SDS Reference Toxicant	<i>Menidia beryllina</i>	20	15	7-day	
	<i>Americamysis bahia</i>	20	20	7-day	
Material Tested	Saltwater Species	NOEC (ppm)		Duration	
		Survival	Growth		
Dispersant	<i>Menidia beryllina</i>	25	10	7-day	
	<i>Americamysis bahia</i>	25	10	7-day	
SDS Reference Toxicant	<i>Menidia beryllina</i>	15	10	7-day	
	<i>Americamysis bahia</i>	15	15	7-day	

TECHNICAL PRODUCT BULLETIN #2025-D-004
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: NOVEMBER 4, 2025
FINASOL OSR 52

DISPERSANT DATA SUBMISSION TECHNICAL BULLETIN FOR § 300.915 DATA AND INFORMATION REQUIREMENTS
PRODUCT NAME: FINASOL OSR 52 CATEGORY: DISPERSANT
GENERAL PRODUCT INFORMATION [§ 300.915(a)]
(1) NAME, ADDRESS, EMAIL, AND TELEPHONE NUMBER OF SUBMITTER [§ 300.915(a)(1)] TotalEnergies Petrochemicals & Refining USA, Inc. 1201 Louisiana Street, Suite 1800 Houston, TX 77002 – US Point of Contact: Nathan Williams Telephone: 713-483-5044 Email: nathan.williams@totalenergies.com
(2) SUBMITTER IDENTIFICATION [§ 300.915(a)(2)] Submitter identity and documentation of that identity, as the manufacturer of the product; vendor, importer, or distributor of the product; and/or designated agent acting on behalf of the manufacturer provided by the submitter on October 03, 2025.
(3) PRODUCT NAME, BRAND, OR TRADEMARK [§ 300.915(a)(3)] FINASOL OSR 52
(4) NAME, ADDRESS, EMAIL, AND TELEPHONE NUMBER OF SUPPLIERS [§ 300.915(a)(4)] TotalEnergies Petrochemicals & Refining USA, Inc. 1201 Louisiana Street, Suite 1800 Houston, TX 77002 – US Point of Contact: Juan Aguirre Telephone: 713-826-8434 Email: juan.aguirre@totalenergies.com
(5) SAFETY DATA SHEET (SDS) [§ 300.915(a)(5)] The Safety Data Sheet for the product provided by the submitter on October 03, 2025.
(6) PRODUCT STORAGE [§ 300.915(a)(6)] 1. <u>Maximum storage temperature (e.g., °F and/or °C):</u> 45°C (113 °F) 2. <u>Minimum storage temperature (e.g., °F and/or °C):</u> -5°C (23°F) 3. <u>Optimum storage temperature (e.g., °F and/or °C):</u> 5-35°C (41-95°F) 4. <u>Humidity (e.g., g/kg):</u> <ul style="list-style-type: none"> Maximum humidity: 90% Minimum humidity: 30% Optimal humidity: 70%

5. Other relevant conditions for product storage: Direct sunlight, high humidity, and saltwater can cause damage to containers; hence their exposure should be minimized as far as possible. It is therefore preferable to store dispersant indoors, i.e. inside warehouse facilities that provide adequate ventilation. If outdoors storage is unavoidable, adequate shelter/cover should be provided. Exposure to temperature extremes and fluctuations should also be avoided wherever feasible. In locations where high or low ambient temperatures are encountered, the use of climate-controlled facilities may be necessary.

6. Description of the consequences to performance if product is not stored within these limits: Phase separation and/or loss of efficiency may occur if the product is not stored within these limits.

(7) SHELF LIFE STORAGE CONDITIONS [§ 300.915(a)(7)]

The initial shelf life is 20 years when the containers remain capped and sealed to prevent contamination and evaporation of solvents and are stored as per advised storage conditions. After storage, stir the product and ensure homogeneity before use.

A study has been mandated to CEDRE laboratory on FINASOL OSR 52 samples aged from 7 to 25 years. It showed that the efficiency remained within the range required for marine dispersants in France.

Additionally, data from stockpile monitoring (using the LR448 method performed at a single laboratory using Medium Fuel Oil (MFO) cut with kerosine to a viscosity of 2,000 mPa s) of 75 different batches in five different countries (France, UK, Bahrain, Singapore, and South Africa) confirms that efficiency is retained on all batches after 10 years of storage, with an average efficiency measured on all tested samples at 90.9% and a yearly average of tested batches fluctuating by no more than 2% from this value.

Finally, a study from French laboratory CEDRE has been presented at Arctic and Marine Oilspill Program (AMOP) 1997. It is based on the quality controls carried out on French Navy dispersant stockpiles (including periodic control every 5 years after purchase) and concludes that FINASOL OSR 52 is stable and keeps its efficiency in the range of 0 to 6 years (no older samples of FINASOL OSR 52 were available at the time of this study).

Past this 20-year period, extended shelf life may be granted upon re-testing of the product efficiency (and toxicity if required). Guidance from IPIECA's support document Dispersant storage, maintenance, transport, and testing should be sought in re-testing process:

- Testing should be performed on samples representative of 10% of stock volume (e.g. 1 tote out of 10 for a same production batch).
- Sampling can be performed with the help of a sampling thief.
- Samples should be stored in compatible (glass or HDPE) and distinctly labelled bottles, with reference from the original container.
- Tests to be performed and pass criteria are the same as those required for product acceptance on NCP Product Schedule.

(8) PRODUCT LABEL [§ 300.915(a)(8)]

A sample product label for all name(s), brand(s), and/or trademark(s) under which the product is to be sold that includes manufacture and expiration dates, and conditions for storage was provided by the submitter on October 03, 2025.

(9) PRODUCT CATEGORY AND PROCESSES [§ 300.915(a)(9)]

Product listed as a dispersant.

A marine dispersant formulation is essentially a solution of different surfactants diluted in a blend of mineral (dearomatized kerosene cut), glycol and water acting as solvent, as can also be inferred from the product composition. As a consequence, its efficacy derives mostly from the properties of surfactant molecules.

On top of being a “thinner” for the (viscous) surfactants to allow for a good operability (pumpability/sprayability) of the dispersant, the solvent acts as “carrier” for the surfactants to soak into the oil slick as both the solvent and crude oil share similar (low) polarities and thus mutual solubility.

Once brought in contact with the oil slick, the amphiphilic surfactant molecules scatter at the oil/water interface, thus lowering the surface tension between oil and water. This reduces the energy needed to create additional surface between both phases, allowing for the wave movements to bring sufficient energy to create droplets of oil in water, stabilized by the surfactant (oil in water emulsion). This process can repeat iteratively, till the size distribution of the droplets makes them small enough (typically below 45 – 70 µm in diameter) to remain dispersed and diluted in the water column by the waves’ energy. Once dispersed, the repulsive interactions between droplets due to the surfactant layer at the water/oil interface prevents the coalescence of oil droplets leading to the re-creation of another oil slick. Ultimately, the combined action of marine currents and agitation will disperse and dilute the droplets into a larger volume of water.

(10) RECOMMENDED PRODUCT USE PROCEDURES [§ 300.915(a)(10)]

Marine dispersants are one tool among several others available to mitigate the consequences of an oil spill. The response to such situations is managed by relevant authorities under the supervision of an On Scene Coordinator and the decision to use (or not use) a marine dispersant in a given situation (depending on location, weather, spill conditions, etc.) depends on complex decision matrixes that exceed the responsibilities of dispersant suppliers may differ depending on local regulations, policies, and practices.

1. Application Method: FINASOL OSR 52 is applied effectively by aircraft or helicopter, from boats, or by subsea injection. Its viscosity has been chosen to be adapted to the usual dispensing systems (nozzles, ramps, nozzle canon, SSDI wand, etc.). FINASOL OSR 52 is intended to be used pure, however it can be prediluted in seawater down to a concentration of 10% if need be to reduce its viscosity in cold water conditions or to allow use on spraying systems designed for older dispersant chemistries with higher flow rates.

Spraying must not give too fine or atomized droplets as in fog. It must be done as moderately coarse droplets, with diameters in the range of 500 – 1,000 μm , whether application is by surface vessel or from the air.

2. Concentration / Application Rate: It is generally recommended to use marine dispersants, including FINASOL OSR 52, in particular with a 1:5 to 1:50 dispersant-to-oil ratio. A 1:20 ratio would correspond approximately to 15 gallons per ton of oil.

However, this recommendation may be adapted according to the nature of the oil, its state of weathering, temperature, thickness of the slick, and other circumstances of the spill, based on in- situ trials on a small scale.

3. Conditions for Use: When treating a spill with FINASOL OSR 52, it is recommended to start the treatment as early as possible, to avoid a thickening of the slick due to either evaporation of light fractions or formation of water-in-oil emulsion.

Apart from its direct influence on oil viscosities, which is treated separately in Application Restrictions (below), water temperature (and ice coverage if relevant) have not been identified as having a decisive influence on FINASOL OSR 52 efficiency, as can be observed in efficiency results at 5 °C and inferred from extrapolating from results obtained with FINASOL OSR 52 in a study conducted by Arctic Response Technology.

Use only receptacles, joints, pipes, etc. which are resistant to hydrocarbons. Do not spray at high pressure (> 3 bar).

Application Restrictions: It is generally considered for marine dispersants, including FINASOL OSR 52 in particular, that:

- Use should be restricted to pollutants with a viscosity not higher than 10,000 mm^2/s , preferably not higher than 5,000 mm^2/s (at sea temperature at the location of the spill). For pollutants whose viscosity is enclosed between 5,000 and 100,00 mm^2/s , result is uncertain, and testing is recommended before treating a spill.
- Sea conditions must allow sufficient energy for breaking the oil into droplets small enough to be dispersed. Oil spill dispersion is considered difficult if not impossible for sea conditions below Beaufort 3 level. Inversely, high winds and/or rough sea (Beaufort 7 or above level) will make dispersant application difficult if not impossible both by boat or aircraft (this is usually taken into account in the decision matrixes for dispersant use).
- FINASOL OSR 52 has been optimized to treat spills in salty water. Efficiency may be reduced in case of application in low salinity water (below 20 PSU).
- Although this may depend on local policies and On Scene Coordinator appreciation, it is usually

recommended to use marine dispersants at sea and not too close from the shore (or from fish/shell farms), and/or in too shallow waters.

Containment, Collection, Recovery, and Disposal: FINASOL OSR 52 is designed to be used as dispersant. As such, it is readily dispersed in sea water and aims at dispersing oil into small droplets and dilute it in sea water. As a consequence, there is no need to consider containment, collection, recovery, or disposal for FINASOL OSR 52 after use.

Disposal of unused (e.g. expired) product should, at all times, comply with the requirements of environmental protection, waste disposal legislation, and any regional local authority requirements. Disposal should be made via a licensed waste disposal contractor.

(11) ENVIRONMENTAL FATE OF COMPONENTS [§ 300.915(a)(11)]

The submitter provided available information on environmental fate, including any known measured data, methodologies, and supporting documentation, on the persistence, bioconcentration factor, bioaccumulation factor, and biodegradability of the product and all of its components in the environment on October 03, 2025.

(12) PHYSICAL/CHEMICAL PROPERTIES [§ 300.915(a)(12)]

Analysis	Result	Unit	Method
(i) Physical State and Appearance:	Light yellow liquid at ambient temperature	Visual	Liquid
(ii) Vapor Pressure	0.6	psi @100°F: <0.05 psi	ASTM D323
(iii) Flash Point	104 110 >95	°C	ASTM D92 ASTM D93A ASTM D56
(iv) Pour Point	-30	°C	ASTM D97
(v) Kinematic Viscosity	33.42 mm ² /s	@104°F	ASTM D445
(vi) Specific Gravity	1.0057	@60°F	ASTM D287
(vii) Particle Size for Solid Components	N/A	NA	N/A
(viii) pH	8.74		Probe

(13) IDENTIFICATION AND CONCENTRATION OF PRODUCT COMPONENTS [§ 300.915(a)(13)]

Under § 300.950, you may only claim as Proprietary Business Information (PBI) the concentration, the maximum, minimum, and average weight percent; and the units of each component of the total formulation as identified in § 300.915(a)(13) and (14) and as applicable. All other product information submitted to EPA as required under § 300.915 and § 300.955 will be available for public disclosure upon submission, without further notice to the submitter.

Chemical Name	CAS #	Concentration Percentage by Weight (PBI)	Intended Function
Sorbitan Monooleate (SMO)	1338-43-8	MAX/MIN/AVG% - PBI	Surfactant

Sorbitan Monooleate, ethoxylated (SMO-E)	9005-65-6	MAX/MIN/AVG% - PBI	Surfactant
Sorbitan Trioleate Ethoxylated (STO-E)	26266-58-0	MAX/MIN/AVG% - PBI	Surfactant
Sodium Dioctyl Sulfosuccinate	577-11-7	MAX/MIN/AVG% - PBI	Surfactant
Carboxylic acids, di, C6-12 compounds, with ethanolamine, Boric acid compound with ethanolamine	(EC 400-180-4)	MAX/MIN/AVG% - PBI	Solvent
2-aminoethanol	141-43-5	MAX/MIN/AVG% - PBI	Solvent
Dipropylene Glycol Methyl Ether	34590-94-8	MAX/MIN/AVG% - PBI	Solvent
Hydrotreated Light Aliphatic Hydrocarbons	64742-47-8	MAX/MIN/AVG% - PBI	Solvent
Demineralized Water	Not applicable	MAX/MIN/AVG% - PBI	Solvent
(14) MICROORGANISMS, ENZYMES AND/OR NUTRIENTS [§ 300.915(a)(14)]			
Finasol OSR 52 contains no microorganisms, enzymes, or nutrients.			
(15) DATA, METHODOLOGY AND SUPPORTING DOCUMENTATION FOR LEVELS OF THE FOLLOWING [§ 300.915(a)(15)]:			
Analyte	Result (mg/L)	Method	
Arsenic	0.0327	SW846 6020B – Metals (ICP/MS)	
Barium	<0.0134	SW846 6020B – Metals (ICP/MS)	
Cadmium	<0.0024	SW846 6020B – Metals (ICP/MS)	
Chromium	0.106	SW846 6020B – Metals (ICP/MS)	
Copper	<0.01	SW846 6020B – Metals (ICP/MS)	
Lead	<0.00367	SW846 6020B – Metals (ICP/MS)	
Mercury	<0.00353	SW846 7470A – Mercury (CVAA)	
Nickel	0.0695	SW846 6020B – Metals (ICP/MS)	
Selenium	0.0139	SW846 6020B – Metals (ICP/MS)	
Silver	<0.0039	SW846 6020B – Metals (ICP/MS)	
Vanadium	<0.0045	SW846 6020B – Metals (ICP/MS)	

Zinc	0.225	SW846 6020B – Metals (ICP/MS)	
Cyanide	0.263	EPA KELADA 01 Method	
Chlorinated Hydrocarbons [Exception: 1,4-Dichlorobenze]	< Method Detection Limit [1.14 µg/l]	SW846 8260C – Volatile Organic Compounds (GC/MS); SW846 8270E – Semivolatile Orangic Compounds (GC/MS)	
Pesticides	<Method Detection Limit	SW846 8081B – Organochlorine Pesticides (GC)	
Polychlorinated Biphenyls (PCBs)	<Method Detection Limit	SW846 8082A - Polychlorinated Biphenyls (PCBs) by Gas Chromatography	
Polycyclic Aromatic Hydrocarbons (PAHs) [Exception: Naphthalene]	<Method Detection Limit [31.7 ug/l]	SW846 8270E – Semivolatile Organic Compounds (GC/MS)	
(16) PROHIBITED AGENT CERTIFICATION [§ 300.915(a)(16)] Certification including data, methodology and supporting documentation indicating that product does not contain any prohibited agents identified in § 300.910(e) provided by the submitter on October 03, 2025.			
(17) LABORATORY INFORMATION [§ 300.915(a)(17)] Information about the accredited laboratory that conducted the required tests, including: (i)Name of the laboratory, address, contact, name, email, and phone number; and (ii) the national and/or international accreditations held by the laboratory that are applicable to test(s) performed were provided by the submitter on October 03,2025.			
(18) LABORATORY TEST DATA AND REPORTS [§ 300.915(a)(18)] All test data and calculations were provided by the submitter on October 03, 2025.			
(19) PRODUCTION VOLUMES [§ 300.915(a)(19)] This submission is intended to extend the listing of FINASOL OSR 52 on the NCP Product Schedule, in order to enable the continued use of existing stockpiles of FINASOL OSR 52 as an option in the eventuality of future oil spill responses. FINASOL OSR 52 is no longer manufactured nor commercialized.			
(20) DESIGN FOR THE ENVIRONMENT (now Safer Choice) [§ 300.915(a)(20)] Not provided.			
(21) INTERNATIONAL PRODUCT TESTING, DATA, AND/OR CERTIFICATIONS [§ 300.915(a)(21)] FINASOL OSR 52 is approved for use as a marine dispersant in France and UK.			
Test	Method	Result	Requirement

Efficiency (IFP “flow through” method)	NF T90-345	79 +/- 3%	>60%
Toxicity (on <i>Palaemonetes varians</i> shrimps)	NF T90-349	LC ₅₀ > 10,000 ppm (LC ₅₀ (NORAMIUM DA 50) = 44 ppm)	LC ₅₀ > 10x LC ₅₀ (NORAMIUM DA 50)
Biodegradability	NF T90-346	91.1% based on CO ₂ evaluation	> 50% after 28 days

PRODUCT CATEGORY TESTING AND LISTING REQUIREMENTS [§ 300.915(b)]

DISPERSANT EFFICACY TEST AND LISTING CRITERIA [§ 300.915(b)(1)]

Listing Criteria: Dispersant must demonstrate for each temperature a Dispersant Effectiveness (DE) at the 95% lower confidence level (LCL95) greater than or equal to:

- ≥70% for Strategic Petroleum Reserve Bryan Mound test oil at 5°C; and
- ≥75% for Strategic Petroleum Reserve Bryan Mound test oil at 25°C.

Test Oil	Dispersant Effectiveness Temperature at 5°C	Dispersant Effectiveness Temperature at 25°C
SPR Bryan Mound	80.6% DE _{LCL95}	90.5% DE _{LCL95}

DISPERSANT TOXICITY TESTS AND LISTING CRITERIA [§ 300.915(b)(2)]

Listing Criteria: Dispersant tested alone must demonstrate:

- For acute toxicity a median lethal concentration for 50% of the test species (LC₅₀) at the lower 95% confidence interval greater than 10 ppm.
- For developmental toxicity the inhibition concentration for 50% of the test species (IC₅₀) at the lower 95% confidence interval greater than 1 ppm; and
- For sub-chronic toxicity the No Observed Effect Concentration (NOEC) greater than 1 ppm.

Acute Toxicity Test Data Summary

Material Tested	Saltwater Species	LC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant Only	<i>Menidia beryllina</i>	50.44	45.34	56.11	96-hr
	<i>Americamysis bahia</i>	15.50	14.90	16.12	48-hr
Dispersant/Reference Oil Mixture	<i>Menidia beryllina</i>	10.28	9.00	11.74	96-hr
	<i>Americamysis bahia</i>	21.99	19.26	25.12	48-hr
SDS Reference Toxicant	<i>Menidia beryllina</i>	6.05	5.27	6.94	96-hr
	<i>Americamysis bahia</i>	12.08	11.76	12.41	48-hr

Developmental Test Data Summary

Material Tested	Sea Urchin Species	IC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Strongylocentrotus purpuratus</i>	7.20	6.91	7.47	72-hr
Copper Chloride Reference Toxicant	<i>Strongylocentrotus purpuratus</i>	11.08	10.84	11.27	72-hr

Subchronic Test Data Summary					
Material Tested	Saltwater Species	LC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Menidia beryllina</i>	49.15	41.31	58.47	7-day
	<i>Americamysis bahia</i>	16.82	14.61	19.38	7-day
Material Tested	Saltwater Species	IC50 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Menidia beryllina</i>	62.64	34.41	92.83	7-day
	<i>Americamysis bahia</i>	15.01	14.00	16.21	7-day
Material Tested	Saltwater Species	IC25 (ppm) with 95% Confidence Interval (CI)			Duration
		Median	Lower CI	Upper CI	
Dispersant	<i>Menidia beryllina</i>	31.33	24.72	49.50	7-day
	<i>Americamysis bahia</i>	11.22	9.81	12.08	7-day
Material Tested	Saltwater Species	LOEC (ppm)		Duration	
		Survival	Growth		
Dispersant	<i>Menidia beryllina</i>	35.20	35.20	7-day	
	<i>Americamysis bahia</i>	17.60	17.60	7-day	
SDS Reference Toxicant	<i>Menidia beryllina</i>	20.0	20.0	7-day	
	<i>Americamysis bahia</i>	20.0	15.0	7-day	
Material Tested	Saltwater Species	NOEC (ppm)		Duration	
		Survival	Growth		
Dispersant	<i>Menidia beryllina</i>	17.60	17.60	7-day	
	<i>Americamysis bahia</i>	8.80	8.80	7-day	
SDS Reference Toxicant	<i>Menidia beryllina</i>	15.00	15.00	7-day	
	<i>Americamysis bahia</i>	15.00	10.00	7-day	

MISCELLANEOUS OIL SPILL CONTROL AGENTS: **TECHNICAL NOTEBOOK BULLETINS**

(Products listed under the Miscellaneous Oil Spill Control Agents category are conditionally listed on the NCP Product Schedule until December 12, 2025. The Miscellaneous Oil Spill Control Agent category has been removed from Subpart J.)

TECHNICAL PRODUCT BULLETIN #M-12
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: AUGUST 31, 1992
REVISED LISTING DATE: SEPTEMBER 13, 1995
“PES-51”

I. NAME, BRAND, OR TRADEMARK

PES-51

Type of Product: Miscellaneous Oil Spill Control Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Practical Environmental Solutions (Formerly known as Petroleum Environmental Services)

P.O. Box 12563

San Antonio, Texas 78212

Phone: (210) 493-7172

Mobile Phone: (210) 875-4011

Fax: (210) 493-7172

E-mail: simsbi@aol.com

Website: www.pes51.com

(Mr. Bill Sims)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Practical Environmental Solutions (Formerly known as Petroleum Environmental Services)

P.O. Box 12563

San Antonio, Texas 78212

Phone: (210) 493-7172

Mobile Phone: (210) 875-4011

Fax: (210) 493-7172

E-mail: simsbi@aol.com

Website: www.pes51.com

(Mr. Bill Sims)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: 124°F

2. Ventilation: Handle product in a normal well ventilated place.

3. Skin and eye contact; protective clothing; treatment in case of contact: Although PES-51 is expected not to pose any specific health hazard, the following precautions are recommended due to possible irritation from the biological by-products contained in the product: Avoid contact with skin, eyes, and clothing. Avoid prolonged or repeated contact with skin, breathing mist, and do not take internally. Keep product away from heat, sparks, and flames, and store in a cool, dry, well ventilated place, away from incompatible materials. Vent container in warm weather to relieve pressure. Do not cut, grind, weld, or drill on or near product containers. Handle empty containers just as would the full ones.

- 4.a. Maximum storage temperature: NA.
- 4.b. Minimum storage temperature: NA
- 4.c. Optimum storage temperature range: NA
- 4.d. Temperatures of phase separations and chemical changes: Not applicable, but PES-51 freezes at -142°F.

V. SHELF LIFE

6 years (unopened drum), 1 year (opened drum).

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: The following PES-51 application methods are applicable for the full range of PES-51 industrial uses, including shoreline and surface treatment, tank cleaning and equipment decontamination. The selection of the method(s) will be dependent on the level and extent of hydrocarbon contamination, type of oil, and its degree of weathering/emulsion and the nature and type of surface to be treated or cleaned. Equipment availability, logistics and manpower requirements should also be considered. Application methods may be combined, if necessary. In addition, for shoreline cleaning, the treatment area will be boomed and contained prior to PES-51 usage. For equipment decontamination, the use of portable de-con pools or secondary containment liners are recommended.

PORTABLE EQUIPMENT

Hand Held Spraying - Spray PES-51 on the contaminated area using a Chapin Steel Sprayer #1729 (or equivalent), 2.5 gallons capacity, or the AU 8000 MicroNair sprayer. After application, allow 3 to 5 minutes for soaking without allowing evaporation of PES-51 (weather dependent). When saturation is attained, hydrocarbon will be seen running off the impacted surface. Rinse the treated surface with available water (fresh or sea water) from the pump until no hydrocarbon remains. The water should be used at ambient temperature. Depending on level and extent of contamination, a pressure washer may also be used for rinsing (ambient may be used). Collect the effluent hydrocarbons with absorbent booms and pads, and squeeze off the oil contaminants from the booms and pads for reuse as process oil.

Airless Sprayer - Depending on the level and extent of the hydrocarbon contamination and the nature of the impacted surface, an airless type sprayer may be used for direct product application. Common types of airless sprayers are: Airlessco, Graeco or equivalents. These airless sprayers can have single or multi-hose attachments and can include wand extensions as required.

Application rate and pressure will vary depending on the equipment type and site specific conditions. After spraying with PES-51, allow to soak for 3 to 5 minutes (weather dependent) avoiding evaporation, rinse/flush surfaces with pumps, fire hoses, deluge headers or pressure washers (ambient).

Pressure Washer with Syphon Feed System - Depending on the level and extent of the hydrocarbon contamination and the nature of the impacted surface proposed for treatment, a pressure washer may be used for direct product application. In most applications, hot water (greater than 120°F) is not necessary. Common types of pressure washers are: Hotsy and Lambda, or equivalents. These pressure washers have a variable rate "detergent syphon feed" system for PES-51 application and can have single or multi-hose attachments which can include wand extensions. Application rate and pressure will vary depending on equipment type and site specific conditions.

After spraying with PES-51, allow to soak for 3 to 5 minutes (weather dependent) avoiding evaporation, rinse/flush surfaces with pumps, fire hoses, deluge headers or pressure washers (ambient).

Air Knife (Modified for PES-51 Application) - PES has developed a patent-pending modified air knife system for product application. This method was developed primarily for rocky, cobble, bedrock type shorelines with both surface subsurface oil. The modified air knife delivers the PES-51 in both a liquid stream (125 psi) or as an aerosol. Compressed air is used to dilate subsurface sediments and allow for distribution of the PES-51. The air knife method is also applicable for surface treatment of impacted rocks, bulkheads, seawalls, rip-rap jetties, etc. After spraying with PES-51, allow to soak for 3 to 5 minutes (weather dependent) avoiding evaporation, rinse/flush surfaces with pumps, fire hoses, deluge headers or pressure washers (ambient). For subsurface treatment, continue flushing with large quantities of low-pressure seawater at ambient temperatures.

MOBILE EQUIPMENT

Boat Spraying – The recommended application rate is 1 to 5 gallons per 200 sq. ft., from a boat with speed of 1 to 3 knots, depending on the sea conditions and oil film thickness on the rocks. For a boat with a mounted AU-8110 MicroNair sprayer (or equivalent sprayer) and a spray swath of about 20 feet, traveling at approximately two knots, 25 acres/hr will be treated. After spraying, rinse PES-51 off the rocks with a hard, coarse spray of sea water. Standard size pumps with fire hoses or deluge headers may be used. Higher pressure rinses may be required if oil is thick and weathered. The shoreline may also be sprayed from the beach side, which will force the oil into the containment boom.

Helicopter Deployed Spraying – Aerial spraying can be utilized for shore treatments and pretreatment with the AU 5000 atomizer (MicroNair) or equivalent sprayer. The recommended aerial application of PES-51 is 14 to 23 liters/minute. The AU 5000 (or equivalent) can be used with fixed-wing aircraft and helicopters operating at speeds of 90 MPH (145 km/hr) and more. The smaller AU 7000 sprayer (or equivalent) is recommended for use at airspeeds below 90 MPH. After spraying, the hydrocarbons can be rinsed off the shore rocks as described above with hand held pumps, deluge headers or boat spraying.

Vehicular Spraying – The recommended vehicular spraying is 50 to 150 ft²/gallon depending on climatic conditions. A MicroNair vehicle-mounted sprayer is recommended. This unit is a self-

contained sprayer kit that combines the AU 8000 sprayhead (or equivalent) with a powerful 4-stroke engine and a 60 liter chemical tank to give complete product coverage. After spraying, the hydrocarbons can then be rinsed off the shore rocks as described above with hand held pumps, deluge headers or boat spraying.

2. Concentration/Application Rate: The product comes already mixed, and ready for use.

For specific application, see rate of application as indicated above.

3. Conditions for Use: Water temperature and salinity do not affect the product performance. PES-51 is effective against hydrocarbons only, and the age of the hydrocarbon is not relevant.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
PES-51	Menidia beryllina	137.00 96-hr
	Mysidopsis bahia	54.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	200.00 96-hr
	Mysidopsis bahia	11.50 48-hr
PES-51 & No. 2 Fuel Oil (1:10)	Menidia beryllina	435.00 96-hr
	Mysidopsis bahia	14.50 48-hr
Reference Toxicant (DSS)	Menidia beryllina	2.20 96-hr
	Mysidopsis bahia	9.80 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 124°F

2. Pour Point: -50°F at 30 min.

3. Viscosity: 30 cSt at 28°C

4. Specific Gravity: 0.840 at 25°C

5. pH: 6.7

6. Chemical Name and Percentage by Weight of the Total Formulation: CONFIDENTIAL

7. Surface Active Agents: CONFIDENTIAL

8. Solvents: CONFIDENTIAL

9. Additives: CONFIDENTIAL

10. Solubility: NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	< 0.005
Cadmium	< 0.01
Chromium	< 0.05
Copper	< 0.05
Lead	< 0.05
Mercury	< 0.005
Nickel	< 0.01
Zinc	< 0.05
Cyanide	< 1.00
Chlorinated Hydrocarbons	< 0.01

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**3/17/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #M-17
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: FEBRUARY 25, 1994
REVISED LISTING DATE: JUNE 14, 1995
“CIAGENT”

I. NAME, BRAND, OR TRADEMARK
CIAGENT

Type of Product: Miscellaneous Oil Spill Control Agent – Solidifier
(formerly CI AGENT, CHEAP INSURANCE, & PETRO-CAPTURE)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
CIAGENT Solutions, LLC

11760 Commonwealth Dr.
Louisville, KY 40299
Phone: updated information required
Fax: updated information required
E-mail: dan@ciagent.com
(Mr. Dan Parker)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
CIAGENT Solutions, LLC

11760 Commonwealth Dr.
Louisville, KY 40299
Phone: updated information required
Fax: updated information required
E-mail: dan@ciagent.com
(Mr. Dan Parker)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Flammable solid at >210°F.
2. Ventilation: Normal ventilation is adequate.
3. Skin and eye contact; protective clothing; treatment in case of contact: Product may cause slight eye irritation if in contact with eyes. Use protective eye goggles when handling the product. In case of eye contact, flush eyes with water. In an enclosed environment, workers should wear a dust mask for personal comfort. In case of a confined space fire, do not enter without full bunker gear and positive pressure NIOSH approved self-contained breathing apparatus. Maintain fire watch at 450°F.
- 4.a. Maximum storage temperature: 190°F
- 4.b. Minimum storage temperature: None
- 4.c. Optimum storage temperature range: 50°F - 80°F

4.d. Temperatures of phase separations and chemical changes: None. Avoid contact with strong oxidizing agents due to possible oxidation reaction with the product.

V. SHELF LIFE

> 5 years, if stored in cool dry area, away from direct sunlight.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: For small scale spills on water (salt or fresh), CIAGENT can be broadcast directly onto the spill, spreading a thin layer from the outer edge into the middle of the spill. Agitation is not necessary. The product is also available in oil absorbent, water repellent booms and pillows. For large spills on water (fresh or salt), CIAGENT may be deployed with an air or water stream directed at the leading edge of the spill. Because of its fine particulate nature, static buildup may occur if the product is applied in dry form at a high rate of delivery.

Dispensing material should be properly grounded to prevent this. The product is relatively non-abrasive and should not harm machinery or pumping systems. Agitation is not necessary.

The polymer has a specific gravity of less than one and will tend to separate and move to the surface when mixed with water. Therefore, in the case of water carrying media, the product should be introduced "just in time" as the media is sprayed, or agitation will be needed to keep the product suspended. The product will remove oils and other hazardous hydrocarbon based materials from fresh or salt water. CIAGENT may be used in a flow-through filter to remediate contaminated water. CIAGENT encapsulates and solidifies the oil, while continuing to float even after saturation. The solidified oil or hazardous material may be removed from water using a vacuum pump or fish net. The material should be put into appropriate containers and disposed of in accordance with federal, state and local regulations. For spills on land, the product would be applied in the same manner as in the water-based spill situation. Agitation is not necessary. To recover solidified oil or hazardous materials from spills on land, the spent material may be collected and swept up using an industrial vacuum cleaner, broom, or shovel. The material should be put into appropriate containers and disposed of in accordance with federal, state and local regulations.

2. Concentration/Application Rate: In general, a 10% to 30% by weight application is required to solidify light, medium, and heavy oils. Solidification may occur faster if additional CIAGENT is applied.

3. Conditions for Use: CIAGENT is equally effective in fresh or salt water, and under any weather conditions; however, colder temperatures may slow the solidification process. The product is most effective on water temperatures between 32°F and 120°F. Depending on the age and/or viscosity of the material, varying amounts of CIAGENT may be required to obtain complete solidification. The recovered solidified oil or hazardous materials may be landfilled, incinerated, used as a secondary fuel, or otherwise disposed of according to federal, state and local regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
CIAGENT	Menidia beryllina	2227.00 96-hr
	Mysidopsis bahia	2617.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	4.36 96-hr
	Mysidopsis bahia	1.45 48-hr
CIAGENT &	Menidia beryllina	5.93 96-hr
No. 2 Fuel (1:10)	Mysidopsis bahia	1.73 48-hr
Reference Toxicant (DSS)	Menidia beryllina	3.68 96-hr
	Mysidopsis bahia	6.82 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

NA

IX. PHYSICAL PROPERTIES AND COMPONENTS

1. Flash Point: No flash observed at 210°F.
2. Pour Point: Not applicable; solid samples
3. Viscosity: Not applicable; solid samples
4. Specific Gravity: 0.94 g/cm³
5. pH: 7.81
6. Chemical Name and Percentage by Weight of the Total Formulation: CONFIDENTIAL
7. Surface Active Agents: None
8. Solvents: None
9. Additives: None
10. Solubility: Negligible

X. ANALYSIS FOR HEAVY METALS AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<1.0
Cadmium	<2.5
Chromium	<2.0
Copper	<2.5
Lead	<5.0
Mercury	<0.050
Nickel	<5.0
Zinc	<2.5
Cyanide	<0.50
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #M-18
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: MARCH 29, 1994
REVISED LISTING DATE: MARCH 12, 1997
“ZYME-FLOW”
(aka, ZYME-TREAT, MARI-ZYME, UNITED 658 PETRO-ZYME)

I. NAME, BRAND, OR TRADEMARK
ZYME-FLOW

(aka, ZYME-TREAT, MARI-ZYME, UNITED 658 PETRO-ZYME) Type of Product:
Miscellaneous Oil Spill Control Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

United Laboratories, Inc.
320 37th Avenue
St. Charles, IL 60174
Phone: (630) 377-0900 x7408 or (800) 323-2594
Fax: (630) 377-0960
E-mail: nsherrel@unitedlabsinc.com
(Ms. Nancy Sherrel)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

United Laboratories, Inc.
320 37th Avenue
St. Charles, IL 60174
Phone: (630) 377-0900 x7408 or (800) 323-2594
Fax: (630) 377-0960
E-mail: nsherrel@unitedlabsinc.com
(Ms. Nancy Sherrel)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable
2. Ventilation: No mechanical ventilation required
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid eye contact due to possible mild eye irritation. In case of eye contact, flush eyes with water. Protective clothing is normally not required.
- 4.a. Maximum storage temperature: 120°F
- 4.b. Minimum storage temperature: 0°F
- 4.c. Optimum storage temperature range: 0°F - 120°F
- 4.d. Temperatures of phase separations and chemical changes: > 3 freeze-thaw cycles.

V. SHELF LIFE

1 year minimum.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: United's ZYME-FLOW is a chemically designed product that will make heavy crudes more pumpable, and break the adhesion between oils and soil, rock or sand. ZYME-FLOW can be applied where the contaminated soil or sand is temporarily removed and placed into a device that can provide mechanical agitation (e.g., a cement mixer or a fractionating tank). Unagitated tanks may also be used, but more time will be required to achieve the goal.

Add ZYME-FLOW solution to the tank. As agitation continues, oils with a specific gravity of less than one will float, while oils with a specific gravity of greater than one will settle. The floating or settled oil can then be removed from the soil or sand. As ZYME-FLOW will not emulsify oils, the recovered oils are almost anhydrous, and the water can be collected and reused. Another method is to physically isolate a small area that is to be cleaned with damming collars, sand bags or other means on the sides and a none permeable layer on the bottom (if possible). Then wash the contaminated area with ZYME-FLOW solution using a pressurized water stream. Keep the area super-saturated with water for several hours to allow oil residues to float to the surface for collection.

ZYME-FLOW can be used to wash the inside or outside of a ship or barge that has been contaminated with oil, using a high pressure sprayer. Bilges of a ship, or barge can also be cleaned using a 1% ZYME-FLOW solution, and allowing the natural movement of the ship to provide the agitation.

2. Concentration/Application Rate: The exact dilution of ZYME-FLOW will vary between 50:1 and 200:1 depending on temperature, viscosity and type of petroleum product.

3. Conditions for Use: ZYME-FLOW is effective in all non-frozen waters with greater efficacy as the temperature increases. The product efficiency is not affected by salinity, but it will be affected by tar sand.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
ZYME-FLOW	Menidia beryllina	35.00 96-hr
	Mysidopsis bahia	26.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	6.90 96-hr
	Mysidopsis bahia	3.70 48-hr
ZYME-FLOW & No. 2 Fuel Oil (1:10)	Menidia beryllina	8.70 96-hr
	Mysidopsis bahia	1.60 48-hr
Reference Toxicant (SDS)	Menidia beryllina	7.07 96-hr
	Mysidopsis Bahia	18.60 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: None
2. Pour Point: 32°F
3. Viscosity: <10 cps
4. Specific Gravity: 0.99
5. pH: 7.0 - 8.0
6. Chemical Name and Percentage by Weight of the Total Formulation: CONFIDENTIAL
7. Surface Active Agents: CONFIDENTIAL
8. Solvents: NA
9. Additives: CONFIDENTIAL
10. Solubility: Soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.005
Cadmium	0.002
Chromium	0.002
Copper	0.020
Lead	0.007
Mercury	0.0004
Nickel	0.070
Zinc	0.040
Cyanide	0.300
Chlorinated Hydrocarbons	<1.00

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**11/03/2008
7/27/2022**

TECHNICAL PRODUCT BULLETIN #M-19
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: APRIL 22, 1996
“WASTE-SET #3200®”

I. NAME, BRAND, OR TRADEMARK
WASTE-SET #3200®

Type of Product: Miscellaneous Oil Spill Control Agent – Oil Spill Solidifying Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Environmental & Fire Technology, LLC
Address: updated information required
Phone: updated information required
(Mr. Cal Blystra)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Environmental & Fire Technology, LLC
Address: updated information required
Phone: updated information required
(Mr. Cal Blystra)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Product will not burn unless preheated. Avoid elevated temperatures (>200°F) for extended periods (>5 days).

Product has a tendency to accumulate a static charge during transport, which is a potential fire hazard if used near flammables.

2. Ventilation: Avoid generating dust clouds.

3. Skin and eye contact; protective clothing; treatment in case of contact: May cause mild mechanical irritation to eyes, skin and respiratory tract. Dust may cause coughing and watery eyes. Pre-existing eye, skin and respiratory disorders may be aggravated by this product. Wear NIOSH-approved respirator to prevent overexposure. Refer to transitional occupational exposure limits established by OSHA in 29CFR 1910.1000. Flush eyes with water; wash skin with soap and water; if molten, treat as for burns. Remove person(s) to fresh air if excessive amounts of dust have been inhaled. Protective gloves and safety glasses should be worn. If material is released or spilled, sweep up or vacuum and place in an approved container.

4.a. Maximum storage temperature: 200°F

4.b. Minimum storage temperature: None

4.c. Optimum storage temperature range: <200°F

4.d. Temperatures of phase separations and chemical changes: >450°F

V. SHELF LIFE

Unlimited.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method:

Spills on Water - For spills on water, surround the spill with WASTE-SET® 3200 to prevent migration. Reinforce containment line with a boom or sweep if necessary. WASTE-SET® and the resulting reacted material will float.

If the interior of the diked spill is not to be reclaimed, fill in the remaining surface area of the spill by broadcasting additional WASTE-SET® 3200 evenly over the spill until the WASTE-SET® no longer reacts with the spill. Alternatively, the product may be introduced under the surface of the spill to rise and react with oils in the suspension layer.

WASTE-SET® can then be swept or netted from the surface of the water.

Spills on Hard Surfaces - For spills on hard surfaces, apply WASTE-SET 3200® heavily to perimeter of spill to prevent migration. After surrounding the spill, reinforcement of the containment line thus formed with a boom or sweep may be advisable depending on the volume and flow rate.

If the interior of the diked spill is not to be reclaimed, fill in the remaining surface of the spilled material by evenly distributing additional WASTE-SET 3200® until the WASTE-SET® no longer reacts with the spill and remains white and on the surface.

Disposal - Dispose of reacted material in accordance with local, state, and federal regulation. Under the EPA Toxicity Characteristic Leaching Procedures (TCLP), WASTE-SET encapsulated material may be eligible for disposal in landfills. Incineration results in extremely low ash content. Dependent upon the nature of the encapsulated material, it may also be disposed of by incorporation into synthetic surfaces such as asphalt.

WASTE-SET® will effectively "encapsulate" crude oil and petroleum-based products, such as gasoline, kerosene, and diesel fuel; in addition to the various following liquid and vapor-phase contaminants:

Aliphatic hydrocarbons	Esters
Aromatic hydrocarbons	Ethers
Chlorinated hydrocarbons	Ketones
Alcohols	Other hydrocarbons

2. Concentration/Application Rate: One pound WASTE-SET® per five pounds of oil (May vary with viscosity and temperature).

3. Conditions for Use: No limitations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
WASTE-SET 3200®	Menidia beryllina	>10000.0 96-hr

	Mysidopsis bahia	5431.0 48-hr
No. 2 Fuel Oil	Menidia beryllina	274.0 96-hr
	Mysidopsis bahia	29.0 48-hr
WASTE-SET 3200® &	Menidia beryllina	552.0 96-hr
No. 2 Fuel Oil	Mysidopsis bahia	58.0 48-hr
Reference Toxicant (SDS)	Menidia beryllina	1.8 96-hr
	Mysidopsis bahia	4.9 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: No flash observed at 310°F
2. Pour Point: NA
3. Viscosity: NA
4. Specific Gravity: 0.94
5. pH: NA
6. Chemical Name and Percentage by Weight of the Total Formulation: CONFIDENTIAL
7. Surface Active Agents: NA
8. Solvents: None
9. Additives: None
10. Solubility: Insoluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND
Cadmium	ND
Chromium	0.44
Copper	0.98
Lead	0.08
Mercury	ND
Nickel	0.38
Zinc	3.1
Cyanide	ND
Chlorinated Hydrocarbons	ND

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**11/03/2008
7/27/2022**

TECHNICAL PRODUCT BULLETIN #M-20
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: APRIL 22, 1996
“WASTE-SET #3400®”

I. NAME, BRAND, OR TRADEMARK
WASTE-SET #3400®

Type of Product: Miscellaneous Oil Spill Control Agent – Oil Spill Solidifying Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Environmental & Fire Technology, LLC
Address: updated information required
Phone: updated information required
(Mr. Cal Blystra)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Environmental & Fire Technology, LLC
Address: updated information required
Phone: updated information required
(Mr. Cal Blystra)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Product will not burn unless preheated. Avoid elevated temperatures (>200°F) for extended periods (>5 days). Product has a tendency to accumulate a static charge during transport, which is a potential fire hazard if used near flammables.
2. Ventilation: Avoid generating dust clouds.
3. Skin and eye contact; protective clothing; treatment in case of contact: May cause mild mechanical irritation to eyes, skin and respiratory tract. Dust may cause coughing and watery eyes. Pre-existing eye, skin and respiratory disorders may be aggravated by this product. Wear NIOSH-approved respirator to prevent overexposure. Refer to transitional occupational exposure limits established by OSHA in 29CFR 1910.1000. Flush eyes with water; wash skin with soap and water; if molten, treat as for burns. Remove person(s) to fresh air if excessive amounts of dust have been inhaled. Protective gloves and safety glasses should be worn. If material is released or spilled, sweep up or vacuum and place in an approved container.
- 4.a. Maximum storage temperature: 200°F
- 4.b. Minimum storage temperature: None
- 4.c. Optimum storage temperature range: <200°F
- 4.d. Temperatures of phase separations and chemical changes: >450°F

V. SHELF LIFE

Unlimited.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method:

Spills on Water – For spills on water, surround the spill with WASTE-SET® 3400 to prevent migration. Reinforce containment line with a boom or sweep if necessary. WASTE-SET® and the resulting reacted material will float. If the interior of the diked spill is not to be reclaimed, fill in the remaining surface area of the spill by broadcasting additional WASTE-SET 3400® evenly over the spill until the WASTE-SET® no longer reacts with the spill. Alternatively, the product may be introduced under the surface of the spill to rise and react with oils in the suspension layer. WASTE-SET® can then be swept or netted from the surface of the water.

Spills on Hard Surfaces – For spills on hard surfaces, apply WASTE-SET® 3400 heavily to perimeter of spill to prevent migration. After surrounding the spill, reinforcement of the containment line thus formed with a boom or sweep may be advisable depending on the volume and flow rate. If the interior of the diked spill is not to be reclaimed, fill in the remaining surface of the spilled material by evenly distributing additional WASTE-SET® 3400 until the WASTE-SET® no longer reacts with the spill and remains white and on the surface.

Disposal – Dispose of reacted material in accordance with local, state, and federal regulation. Under the EPA Toxicity Characteristic Leaching Procedures (TCLP), WASTE-SET® encapsulated material may be eligible for disposal in landfills. Incineration results in extremely low ash content. Dependent upon the nature of the encapsulated material, it may also be disposed of by incorporation into synthetic surfaces such as asphalt.

WASTE-SET® will effectively "encapsulate" crude oil and petroleum-based products, such as gasoline, kerosene, and diesel fuel; in addition to the various following liquid and vapor-phase contaminants:

Aliphatic hydrocarbons	Esters
Aromatic hydrocarbons	Ethers
Chlorinated hydrocarbons	Ketones
Alcohols	Other hydrocarbons

2. Concentration/Application Rate: One pound WASTE-SET® per five pounds of oil (May vary with viscosity and temperature).

3. Conditions for Use: No limitations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
WASTE-SET 3400®	Menidia beryllina	>10000.0 96-hr
	Mysidopsis bahia	>10000.0 48-hr
No. 2 Fuel Oil	Menidia beryllina	274.0 96-hr
	Mysidopsis bahia	29.0 48-hr

WASTE-SET 3400® &	Menidia beryllina	442.0 96-hr
No. 2 Fuel Oil	Mysidopsis bahia	36.0 48-hr
Reference Toxicant (SDS)	Menidia beryllina	1.8 96-hr
	Mysidopsis bahia	4.9 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: No flash observed at 350°F
2. Pour Point: NA
3. Viscosity: NA
4. Specific Gravity: 0.91
5. pH: NA
6. Chemical Name and Percentage by Weight of the Total Formulation: CONFIDENTIAL
7. Surface Active Agents: NA
8. Solvents: None
9. Additives: None
10. Solubility: Insoluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND
Cadmium	ND
Chromium	0.41
Copper	0.97
Lead	0.08
Mercury	ND
Nickel	3.3
Zinc	4.0
Cyanide	ND
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #M-22
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: FEBRUARY 27, 1998
REVISED LISTING DATE: OCTOBER 5, 1998
“PX-700®”

I. NAME, BRAND, OR TRADEMARK
PX-700®

Type of Product: Miscellaneous Oil Spill Control Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Enviro-Tech
715 NE 19th Place #22
Cape Coral, FL 33909
Phone: (239) 673-8280
Fax: (239) 424-8408
E-mail: info@px700.com
Website: www.px700.com
(Mr. Charlie Jones)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Enviro-Tech
715 NE 19th Place #22
Cape Coral, FL 33909
Phone: (239) 673-8280
Fax: (239) 424-8408
E-mail: info@px700.com
Website: www.px700.com
(Mr. Charlie Jones)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Not flammable; no special precautions necessary.
2. Ventilation: None required; no vapor emissions at normal temperatures, summer and winter.
3. Skin and eye contact; protective clothing; treatment in case of contact: Product contains a surfactant; avoid prolonged skin contact. Mild eye irritant; in case of eye contact, flush with copious amounts of water. No protective clothing required. Contact treatment is to flush with water. Product is acidic (pH 3.5-4.0). Eye protection is recommended as a precaution against splashing.
- 4.a. Maximum storage temperature: 120°F
- 4.b. Minimum storage temperature: 30°F
- 4.c. Optimum storage temperature range: 65°F - 85°F
- 4.d. Temperatures of phase separations and chemical changes: Separation may occur after 3 months. Separation will not affect product performance.

V. SHELF LIFE

Two years.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: To remove oily sheen from areas surrounding an oil spill, spray undiluted PX-700® directly over area at an application rate of one gallon for every 900 to 1200 square feet of surface area. Dilute PX-700® 25:1 for cleaning equipment and other surfaces. Either spray or immerse equipment, as applicable. Dilute PX-700® 50:1 for immersing wildlife to remove oil.

2. Concentration/Application Rate: At normal temperatures product is free flowing and applied full strength to remove oily sheen from aquatic environments, soils, and wastewater.

3. Conditions for Use: Water salinity, water temperature, types and ages of pollutants. Do not allow product to freeze, as separation may occur. Product may work more slowly at low temperatures. At full strength or diluted with fresh water, product will have a specific gravity lower than sea water and should float. Use of PX-700® should aid skimming and other conventional oil recovery operations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
PX-700®	Menidia beryllina	380.00 96-hr
	Mysidopsis bahia	297.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	7.07 96-hr
	Mysidopsis bahia	1.89 48-hr
PX-700®	Menidia beryllina	5.65 96-hr
	Mysidopsis bahia	2.77 48-hr
& No. 2 Fuel Oil (1:10)	Menidia beryllina	6.16 96-hr
	Mysidopsis bahia	23.00 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: Not flammable

2. Pour Point: 30°F

3. Viscosity: Equivalent to water

4. Specific Gravity: 1.0

5. pH: 3.5 to 4.0 standard units

6. Chemical Name and Percentage by Weight of the Total Formulation: CONFIDENTIAL

7. Surface Active Agents: Less than 5% Cocamide
8. Solvents: None
9. Additives: Citric acid for pH control
10. Solubility: 100% soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.47
Cadmium	ND
Chromium	ND
Copper	0.14
Lead	ND
Mercury	ND
Nickel	ND
Zinc	0.77
Cyanide	ND
Chlorinated Hydrocarbons	CONFIDENTIAL

TECHNICAL PRODUCT BULLETIN #M-23
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: NOVEMBER 23, 1998
“ALSOCUP”

I. NAME, BRAND, OR TRADEMARK

ALSOCUP

Type of Product: Miscellaneous Oil Spill Control Agent – Solidifier

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

REVCOM Associates

1550 Rimpau Avenue #53

Corona, CA 92881

Phone: (951) 737-0104

E-mail: revcom@sbcglobal.net

(Mr. Dave Naylor, President)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

REVCOM Associates

1550 Rimpau Avenue #53

Corona, CA 92881

Phone: (951) 737-0104

E-mail: revcom@sbcglobal.net

(Mr. Dave Naylor, President)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: NA

2. Ventilation: NA

3. Skin and eye contact; protective clothing; treatment in case of contact: ALSOCUP is practically non-irritating to the eyes and is non-irritating to the skin. Safety glasses and protective clothing should be worn when applying the material. The product is not expected to cause irritation to the nose, throat, or respiratory tract.

4.a. Maximum storage temperature: 163°F

4.b. Minimum storage temperature: 0°F

4.c. Optimum storage temperature range: 0°F to 163°F

4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

ALSOCUP has a shelf life of five years.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: ALSOCUP is used to collect petroleum-based products spilled on water or land. When ALSOCUP comes into contact with a petroleum product it chemically bonds and traps the petroleum. Once captured, spilled product cannot be released from ALSOCUP. ALSOCUP does not absorb water and will not sink. The product can be collected by skimming with pumps or mechanical devices.
2. Concentration/Application Rate: ALSOCUP is used by applying one pound of product to each 10 pounds of spilled petroleum products.
3. Conditions for Use: Water temperature does not appear to affect the ability of ALSOCUP to collect petroleum products. Heavy seas may prevent containment of an oil spill, and the product would lose efficiency if the oil product dispersed. Booms and dams that contain the petroleum product into an area are most effective when using ALSOCUP. In water the motion of the sea will mix the product with oil. On land a mechanical means is necessary to combine the oil with ALSOCUP. ALSOCUP will collect petroleum products at any stage; however, it is most effective early in the spill before dispersion.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

ALSOCUP is a non-toxic substance. The product is generally considered to have a low order of acute oral toxicity.

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
ALSOCUP	Menidia beryllina	>100	96-hr
	Mysidopsis bahia	>100	48-hr
No. 2 Fuel Oil	Menidia beryllina	8.1	96-hr
	Mysidopsis bahia	3.9	48-hr
ALSOCUP & No. 2 Fuel Oil (1:10)	Menidia beryllina	14.0	96-hr
	Mysidopsis bahia	10.0	48-hr
Reference Toxicant (DSS)	Menidia beryllina	NA	
	Mysidopsis bahia	NA	

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: NA
2. Pour Point: NA
3. Viscosity: NA
4. Specific Gravity: NA
5. pH: NA
6. Surface Active Agents: NA
7. Solvents: NA
8. Additives: NA
9. Solubility in Water: NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.0211
Cadmium	0.090
Chromium	0.456
Copper	0.445
Lead	0.454
Mercury	0.00492
Nickel	0.474
Zinc	0.433
Cyanide	ND
Chlorinated Hydrocarbons	NA

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**5/18/2006
7/27/2022**

TECHNICAL PRODUCT BULLETIN #M-24
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JANUARY 26, 2001
“RAPIDGRAB 2000™”

**I. NAME, BRAND, OR TRADEMARK
RAPIDGRAB 2000™**

Type of Product: Miscellaneous Oil Spill Control Agent – Solidifier

**II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
GlobeMark Resources Ltd.**

1312 Mill Creek Drive
Salado, TX 76517
Mobile: (254) 231-2251
E-mail: fiddler656@gmail.com
Website: www.globemarkresources.com
(Ms. Joannie Docter)

**III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
GlobeMark Resources Ltd.**

1312 Mill Creek Drive
Salado, TX 76517
Mobile: (254) 231-2251
E-mail: fiddler656@gmail.com
Website: www.globemarkresources.com
(Ms. Joannie Docter)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: IMO - Non-flammable; DOT - Non-hazardous
2. Ventilation: Use with ventilation equal to unobstructed outdoors in a moderate breeze.
3. Skin and eye contact; protective covering; treatment in case of contact: Avoid skin and clothing contact. If skin contact occurs, immediately wash with large amounts of water and soap (if possible). Remove any contaminated clothing or shoes. Launder before reusing. If irritation persists, seek medical assistance. For areas where contact is likely, wear long sleeve shirt, chemical resistant gloves, and chemical resistant goggles.
- 4.a. Maximum storage temperature: 120°F
- 4.b. Minimum storage temperature: 0°F
- 4.c. Optimum storage temperature range: 32°F to 90°F
- 4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

The shelf life of unopened drums of RAPIDGRAB 2000™ is unlimited. Containers should be capped when not being used to prevent contamination and evaporation.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: RAPIDGRAB 2000™ is a non-ionic liquid formulation that may be effectively applied by mist spraying onto floating oil slicks and sheens that are often found in harbors and at sea as the result of oil leakage and spills from ships. It instantly reduces and confines floating oils by the oleophitic synergistic effect of contraction and congealment into a physical state that greatly simplifies cleanup operations. Oil slicks and sheens may be reduced by up to 1,000 percent or more. The broad temperature range for RAPIDGRAB 2000™ sprays are from 32°F to 120°F.

Aerial Spraying - Typical application altitudes of 30 to 50 feet are advised although higher altitudes may be used if condition warrant. Spray nozzle should be about ¼ inches in diameter at 104 knots or more to create enough air shear sufficient to break the RAPIDGRAB 2000™ into proper sized droplets. A ½-inch diameter nozzle may be needed for temperatures below 50°F.

Boat Spraying - Mist sprays may be applied from shipboard by power “foggers.”

2. Concentration/Application Rate: RAPIDGRAB 2000™ should be mist sprayed full strength on surface oil until sufficient herding results are achieved. Results will vary depending on oil type, temperature, wave action, and viscosity.

3. Conditions for Use: RAPIDGRAB 2000™ is designed to be used after oil has been contained by booms or other similar apparatus. Timely treatment with RAPIDGRAB 2000™, even at low application rates, can help to contain the sheen/spreading effect of the oil slick.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
RAPIDGRAB 2000™	Menidia beryllina	5.13 96-hr
	Mysidopsis bahia	2.29 48-hr
No. 2 Fuel Oil	Menidia beryllina	9.34 96-hr
	Mysidopsis bahia	3.12 48-hr
RAPIDGRAB 2000™ & No. 2 Fuel Oil (1:10)	Menidia beryllina	4.07 96-hr
	Mysidopsis bahia	2.60 48-hr
Reference Toxicant (SRTT)	Menidia beryllina	2.97 96-hr
	Mysidopsis bahia	6.71 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 110°C
2. Pour Point: 30°F
3. Viscosity: 20.2
4. Specific Gravity: 0.84
5. pH: 6.95
6. Surface Active Agents: Oleophilic surfactant
7. Solvents: Proprietary formulation oleophilic surfactants
8. Additives: None
9. Solubility in Water: Miscible in oil and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND
Cadmium	ND
Chromium	ND
Copper	ND
Lead	ND
Mercury	<0.1
Nickel	ND
Zinc	ND
Cyanide	2.8
Chlorinated Hydrocarbons	ND

LISTING CHANGES PENDING;
VERIFICATION BY MANUFACTURER AND EPA REQUIRED

TECHNICAL PRODUCT BULLETIN #M-25
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: NOVEMBER 9, 2006
“OIL SOLUTIONS POWDER”
(aka, AQUA N-CAP™ POLYMER)

I. NAME, BRAND, OR TRADEMARK
OIL SOLUTIONS POWDER
(aka, AQUA N-CAP™ POLYMER)
Type of Product: Miscellaneous Oil Spill Control Agent – Solidifier

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Oil Solutions International
35 Mill Street
Amityville, NY 11701
Phone: (631) 608-8889
Fax: (631) 789-1676
E-mail: 4oilgreen@gmail.com
Website: www.cleaningupoil.com
(Mr. Dennis J. Traina, President)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Oil Solutions International
35 Mill Street
Amityville, NY 11701
Phone: (631) 608-8889
Fax: (631) 789-1676
E-mail: 4oilgreen@gmail.com
Website: www.cleaningupoil.com
(Mr. Dennis J. Traina, President)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable
2. Ventilation: Work in a well-ventilated area. Avoid excessive inhalation of dust.
3. Skin and eye contact; protective covering; treatment in case of contact: Skin contact – No recommendation is made specifying the need for personal protective clothing to prevent skin contact. Person(s) should wash daily at the end of each work shift. Exposed areas should be thoroughly washed with water. Eye contact – Product may cause irritation as any normal dust. Wear appropriate eye protection, compliant with ANSI Standard Z87.1, to prevent eye contact. If eye irritation or redness is experienced, promptly wash eyes with large amounts of water, for at least 15 minutes, occasionally lifting the lower and upper lids. Should eye irritation persist, seek

medical attention immediately. Contact lenses should not be worn when working with this product. Inhalation – Wear appropriate respiratory protection, compliant with OSHA standard 29 CFR 1910.134, to prevent inhalation. If a respiratory disorder is observed, remove person(s) from the work area immediately. Should respiratory disorder persist, seek medical attention immediately. Ingestion – Rinse mouth with water and seek medical attention immediately.

4.a. Maximum storage temperature: 185°F

4.b. Minimum storage temperature: NA

4.c. Optimum storage temperature range: 185°F

4.d. Temperatures of phase separations and chemical changes: None. Polymer may accumulate static charge during transport, handling, and processing. Static charge can be a potential fire hazard in the presence of volatile or flammable materials or in high airborne dust conditions.

V. SHELF LIFE

Not limited.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Apply OIL SOLUTIONS POWDER along the outer edges of spill area to prevent spill migration. Proceed by applying product onto remaining spill area, until a light white excess of product is observed. OIL SOLUTIONS POWDER may be broadcast onto the spill by hand or with a mechanical blower. Lighter hydrocarbons and synthetic oils will clump into a soft cluster like material easily recoverable with a net or other means as appropriate.

2. Concentration/Application Rate: Apply OIL SOLUTIONS POWDER at a rate of 0.5 to 2 lbs per gallon of spilled hydrocarbon. Depending on the type of hydrocarbon and recovery operations employed, more or less product may be used to achieve recoverable solid mat/residue. Allow approximately 30 – 60 minutes of contact time, product will form an elastic or rubber-like mat material. Mat like material may be removed whole or segmented as appropriate.

3. Conditions for Use: OIL SOLUTIONS POWDER differs from traditional sorbents in that it initially behaves like a synthetic sorbent, then as a solidifier as the molecular microencapsulating process occurs. Once encapsulated, the spilled oil is captured within the polymer matrix. OIL SOLUTIONS POWDER is designed to cleanup a wide variety of crude oil, refined hydrocarbon products (i.e., fuels, oils, hydraulic fluids), and synthetic fluids spilled on water and surfaces.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
OIL SOLUTIONS POWDER	Menidia beryllina	484,000 96-hr
	Mysidopsis bahia	104,000 48-hr
No. 2 Fuel Oil	Menidia beryllina	15.80 96-hr
	Mysidopsis bahia	1.45 48-hr
OIL SOLUTIONS POWDER & No. 2 Fuel Oil (1:10)	Menidia beryllina	22.50 96-hr
	Mysidopsis bahia	2.13 48-hr
Reference Toxicant (SRTT)	Menidia beryllina	3.65 96-hr
	Mysidopsis bahia	9.55 48-hr

b. Effectiveness:
NA

VIII. MICROBIOLOGICAL ANALYSIS NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 230°F
2. Pour Point: NA
3. Viscosity: NA
4. Specific Gravity: 0.91
5. pH: 4.08
6. Surface Active Agents: NA
7. Solvents: NA
8. Additives: None
9. Solubility in Water: Negligible

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<1.0
Cadmium	<0.05
Chromium	<0.325
Copper	17.25
Lead	<0.08
Mercury	0.02
Nickel	<0.225
Zinc	<0.45
Cyanide	<0.1
Chlorinated Hydrocarbons	ND

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**7/23/2021
7/27/2022**

TECHNICAL PRODUCT BULLETIN #M-26
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JUNE 30, 2008
“ELASTOL”
(aka, SEPARATE, LIQUID ELASTOL)

I. NAME, BRAND, OR TRADEMARK
ELASTOL
(aka, SEPARATE, LIQUID ELASTOL)
Type of Product: Miscellaneous Oil Spill Control Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Action Additives, Inc.
205 Industrial Road
P.O. Box 965
Ducktown, TN 37326
Phone: updated information required
(Mr. Tim Kaylor)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Design Engineering Systems Analysis
P.O. Box 293
Alexandria, VA 22313
Phone: (703) 4613912
E-mail: escambos@actionadditivesinc.com
(Mr. Ernest T. Scambos)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Autoignition temperature for product is 392°F. Product is combustible in liquid form and can form combustible mixtures and possibly explosive mixtures above the flash point. Use water spray to cool fire exposed surfaces and to protect personnel. Isolate “fuel” supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boil over. Product is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition source where they may ignite.
2. Ventilation: Product is moderately volatile. Ensure proper ventilation. Avoid formation and inhalation of spray mist and vapors. Do not wear contaminated clothing. Keep away from fire and heated objects. Avoid formation of aerosols. Avoid squirting and use dosage pump when transferring.
3. Skin and eye contact; protective covering; treatment in case of contact: Protection depends on use and condition of work environment. Ensure good personal hygiene, wash hands regularly

with soap and water. Avoid contact with skin and eyes and inhalation of fumes/aerosols. All new protective gear must be of CE standard. There must be an eye rinsing kit available at the work place. Where there is danger of inhalation, use mask with brown filter. If the product is sprayed and there is a risk of aerosol formation, use mask with combination filter A2-P2. When used regularly, measuring routines for solvent measurement should be implemented. Level of contamination should be kept as low as possible.

4.a. Maximum storage temperature: ~160°F

4.b. Minimum storage temperature: -100°F

4.c. Optimum storage temperature range: 40-70°F

4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

At least 5 years when stored at temperatures below 150°F.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: ELASTOL can be applied to the surface of an oil/water separator tank or added to a waste stream before it enters a separation tank. ELASTOL floats on water, dissolving when it comes in contact with petroleum products (e.g., gasoline, diesel, jet fuel, fuel oil, crude, etc.). It remains effective for long periods, but naturally degrades when exposed to the atmosphere over longer periods. ELASTOL treated oil may increase the performance of containment and recovery equipment:

- Containment booms – may have higher current and tow speed capability
- Mechanical skimming equipment – may be improved 2 to 10 times its normal recovery rates
- Drum skimmers – may recover little or no water with the oil

When applied early to a spill, ELASTOL may reduce emulsification and dispersion of oil. In addition, it may reduce the penetration of oil into porous soils and sandy beaches.

2. Concentration/Application Rate: ELASTOL can be used at very low concentrations from 100-1,500 ppm (0.01% to 0.15%). The amount of ELASTOL to be used is dependent upon the viscosity of the oil being removed. For example, one gallon of ELASTOL will remove:

- 13 gallons of gasoline
- 34 gallons of diesel
- 84 gallons of medium oil
- 150 gallons of heavy oil

3. Conditions for Use: ELASTOL may be used on fresh or salt water (under warm or cold temperatures). Prompt application may maximize effectiveness. The older the pollutants the few light oil elements remain in the oil, which may reduce the effectiveness of recovery.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
ELASTOL	Menidia beryllina	1,333 96-hr
	Mysidopsis bahia	94 48-hr
No. 2 Fuel Oil	Menidia beryllina	5.4 96-hr
	Mysidopsis bahia	3.3 48-hr
ELASTOL & No. 2 Fuel Oil (1:10)	Menidia beryllina	8.2 96-hr
Reference Toxicant (SDS)	Mysidopsis bahia	3.7 48-hr
	Menidia beryllina	7.4 96-hr
	Mysidopsis bahia	10.7 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 176°F
2. Pour Point: -71°F
3. Viscosity: 3.46 cSt @ 77°F
4. Specific Gravity: 0.83@t 60°F
5. pH: 6.8 – 7.0
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL
8. Additives: CONFIDENTIAL
9. Solubility in Water: Insoluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND
Cadmium	ND
Chromium	ND
Copper	ND
Lead	ND
Mercury	ND
Nickel	ND
Zinc	1.4
Cyanide	ND
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #M-27
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JUNE 03, 2010
“OIL BOND®”

I. NAME, BRAND, OR TRADEMARK
OIL BOND®

Type of Product: Miscellaneous Oil Spill Control Agent - Solidifier

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Solidification Products International, Inc.

P.O. Box 35
524 Forrest Road
Northford, CT 06472
Phone: (203) 484-9494
Toll Free: (800) 758-3634
Fax: (203) 484-9492
E-mail: dgannon@oilbarriers.com
(Ms. Donna Gannon)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Solidification Products International, Inc.

P.O. Box 35
524 Forrest Road
Northford, CT 06472
Phone: (203) 484-9494
Toll Free: (800) 758-3634
Fax: (203) 484-9492
E-mail: dgannon@oilbarriers.com
(Ms. Donna Gannon)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Not classified as flammable, but will burn. Maintain a fire watch if OIL BOND® is heated above 450°F.
2. Ventilation: Normal ventilation is adequate. For confined space entry or lack of exhaust in a contained area, avoid generating dust. Dust in excessive concentration can result in an explosive mixture in air. Wear approved NIOSH respirator with particulate pre-filter for dust.
3. Skin and eye contact; protective covering; treatment in case of contact: Product dust may be mildly irritating to eyes and respiratory tract. Wear approved standard issue work clothes, gloves, dust mask, and dust tight goggles as needed. In case of contact with eyes, flush with water. If prolonged skin contact, wash with soap and water. For inhalation of dust, remove to fresh air.
- 4.a. Maximum storage temperature: 180°F
- 4.b. Minimum storage temperature: None

4.c. Optimum storage temperature range: Ambient. Avoid elevated temperatures >200°F for extended periods of time.

4.d. Temperatures of phase separations and chemical changes: >450°F chance of auto-combustion. Avoid strong oxidizing agents.

V. SHELF LIFE

5 years. Store OIL BOND® in cool, dry area away from direct sunlight to prolong shelf life.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: OIL BOND® will absorb and solidify hydrocarbon spills on freshwater and saltwater or land applications. For small spills, OIL BOND® may be broadcast by hand, and booms and pillows may be used to ring the spill. For large spills, OIL BOND® may be distributed by equipment with an air or water stream. Ground all dispensing equipment if deploying dry OIL BOND® at a high rate of speed to prevent static discharge. Introduce OIL BOND® with dispensing water spray just before final discharge to allow mixing of OIL BOND® with the water stream. Allow OIL BOND® contact time with the spilled fuel or hydrocarbon waste for 10 minutes to 1 hour before collection to allow absorption and solidification. Lighter fuels require less solidification time than heavier viscosity fuels such as No. 6 fuel oil or heavy crude. OIL BOND® is non-toxic and biologically inactive, and will remain floating on the surface of the water before and after solidification.

Collect solidified materials with a net or vacuum equipment from the surface of the water. For land spills shovel, sweep, or vacuum solidified material. Place the solidified debris in approved, labeled, and sealed containers as required by local, state, federal, international, or country-specific regulations.

Depending on the inherent nature of the spilled liquid that was solidified, disposal options include landfilling, incineration, waste to energy incineration, or use as a secondary fuel.

2. Concentration/Application Rate: OIL BOND® should be applied at a rate of 15% to 30% by weight to a spilled hydrocarbon liquid. Lighter viscosity hydrocarbon waste and oils require less OIL BOND® than heavier fuels. Conditions for use on spills may be highly variable, degraded product or extremely heavy viscosity fuels may require additional OIL BOND® to obtain complete solidification.

3. Conditions for Use: OIL BOND® may be used on any hydrocarbon waste, oil or fuel on freshwater, saltwater, or land applications. During rough weather with high winds or seas a conventional containment collection boom is recommended to corral the spill allowing easier retrieval and contact time with OIL BOND®. Cold water temperatures may require longer contact time to fully solidify a spill.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
OIL BOND®	Menidia beryllina	>10000	96-hr
	Mysidopsis bahia	>10000	48-hr
No. 2 Fuel Oil	Menidia beryllina	3.0	96-hr
	Mysidopsis bahia	7.1	48-hr
OIL BOND® & No. 2 Fuel Oil (1:10)	Menidia beryllina	3.8	96-hr
	Mysidopsis bahia	9.6	48-hr
Reference Toxicant (SDS)	Menidia beryllina	8.0	96-hr
	Mysidopsis bahia	11.3	48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >200°F
2. Pour Point: NA, solid product
3. Viscosity: NA, solid product
4. Specific Gravity: 0.21
5. pH: 8.8
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: None
8. Additives: Pigment/Antioxidant
9. Solubility in Water: Insoluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.6
Cadmium	<0.32
Chromium	<0.32
Copper	0.71
Lead	<0.32
Mercury	<0.07
Nickel	0.97
Zinc	0.32
Cyanide	<0.50
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #M-28
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: AUGUST 17, 2010
“AQUAFLEX®”

I. NAME, BRAND, OR TRADEMARK

AQUAFLEX® (OPEN-CELL ELASTOMERIC SORBENTS)
Type of Product: Miscellaneous Oil Spill Control Agent
(formerly OPFLEX®)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

AquaFlex Holdings LLC

P.O. Box 355

West Hyannisport, MA 02672

Phone: (508) 345-6520

Fax: (508) 425-2990

E-mail: ssmith@aflx.com

Website: www.aqflx.com

(Mr. Scott Smith)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

AquaFlex Holdings LLC

P.O. Box 355

West Hyannisport, MA 02672

Phone: (508) 345-6520

Fax: (508) 425-2990

E-mail: ssmith@aflx.com

Website: www.aqflx.com

(Mr. Scott Smith)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: No special requirements. No special handling is required.
3. Skin and eye contact; protective covering; treatment in case of contact: No special equipment or clothing required. If eye or skin irritation occurs, flush with plenty of fresh water.
- 4.a. Maximum storage temperature: 120°F continuous
- 4.b. Minimum storage temperature: No minimum
- 4.c. Optimum storage temperature range: 40°F to 120°F
- 4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

Shelf life is unlimited when stored in plastic bags.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Example – AquaFlex foam is fabricated into 40 6-foot strips that are in mesh netting. These booms can be connected end-to-end and positioned behind containment booms to absorb oil that has breached the containment.
2. Example – AquaFlex foam is fabricated into 1/4" x 16" x 18" pads that can be deployed by placing on an oil patch to absorb the oil from the water surface.
3. Example – AquaFlex foam can be cut into small cubes such as 1 cubes and contained in a net or mesh tube to create a very high surface area absorbent boom.
4. Example – AquaFlex foam can be fabricated into mega pads of 1/4" x 1 foot x 6 foot sections to be connected on the back of a containment boom system to absorb oil which flows over the boom, especially in marsh areas.
5. Example – AquaFlex foam can be fabricated into multiple mops that are strung between support posts at the shoreline to remove oil from the surf.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
AQUAFLEX®	Menidia beryllina	>35640	96-hr
	Mysidopsis bahia	8630	48-hr
No. 2 Fuel Oil	Menidia beryllina	3.35	96-hr
	Mysidopsis bahia	2.24	48-hr
AQUAFLEX® &	Menidia beryllina	5.49	96-hr
No. 2 Fuel Oil (1:10)	Mysidopsis bahia	1.67	48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.19	96-hr
	Mysidopsis bahia	10.53	48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: NA
2. Pour Point: NA, solid product
3. Viscosity: NA, solid product
4. Specific Gravity: 0.0415 g/mL
5. pH: NA
6. Surface Active Agents: NA
7. Solvents: CONFIDENTIAL
8. Additives: CONFIDENTIAL

9. Solubility in Water: Insoluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.179 (brl)
Cadmium	<0.089 (brl)
Chromium	<0.268 (brl)
Copper	1.74
Lead	0.286
Mercury	<0.0031 (brl)
Nickel	<0.446 (brl)
Zinc	139
Cyanide	0.498
Chlorinated Hydrocarbons	<2.43 (brl)

TECHNICAL PRODUCT BULLETIN #M-29
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: AUGUST 17, 2010
“GELCO 200”

I. NAME, BRAND, OR TRADEMARK

GELCO 200

Type of Product: Miscellaneous Oil Spill Control Agent - Solidifier

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

UESS, Ltd.

Box 6088

Drayton Valley, AB, Canada

T7A 1R6

Phone: (780) 621-6870

E-mail: hugh.morrison@telus.net

(Mr. Hugh Morrison)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

UESS, Ltd.

Box 6088

Drayton Valley, AB, Canada

T7A 1R6

Phone: (780) 621-6870

E-mail: hugh.morrison@telus.net

(Mr. Hugh Morrison)

*Currently only one distributor, which serves as a point of contact.

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: >150°F

2. Ventilation: Store in well-ventilated location. Where local exhaust ventilation is not practical and odors are detected, use a negative pressure half face respirator with a cartridge designed to protect against organic vapors and dust if also present, a particulate pre-filter should be used. For high airborne dust concentrations, use a cartridge to be used against nuisance dust.

3. Skin and eye contact; protective covering; treatment in case of contact: Use cloth gloves if desired. Dust-tight mono-glasses and standard issue work-wear. In case of contact with eyes or skin, flush with water.

4.a. Maximum storage temperature: 200°F

4.b. Minimum storage temperature: None

4.c. Optimum storage temperature range: 40-90°F

4.d. Temperatures of phase separations and chemical changes: Begins to oxidize exothermically at high temperatures (230°F).

4.e. Store in a cool, dry location. Away from direct sunlight or sources of intense heat.

- 4.f. Maintain fire watch if material temperature reaches 536°F (280°C).
- 4.g. Product may accumulate static charge during processing, handling, and transport. Earth/ground all equipment used in handling and applying this product.
- 4.h. Avoid contact with strong oxidizing agents.
- 4.i. Do not stack Flexible Intermediate Bulk Containers or palletized bags.

V. SHELF LIFE

>10 years when stored in dry, cool area out of sunlight.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: For small scale spills on water (fresh or salt), GELCO 200 can be broadcast directly onto the spill by hand or small hand held spreader from the outer edge back into the middle of the spill. Agitation is not necessary for GELCO 200 to be effective. The product can also be used and is available in booms, socks, and pillows.

For large spills on water (fresh or salt), GELCO 200 may be deployed with an air or water stream directed at the leading edge of the spill. Dispensing equipment should be properly grounded to prevent static electricity build-up if pumping GELCO 200 in dry form at high rates of delivery. If used with a water carrying media, product will require agitation to keep product suspended if there is a delay or travel time associated between batching and delivering product upon spill.

GELCO 200 will remove oils and other hazardous hydrocarbon based materials from both salt and fresh water. GELCO 200 encapsulates and solidifies the oil, and remains buoyant even after total saturation. The solidified products can be removed from the water with hand vacs, vacuum barges, commercial fishing nets, and conveyors. Solidified materials should be placed into appropriate containers and disposed of in accordance with all applicable federal, state, and local regulations.

Land Application

For spills on land, the product would be applied in the same manner. The product can also be applied by sand-blasting equipment/hopper or pneumatic air seeders. Agitation is not necessary in most scenarios. Some fine agitation may be necessary to remove contaminated materials from native grasses and marsh areas.

Many factors are taken into consideration before determining the best method(s) of application. They include weather, geography, access, land use, and habitat of affected spill area.

When removing contaminants from land, it should be a priority to minimize the volume of land taken to preserve the integrity of the land and to minimize the volume of waste requiring disposal.

To recover solidified oil or hazardous materials from spills on land, the solidified product can be collected and removed efficiently and effectively using a variety of manual and mechanical

means.

Manual methods include picking up by hand, using brooms, rakes, shovels, and squeegees to remove and pick up solidified petroleum waste product.

Mechanical means include using hand held vacuums, portable vac units, vac-trucks, or commercial shop vacs. Once the spilled product is solidified by GELCO 200, it will not leach. GELCO 200 is extremely hydrophobic and will not take on water, which may help to keep the volume of waste produced down, depending on the characterization of any non-solidified oil and water remaining in the area treated. Pressure flushing the solidified product or raw into a containment area where it can be solidified – a boomed area, containment dike, bell hole, etc. for removal by vacuum – is also a very practical method for removal.

Land spill cleanup of solidified oil/product

Collection and disposal of materials generated from application to oil spilled on land involve greater variation in waste composition, and appropriate disposal techniques have to be selected for the particular circumstances. Proper precautions, including testing as necessary to identify the characteristics of wastes generated from the application of GELCO 200, should be taken to determine the safe and legally required means of recovering, handling, storing, transporting, treating, recycling, or disposing of materials produced from the application of GELCO 200 to oil spilled on land.

All materials should be placed into appropriate containers, characterized by knowledge or testing as to waste type, and handled, stored, transported, treated, or disposed of in accordance with all applicable federal, state, and local regulations. Professional advice should be obtained where needed.

2. Concentration/Application Rate: GELCO 200 is usually applied at a ratio of 5-20% of GELCO 200 to waste by weight to solidify light, medium, and heavy hydrocarbons. Solidification typically occurs 1-3 minutes for most oils. GELCO 200 has been used effectively on heavier crudes including Bunker C within the application rates noted above.

3. Conditions for Use: GECLO 200 is effective in all environments and under a broad range of weather conditions. The product is most effective on water temperatures between 32°F and 120°F. Depending upon the age and/or viscosity of the material, varying amounts of GELCO 200 may be required to obtain complete solidification. The recovered solidified product can be disposed of in landfills, incinerated, or disposed of in accordance with all applicable federal, state, and local regulations. Some products can be recovered from the solidified mass through a heat process that would allow the solidified product to release itself from the GELCO 200.

UESS, Ltd. has had TCLP tests completed on several occasions and have not had any field instances of product being released in our methods of recovery and disposal to date due to pressure related issues.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
GELCO 200	Menidia beryllina	>10000	96-hr
	Mysidopsis bahia	>1000	48-hr
No. 2 Fuel Oil	Menidia beryllina	9.26	96-hr
	Mysidopsis bahia	6.58	48-hr
GELCO 200 & No. 2 Fuel Oil (1:10)	Menidia beryllina	3.15	96-hr
	Mysidopsis bahia	3.51	48-hr
Reference Toxicant (SDS)	Menidia beryllina	8.03	96-hr
	Mysidopsis bahia	14.5	48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >150°F
2. Pour Point: NA, solid product
3. Viscosity: NA, solid product
4. Specific Gravity: 0.25 g/cm³ at 4°C
5. pH: 4.75
6. Surface Active Agents: NA
7. Solvents: NA
8. Additives: CONFIDENTIAL
9. Solubility in Water: Insoluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.577
Cadmium	<0.289
Chromium	<0.577
Copper	<0.577
Lead	<0.577
Mercury	<0.100
Nickel	5.91
Zinc	0.788
Cyanide	ND
Chlorinated Hydrocarbons	ND

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**1/10/2017
7/27/2022**

TECHNICAL PRODUCT BULLETIN #M-30
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: APRIL 26, 2012
“NORSOREX® APX”

I. NAME, BRAND, OR TRADEMARK

NORSOREX® APX

Type of Product: Miscellaneous Oil Spill Control Agent – Solidifier

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

D-NOV GmbH

Perfektastrasse 86

A-1230 Vienna

Austria, Europe

Office: updated information required

Phone: updated information required

Fax: updated information required

E-mail: updated information required

Website: updated information required

(Mr. Gerhard Karall, COO)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

D-NOV GmbH

Perfektastrasse 86

A-1230 Vienna

Austria, Europe

D-NOV GmbH

Perfektastrasse 86

A-1230 Vienna

Austria, Europe

Office: updated information required

Phone: updated information required

Fax: updated information required

E-mail: updated information required

Website: updated information required

(Mr. Gerhard Karall, COO)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: >174°F

2. Ventilation: Dust explosions are possible while handling organic powders at high

concentrations; therefore, provide proper air ventilation with fresh air or other methods to avoid dust formation. General dust limits (DE-TRGS 900): 3 mg/m³ (respirable dust fraction), 10 mg/m³ (inhalable dust fraction), short-term exposure value (TRGS 900, 2.3) – excess factor 4. For short-term exposure wear dust masks.

3. Skin and eye contact; protective covering; treatment in case of contact: Avoid contact to skin and eyes. Do not breathe dust. Wear protective goggles, gloves, and clothing. Following skin contact, wash with plenty of water and pH-neutral soap. Obtain medical attention if irritation symptoms persist. Following eye contact, remove contact lenses immediately and rinse with plenty of water (also under the eyelids) for at least 15 minutes. Obtain medical attention. Following ingestion, remove all of product from the respiratory system and wash oral cavity. Drink 200-300 ml of water. Do not induce vomiting without medical advice. Obtain medical attention.

4.a. Maximum storage temperature: 45°C/113°F

4.b. Minimum storage temperature: -5°C/23°F

4.c. Optimum storage temperature range: -5°C to 30°C/23°F to 86°F

4.d. Temperatures of phase separations and chemical changes: The material composition does not change with the temperature (no phase separation). Chemical changes occur at temperatures >45°C/113°F with oxygen. The material changes from white to yellow and the absorption behavior decreases.

V. SHELF LIFE

Shelf life is 3 years from date of production. Keep material stored in original containers in a dark, dry area until use. The product should be used within 6 months after opening the original container.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: NORSOREX[®] APX is a special polymer with very high affinity for hydrocarbons and, since it is hydrophobic, it is also insoluble in water. NORSOREX[®] APX can be used in free powder or pad form (sealed bags containing the powder). NORSOREX[®] APX powder can bond to a variety of liquid hydrocarbons in two stages. First, due to the fast absorption process further oil spreading is prevented (forming of a gel). Second, the oil solidifies to a non-leaching inert, firm cohesive “rubber-like” mass within a few hours, which can be easily collected and burned, disposed of or used for other purposes (e.g., rubber industry in a full green recycle process). It is a combination of an adsorption and absorption process.

Use NORSOREX[®] APX powder or pads by estimating the hydrocarbon quantity and checking with the application chart to individuate the necessary quantity. The suggestion to optimize the usage is to keep ratio values of NORSOREX[®] APX to hydrocarbon as close as possible to the application chart. If possible, use pretests to test the process. Deploy NORSOREX[®] APX in the environment where there is hydrocarbon to be removed or recovered. NORSOREX[®] APX can be applied by hand or through mechanical spreading. According to the desired performance, wait the necessary reaction time. Reaction takes place within minutes and it reaches 80 percent of its efficiency after only a few hours. Maximum efficiency (100 percent) can be reached in less than 24 hours. Once NORSOREX[®] APX has reacted, it is possible to recover the hydrocarbon in solid

form.

2. Concentration/Application Rate:

Type of Hydrocarbon (HC)	kg _{HC} /kg _{AP} X	kg _{APX} /kg _H C	kg _{APX} /m ³ _H C	L _{HC} /L _{AP} X	L _{APX} /L _H C
Benzene	23.0	0.043	38.1	9.189	0.109
Toluene	18.0	0.056	48.2	7.267	0.138
Hexane	4.2	0.238	155.9	2.245	0.445
Heptane	5.0	0.200	135.9	2.575	0.388
Cyclorhexane	6.8	0.147	114.6	3.055	0.327
Dichloromethane/Methylene chloride	18.0	0.056	73.9	4.737	0.211
Chloroform	26.0	0.038	57.0	6.136	0.163
Trichloroethane/Trichloroethylene	31.8	0.031	45.9	7.623	0.131
Tetrachloroethene/Trichloroethylene	31.0	0.032	52.3	6.689	0.149
1,2-Dichlorobenze	27.4	0.036	47.4	7.377	0.136
Pyralene 60 (60% PCB/40%TCB)	36.4	0.027	39.3	8.909	0.112
Pyralene 78 (78% PCB/22% TCB)	28.8	0.035	52.4	6.675	0.150
Diethyl glycol	2.7	0.370	3.11.1	1.125	0.889
Diocylphthalate	2.8	0.357	353.9	0.990	1.010
Heavy Crude Oil A	12.0	0.083	75.0	4.667	0.214
Heavy Crude Oil B	9.0	0.111	88.9	3.938	0.254
Light Crude Oil	9.5	0.105	88.4	3.958	0.253
Kerosene	10.2	0.098	79.4	4.407	0.227
Diesel	10.0	0.100	82.3	4.253	0.235
Aromatic Process Oils	8.3	0.120	120.5	2.905	0.344
Naphthenic Process Oils	8.3	0.120	108.4	3.228	0.310
Paraffinic Process Oils	4.0	0.250	217.5	1.609	0.621
Refrigerator Oils	10.7	0.093	81.3	4.305	0.232
Turbine Oils	4.3	0.233	209.3	1.672	0.598
Machine Oils	4.5	0.222	200.0	1.750	0.571
Motor Oils	3.8	0.263	228.9	1.529	0.654
Vegetable Oils	2.7	0.370	337.0	1.038	0.963
HC – Hydrocarbon APX – NORSOREX® APX kg _{xx} – Kilogram of xx M ³ _{xx} – Cubic meters of xx L _{xx} – Liter of xx kg _{APX} /m ³ _{HC} – Kilograms of NORSOREX® APX per cubic			Bulk density of NORSOREX® APX powder: 0.35 g/cm ³ The results are tested at room temperature (23°C/73°F) and most substrates show an improvement of 10 until 15% at		

Type of Hydrocarbon (HC)	kg _{HC} /kg _{AP} X	kg _{APX} /kg _H C	kg _{APX} /m ³ _H C	L _{HC} /L _{AP} X	L _{APX} /L _H C
meter of hydrocarbon			40°C. The best performance is achieved at 60°C with an improvement of about 30%. At higher temperatures the effect of improvement falls and over 100°C significant.		

3. Conditions for Use:

To recover the solidified NORSOREX[®] APX from the environment, mechanically collect the material and transport it to the nearest designated disposal location. NORSOREX[®] APX has the capability of 3.5 bar of pressure before it will start leaking. Do not discharge into drains, surface waters, or ground waters. NORSOREX[®] APX is not biodegradable. The resulting “rubber-like” material could still be hazardous so extreme caution should be exercised when handling these materials. Very polar substances such as organic acids, alcohols or glycols show a reduced absorption efficiency of the product. The water temperature has an influence on the reaction time. Cold water slows down the solidification process. The ages of pollutants only have an influence on the absorption performance if their viscosity or polarity are increased to the typical values for the “fresh” pollutant.

Avoid damage to NORSOREX[®] APX pads if the application environment is characterized by rough water. This will ensure the easiest deployment and recovery procedure. If allowed by current regulations and if properly contained, the free powder form is recommended to optimize the contact interface between NORSOREX[®] APX and the liquid hydrocarbon.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
NORSOREX [®] APX	Menidia beryllina	>100,000.00 96-hr
	Mysidopsis bahia	>100,000.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	15.10 96-hr
	Mysidopsis bahia	2.41 48-hr
NORSOREX [®] APX & No. 2 Fuel Oil (1:10)	Menidia beryllina	39.80 96-hr
	Mysidopsis bahia	3.06 48-hr
Reference Toxicant (SDS)	Menidia beryllina	2.01 96-hr
	Mysidopsis bahia	6.63 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 174°F
2. Pour Point: NA
3. Viscosity: NA
4. Specific Gravity: 0.91047 at 60°F
5. pH: 7.10
6. Surface Active Agents: Polynorbornene
7. Solvents: NA
8. Additives: Phenolic antioxidant, flow agent
9. Solubility in Water: Insoluble in water

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND
Cadmium	ND
Chromium	0.40
Copper	0.14
Lead	ND
Mercury	0.011
Nickel	ND
Zinc	55.40
Cyanide	0.222
Chlorinated Hydrocarbons	ND

LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:

3/10/2016
7/27/2022

TECHNICAL PRODUCT BULLETIN #M-31
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: NOVEMBER 9, 2015
“CAS 100[®]”

I. NAME, BRAND, OR TRADEMARK
CAS 100[®]

Type of Product: Miscellaneous Oil Spill Control Agent – Solidifier

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Tradewinds Environmental Safety Services SA de CV
Calle 1 “E” No. 245 por 30 y 36
Col. Campestre
Merida, Mexico C.P 97120
Phone: updated information required
E-mail: updated information required
(Mr. Michael Harper)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
EPC Evolved Products, Inc.
5889 Greenwood Plaza Boulevard, Suite 201
Greenwood Village, CO 80111
Phone: 720-496-0023
E-mail: dave.washington@epces.com
(Mr. Dave Washington)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-Flammable
2. Ventilation: Work in well ventilated area. Avoid excessive inhalation of fine particles.
3. Skin and eye contact; protective covering; treatment in case of contact: Avoid contact to eyes. Do not breathe in particles. Wear protective goggles, gloves and clothing. Following skin contact, wash with plenty of soap and water. Remove exposed or contaminated clothing, taking care not to contaminate the eyes. Please seek medical attention if adverse effects continue after flushing. Following eye contact, remove contact lenses (if necessary) and rinse with gently running water for at least 15 minutes. Obtain medical attention. Following ingestion, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Drink large quantities of water. Following inhalation, move to fresh air location. Seek medical attention if adverse symptoms continue after removal to fresh air.
- 4.a. Maximum storage temperature: 140°F

- 4.b. Minimum storage temperature: -40°F
 4.c. Optimum storage temperature range: -40°F to 140°F
 4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

The shelf life of CAS 100[®] is 1 year from date of production if stored in a dry dark location. Keep material stored in original containers in a dark, dry area until use. If the product is exposed to UV rays consistently, it will degrade over time.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: In powder form, apply CAS 100[®] along the outer edges of spill area to prevent migration. Continue to apply CAS 100[®] inside spill area until the area is saturated with product. Depending on type of hydrocarbon, the resulting oil/CAS 100[®] mixture can be rolled up like a carpet or clumps of the solid can be removed with a net. In pad form, booms can be used to prevent migration of oil spill. Pads can be used to clean up the spill area by placing them on the oil spill itself. Once the pad is saturated, it can be easily removed by simply picking up the pad.

2. Concentration/Application Rate: CAS 100[®] is used by applying 1 pound of product to each 10 pounds of spilled hydrocarbon. The contact time varies from just a few seconds to several hours depending upon the quantity of the spill. Hydrocarbon viscosities decrease as temperatures increase causing an increase in the time required for the gelling process of hydrocarbon to CAS 100[®].

3. Conditions for Use: CAS 100[®] can be used on any concentration of water salinity and water temperature. There is no restriction of the types of ages of the hydrocarbon being processed. Depending upon the types of the hydrocarbon, the resulting CAS 100[®]/oil mixture can be in the form of a carpet, rubber ball or crumb like material. CAS 100[®] has a fast gelling characteristic, which prevents the hydrocarbon from spreading further. Once the hydrocarbon comes in contact with CAS 100[®], the result is a non-leaching solid within a few minutes (or hours) depending on the size of the spill. The resulting solid should be collected at the spill site and disposed of according to federal, state and local regulations. Collecting the solid at the spill site will prevent the resulting CAS 100[®]/oil mixture from reaching open water.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
CAS 100 [®]	Menidia beryllina	>1000 96-hr
	Mysidopsis bahia	>1000 48-hr
No. 2 Fuel Oil	Menidia beryllina	4.81 96-hr
	Mysidopsis bahia	1.93 48-hr
CAS 100 [®] & No. 2 Fuel Oil (1:10)	Menidia beryllina	5.94 96-hr
	Mysidopsis bahia	1.41 48-hr
Reference Toxicant (SDS)	Menidia beryllina	8.84 96-hr
	Mysidopsis bahia	23.00 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >200°F
2. Pour Point: NA (solid material)
3. Viscosity: NA (solid material)
4. Specific Gravity: 0.51
5. pH: 6.94
6. Surface Active Agents: NA
7. Solvents: NA
8. Additives: NA
9. Solubility in Water: Insoluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<2.0
Cadmium	<0.5
Chromium	<1.0
Copper	<2.5
Lead	<2.0
Mercury	<0.029
Nickel	<4.0
Zinc	<5.0
Cyanide	<0.22
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #M-32
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: APRIL 21, 2016
“S-200 OILGONE®”

I. NAME, BRAND, OR TRADEMARK

S-200 OILGONE®

Type of Product: Miscellaneous Oil Spill Control Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

RBL Environmental, LLC*

1311 Dorothy Avenue

Phoenixville, PA 19460

Phone: (610) 520-7665

E-mail: jim.lynn@iepusa.com

(Mr. James Lynn)

*(*RBL Environmental, LLC is the manufacturer and marketer for International Environmental Products)*

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

RBL Environmental, LLC

1311 Dorothy Avenue

Phoenixville, PA 19460

Phone: (610) 520-7665

E-mail: jim.lynn@iepusa.com

(Mr. James Lynn)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-Flammable

2. Ventilation: Ensure good ventilation. This can be achieved by local suction and or general air extraction. If this is insufficient to maintain the concentration under Workplace Exposure Limits (WEL), suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed below. Respiration protection normally not necessary. If Occupational Exposure Standards (OES) or Maximum Exposure Limits (MELs) are exceeded, use appropriate air purifying respirator with filter.

EXPOSURE CONTROL/PERSONAL PROTECTION

Exposure limit values: Not applicable

Name	WEL-TWA	WEL-STEL	Content
2-(2-butoxyethoxy)-ethanol	10 ppm	15 ppm	1-5%
Butyl carbitol®	(67.5 mg/m ³) (WEL, EC)	(101.2 mg/m ³) (WEL, EC)	

WEL-TWA: Workplace Exposure Limit–Time-Weighted Average; WEL-STEL: Workplace Exposure Limit–Short-Term Exposure Limit; EC: European Commission

3. Skin and eye contact; protective covering; treatment in case of contact: General hygiene

measures for the handling of chemicals are applicable. Wash hands before breaks and at end of shift. Keep away from food, drink and animal feeding supplies. Skin Protection: wear protective work garments (e.g., safety shoes, long-sleeves). Wear chemical resistant protective gloves; or if applicable, gloves made of protective neoprene or butyl rubber. Protective hand cream is recommended. Eye Protection: wear tight fitting protective goggles with side protection.

4.a. Maximum storage temperature: 132°F

4.b. Minimum storage temperature: 32°F

4.c. Optimum storage temperature range: 55°F to 85°F

4.d. Temperatures of phase separations and chemical changes: <0°F and >212°F. Phase separation will be eliminated when returning to ambient temperatures.

V. SHELF LIFE

Recommended shelf life is 10 years if product is kept in the unopened, original container.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: S-200 OILGONE® is a water like liquid and can be sprayed with traditional liquid spraying equipment, such as pressurized sprayers or backpack sprayers. Apply product directly to the hydrocarbon.

2. Concentration/Application Rate: The recommended application rate for spraying on the spill is approximately 1:1 by weight of the product as compared to the hydrocarbon being agglomerated. For example, use 1 gallon of product for every 1 gallon of hydrocarbon to be treated. For sheens, apply 1 gallon of product for every 8 square yards of surface area.

3. Conditions for Use: S-200 OILGONE® is a hydrocarbon coagulator used for the cleanup of hydrocarbon spills on water. These hydrocarbons include, but are not limited to, gasoline, No. 2 to No. 6 Fuel Oil, jet fuels, kerosene, lubricating oils, hydraulic oils and crude oils. Once applied, the hydrocarbon will agglomerate with S-200 OILGONE® and remain on the water's surface. To prevent the hydrocarbon or agglomeration from reaching open water during application, use traditional booms to contain the spill. The agglomeration will form gel like balls, eliminating the sheen and allowing for the product:oil mixture to be removed from the water's surface using traditional skimming tools. The resulting gel like balls should be collected at the spill site and disposed of according to federal, state and local regulations. S-200 OILGONE® can be used in salt, brackish or fresh water. The product can be applied at any ambient temperature on any hydrocarbon pollutant whether fresh or weathered. The size of the gel balls will be dependent on the quantity (not type) of hydrocarbon spilled.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
S-200 OILGONE®	Menidia beryllina	326.22 96-hr
	Mysidopsis bahia	47.29 48-hr
No. 2 Fuel Oil	Menidia beryllina	21.11 96-hr
	Mysidopsis bahia	2.56 48-hr
S-200 OILGONE® & No. 2 Fuel Oil (1:10)	Menidia beryllina	15.83 96-hr
	Mysidopsis bahia	2.46 48-hr

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
Reference Toxicant (SDS)	Menidia beryllina	3.47 96-hr
	Mysidopsis bahia	4.91 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >212°F
2. Pour Point: 29 °F
3. Viscosity: 6.9 cst@40°C
4. Specific Gravity: 0.9796
5. pH: 7.01
6. Surface Active Agents: Confidential
7. Solvents: Confidential
8. Additives: Confidential
9. Solubility in Water: Miscible

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.5
Cadmium	<0.25
Chromium	<0.25
Copper	<0.5
Lead	<0.6
Mercury	<0.0025
Nickel	<0.5
Zinc	0.54
Cyanide	<0.025
Chlorinated Hydrocarbons	<0.1

TECHNICAL PRODUCT BULLETIN #M-33
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: AUGUST 22, 2016
“HYDRO-BOND™”

I. NAME, BRAND, OR TRADEMARK

HYDRO-BOND™

Type of Product: Miscellaneous Oil Spill Control Agent – Solidifier

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Oil Spill Solutions, LLC

153 Foster Street

Center, TX 75935

Phone: (936) 598-6595

Fax: (936) 598-6338

E-mail: fred@fredwulf.com

Website: www.oilspillsolutionsllc.com

(Mr. Fred Wulf)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Oil Spill Solutions, LLC

153 Foster Street

Center, TX 75935

Phone: (936) 598-6595

Fax: (936) 598-6338

E-mail: fred@fredwulf.com

Website: www.oilspillsolutionsllc.com

(Mr. Fred Wulf)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-Flammable (DOT: Non-Hazardous)

2. Ventilation: Personal protective equipment should be used when applying Hydro-Bond™. Recommended equipment would include safety glasses or goggles, disposable respirators, nuisance dust mask or procedural mask, disposable gloves and long sleeves. Odors/vapors may produce mild and temporary discomfort to the respiratory tract resulting in wheezing, tightness in the chest, shortness of breath and coughing. Although they may be present in low amounts, dust and small pieces of material may aggravate bronchitis, asthma, and emphysema if inhaled.

3. Skin and eye contact; protective covering; treatment in case of contact: Hydro-Bond™ in contact with the skin may result in irritation (redness, itching) or other effects with some individuals. In case of skin contact wash exposed skin thoroughly with soap and water. As some are sensitive or allergic to natural rubber (Latex), if irritation develops and is prolonged and/or sore, consult a physician. Hydro-Bond™ material is abrasive if it enters the eye, which can cause irritation to severe damage if left untreated. In case of eye contact flush eyes with plenty of water

for at least 15 minutes. Avoid rubbing the eye. If experiencing prolonged irritation or soreness, seek medical attention. In the event that Hydro-Bond™ is ingested there may be irritation of mucus membranes of mouth, throat, esophagus and stomach along with nausea may occur. Abrasion to the mouth, esophagus, stomach and intestinal tract may occur. If inhaled, in emergency situations, use proper respiratory protection and immediately remove the affected person from the exposure. Keep at rest. Administer artificial respiration if breathing has stopped. Seek medical attention. If swallowed do not induce vomiting. Rinse mouth well with water. Never give anything by mouth to an unconscious person. Seek medical attention. Repeated unprotected exposure to Hydro-Bond™ may result in sensitization to susceptible individuals. General advice: If negative symptoms develop while handling the product, move out of the area to prevent further exposure. Consult a physician as a precautionary measure if symptoms develop after being subjected to unprotected exposure of the material. If eye or skin irritation occurs flush with plenty of fresh water.

4.a. Maximum storage temperature: 120°F continuous, 140°F up to 5 days

4.b. Minimum storage temperature: 35°F

4.c. Optimum storage temperature range: 40°F to 120°F

4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

Unlimited in sealed poly drums or totes (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Product is best used in contained systems such as barriers, socks, mats, blankets, etc. Containment systems should be fully deployed before the application of Hydro-Bond™ to better facilitate rapid and complete recovery. For smaller spills a drum pump with sprayer and large orifice may be used to apply the Hydro-Bond™ material, mixing with salt or fresh water, depending on the spill being in salt or fresh water, as required depending on the type and viscosity of oil being treated. Aged hydrocarbon pollutants will tend to be more concentrated and more viscous; this may require additional quantities of Hydro-Bond™ to be applied. A higher viscosity hydrocarbon spill will require higher concentrations of Hydro-Bond™ and longer dwell times to ensure maximum absorption.

2. Concentration/Application Rate: In contained spills, product may be applied directly to water-borne spills on a 1:18 ratio by weight or a 1:1 ratio by volume. On heavy oils use Product directly on the spill with a 1:1 ratio by volume of spilled contaminant.

3. Conditions for Use: Effective in salt water or fresh water, with no limitation as to usage within optimum temperature parameters (application may be made at or above 30°F). In applications wherein the salinity of the water is higher in content, application of Hydro-Bond™ should be targeted more accurately to the spill concentrations as the hydrocarbon pollutant will be concentrated closer to the surface and effort should be made to ensure that the exposed pollutant is covered to the greatest extent possible. After treatment with Hydro-Bond™, residue should be collected by means of surface skimmers, vacuum pumps, skimming booms, etc. and removed from the site. The specific collection process and methodologies should be determined by on-site coordinator based on practices of the area and available equipment. Collected residue should be disposed of in accordance with local, state, and federal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
HYDRO-BOND™	Menidia beryllina	6544.77 96-hr
	Mysidopsis bahia	5000.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	41.81 96-hr
	Mysidopsis bahia	5.88 48-hr
HYDRO-BOND™ & No. 2 Fuel Oil (1:10)	Menidia beryllina	19.93 96-hr
	Mysidopsis bahia	1.93 48-hr
Reference Toxicant (SDS)	Menidia beryllina	7.52 96-hr
	Mysidopsis bahia	5.47 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >212°F
2. Pour Point: N/A
3. Viscosity: N/A
4. Specific Gravity: 0.9524 @60°F
5. pH: N/A
6. Surface Active Agents: N/A
7. Solvents: N/A
8. Additives: None
9. Solubility in Water: Not soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<2.0
Cadmium	<1.0
Chromium	6.07
Copper	69.0
Lead	53.5
Mercury	<0.020
Nickel	2.16
Zinc	4140
Cyanide	<0.118
Chlorinated Hydrocarbons	<80 (ug)

TECHNICAL PRODUCT BULLETIN #M-34
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: APRIL 16, 2021
“AQUAPAL®”

I. NAME, BRAND, OR TRADEMARK
AQUAPAL® (OPEN-CELL POLYOLEFIN FOAM SORBENT)
Type of Product: Miscellaneous Oil Spill Control Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Palziv North America
7966 NC 56 Highway
Louisburg, NC 27549
Phone: (508) 345-6520
Fax: (919) 496-2523
E-mail: ssmith@aqflx.com
Website: www.palzivna.com
(Mr. Scott Smith)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Palziv North America
7966 NC 56 Highway
Louisburg, NC 27549
Phone: (919) 497-0010
Fax: (919) 496-2523
E-mail: tlehnartz@palzivna.com
Website: www.palzivna.com
(Mr. Tom Lehnartz)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous).
2. Ventilation: No special requirements. No special handling is required.
3. Skin and eye contact; protective covering; treatment in case of contact: No special equipment or clothing required; however, at all times, from deployment to reuse to disposal of AquaPal®, it is recommended that deployment personnel wear appropriate personal protective equipment including, but not limited to, impervious gloves, goggles, face masks/shields (as necessary that be dependent upon local air quality testing), and Tyvek suits. If eye or skin irritation occurs, flush with plenty of fresh water. Depending upon the type of spill and specific oil spilled, there may be supplemental safety requirement at the spill site. It is strongly recommended that deployment personnel follow all health and safety recommendations established for the spill site.
- 4.a. Maximum storage temperature: 120°F continuous, 140°F up to 5 days.
- 4.b. Minimum storage temperature: No minimum
- 4.c. Optimum storage temperature range: 40°F to 120°F

4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

Shelf life is unlimited when stored in plastic bags.

VI. RECOMMENDED APPLICATION PROCEDURE

Mechanism of Action:

AquaPal® is an open-cell foam manufactured in continuous rolls from polymers that are naturally oleophilic (and thus water repellant/hydrophobic). AquaPal® is deployed in roll form and/or fabricated into various configurations (e.g., eelgrass, pads, netted booms). When placed in an environment of oil and water, AquaPal® attracts oil and repels water. The open-cell structure provides capillaries for the oil to fill, and oil travels into the foam structure by capillary action. AquaPal® should be removed from the spill environment when the products are saturated with oil; and the oil should be disposed of according to federal, state, and local regulations.

The following are examples of various product configurations of AquaPal®:

- Example – AquaPal® foam rolls with thickness of 1/4 – 3/8 inches, widths of 20 to 60 inches, and lengths of 2 – 100 feet can be deployed directly on an oil patch/slick to absorb the oil from the water surface.
- Example – AquaPal® foam is fabricated into 10-foot strips to make round, netted booms. These booms can be connected end-to-end and positioned in front and/or behind containment booms to absorb oil that has breached the containment.
- Example – AquaPal® foam is fabricated into 3/8-inch-thick x 1/2-inch-wide x 6-inch-long pads that can be deployed by placing on an oil patch to absorb the oil from the water surface.
- Example – AquaPal® foam can be cut into small strips such as 3/8-inch-thick x 1/2-inch-wide x 6 inches long and contained in a net or mesh bag to create a high surface area oil absorbent filter bag.
- Example – AquaPal® foam can be fabricated into eelgrass configurations of 5-foot sections with a rope and carabiner clips at each end with eelgrass blades of 3/8-inch-thick x 3/4-inches wide x 18 inches long to be connected on the back of a containment boom systems to absorb oil which flows over or under the boom, especially in marsh areas and other sensitive ecosystems.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
AQUAPAL®	Menidia beryllina	3134.10 96-hr
	Mysidopsis bahia	>17040.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	18.84 96-hr
	Mysidopsis bahia	3.40 48-hr
AQUAPAL® & No. 2 Fuel Oil (1:10)	Menidia beryllina	17.76 96-hr
	Mysidopsis bahia	3.56 48-hr
Reference Toxicant (SLS)	Menidia beryllina	3.56 96-hr
	Mysidopsis bahia	7.02 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point (ASTM D-56): >212°F
2. Pour Point: NA, solid product
3. Viscosity: NA, solid product
4. Specific Gravity (ASTM D-792): 0.386 g/mL
5. pH: NA
6. Surface Active Agents: NA
7. Solvents: NA
8. Additives: CONFIDENTIAL
9. Solubility in Water: Not soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<3.86 (mg/L)
Cadmium	<0.725 (mg/L)
Chromium	<1.70 (mg/L)
Copper	1.90 (mg/L)
Lead	<1.21 (mg/L)
Mercury	<0.0036 (mg/L)
Nickel	0.954 (mg/L)
Zinc	16.3 (mg/L)
Cyanide	0.02 (mg/L)
Chlorinated Hydrocarbons	<5.00 (mg/L)

**HERDING AGENTS (FORMERLY
KNOWN AS SURFACE COLLECTING
AGENTS): TECHNICAL NOTEBOOK
BULLETINS**

TECHNICAL PRODUCT BULLETIN #S-5
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JUNE 29, 2012
UPDATED LISTING LETTER DATE: SEPTEMBER 25, 2023
“THICKSLICK 6535”

I. NAME, BRAND, OR TRADEMARK

THICKSLICK 6535

Type of Product: Surface Collecting Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

EKL Leasing Company

4500 Clinton Street

West Seneca, NY 14224

Phone: 716-465-1730

E-mail: Oilfence@aol.com

(Mr. Peter Lane)

Mailing Address

P.O. Box 575

Orchard Park, NY 14127

(Mr. Peter Lane)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

EKL Leasing Company

4500 Clinton Street

West Seneca, NY 14224

Phone: 716-465-1730

E-mail: Oilfence@aol.com

(Mr. Peter Lane)

Mailing Address

P.O. Box 575

Orchard Park, NY 14127

(Mr. Peter Lane)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: IMO – Non-Flammable; DOT – Non-Hazardous

2. Ventilation: Use with ventilation equal to unobstructed outdoors in a moderate breeze

3. Skin and eye contact; protective covering; treatment in case of contact: May produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. May cause skin irritation after prolonged or repeated exposure. Avoid skin and clothing contact. If skin contact occurs, immediately wash with large amounts of soap and water (if possible). Remove any contaminated clothing and shoes. Launder before reusing. If irritation persists, seek medical assistance. For areas where contact is likely, wear long sleeve shirt, chemical resistant gloves, and chemical resistant goggles.

4.a. Maximum storage temperature: 120°F

4.b. Minimum storage temperature: -40°F

4.c. Optimum storage temperature range: 59°F to 77°F

4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

Minimum of three years in unopened container.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Spray on water around the perimeter of an oil slick using a pressurized backpack sprayer or aerial applicator.
2. Concentration/Application Rate: 6.4 U.S. gallons/mile (or 15L/km).
3. Conditions for Use: THICKSLICK 6535 is designed to aid in situ burning of free oil in calm water with drift ice where fire boom would be ineffective. When sprayed on the water around the perimeter of an oil slick, THICKSLICK 6535 will concentrate the oil to a thickness suitable for igniting a burn. It works in all water temperatures and salinities and works best with fluid petroleum that has not weathered significantly.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
THICKSLICK 6535	Menidia beryllina	138 96-hr
	Mysidopsis bahia	286 48-hr
No. 2 Fuel Oil	Menidia beryllina	37.6 96-hr
	Mysidopsis bahia	2.43 48-hr
THICKSLICK 6535 & No. 2 Fuel Oil (1:10)	Menidia beryllina	5.91 96-hr
	Mysidopsis bahia	1.53 48-hr
Reference Toxicant (SDS)	Menidia beryllina	3.02 96-hr
	Mysidopsis bahia	8.23 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >180°F
2. Pour Point: 21.2 °F
3. Viscosity: 118 SUS at 100 °F
4. Specific Gravity: 0.9745 at 60°F
5. pH: 6.45
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL
8. Additives: None
9. Solubility in Water: Partly miscible

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND
Cadmium	ND
Chromium	ND
Copper	ND
Lead	ND
Mercury	ND
Nickel	ND
Zinc	ND
Cyanide	ND
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #S-6
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JUNE 29, 2012
UPDATED LISTING LETTER DATE: SEPTEMBER 25, 2023
“SILTECH OP-40”

I. NAME, BRAND, OR TRADEMARK
SILTECH OP-40

Type of Product: Surface Collecting Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

EKL Leasing Company
4500 Clinton Street
West Seneca, NY 14224
Phone: 716-465-1730
E-mail: Oilfence@aol.com
(Mr. Peter Lane)

Mailing Address
P.O. Box 575
Orchard Park, NY 14127
(Mr. Peter Lane)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

EKL Leasing Company
4500 Clinton Street
West Seneca, NY 14224
Phone: 716-465-1730
E-mail: Oilfence@aol.com
(Mr. Peter Lane)

Mailing Address
P.O. Box 575
Orchard Park, NY 14127
(Mr. Peter Lane)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: IMO – Non-Flammable; DOT – Non-Hazardous
2. Ventilation: Use with ventilation equal to unobstructed outdoors in a moderate breeze
3. Skin and eye contact; protective covering; treatment in case of contact: May produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. May cause skin irritation after prolonged or repeated exposure. Avoid skin and clothing contact. If skin contact occurs, immediately wash with large amounts of soap and water (if possible). Remove any contaminated clothing and shoes. Launder before reusing. If irritation persists, seek medical assistance. For areas where contact is likely, wear long sleeve shirt, chemical resistant gloves, and chemical resistant goggles.
- 4.a. Maximum storage temperature: 120°F
- 4.b. Minimum storage temperature: -40°F
- 4.c. Optimum storage temperature range: 59°F to 77°F
- 4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

Minimum of three years in unopened container.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Spray on water around the perimeter of an oil slick using a pressurized backpack sprayer or aerial applicator.
2. Concentration/Application Rate: 6.4 U.S. gallons/mile (or 15L/km).
3. Conditions for Use: SILTECH OP-40 is designed to aid in situ burning of free oil in calm water with drift ice where fire boom would be ineffective. When sprayed on the water around the perimeter of an oil slick, SILTECH OP-40 will concentrate the oil to a thickness suitable for igniting a burn. It works in all water temperatures and salinities and works best with fluid petroleum that has not weathered significantly.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
SILTECH OP-40	Menidia beryllina	3.33 96-hr
	Mysidopsis bahia	6.83 48-hr
No. 2 Fuel Oil	Menidia beryllina	40.50 96-hr
	Mysidopsis bahia	6.43 48-hr
SILTECH OP-40 & No. 2 Fuel Oil (1:10)	Menidia beryllina	9.70 96-hr
	Mysidopsis bahia	3.27 48-hr
Reference Toxicant (SDS)	Menidia beryllina	2.33 96-hr
	Mysidopsis bahia	8.68 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >180°F
2. Pour Point: -74.2 °F
3. Viscosity: 53 SUS at 100 °F
4. Specific Gravity: 0.98816 at 60°F
5. pH: 8.03
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: None
8. Additives: None
9. Solubility in Water: Partly miscible

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND
Cadmium	ND
Chromium	ND
Copper	ND
Lead	ND
Mercury	ND
Nickel	ND
Zinc	ND
Cyanide	ND
Chlorinated Hydrocarbons	ND

SURFACE WASHING AGENTS: **TECHNICAL NOTEBOOK BULLETINS**

TECHNICAL PRODUCT BULLETIN #SW-2
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JANUARY 7, 1985
REVISED LISTING DATE: AUGUST 21, 1995
"TOPSALL #30"
(aka, SUPERALL #38)

I. NAME, BRAND, OR TRADEMARK
TOPSALL #30 (AKA, SUPERALL #38)
Type of Product: Surface Washing Agent (Oil and Petroleum Cleaning Agent)
(formerly #D-20)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT	
<u>TOPSALL #30</u>	<u>SUPERALL #38</u>
Stutton North Corporation	Superall Products LLP
P.O. Box 724	P.O. Box 2954
Mandeville, LA 70470	Spring, TX 77383
Phone: (985) 626-3900	Phone: (281) 351-4800
Fax: (985) 674-0476	Fax: (281) 351-4855
(Mr. David Anton)	E-mail: info@superall.com
	Website: www.superall.com
	(Mr. Sammy Roberts II)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS	
<u>TOPSALL #30</u>	<u>SUPERALL #38</u>
Stutton North Corporation	Superall Environmental LLC
P.O. Box 724	P.O. Box 2954
Mandeville, LA 70470	Spring, TX 77383
Phone: (985) 626-3900	Phone: (281) 351-4800
Fax: (985) 674-0476	Fax: (281) 351-4855
(Mr. David Anton)	E-mail: info@superall.com
	Website: www.superall.com
	(Mr. Sammy Roberts II)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: TOPSALL #30 (aka, SUPERALL #38) is non-flammable.
2. Ventilation: Normal type household ventilation is adequate for handling and storage.
3. Skin and eye contact; protective clothing; treatment in case of contact:
In case of contact with eyes, wash thoroughly with large amounts of water. If irritation persists, seek medical attention. Use protective gloves for manual cleaning.
- 4.a. Maximum storage temperature: 120°F
- 4.b. Minimum storage temperature: 20°F

4.c. Optimum storage temperature range: 40°F to 100°F

4.d. Temperatures of phase separations and chemical changes: TOPSALL #30 (aka, SUPERALL #38) has a pour point of 20°F and a boiling point of 212°F.

V. SHELF LIFE

TOPSALL #30 (aka, SUPERALL #38) has a shelf life of not less than two years.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: For general use, apply by spray, mop, etc. Agitate severe spots and rinse thoroughly for a residue-free surface.

2. Concentration/Application Rate: Normal cleaning (rigs and platforms, bilges, decks, waterline scum, shop machinery and equipment) use 1 part TOPSALL #30 (aka, SUPERALL #38) to up to 20 parts water.

Heavy cleaning (degassing tanks and barges, engine rooms and soot, oil stained concrete, petroleum based drilling muds) use 1 part TOPSALL #30 (aka, SUPERALL #38) to up to 15 parts water.

Severe cleaning (Black magic, Bunker C, crude oil, holding tanks, grease traps) use 1 part TOPSALL #30 (aka, SUPERALL #38) to up to 5 parts water.

Steam cleaning use 1 part TOPSALL #30 (aka, SUPERALL #38) to up to 50 parts of water.

Pressure wash use 1 part TOPSALL #30 (aka, SUPERALL #38) to up to 30 parts water.

DO NOT USE UNDILUTED ON COMPOSITION FLOORS, WATER BASED PAINTED SURFACES, OR ALUMINUM.

3. Conditions for Use: Recommended for cleaning petroleum fractions from decks, platforms, bilges, rigs, and other seagoing equipment, as noted above.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
TOPSALL #30	Menidia beryllina	156.60 96-hr
(aka, SUPERALL #38)	Mysidopsis bahia	115.80 48-hr
No. 2 Fuel Oil	Menidia beryllina	6.40 96-hr
	Mysidopsis bahia	1.30 48-hr
TOPSALL #30	Menidia beryllina	4.60 96-hr
(aka, SUPERALL #38) &	Mysidopsis bahia	5.00 48-hr
No. 2 Fuel Oil (1:10)		
Reference Toxicant (DSS)	Menidia beryllina	1.60 96-hr
	Mysidopsis bahia	10.00 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >212°F
2. Pour Point: 20°F
3. Viscosity: 30.53 SUS at 100°F
4. Specific Gravity: 1.06 at 70°F
5. pH: 12.6
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: None
8. Additives: CONFIDENTIAL
9. Solubility: Miscible with water

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.05
Cadmium	<0.002
Chromium	0.031
Copper	0.25
Lead	0.02
Mercury	<0.01
Nickel	<0.01
Zinc	0.25
Cyanide	<0.1
Chlorinated Hydrocarbons	<0.1

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**11/03/2008
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-9
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: MAY 25, 1989
REVISED LISTING DATE: APRIL 16, 1996
“CN-110”

I. NAME, BRAND, OR TRADEMARK

CN-110

Type of Product: Surface Washing Agent
(formerly D-37)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Chemex, Inc.

107-B Balboa Drive

Broussard, LA 70518

Phone: updated information required

E-mail: updated information required

(Contact: updated information required)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Chemex, Inc.

107-B Balboa Drive

Broussard, LA 70518

Phone: updated information required

E-mail: updated information required

(Contact: updated information required)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.

2. Ventilation: None needed.

3. Skin and eye contact; protective clothing; treatment in case of contact: As in handling any industrial chemical, the standard precautions of wearing chemical-resistant gloves and eye protection are recommended.

4.a. Maximum storage temperature: 120°F

4.b. Minimum storage temperature: -40°F

4.c. Optimum storage temperature range: 70°F-80°F

4.d. Temperatures of phase separations and chemical changes: Product does not lose effectiveness between temperatures of -40°F through 120°F, although it will become hazy if the temperature is sustained at less than 30°F over a 24-hour period.

V. SHELF LIFE:

CN-110 has a shelf life of 2 years.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: There are no application restrictions. The preferred application method is by spraying and/or applying the product over the pollutant (primarily oil of any viscosity) on the stained area. Immediately, the product begins to work on breaking the physical bond between the oil and the object desired to be cleaned. The full effect of CN-110 on hard, porous and most non-porous materials usually takes a minimum of 30 minutes with a maximum retention time of 60 minutes. Then the freed oil is sprayed off with available water. The oil is then safely and effectively skimmed without dispersed oil remaining in the affected waters. If "herding" or "corralling" a slick is desired, CN-110 can also be applied without the increased toxicities by dispersing minute particles of oil into the affected water stream.

2. Concentration/Application Rate: Application concentration for cleaning shorelines is approximately 1 gallon per 75-100 square feet of affected area. Depending on depths of shorelines, this amount will give a residual of much less than 1 ppm of CN-110 in the affected waters. This residual should be lower than the toxicity of the spilled oil.

If "herding" is desired, the application concentration should be in its original state while either spraying CN-110 around the slick or dropping small amounts from a plane. The resulting residual concentration in this case should be the same as shoreline cleaning or less.

If it is desired that CN-110 be added to a high-pressure cleaning system or steam, the dilution rate should be no lower than 10%. This will lower the CN-110 residual in the affected waters to the parts per billion range.

3. Conditions for Use: Preferably fresh water, at temperature of 32°F.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
CN-110	Menidia beryllina	52,233.00 96-hr
	Mysidopsis bahia	12,262.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	1.90 96-hr
	Mysidopsis bahia	0.90 48-hr
CN-110	Menidia beryllina	7.40 96-hr
No. 2 Fuel Oil (1:10)	Mysidopsis bahia	1.19 48-hr
Reference Toxicant (DSS)	Menidia beryllina	1.80 96-hr
	Mysidopsis bahia	5.90 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: None
2. Pour Point: 30°F
3. Viscosity: 45.7 cSt at 78°F
4. Specific Gravity: 1.025
5. pH: 11.4
6. Surface Active Agents: Trace amounts of a sulfonated compound
7. Solvents: None
8. Additives: Complex silicate solution
9. Solubility: NA

X. ANALYSIS FOR HEAVY METALS, CYANIDES, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.22
Cadmium	<0.088
Chromium	0.109/0.131*
Copper	0.238/0.234*
Lead	<0.275
Mercury	<0.0001
Nickel	<0.11
Zinc	<0.374/<0.369*
Cyanide	0.25
Chlorinated Hydrocarbons	ND

* Duplicate Analyses

TECHNICAL PRODUCT BULLETIN #SW-10
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 21, 1989
REVISED LISTING DATE: SEPTEMBER 27, 1995
“COREXIT™ EC9580A”

I. NAME, BRAND, OR TRADEMARK
COREXIT™ EC9580A

Type of Product: Surface Washing Agent (hydrocarbon based)
(formerly COREXIT 9580 SHORELINE CLEANER; D-38)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Corexit Environmental Solutions LLC

11177 South Stadium Drive
Sugar Land, TX 77478

Product Management:

Phone: (281) 632-8827

E-mail: corexitinfo@corexit.com

(Mr. Huw Jones)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Corexit Environmental Solutions LLC

11177 South Stadium Drive
Sugar Land, TX 77478

Product Management:

Phone: (281) 632-8827

E-mail: corexitinfo@corexit.com

(Mr. Huw Jones)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: IMO nonflammable; DOT combustible
2. Ventilation: Use with ventilation equal to unobstructed outdoors in moderate breeze.
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid contact with eyes, skin and clothing. Wash skin with soap and water. Flush eyes with plenty of water until irritation subsides. Remove to fresh air.
- 4.a. Maximum storage temperature: 170°F
- 4.b. Minimum storage temperature: -30°F
- 4.c. Optimum storage temperature range: 40°F-100°F
- 4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

The shelf life of unopened drums of COREXIT™ EC9580A is unlimited.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: COREXIT™ EC9580A contains a balanced formula of specifically selected biodegradable surfactants in a de-aromatized hydrocarbon solvent system. COREXIT™ EC9580A has a very low degree of toxicity to marine and shoreline organisms.

Shorelines, Mangroves, and Seagrasses – COREXIT™ EC9580A is sprayed directly on the oiled rocky shorelines, mangroves or seagrasses full strength as supplied. After a soak time of zero to thirty minutes, rinse the cleaner and the oil released from the shoreline surface into the water where it can be readily recovered by conventional means such as skimmers or absorbents. The soak time may vary with temperature, oil density and degree of weathering.

2. Concentration/Application Rate: The recommended dosage is approximately 1 gallon per 100 square feet but this can vary depending on the amount of weathering and oiling. The product should be applied full strength as supplied. Since it is hydrocarbon-based, the product should not be diluted with water during application as this will greatly reduce effectiveness.

3. Conditions for Use: COREXIT™ EC9580A is useful on shorelines in fresh or salt water. It is effective on all types of oil including heavily weathered and emulsified oil (“chocolate mousse”) containing up to 50 percent water.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
COREXIT™ EC9580A	Menidia beryllina	86.88 96-hr
	Mysidopsis bahia	31.96 48-hr
No. 2 Fuel Oil	Menidia beryllina	10.72 96-hr
	Mysidopsis bahia	16.12 48-hr
COREXIT™ EC9580A & No.2 Fuel Oil (1:10)	Menidia beryllina	13.20 96-hr
	Mysidopsis bahia	9.06 48-hr
Reference Toxicant (DSS)	Menidia beryllina	7.02 96-hr
	Mysidopsis bahia	9.82 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer’s recommendations for concentrations and application rates for field use.

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 174°F
2. Pour Point: -65°F
3. Viscosity: 8 cSt at 104°F, 28 cSt at 32°F
4. Specific Gravity: 0.810 at 60°F
5. pH: Not Applicable
6. Surface Active Agents: CONFIDENTIAL

7. Solvents: De-aromatized Hydrocarbon

8. Additives: None

9. Solubility: Not Applicable

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.06
Cadmium	<0.002
Chromium	0.003
Copper	<0.001
Lead	<0.009
Mercury	<0.0002
Nickel	0.01
Zinc	0.041
Cyanide	<0.05
Chlorinated Hydrocarbons	ND

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**3/03/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-11
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JUNE 26, 1989
REMOVAL DATE: SEPTEMBER 15, 1994
RELISTING DATE: JULY 07, 2010
“DE-SOLV-IT INDUSTRIAL FORMULA”

I. NAME, BRAND, OR TRADEMARK
DE-SOLV-IT INDUSTRIAL FORMULA
Type of Product: Surface Washing Agent
(formerly D-40)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Orange-Sol Blending and Packaging
1400 N Fiesta Boulevard
Gilbert, AZ 85233
Phone: (800) 877-7771
Fax: (480) 497-0444
E-mail: updated information required
Website: www.orange-sol.com
(Mr. Albert Farnsworth or
Mr. Jack Farnsworth at (480) 319-0141)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Bell Tech
Master Distributor
P.O. Box 2198
Valdez, AK 99686
Phone: (907) 602-0111
Fax: (907) 835-4535
E-mail: bellenterprise@cvinternet.net
(Mr. Randy Bell)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Not regulated unless shipped by land in a package having a capacity of 3,500 gallons or more). Combustible Class IIIA per OSHA, 29 CFR 1910.106
2. Ventilation: No special requirements
3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment of clothing required; however, goggles are recommended where splash is potential. If eye or skin

irritation occurs, flush with ample fresh water.

4.a. Maximum storage temperature: 120°F continuous, 140°F up to 5 days

4.b. Minimum storage temperature: -20°F

4.c. Optimum storage temperature range: 0°F to 120°F

4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

Two (2) years in sealed polydrums or totes (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: DE-SOLV-IT (DSI) is to be used in neat form. DSI works just as well with fresh or salt water. This product works well with all types of oils. Product can be used on oil-contaminated beaches.

2. Concentration/Application Rate: Use DSI directly on the contaminated area, or up to approximately a 1:10 dilution ratio (product:water). Lighter oils will require a 1:10 to 1:30 product to water dilution ratio. Warmer waters (greater than 78°F) and/or good agitation during application will require less product. Response personnel can determine best method to collect clean up residue. Clean up residue should be collected and disposed of in accordance to local, state, and federal regulations.

3. Conditions for Use: Effective in salt or fresh water, with no limitations as to usage within optimum temperature parameters (application may be made at or above 35°F, with optimum above 48°F).

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
DE-SOLV-IT	Menidia beryllina	37.71 96-hr
	Mysidopsis bahia	4.57 48-hr
No. 2 Fuel Oil	Menidia beryllina	3.76 96-hr
	Mysidopsis bahia	2.04 48-hr
DE-SOLV-IT & No. 2 Fuel Oil (1:10)	Menidia beryllina	9.40 96-hr
	Mysidopsis bahia	1.68 48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.25 96-hr
	Mysidopsis bahia	11.71 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 145°F

2. Pour Point: -84°F

3. Viscosity: 1.8 cSt @ 40°C

4. Specific Gravity: 1.8345 @60°F
5. pH: 6.6
6. Surface Active Agents: Nonionic PROPRIETARY Surfactants
7. Solvents: PROPRIETARY
8. Additives: None
9. Solubility: Miscible in oil and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.010
Cadmium	<0.005
Chromium	<0.015
Copper	<0.015
Lead	<0.010
Mercury	<1 µg/L
Nickel	<0.025
Zinc	0.015
Cyanide	<0.010
Chlorinated Hydrocarbons	<6.00

LISTING CHANGES PENDING;
VERIFICATION BY MANUFACTURER AND EPA REQUIRED

TECHNICAL PRODUCT BULLETIN #SW-12
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: AUGUST 11, 1989
REVISED LISTING DATE: NOVEMBER 2, 1995
“PREMIER 99”

I. NAME, BRAND, OR TRADEMARK

PREMIER 99

Type of Product: Surface Washing Agent (Water Based)
(formerly D-41)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Gold Coast Chemical Products

2357 Stirling Road

Dania Beach, FL 33312

Phone: (954) 893-0044

Fax: (954) 893-8884

E-mail: noslime@goldcoastchemical.com

(Mr. Eli Finkelberg or Ms. Maria Morris)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Gold Coast Chemical Products

2357 Stirling Road

Dania Beach, FL 33312

Phone: (954) 893-0044

Fax: (954) 893-8884

E-mail: noslime@goldcoastchemical.com

(Mr. Eli Finkelberg or Ms. Maria Morris)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: None

2. Ventilation: Adequate ventilation is needed if in closed environment.

3. Skin and eye contact; protective clothing; treatment in case of contact: Skin and eye contact: Detergents will defat skin and eyes. May cause irritation. Protective clothing: Use protective gloves for manual cleaning and splash goggles. Treatment in case of contact: If splashed on skin, wash with copious amounts of water. If ingested, drink diluted vinegar or lemon juice. Get medical attention.

4.a. Maximum storage temperature: 125°F

4.b. Minimum storage temperature: 0°F

4.c. Optimum storage temperature range: 0°F - 75°F

Avoid freezing the product. If material freezes and separation is experienced, it should be warmed and mixed together.

4.d. Temperatures of phase separations and chemical changes: No separation expected down to 20°F.

V. SHELF LIFE

Unopened material – at least 5 years is expected.

Opened material – at least 2 years is expected.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Apply by spray, mop, or pressure washer, etc. Agitate severe spots. Rinse thoroughly for residue free surface.

2. Concentration/Application Rate:

Normal Cleaning – 1 part PREMIER 99 to up to 20 parts water.

Heavy Cleaning – 1 part PREMIER 99 to up to 15 parts water.

Severe Cleaning – 1 part PREMIER 99 to up to 5 parts water.

Steam Cleaning – 1 part PREMIER 99 to up to 50 parts water.

Pressure Wash – 1 part PREMIER 99 to up to 30 parts water.

3. Conditions for Use: Water salinity, water temperature, types and ages of pollutants are not determined.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
PREMIER 99	Menidia beryllina	565.70 96-hr
	Mysidopsis bahia	94.70 48-hr
No. 2 Fuel Oil	Menidia beryllina	10.20 96-hr
	Mysidopsis bahia	2.10 48-hr
PREMIER 99 & No. 2 Fuel Oil (1:10)	Menidia beryllina	8.20 96-hr
	Mysidopsis bahia	2.50 48-hr
Reference Toxicant (DSS)	Menidia beryllina	1.55 96-hr
	Mysidopsis bahia	7.96 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 160°F

2. Pour Point: NA
3. Viscosity: 15 cps
4. Specific Gravity: 1.01
5. pH: 10 - 11.5
6. Surface Active Agents: Active 8000* - Purity Chemical <10%
7. Solvents: <5%
8. Additives: <5%
9. Solubility: Complete in Water

*NOTE: Particular chemical composition of Active 8000 is considered by Purity Chemical as a trade secret. More detailed information can be given by Purity Chemical – Mr. Jim Palmer, 1800 NW 70th Avenue, Miami, FL 33126, 1-800-654-0235, FAX (305) 592-2601.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	< 0.01
Cadmium	< 0.0005
Chromium	< 0.1
Copper	< 0.1
Lead	< 0.005
Mercury	< 0.001
Nickel	< 0.5
Zinc	< 0.1
Cyanide	< 0.005
Chlorinated Hydrocarbons	ND

LISTING CHANGES PENDING;
VERIFICATION BY MANUFACTURER AND EPA REQUIRED

TECHNICAL PRODUCT BULLETIN #SW-15
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: APRIL 23, 1990
REVISED LISTING DATE: AUGUST 30, 1995
“SIMPLE GREEN®”

I. NAME, BRAND, OR TRADEMARK
SIMPLE GREEN®

Type of Product: Surface Washing Agent (Water Based)
(formerly D-46)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Sunshine Makers, Inc.

15922 Pacific Coast Highway
Huntington Beach, CA 92649
Phone: (800) 228-0709
Phone: (562) 795-6000
Fax: (562) 592-3830
E-mail: LLorincz@simplegreen.com
(Ms. Laura Lorincz)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Sunshine Makers, Inc.

15922 Pacific Coast Highway
Huntington Beach, CA 92649
Phone: (800) 228-0709
Phone: (562) 795-6000
Fax: (562) 592-3830
E-mail: LLorincz@simplegreen.com
(Ms. Laura Lorincz)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD
APPLICATION

1. Flammability: Non-flammable.
2. Ventilation: Not required.
3. Skin and eye contact; protective clothing; treatment in case of contact: SIMPLE GREEN® is safe for use on skin and will not cause irritation in the majority of users. Avoid contact with eyes, irritation may result. Wear splash goggles or full face-shield and have eye washing equipment available in areas where potential is high for eye contact. No special precautions or additional protective equipment are required during handling or use. SIMPLE GREEN® is provided with a Material Safety Data Sheet (No. 1002).

- 4.a. Maximum storage temperature: 140°F
- 4.b. Minimum storage temperature: 34°F
- 4.c. Optimum storage temperature range: >32°F and <140°F
- 4.d. Temperatures of phase separations and chemical changes: SIMPLE GREEN® is stable and phase separation will not occur at temperatures within the above storage range.

V. SHELF LIFE

SIMPLE GREEN® has an unlimited shelf life.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Spray on oily surface.
2. Concentration/Application Rate: For open water, spray concentrated product directly on surface of oil at a ratio of 4 parts of oil to 1 part of SIMPLE GREEN®. Site conditions may warrant alternative procedures to maintain effectiveness.
3. Conditions for Use: Equally effective in fresh water, estuarine, and marine environments at all temperatures. SIMPLE GREEN® contains no known EPA Priority Pollutants.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
SIMPLE GREEN®	Menidia beryllina	27.90 96-hr
	Mysidopsis bahia	77.60 48-hr
No. 2 Fuel Oil	Menidia beryllina	6.50 96-hr
	Mysidopsis bahia	3.70 48-hr
SIMPLE GREEN® & No. 2 Fuel Oil (1:10)	Menidia beryllina	8.30 96-hr
	Mysidopsis bahia	4.40 48-hr
Reference Toxicant (DSS)	Menidia beryllina	7.80 96-hr
	Mysidopsis bahia	21.20 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

VIII. MICROBIOLOGICAL ANALYSIS

SIMPLE GREEN® contains no microorganisms, enzymes, or biological material.

IX. PHYSICAL PROPERTIES

1. Flash Point: >200°F
2. Pour Point: None
3. Viscosity: 2.0 Centistokes at 78°F
4. Specific Gravity: 1.0257 g/ml at 72°F
5. pH: 9.5
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL

8. Additives: CONFIDENTIAL

9. Solubility: Infinitely miscible.

(Increasing salt concentrations in marine ecosystems will lead to complexes with SIMPLE GREEN[®] that may become visible at ratios above one part SIMPLE GREEN[®] to 99 parts seawater.)

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<5.0000
Cadmium	<0.0233
Chromium	0.1150
Copper	<0.7500
Lead	0.0776
Mercury	<0.0125
Nickel	<2.3000
Zinc	<4.4000
Cyanide	<1.0000
Chlorinated Hydrocarbons	<1.0

TECHNICAL PRODUCT BULLETIN #SW-16
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 8, 1991
REVISED LISTING DATE: JUNE 14, 1995
"AQUACLEAN"

I. NAME, BRAND, OR TRADEMARK
AQUACLEAN
Type of Product: Surface Washing Agent
(formerly D-52)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Madison Chemical Company, Inc.
3141 Clifty Drive
Madison, IN 47250
Phone: (812) 273-6000
Fax: (812) 273-6002
E-mail: steve.preece@madchem.com
(Dr. Steve Preece)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Madison Chemical Company, Inc.
3141 Clifty Drive
Madison, IN 47250
Phone: (812) 273-6000
Fax: (812) 273-6002
E-mail: steve.preece@madchem.com
(Dr. Steve Preece)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.
2. Ventilation: Handle in a well-ventilated space. Local exhaust is recommended if TLV's are exceeded.
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid eye and skin contact. In case of such contact, immediately flush with large amount of cool water for at least 15 minutes, and call a physician. Wear protective eye goggles, impermeable protective gloves, and protective clothing when handling the product. Wash contaminated protective equipment (including clothing, shoes, eye goggles, gloves, etc.) thoroughly in soap and water, rinse repeatedly in clean water and dry before reuse. Avoid ingestion, breathing dusts, mists, or fumes. In case of ingestion, induce vomiting, give water and call a physician. In case of inhalation, move the affected person to fresh air, and call a physician.
- 4.a. Maximum storage temperature: 140°F

- 4.b. Minimum storage temperature: 50°F
 4.c. Optimum storage temperature range: >50°F to <104°F
 4.d. Temperatures of phase separations and chemical changes: <50°F, >104°F

V. SHELF LIFE

18 months if stored between 50°F and 104°F, and away from acids.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: AQUACLEAN may be introduced with a pressure spray to cover the affected area, after the appropriate dilution or concentration is prepared. After application, agitate spill area with water using a solid stream flow.
 For manual cleaning with AQUACLEAN, follow instructions in the product data sheet provided by the manufacturer.
2. Concentration/Application Rate: For small spills, dilute 3 to 1 with water and apply as above. For large spills, prepare a 33% solution of AQUACLEAN and apply through a foam eductor at 6% setting with approximately 90 gallons per minute flow at the nozzle.
 For spills on shorelines and beaches, dilute AQUACLEAN 50% with fresh water and apply using a pressure spray to cover the entire contaminated area. Then rinse with fresh water.
3. Conditions for Use: Water temperature should be above 41°F.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
AQUACLEAN	Menidia beryllina	70.7 96-hr
	Mysidopsis bahia	32.7 48-hr
No. 2 Fuel Oil	Menidia beryllina	4.4 96-hr
	Mysidopsis bahia	1.8 48-hr
AQUACLEAN and	Menidia beryllina	6.5 96-hr
No. 2 Fuel (1:10)	Mysidopsis bahia	2.1 48-hr
Reference Toxicant (DSS)	Menidia beryllina	1.4 96-hr
	Mysidopsis bahia	4.9 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: None detected
2. Pour Point: -20°F
3. Viscosity: 16.5 cP at 25°C (77°F)
4. Specific Gravity: 1.06 at 25°C (77°F)
5. pH: 11.8 (at full strength)
6. Chemical Name and Percentage by Weight of the Total Formulation: CONFIDENTIAL
7. Surface Active Agents: Anionic and nonionic synthetic surfactants.
8. Solvents: CONFIDENTIAL
9. Additives: CONFIDENTIAL
10. Solubility: Completely soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	1.10
Cadmium	0.16
Chromium	0.20
Copper	0.66
Lead	1.83
Mercury	<0.01
Nickel	0.80
Zinc	0.29
Cyanide	0.06
Chlorinated hydrocarbons	4.20

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**6/10/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-18
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: OCTOBER 23, 1996
“NATURE’S WAY HS” *(There is only one listing and no “aka’s” for this product.)*

I. NAME, BRAND, OR TRADEMARK
NATURE’S WAY HS
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Integra Environmental, Ltd.
5825 Centralcrest
Houston, TX 77092
Phone: updated information required
Fax: updated information required
Email: updated information required
Website: updated information required
(Ms. Cathy Kaiser)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Integra Environmental, Ltd.
5825 Centralcrest
Houston, TX 77092
Phone: updated information required
Fax: updated information required
Email: updated information required
Website: updated information required
(Ms. Cathy Kaiser)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.
2. Ventilation: No special precautions are required, but in case of inhalation, move person to fresh air.
3. Skin and eye contact; protective clothing; treatment in case of contact: Flush contaminated skin with plenty of water for at least 15 minutes. Consult a physician if irritation develops. Protective gloves are recommended for extended or prolonged contact, (e.g., immersing hands). Tight fitting safety goggles are recommended for handling product in concentrated form, especially if contacts are worn.
- 4.a. Maximum storage temperature: 130°F

- 4.b. Minimum storage temperature: 32°F
- 4.c. Optimum storage temperature: 90°F
- 4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

NATURE'S WAY HS has a five year shelf life.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: NATURE'S WAY HS may be applied by spraying, pouring, dispensing equipment, or by manual or automatic scrubber machines. Do not mix the product with any other cleaner nor allow any other cleaners to contact surfaces where HS is being used. Hot water should never be used.
2. Concentration/Application Rate: Apply NATURE'S WAY HS full strength (undiluted) to surface area with sprayer, concentrating on areas with heaviest contamination first. To speed clean-up of shorelines and beaches, pressure spray into cracks and crevices prior to scrubbing. Agitate and scrub well using power brushes, hand brushes, brooms or mops. If possible, allow the scrubbed solution to remain on the surface for at least 15 minutes. If allowed to soak overnight, the next morning the treated surface must be re-wet with water, reagitated, and rinsed. Additional product will not be necessary at that time.
3. Conditions for Use: For heavily contaminated surfaces, NATURE'S WAY HS should always be used full strength. For moderate accumulations HS may be diluted to as little as 2 oz. per gallon of cool water for cleaning light contamination. For average contamination, a dilution of 12 oz. per gallon is recommended (1 part NATURE'S WAY HS to 10 parts water). For light use, 4 to 6 oz. of product per gallon water will be sufficient.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
NATURE'S WAY HS	Menidia beryllina	152.14 96-hr
	Mysidopsis bahia	193.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	3.15 96-hr
	Mysidopsis bahia	0.96 48-hr
NATURE'S WAY HS	Menidia beryllina	3.91 96-hr
No. 2 Fuel Oil (1:10)	Mysidopsis bahia	1.07 48-hr
Reference Toxicant (DSS)	Menidia beryllina	- 96-hr
	Mysidopsis bahia	5.71 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

a. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS
NA

IX. PHYSICAL PROPERTIES

1. Flash Point: NA
2. Pour Point: Flowable at all temperatures above freezing
3. Viscosity: <100 CPS
4. Specific Gravity: 1.01
5. pH: 8 - 9.5
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL
8. Additives: CONFIDENTIAL
9. Solubility: NA

X. ANALYSIS FOR HEAVY METALS AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.003
Cadmium	<0.005
Chromium	<0.010
Copper	0.020
Lead	<0.002
Mercury	<0.0002
Nickel	<0.030
Zinc	0.260
Cyanide	<0.020
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-19
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JANUARY 30, 1997
“CYTOSOL”

I. NAME, BRAND, OR TRADEMARK

CYTOSOL

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

CytoCulture International, Inc.

122 Martina Street

Point Richmond, CA 94801-3829

Phone: (510) 233-0102

Fax: (510) 233-3777

Emergency Mobile: (510) 233-0102

E-mail First Response: rvwedel@gmail.com

E-mail: cytoculture@gmail.com

Website: www.cytosolbiosolvent.com

Website: www.cytoculture.com

(Dr. Randall von Wedel)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

CytoCulture International, Inc.

122 Martina Street

Point Richmond, CA 94801-3829

Phone: (510) 233-0102

Fax: (510) 233-3777

Emergency Mobile: (510) 233-0102

E-mail First Response: rvwedel@gmail.com

E-mail: cytoculture@gmail.com

Website: www.cytosolbiosolvent.com

Website: www.cytoculture.com

(Dr. Randall von Wedel)

Foss Environmental, Inc.

7440 West Marginal

Seattle, WA 98108-4141

Phone: (206) 768-1450

Fax: (206) 767-3460

(Mr. Larry Pintler)

Advanced Cleanup Technologies, Inc.

20928 Lamberton Avenue

Carson, CA 90810

Phone: (800) 334-2284

Fax: (310) 763-9076

(Mr. Walt Dorn)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable. However, keep the product away from heat and avoid contact with strong oxidizing agents. Ensure proper disposal of product-saturated absorbents, rags, and combustible materials to avoid the possibility of spontaneous combustion.
2. Ventilation: Product is not volatile. However, in the event of aerosol inhalation, immediately move victim to fresh air. If victim has stopped breathing, give artificial respiration, preferably by mouth to mouth. Get medical attention immediately.
3. Skin and eye contact; protective clothing; treatment in case of contact: The CYTOSOL contains no volatile hydrocarbons or petroleum constituents. However, as a precautionary measure, wear gloves and safety glasses meeting the specifications of ANSI Standard Z87.1. Avoid breathing aerosols. Avoid prolonged contact with skin.
- 4.a. Maximum storage temperature: 110°F
- 4.b. Minimum storage temperature: 39°F
- 4.c. Optimum storage temperature: 55°F
- 4.d. Temperatures of phase separations and chemical changes: Avoid freezing. At temperatures below the cloud point (43°F), the product may become cloudy, but will return to normal upon warming, with no effect on performance. Store product in airtight containers, if possible, without excessive exposure to moisture.

V. SHELF LIFE

Closed container: 10 years in a dry environment.

Open container: 1 year in a warm, humid environment.

The product does not deteriorate appreciably over time, but will grow bacteria if water condensation accumulates in the container.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: The CYTOSOL is applied to oiled shorelines to extract and recover weathered petroleum by flotation with passive water deluges from header pipes or manual spraying. Remaining residual hydrocarbons are biodegraded, either passively by intrinsic bioremediation, or aggressively by enhancing the process with controlled amounts of nutrients and/or acclimated cultures of bacteria cultured from the site, when approved by local, state and federal agencies.

The CYTOSOL process is most suitable for the treatment of heavily oiled shorelines that do not respond well to conventional treatments, or that are considered too sensitive for mechanical/pressure wash strategies. Prior to the application of CYTOSOL, collection booms, oil skimmers, sorbent pads, or other appropriate containment and collection mechanisms must be deployed and operational.

2. Concentration/Application Rate: CYTOSOL may be applied with a variety of spraying or washing equipment, depending upon the scale and type of shoreline to be cleaned. The product is to be used only neat and undiluted, for direct application to spilled oil. For large beach areas, CYTOSOL can be sprayed from water trucks or work boats equipped with pumps, hoses, and

nozzles to deliver the product as an aerial spray. In smaller applications, CYTOSOL may be applied with hand sprayers or portable pumps to spray the product directly onto oiled surfaces. Dose rates will vary with the type and amount of petroleum spilled, the extent of weathering, and other site specific conditions, including temperature, porosity of shoreline, and residence time available to let the product contact the oil. In general, the ratio of applied CYTOSOL to crude oil is between 0.5:1 and 1:1. The quantity of CYTOSOL applied should be approximately equivalent to the quantity of petroleum accumulated on the shoreline, or as required to dissolve and remove weathered oil. After application, the product should be allowed to penetrate and dissolve the weathered petroleum for at least one hour, preferably longer. Cold weather applications will require more contact time before initiating recovery. In tidal areas, it is advisable to apply the CYTOSOL as the tide is ebbing (receding) to maximize contact time. Trapped oil may continue to be released for several days, requiring that containment devices be left in place.

3. Conditions for Use: The following shoreline types are appropriate for the use of CYTOSOL: Coarse sand beaches where petroleum has penetrated into sand; marsh areas and vegetated wetlands where oil has coated plants and become trapped; concrete bulkheads, rip rap and piers that may have trapped oil; oiled pilings; gravel or cobble shorelines and rocky shores, where oil has become trapped in pockets; and, public beaches, fisheries, hatcheries, river banks, and other sensitive or high impact sites. The CYTOSOL has been fielded tested successfully for removing oil from mussel beds and intertidal zones, pilings and concrete rip rap. The CYTOSOL also proved effective in facilitating the removal of oil from the banks and vegetation along an oiled creek.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
CYTOSOL	Menidia beryllina	738.0 96-hr
	Mysidopsis bahia	124.0 48-hr
No. 2 Fuel Oil	Menidia beryllina	38.9 96-hr
	Mysidopsis bahia	5.9 48-hr
CYTOSOL & No. 2 Fuel Oil (1:10)	Menidia beryllina	24.3 96-hr
	Mysidopsis bahia	7.0 48-hr
Reference Toxicant (DSS)	Menidia beryllina	13.8 96-hr
	Mysidopsis bahia	22.2 48-hr

NOTE: This toxicity data was derived with the EPA protocols for dispersants using a blender to emulsify the product into the water for testing organisms. The CYTOSOL emulsion created microdroplets of product which may have had direct physical effects on the test larvae. Since the solubility of the product in water is so low (14 ppm or less), it is probable that the observed effects on the test organisms was caused by larvae having direct contact with droplets of product rather than by a true chemical toxicity from the trace amount of dissolved product. In practice, the CYTOSOL would not be emulsified to any great extent during application. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 360°F
2. Pour Point: 10°F
3. Viscosity: 4.15 CST @ 104°F
4. Specific Gravity: 0.8877 @ 60°F
5. pH: Neutral
6. Surface Active Agents: None
7. Solvents: No Petroleum Distillates
8. Additives: CONFIDENTIAL
9. Solubility: 14 ppm in fresh water, 7 ppm in sea water

X. ANALYSIS FOR HEAVY METALS AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration</u>
Arsenic	ND
Cadmium	ND
Chromium	ND
Copper	ND
Lead	ND
Mercury	ND
Nickel	ND
Zinc	ND
Cyanide	ND
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-20
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: MARCH 21, 1997
“BIOSOLVE® PINKWATER®”

I. NAME, BRAND, OR TRADEMARK

BIOSOLVE® PINKWATER®

Type of Product: Surface Washing Agent
(formerly BIOSOLVE® HYDROCARBON MITIGATION™ AGENT)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

The BioSolve® Company

24 Victory Lane

Dracut, MA 01826

Phone: (781) 482-7900 or (800) 225-3909

Fax: (781) 482-7909

Website: www.biosolve.com

E-mail: info@biosolve.com

(Mr. Stephen Hosmer)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

The BioSolve® Company

24 Victory Lane

Dracut, MA 01826

Phone: (781) 482-7900 or (800) 225-3909

Fax: (781) 482-7909

Website: www.biosolve.com

E-mail: info@biosolve.com

(Mr. Stephen Hosmer)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable

2. Ventilation: Normal

3. Skin and eye contact; protective clothing; treatment in case of contact: Flush contaminated eyes thoroughly with water for 15 minutes, and get medical attention. Remove contaminated clothing, wash exposed area with soap and water, wash clothing before reuse. Get medical attention if irritation develops. Get medical attention for ingestion. No medical attention is necessary with inhalation. There are no special storage requirements or special handling precautions; use good normal hygiene.

4.a. Maximum storage temperature: 120°F (50°C)

4.b. Minimum storage temperature: 35°F (1.5°C)

4.c. Optimum storage temperature: 60°F (15°C)

4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

BIOSOLVE® has a 10+ year shelf life if unopened.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Dilute or use eductors to specified rate and apply through fire hose, power washers, steam powered units, or chemical boom sprayers with nozzles that produce a shearing action. Special nozzles to apply the solution as droplets are not necessary. For shoreline cleanup involving heavy or weathered crude, presoak to a 6% solution may be necessary.

2. Concentration/Application Rate: BIOSOLVE® is a highly concentrated product and must be diluted with water before use. Dilution ratios vary depending on site specific conditions. Dilution ratio's normally run at 6%, 3%, or 1%. For heavy, mousse, or weathered oil, a 3% to 6% solution should be applied. For light or refined products, apply at 2% to 3%. For sheens, apply at .5 to 1%. Since testing shows that BIOSOLVE® quickly emulsifies weathered crude, it is not critical to apply immediately after a spill occurs; impact considerations can be fully considered prior to action taken.

Surface Washing Applications: BIOSOLVE® applied through power washers in light dilution is very effective in attaining the removal of oils from rock, cobblestone, shorelines, and sea walls. In marsh or wetland applications, BIOSOLVE® prevents the oil from clinging to grasses and mangroves.

Rigs and Platforms: BIOSOLVE® is used to inert undersea pipelines before plugging and abandonment, degas tanks and platforms during work over operations, and to wash drill cuttings to remove oils and prevent sheens on surface waters.

3. Conditions for Use: May be used with salt or fresh water. Temperature is not relevant.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
BIOSOLVE®	Menidia beryllina	6.4	96-hr
	Mysidopsis bahia	3.6	48-hr
No. 2 Fuel Oil	Menidia beryllina	5.6	96-hr
	Mysidopsis bahia	2.7	48-hr
BIOSOLVE® & No. 2 Fuel Oil (1:10)	Menidia beryllina	7.4	96-hr
	Mysidopsis bahia	1.3	48-hr
Reference Toxicant (SDS)	Menidia beryllina	7.2	96-hr
	Mysidopsis bahia	13.4	48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and

application rates for field use.

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

(Liquid concentrate)

1. Flash Point: NA, Water based >200°F (93.3°C)

2. Pour Point: 32.9°F (0.5°C)

3. Viscosity: 77.5 Centistokes (concentrate), 490 centipoise (concentrate), 15 centipoise at 6%, at 60.08°F or 15.6°C

4. Specific Gravity: 1.025 at 60°F or 15.5°C

5. pH: 9.37 +/- 0.5

6. Chemical Name and Percentage by Weight of the Total Formulation: CONFIDENTIAL

7. Surface Active Agents: CONFIDENTIAL

8. Solvents: CONFIDENTIAL

9. Additives: CONFIDENTIAL

10. Solubility: Complete-true solution formed with water

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.2
Cadmium	<0.18
Chromium	<0.5
Copper	<0.6
Lead	<0.2
Mercury	<0.07
Nickel	<0.6
Silver	<0.4
Zinc	0.51
Cyanide	<0.01
Chlorinated Hydrocarbons	<0.5

LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:

7/19/2021
7/27/2022

TECHNICAL PRODUCT BULLETIN #SW-21
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: MARCH 2, 1998
“PETROTECH 25”

I. NAME, BRAND, OR TRADEMARK
PETROTECH 25
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Petrotech America Corporation
130 William Street, Suite 802
New York, NY 10038
Phone: (212)933-9071, ext. 7001
Fax: (877) 226-4028
E-mail: Info@helpenvironmental.com
(Mr. Lawrence Gallo)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Petrotech America Corporation
130 William Street, Suite 802
New York, NY 10038
Phone: (212)933-9071, ext. 7001
Fax: (877) 226-4028
E-mail: Info@helpenvironmental.com
(Mr. Lawrence Gallo)

Manufacturing Plant:

Clariant Corp.
Charlotte, NC

H.E.L.P. Environmental
926 3rd Avenue
Brooklyn, NY 11232

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.
2. Ventilation: Normal.
3. Skin and eye contact; protective clothing; treatment in case of contact: No special handling is required beyond that prescribed under the general OSHA rules for non-hazardous, non-flammable and noncorrosive liquids. This is not to suggest that contact with eyes and skin is totally without risk for allergy. Contact with eyes and skin is to be avoided, as suggested under OSHA procedures.
- 4.a. Maximum storage temperature: +45°C

4.b. Minimum storage temperature: -5°C (can be stored below its freezing point without detectable loss of performance provided that it is warmed to within liquid range prior to application.)

4.c. Optimum storage temperature: $>-5^{\circ}\text{C}$ and $\leq +45^{\circ}\text{C}$

4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

PETROTECH 25 has an unlimited shelf-life when maintained in the factory sealed containers and stored within the prescribed temperature limits. Climatic factors such as humidity have no effect on closed container storage although the product is hygroscopic and will absorb water if left for long periods in open containers.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: It is recommended that the surface washing agent PETROTECH 25 be applied to contaminated surfaces in one of three ways: (a) a mixture of ten parts PETROTECH 25 to ninety parts water, either fresh or saltwater, should be discharged over the surface by commercial pressure washer, hot or cold; (b) the same mixture discharged on the surface using standard firefighting apparatus preferably at a nozzle pressure of 100 PSI plus; or (3) PETROTECH 25 in concentrated form can be applied to the surface and manually or mechanically brushed and then water applied.

2. Concentration/Application Rate: Generally, PETROTECH 25 is applied neat in its factory supplied concentrate form. However, for lighter oils where educting or proportioning equipment is available, an aqueous solution of PETROTECH 25 between 3 and 10 percent may be used. Broadly speaking, PETROTECH 25 has no solvent action. For any given oil spill of a specific nature, the application rate is unaffected by neat or diluted application as long as the concentrate to oil ratio remains the same. Applications of diluted PETROTECH 25 in the 6 - 10 percent range via firefighting equipment can be used on automobile and aviation gasoline's together with the lighter oils such as diesel and all jet fuels.

The dosage of PETROTECH 25 to be used depends upon two factors: 1) The nature of the oil, and 2) The energy used in its application to the contaminated substrate.

3. Conditions for Use: May be used with salt or fresh water. Temperature is not relevant.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
PETROTECH 25	Menidia beryllina	601.0 96-hr
	Mysidopsis bahia	350.0 48-hr
No. 2 Fuel Oil	Menidia beryllina	2.8 96-hr
	Mysidopsis bahia	1.8 48-hr
PETROTECH 25 & No. 2 Fuel Oil (1:10)	Menidia beryllina	3.4 96-hr
	Mysidopsis bahia	1.0 48-hr
Reference Toxicant (DSS)	Menidia beryllina	7.9 96-hr
	Mysidopsis bahia	19.8 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

(Liquid concentrate)

1. Flash Point: None
2. Pour Point: 0°C
3. Viscosity: 700 CP
4. Specific Gravity: 1.03
5. pH: 7.5
6. Chemical Name and Percentage by Weight of Total Formulation: CONFIDENTIAL
7. Surface Active Agents: CONFIDENTIAL
8. Solvents: CONFIDENTIAL
9. Additives: CONFIDENTIAL
10. Solubility: 100%

X. ANALYSIS FOR HEAVY METALS AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.10
Cadmium	<0.08
Chromium	<0.10
Copper	<0.26
Lead	0.047
Mercury	<0.0005
Nickel	<0.40
Zinc	0.256
Cyanide	0.70
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-23
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: MARCH 1, 1999
“PETRO-CLEAN”

I. NAME, BRAND, OR TRADEMARK

PETRO-CLEAN

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

B.R.A.T. Microbial Products Inc.

208 Cinnabar Bay Court

League City, TX 77573

Phone: (713) 724-9226

E-mail: alabastercorp@gmail.com

(Mr. John Sheffield)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

B.R.A.T. Microbial Products Inc.

208 Cinnabar Bay Court

League City, TX 77573

Phone: (713) 724-9226

E-mail: alabastercorp@gmail.com

(Mr. John Sheffield)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable

2. Ventilation: Normal

3. Skin and eye contact: Protective clothing; treatment in case of contact. Eyes-flush with water using eye cup of fountain for 15 minutes. Seek medical attention if irritation persists. Wash contaminated clothing and footwear before reuse. Ingestion – seek medical attention. Inhalation – no medical attention is required.

4.a. Maximum storage temperature: 120°F

4.b. Minimum storage temperature: 35°F

4.c. Optimum storage temperature range:

4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

Indefinite when stored properly.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: PETRO-CLEAN is applied through power washers or even garden type sprayers in light dilution is very effective in removing petrochemical hydrocarbons from rocks, shorelines, sea walls, bridges, and highways. In wetland applications, PETRO-CLEAN prevents hydrocarbons from attaching to grasses, trees, rocks, etc.
2. Concentration/Application Rate: Dilute or use eductors to specified rate and apply through fire hose, power washers, or sprayers to contaminated area. PETRO-CLEAN is a highly concentrated product and must be diluted before use. Dilution ratios vary depending on the specific conditions of the contaminated site. Normal recommended dilutions are from 0.5% to 6%. On heavy or weathered crude, pre-soaking with 6% may be necessary. For light or refined products, apply as 3% to 6% solution. For sheens on water apply a 0.5% to 1.0% solution.
3. Conditions for Use: May be used with salt or fresh water

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
PETRO-CLEAN	Menidia beryllina	100	96-hr
	Mysidopsis bahia	110	48-hr
No. 2 Fuel Oil	Menidia beryllina	110	96-hr
	Mysidopsis bahia	110	48-hr
PETRO-CLEAN & No. 2 Fuel Oil (1:10)	Menidia beryllina	115	96-hr
	Mysidopsis bahia	105	48-hr
Reference Toxicant (DSS)	Menidia beryllina	1.14	96-hr
	Mysidopsis bahia	0.98	48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: > 200°F
2. Pour Point: -17°F
3. Viscosity: 1.26 @ 75°F
4. Specific Gravity: 0.99 @ 75°F
5. pH: 8.05 (10% solution, s.u.)
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: None
8. Additives: CONFIDENTIAL
9. Solubility in Water: 100 percent

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.10
Cadmium	<0.10
Chromium	<0.01
Copper	<0.01
Lead	<0.002
Mercury	<0.01
Nickel	<0.01
Zinc	<0.01
Cyanide	<2.0
Chlorinated Hydrocarbons	<1.0

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**8/17/2012
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-24
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JULY 14, 2000
“DO-ALL #18”

I. NAME, BRAND, OR TRADEMARK
DO-ALL #18
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Radcob Solutions, Inc.
4800 North State Road 7, Suite #105
Lauderdale Lakes, FL 33319
Phone: (954) 249-2178
Fax: (954) 640-7080
Email: updated information required
Website: updated information required
(Mr. Adam Goldberg)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Radcob Solutions, Inc.
4800 North State Road 7, Suite #105
Lauderdale Lakes, FL 33319
Phone: (954) 249-2178
Fax: (954) 640-7080
Email: updated information required
Website: updated information required
(Mr. Adam Goldberg)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: DO-ALL #18 is water based, contains no solvents and is non-flammable.
2. Ventilation: Normal room ventilation.
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid contact with skin, eyes, and clothing. Wear safety glasses or goggles and protective gloves when handling. In case of eye contact, flush immediately with water for at least 15 minutes. If persistent irritation occurs, call a physician. For skin contact, wash thoroughly with soap and water.
- 4.a. Maximum storage temperature: 100°F
- 4.b. Minimum storage temperature: 35°F
- 4.c. Optimum storage temperature range: 40°F to 100°F

4.d. Temperatures of phase separations and chemical changes: DO-ALL #18 has a pour point of 32°F and phase separation occurs at 105°F.

V. SHELF LIFE

DO-ALL #18 has a shelf life of at least two (2) years.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: May be diluted with fresh or salt water. For general use, apply by spray, mop, etc. Agitate severe spots, rinse thoroughly for residue-free surface.

2. Concentration/Application Rate: To clean oil from beaches, rocks, and piers as a shore-line cleaner, first use a pre-treatment or soaking, using one (1) part DO-ALL #18 diluted with three (3) parts of water. Allow 30 to 45 minutes to soften viscous oil deposits (soak time may vary with temperature, oil density, and degree of weathering). After the soaking period, dilute one (1) part of DO-ALL #18 with 15 parts of water and apply with a high pressure water hose (50 - 100 PSI). Oil released can then be removed by vacuuming, skimmers, or absorbents.

For normal cleaning of shop machinery, bilges, decks, waterline scum, rigs, and platforms, dilute one (1) part DO-ALL #18 with up to 20 parts of water.

For heavy cleaning and degreasing of tanks, barges, engine rooms and soot, oil stained concrete, and petroleum based drilling muds, dilute one (1) part DO-ALL #18 with up to 15 parts of water.

For severe cleaning of holding tanks, grease traps, black magic, crude oil, and Bunker C, dilute one (1) part DO-ALL #18 with up to five (5) parts of water.

For steam cleaning, dilute one (1) part of DO-ALL #18 with up to 50 parts of water.

For pressure washing, dilute one (1) part DO-ALL #18 with up to 30 parts of water.

DO NOT USE UNDILUTED ON COMPOSITION FLOORS, WATER-BASED PAINTED SURFACES, OR ALUMINUM,

3. Conditions for Use: Recommended for cleaning petroleum fractions from beaches, rocks, piers, bilges, decks, waterline scum, rigs, platforms, tanks, barges, engine rooms, machinery, holding tanks, and grease traps.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
DO-ALL #18	Menidia beryllina	66.10 96-hr
	Mysidopsis bahia	288.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	9.10 96-hr
	Mysidopsis bahia	0.65 48-hr
DO-ALL #18 & No. 2 Fuel Oil (1:10)	Menidia beryllina	9.38 96-hr
	Mysidopsis bahia	0.57 48-hr
Reference Toxicant (SDS)	Menidia beryllina	6.36 96-hr
	Mysidopsis bahia	16.53 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >200°F
2. Pour Point: 32°F
3. Viscosity: 1.8 @ 68°F
4. Specific Gravity: 1.07 @ 68°F
5. pH:13.1
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: None
8. Additives: CONFIDENTIAL
9. Solubility in Water: Soluble with water.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND (<0.02)
Cadmium	ND (<0.02)
Chromium	ND (<0.02)
Copper	0.33
Lead	ND (<0.02)
Mercury	ND (<0.00)
Nickel	ND (<0.10)
Zinc	0.28
Cyanide	0.26
Chlorinated Hydrocarbons	ND (<0.30)

TECHNICAL PRODUCT BULLETIN #SW-25
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JULY 9, 2001
“SC-1000®”

I. NAME, BRAND, OR TRADEMARK

SC-1000®

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

GEMTEK® Products

4640 East Elwood Street

Phoenix, AZ 85040

Emergency Number: (602) 265-8586

Phone: (800) 331-7022

Fax: (602) 265-7241

E-mail: sarahkristoff@gemtek.com

(Ms. Sarah S. Kristoff)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

GEMTEK® Products

4640 East Elwood Street

Phoenix, AZ 85040

Emergency Number: (602) 265-8586

Phone: (800) 331-7022

Fax: (602) 265-7241

E-mail: sarahkristoff@gemtek.com

(Ms. Sarah S. Kristoff)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.

2. Ventilation: General room ventilation is satisfactory.

3. Skin and eye contact; protective clothing; treatment in case of contact: Non-irritating, no first aid needed. May be an eye irritant. Do not spray into eyes; safety glasses are recommended. If irritation does occur, rinse thoroughly with water.

4.a. Maximum storage temperature: None.

4.b. Minimum storage temperature: Room temperature.

4.c. Optimum storage temperature range: 70°F to 90°F

4.d. Temperatures of phase separations and chemical changes: Low temperature can cause handling problems; viscosity of material will increase. The product is an organic compound and it will not typically stratify. The cloud point is 54°F. At 212°F it will boil and at somewhat less (around 130°F) water vapor will form. Repeat freeze/thaw/boiling cycles over a 30-day period

has not demonstrated noticeable break down of the product.

V. SHELF LIFE

Minimum of 5 years.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: SC-1000® is a highly concentrated cleaning compound capable of a multitude of cleaning applications with dilutions ranging from full strength to far in excess of 1:350. Depending on the specific factors in the cleaning environment, the desired cleaning speed with the least amount of SC-1000® can be determined. When diluting, it is recommended that SC-1000® be added to premeasured water to minimize foaming in the solution.

2. Concentration/Application Rate: Beach Waterfront, Rocky Soils, Break Water Structures, and Pier Facilities: For beach sands or light rocky soils, burning or creating a temporary shallow wash tank is most successful. Fill one-half of the tank with contaminated beach sand, then add a solution of SC-1000® and clean water (ocean or fresh) to cover the sand. Gentle agitation will release the oil to the surface of the tank where it can be collected. For rocky surfaces spray with a 20 percent solution of SC-1000® using a horizontal eductor sprayer, spraying side-to-side, allowing the soil to dwell for several minutes before spraying top-to-bottom with clean ocean or fresh water to rinse oil into perimeter oil booms, blankets or impermeable sheeting.

Washing Marine Vegetation - Use a non-pressure/impact spraying equipment to dispense a 0.01 percent SC-1000® solution and allow to stand for 5-10 minutes before a final rinsing with fresh or ocean water. Washing Marine Equipment - For wet oils and bunker crude, use SC-1000™ at 20 percent solution (preferably warmer than 80°F) and spray or wipe. Apply directly to equipment, allow to dwell for 1-2 minutes and then spray rinse with fresh or ocean water. For hardened oils, fuels, and viscous lubricants, apply SC-1000® blended with SC-Supersolve™ (a non-toxic, low aromatic, water miscible solvent) at the ratio of 80/20 then dilute with water to a 50 percent solution, spray or wipe onto surface, let stand for 1-2 minutes before rinsing.

Heavy Cleaning Examples – Dilution full strength 1:5; diesel engines, auto parts, baked on oil or lube grease, dried oil/enamel, latex paints, thick food syrups, insect smears, dried animal or vegetable fats, hard resins, thick dust-laden oily dirt, asphalt and grass or plant stains.

Average Cleaning Examples – Dilution 1:5 up to 1:20; automotive work counters and tools, food and beverage processing equipment, oily or food-laden floors, manufacturing work areas, vehicle maintenance, shipping containers, utility equipment, and parts washers. General Maintenance Examples - 1:20 up to 1:100; vehicle washing, general janitorial for offices/schools/hospitals/recreation and related equipment, pressure sprayers, food preparation and storage, painted/plastic laminate surfaces, sports equipment, general cleaning, immersion tanks, and ultrasonics.

3. Conditions for Use: SC-1000® may be used on any surface that is compatible with water. The product may tarnish some soft aluminum surfaces if not adequately diluted and rinsed with water.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
SC-1000®	Menidia beryllina	26.40 96-hr
	Mysidopsis bahia	15.20 48-hr
No. 2 Fuel Oil	Menidia beryllina	8.85 96-hr
	Mysidopsis bahia	1.57 48-hr
SC-1000® & No. 2 Fuel Oil	Menidia beryllina	4.72 96-hr
	Mysidopsis bahia	2.13 48-hr
Reference Toxicant (SDS)	Menidia beryllina	2.22 96-hr
	Mysidopsis bahia	10.5 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >212°F
2. Pour Point: 25°F
3. Viscosity: <10 cps @ 25°C
4. Specific Gravity: 1.009
5. pH: 10.2 - 10.5
6. Surface Active Agents: CONFIDENTIAL.
7. Solvents: None.
8. Additives: CONFIDENTIAL.
9. Solubility in Water: Soluble in water.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	1.33
Cadmium	ND
Chromium	ND
Copper	0.100
Lead	ND
Mercury	ND
Nickel	ND
Zinc	0.20
Cyanide	ND
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-26
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: AUGUST 06, 2001
“GOLD CREW SW”

I. NAME, BRAND, OR TRADEMARK

GOLD CREW SW

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Gold Crew Products & Services, LLC

P.O. Box 12032

Orange, CA 92869

Phone: (714) 288-8781

Mobile: (714) 318-5997

E-mail: jfigueira@goldcrew.net

E-mail: jfigueira@ecschem.com

(Mr. Jim Figueira)

ECS

5713 Wollochet Drive NW, Suite B

Gig Harbor, WA 98332

Phone: (253) 263-8040

E-mail: egrubbs@ecschem.com

Website: www.ecschem.com

(Mr. Ed Grubbs)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Gold Crew Products & Services, LLC

P.O. Box 12032

Orange, CA 92869

Phone: (714) 288-8781

Mobile: (714) 318-5997

E-mail: jfigueira@goldcrew.net

E-mail: jfigueira@ecschem.com

(Mr. Jim Figueira)

ECS

5713 Wollochet Drive NW, Suite B

Gig Harbor, WA 98332

Phone: (253) 263-8040

E-mail: egrubbs@ecschem.com

Website: www.ecschem.com

(Mr. Ed Grubbs)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.

2. Ventilation: Normal.

3. Skin and eye contact; protective clothing; treatment in case of contact: Extensive testing indicates that GOLD CREW SW is non-hazardous and non-toxic to humans; however, good hygiene practices should always be followed as outlined below:

Eyes- flush with water; get medical attention if required; Skin - remove contaminated clothing, wash exposed area, and wash clothing before use. If irritation develops get medical attention; Ingestion - get medical attention if required; Inhalation - none considered necessary.

4.a. Maximum storage temperature: When above 120°F, keep container closed and stored in a cool dark place. Evaporation may change product's characteristics.

4.b. Minimum storage temperature: Product will freeze below 25°F. No phase separation will occur. If frozen, thaw, and stir well.

- 4.c. Optimum storage temperature range: 25°F to 120°F
- 4.d. Temperatures of phase separations and chemical changes: No separation at any temperature between 32-120°F. No tendency to “layer out” or separate, standing for 30 days. No separation of layering after freezing.

V. SHELF LIFE

20 years (unopened).

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Apply through hand pump sprayer and allow to soak.
2. Concentration/Application Rate: As a presoak dilute 20 parts water to 1 part SW. For crude oil, allow about 1 hour. For medium distillates, allow 30 minutes. For light distillates, allow 15 minutes. Time may vary depending on weather conditions. After allowing the solution to presoak, wash the area in the following manner: Apply through a power washer or through a steam powered unit at 1 percent, 3 percent, or 5 percent depending on oil viscosity and temperature.
3. Conditions for Use: Equally effective with salt or fresh water.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
GOLD CREW SW	Menidia beryllina	13.80 96-hr
	Mysidopsis bahia	20.40 48-hr
No. 2 Fuel Oil	Menidia beryllina	6.75 96-hr
	Mysidopsis bahia	2.82 48-hr
GOLD CREW SW & No. 2 Fuel Oil (1:10)	Menidia beryllina	6.34 96-hr
	Mysidopsis bahia	2.70 48-hr
Reference Toxicant (SDS)	Menidia beryllina	2.22 96-hr
	Mysidopsis bahia	9.52 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >200
2. Pour Point: 25°F
3. Viscosity: 33.87 CST
4. Specific Gravity: 1.035
5. pH: 9.76 +/- 0.01
6. Surface Active Agents: CONFIDENTIAL.
7. Solvents: None.

8. Additives: CONFIDENTIAL.

9. Solubility in Water: Complete.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<1.0
Cadmium	<0.10
Chromium	<1.0
Copper	<1.0
Lead	<0.5
Mercury	<0.02
Nickel	<1.0
Zinc	0.44
Cyanide	ND
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-28
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: NOVEMBER 05, 2001
“NALE-IT”

I. NAME, BRAND, OR TRADEMARK

NALE-IT

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

SPL Control LLC

P.O. Box 627

Elmore City, OK 73433

Phone: (580) 788-2187

E-mail: splcontrol@aol.com

(Mr. Tom Luster)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

SPL Control LLC

P.O. Box 627

Elmore City, OK 73433

Phone: (580) 788-2187

E-mail: splcontrol@aol.com

(Mr. Tom Luster)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable
2. Ventilation: Workers should be in well ventilated areas; if in a confined area, use a respirator.
3. Skin and eye contact; protective clothing; treatment in case of contact: Workers should wear protective goggles or safety glasses. Prolonged contact with skin may result in dryness.
- 4.a. Maximum storage temperature: NA
- 4.b. Minimum storage temperature: >32°F
- 4.c. Optimum storage temperature range: 40°F to 200°F
- 4.d. Temperatures of phase separations and chemical changes: No phase separation or hazardous polymerization will occur.

V. SHELF LIFE

Indefinite.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: NALE-IT may be applied using a pressure sprayer.
2. Concentration/Application Rate: For pit closures, surface hydrocarbon spills, compressor

stations, pipeline and flow line leaks, well head and tank farm leaks, and highway spills.
(petroleum products) mix 1 part NALE-IT with 20 parts water.

3. Conditions for Use: Equally effective with fresh or salt water.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
NALE-IT	Menidia beryllina	273.30	96-hr
	Mysidopsis bahia	69.00	48-hr
No. 2 Fuel Oil	Menidia beryllina	6.93	96-hr
	Mysidopsis bahia	2.29	48-hr
NALE-IT & No. 2 Fuel Oil (1:10)	Menidia beryllina	3.82	96-hr
	Mysidopsis bahia	1.84	48-hr
Reference Toxicant (SDS)	Menidia beryllina	2.60	96-hr
	Mysidopsis bahia	8.56	48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >212°F
2. Pour Point: 30°F
3. Viscosity: 1.18
4. Specific Gravity: 1.02
5. pH: 6.8 - 7.2
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: None
8. Additives: CONFIDENTIAL
9. Solubility in Water: Soluble in fresh and sat water.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.82
Cadmium	ND
Chromium	ND
Copper	0.173
Lead	ND
Mercury	ND
Nickel	ND
Zinc	0.18
Cyanide	ND
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-30
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JULY 24, 2002
“F-500”

I. NAME, BRAND, OR TRADEMARK

F-500

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Hazard Control Technologies, Inc.

150 Walter Way

Fayetteville, GA 30214

Phone: (770) 719-5112

Fax: (770) 719-5117

E-mail: egriffin@hct-world.com

(Ms. Esther Griffin)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Hazard Control Technologies, Inc.

150 Walter Way

Fayetteville, GA 30214

Phone: (770) 719-5112

Fax: (770) 719-5117

E-mail: egriffin@hct-world.com

(Ms. Esther Griffin)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.

2. Ventilation: Local exhaust – no special requirements.

3. Skin and eye contact; protective clothing; treatment in case of contact: Eye contact – may cause eye irritation, flush with water. Wear splash proof protection goggles or full-face shield. If irritation persists contact a physician. Skin contact – may cause mild irritation, flush with water. Wear rubber and vinyl gloves and apron. Product has been tested and found to be non-skin sensitizing per OECD 406. Ingestion – may cause gastrointestinal irritation. Drink plenty of water to dilute. Do not induce vomiting. If irritation persists contact a physician. Inhalation – elevated temperature vapors may cause irritation to respiratory tract. Remove to fresh air.

4.a. Maximum storage temperature: 130°F

4.b. Minimum storage temperature: 17°F

4.c. Optimum storage temperature range: 35°F - 130°F

4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

The shelf life is 15 years when stored between 35°F - 130°F in unopened containers.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Standard fire apparatus spray nozzle with agitation onto and into spill.
2. Concentration/Application Rate: 1 part F-500:8 parts hydrocarbon:32 parts water (fresh or salt).
3. Conditions for Use: Water temperature: 33°F - 211°F. Effective on both polar and non-polar hydrocarbons

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
F-500	Menidia beryllina	<10.00 96-hr
	Mysidopsis bahia	32.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	56.00 96-hr
	Mysidopsis bahia	100.00 48-hr
F-500 & No. 2 Fuel Oil (1:10)	Menidia beryllina	<10.00 96-hr
	Mysidopsis bahia	32.00 48-hr
Reference Toxicant (DSS)	Menidia beryllina	1.14 96-hr
	Mysidopsis bahia	0.98 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >200°F
2. Pour Point: -17°F
3. Viscosity: 54-56 centistokes @ 72°F
4. Specific Gravity: 0.99 g/cc @ 72°F
5. pH: 7.00
6. Surface Active Agents: PROPRIETARY/CONFIDENTIAL
7. Solvents: None
8. Additives: None
9. Solubility in Water: Complete

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.03
Cadmium	<0.01
Chromium	<0.01
Copper	<0.05
Lead	<0.025
Mercury	<0.005
Nickel	<0.02
Zinc	<0.07
Cyanide	<0.02
Chlorinated Hydrocarbons	<0.10

TECHNICAL PRODUCT BULLETIN #SW-31
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: OCTOBER 27, 2003
“ENVIROCLEAN”

I. NAME, BRAND, OR TRADEMARK
ENVIROCLEAN

Type of Product: Surface Washing Agent
(formerly ENVIRO CLEAN 165)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Blind Gate Holdings, LLC
14 Largo Woods Place
The Woodlands, TX 77382
Phone: (281) 216-6363
E-mail: jgibson@evergreenchems.com
E-mail: mgibson@evergreenchems.com
Website: www.evergreenchems.com
(Mr. Jonathan Gibson)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Evergreen Chemical Solutions, LLC
6700 Woodlands Parkway, Suite 230-250
Spring, TX 77382
Phone: 281-216-6363
E-mail: jgibson@evergreenchems.com
Website: www.evergreenchems.com
(Mr. Jonathan Gibson)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.
2. Ventilation: Normal.
3. Skin and eye contact; protective clothing; treatment in case of contact: Use good normal hygiene and avoid contact with skin and eyes. Gloves and goggles are recommended for field application and product handling. If contact with eyes flush with water for 15 minutes and seek medical attention. For contact with skin, wash area with soap and water. May cause redness, edema, and drying of skin. Seek medical attention if irritation develops. In case of ingestion, seek medical attention. Not considered an inhalation risk.
- 4.a. Maximum storage temperature: 120°F
- 4.b. Minimum storage temperature: 28°F
- 4.c. Optimum storage temperature range: 30°F - 120°F
- 4.d. Temperatures of phase separations and chemical changes: Temperature fluctuations will not

cause separation or deterioration of product. Product blend is stable and will not undergo phase separation of ingredients or stratification of contents over time.

V. SHELF LIFE

Unlimited if unopened.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Dilute product with water prior to use. Apply product via manual pressure applicator (i.e., hand pump), or other delivery equipment, to impacted surfaces. Allow product to soak prior to rinse/recovery if heavily saturated with oil. On hard surfaces, product may be applied and agitated with a brush or other physical means prior to recovery of effluent. Product may also be pre-mixed and used in a batch tank or through an eduction/metering system for flushing and recovery operations.
2. Concentration/Application Rate: ENVIROCLEAN is a concentrated product and must be diluted prior to use. Concentrations vary based upon type of oil and degree of surface saturation. For light ends (i.e., gas condensate/gasoline) a 1% - 2% solution may be used to flush area to containment. (A higher concentration solution of 6% should be used if flammable vapor presents an explosion hazard.) For lighter oils (i.e., No. 2 Fuel Oil) a 3% solution may be used to flush impacted areas to containment. For heavy ends (i.e., crude oil/No. 6 Fuel Oil) a 6% solution of ENVIROCLEAN should be applied and allowed to soak into containment/substrate for up to an hour to allow for release of oil. The surface should then be flushed to containment with a 1% - 3% solution of ENVIROCLEAN. Product may be used as noted above through any pressure or steam equipment. The use of a "hot" unit is recommended when oils are at low temperature or have been weathered.
3. Conditions for Use: ENVIROCLEAN may be diluted with hard, soft, brackish, salt, or most waters of sufficient quality for operations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
ENVIROCLEAN	Menidia beryllina	27.80 96-hr
	Mysidopsis bahia	22.60 48 hr
No. 2 Fuel Oil	Menidia beryllina	8.77 96-hr
	Mysidopsis bahia	1.53 48-hr
ENVIROCLEAN& No. 2 Fuel Oil (1:10)	Menidia beryllina	8.13 96-hr
	Mysidopsis bahia	1.76 48 hr
Reference Toxicant (DSS)	Menidia beryllina	1.83 96-hr
	Mysidopsis bahia	3.37 48 hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >200°F
2. Pour Point: 28.8°F
3. Viscosity: 9 Centipose
4. Specific Gravity: 1.028
5. pH: 8.63
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: None
8. Additives: CONFIDENTIAL
9. Solubility in Water: Complete

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.002
Cadmium	<0.001
Chromium	<0.005
Copper	<0.002
Lead	<0.005
Mercury	<0.0002
Nickel	<0.005
Zinc	<0.002
Cyanide	<0.1
Chlorinated Hydrocarbons	<0.05

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**3/09/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-32
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 21, 2006
“BG-CLEAN™ 401”

I. NAME, BRAND, OR TRADEMARK
BG-CLEAN™ 401
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Amiran BioChemicals, LLC
7221 South 10th Street
Oak Creek, WI 53154
Phone: updated information required
Fax: updated information required
(Dr. Mohsen Amiran)
Phone: updated information required
Fax: updated information required
E-mail: updated information required
(Mr. Sherwin Amiran)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Amiran BioChemicals, LLC
7221 South 10th Street
Oak Creek, WI 53154
Phone: updated information required
Fax: updated information required
(Dr. Mohsen Amiran)

BioCenter, Inc.
P.O. Box 170498
Milwaukee, WI 53217
Phone: (414) 768-7100
Fax: (414) 768-7106
E-mail: skelling@aol.com
(Mr. Scott Kelling)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: BG-CLEAN™ 401 is not classified as flammable by either USDOT or IMO regulations.

2. Ventilation: Avoid prolonged breathing of vapors.
3. Skin and eye contact; protective clothing; treatment in case of contact:
BG-CLEAN™ 401 is an organic compound with a slightly alkaline pH. No extraordinary precautions are required during handling. Avoid unnecessary contact with skin or eyes. No special protective clothing is required. Body areas exposed to BG-CLEAN™ 401 may be flushed with water to clean off the chemical.
- 4.a. Maximum storage temperature: 180°F
- 4.b. Minimum storage temperature: -25°F
- 4.c. Optimum storage temperature range: 68°F
- 4.d. Temperatures of phase separations and chemical changes: BG-CLEAN™ 401 is not adversely affected by changes in storage temperature unless evaporation is allowed to occur. Phase separation does not occur when the product is stored in below freezing conditions. BG-CLEAN™ 401 is ready for use as soon as it is rewarmed to approximately 34-40°F. Product will expand when frozen.

V. SHELF LIFE

The shelf life of unopened containers of BG-CLEAN™ 401 is unlimited. Containers should always be capped when not in use to prevent contamination and evaporation.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: BG-CLEAN™ 401 is applied by one of two methods. 1) For situations where cleanup starts shortly after contamination and the oil has not yet weathered, use a high pressure spray. BG-CLEAN™ 401 is proportioned into a stream of water and sprayed directly on the surface to be cleaned at a rate of 60-70 gpm. 2) For difficult cleaning situations such as weathered crude oil on a rocky beach, a three step procedure should be used. First presoak the contaminated area by proportioning BG-CLEAN™ 401 into a low pressure stream of water at a rate of about 20 gpm. Allow the spray to soak for 15-30 minutes. Then proportion BG-CLEAN™ 401 into a high pressure water stream and apply at a rate of 60-70 gpm. Selection of the best procedure depends on site conditions. BG-CLEAN™ 401 effectiveness is increased when applied with water heated to between 100°F and 180°F. As ambient temperature decreases, the benefits of applying heated spray increase.
The efficiency of BG-CLEAN™ 401 depends directly on mixing of the BG-CLEAN™ 401 molecules with the hydrocarbon molecules. Given good mixing, BG-CLEAN™ 401 can be used on all hydrocarbons except asphalt.
2. Concentration/Application Rate: Dilute BG-CLEAN™ 401 water. The amount of spray required varies with the amount of oil. Concentrations ranging from 5:1 to 100:1 have been found useful depending on hydrocarbon concentrations and viscosity. During application, adjust the concentration of BG-CLEAN™ 401 to suit the cleaning effect desired.
3. Conditions for Use: BG-CLEAN™ 401 is recommended as a cleaner for piers, seawalls, pilings, ship's hulls, and rocky beaches. It can be used on metal, wood, and plastics. BG-CLEAN™ 401 is also highly useful for cleaning contaminated solids such as soil. This includes a range from normal soil aggregate to 100% sand. Two conditions are required for maximum cleaning; thorough mixing of BG-CLEAN™ 401 with the oil and an adequate concentration of

BG-CLEAN™ 401.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
BG-CLEAN™ 401	Menidia beryllina	787.00 96-hr
	Mysidopsis bahia	477.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	16.90 96-hr
	Mysidopsis bahia	2.92 48-hr
BG-CLEAN™ 401	Menidia beryllina	13.10 96-hr
No. 2 Fuel Oil (1:10)	Mysidopsis bahia	2.86 48-hr
Reference Toxicant (SDS)	Menidia beryllina	3.93 96-hr
	Mysidopsis bahia	8.80 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point, ASTM D-93: >76.6°C (>170°F)
2. Pour Point, ASTM D-97: -4°C
3. Viscosity, ASTM D-88: 24 SUS@ 100°F
4. Specific Gravity, ASTM D-1298: 1.00604 @ 60°F
5. pH: 8.227
6. Surface Active Agents: Proprietary
7. Solvents: Proprietary
8. Additives: Proprietary
9. Solubility: Miscible in water.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.118
Cadmium	<0.020
Chromium	<0.125
Copper	0.049
Lead	0.166
Mercury	<0.02
Nickel	<0.125
Zinc	0.280
Cyanide	0.002
Chlorinated Hydrocarbons	ND

LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:

7/15/2021
7/27/2022

TECHNICAL PRODUCT BULLETIN #SW-33
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: NOVEMBER 27, 2006
“E-SAFE[®]”

I. NAME, BRAND, OR TRADEMARK
E-SAFE[®]
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
PLUTUS Environmental Technologies, Inc.
3138 Hatcher Mountain Road
300 John L Marshall Drive
Sevierville, TN 37862-8323
Phone: (865) 214-0350
E-mail: plutusceo@mail.com
(Mr. James Hatcher)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
PLUTUS Environmental Technologies, Inc.
3138 Hatcher Mountain Road
300 John L Marshall Drive
Sevierville, TN 37862-8323
Phone: (865) 214-0350
E-mail: plutusceo@mail.com
(Mr. James Hatcher)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable until >170°F
2. Ventilation: Handle in a well-ventilated space. Local exhaust is recommended if TLV's are exceeded.
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid eye and (sensitive) skin contact. In case of contact, immediately flush with large amount of cool water of at least 5 minutes. Wear protective eye goggles when using any chemicals. Impermeable protective gloves are recommended for sensitive skin types. Protective clothing is not required. Rinse contaminated clothing, shoes, goggles, and gloves in simple tap water to remove any chemical residue. Avoid ingestion, breathing dusts, mists, or fumes. In case of ingestion drink several glasses of water. Do not induce vomiting. In case of inhalation, move affected person to fresh air.
- 4.a. Maximum storage temperature: 160°F

4.b. Minimum storage temperature: -15°F

4.c. Optimum storage temperature range: 40°F – 110°F

4.d. Temperatures of phase separations and chemical changes: No phase separations will occur. Continued exposure to direct sunlight may cause a change in color, but performance is not affected.

V. SHELF LIFE

Unlimited if left in unopened containers stored at 40°F - 110°F and away from direct sunlight.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: E-SAFE® may be introduced with a pressure spray to cover the affected area. The contaminated area should be thoroughly moistened. Following the spray application the treated area should be soaked with water to facilitate penetration. Heavy soil such as clay will be cleaned by E-SAFE®, but tilling or aerating the soil will rapidly shorten penetration time. Sand or loam may require heavy dosage with E-SAFE® because hydrocarbon migration is so rapid in these soil types. Treatment of fouled beach areas should have E-SAFE® sprayed on all contaminated surfaces. Any remaining hydrocarbons may then be effectively vacuumed or wiped away from the treated surfaces. Incidental wave action or rainfall will enhance coverage and penetration by E-SAFE®.

2. Concentration/Application Rate: E-SAFE® should be applied full strength. Beginning treatment for hydrocarbon contaminated surface is one gallon of E-SAFE® per 100 square foot of surface area. This dosage is recommended when the ambient temperature is 72°F and humidity is moderate. Higher temperature or lower humidity will increase the need for repeated applications or a higher volume of E-SAFE® per application.

3. Conditions for Use: E-SAFE® works on all soil types and weather conditions that allow hydrocarbon penetration. E-SAFE® follows the same path, channel, or gradient as the contaminant. When visible detection reveals that E-SAFE® has been absorbed by, or has penetrated the soil, water should be applied to the site. E-SAFE® is soluble in water and also breaks the surface tension of the transporting water molecules.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
E-SAFE®	Menidia beryllina	329.00	96-hr
	Mysidopsis bahia	257.00	48-hr
No. 2 Fuel Oil	Menidia beryllina	5.45	96-hr
	Mysidopsis bahia	10.20	48-hr
E-SAFE®	Menidia beryllina	8.77	96-hr
	Mysidopsis bahia	14.20	48-hr
No. 2 Fuel Oil (1:10)	Menidia beryllina	8.07	96-hr
	Mysidopsis bahia	16.00	48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point, ASTM D-93: >170°F
2. Pour Point, ASTM D-97: -27°C
3. Viscosity, ASTM D-88: 11SFS@ 100°F
4. Specific Gravity, ASTM D-1298: 1.0118 @ 60°F
5. pH: 8.04
6. Surface Active Agents: Confidential
7. Solvents: Confidential
8. Additives: Confidential
9. Solubility: Soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.005
Cadmium	<0.0008
Chromium	<0.025
Copper	0.061
Lead	0.082
Mercury	<0.007
Nickel	<0.003
Zinc	0.214
Cyanide	0.200
Chlorinated Hydrocarbons	ND

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**7/15/2021
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-34
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: NOVEMBER 27, 2006
“SHEEN-MAGIC®”

I. NAME, BRAND, OR TRADEMARK
SHEEN-MAGIC®
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
PLUTUS Environmental Technologies, Inc.
3138 Hatcher Mountain Road
300 John L Marshall Drive
Sevierville, TN 37862-8323
Phone: (865) 214-0350
E-mail: plutusceo@mail.com
(Mr. James Hatcher)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
PLUTUS Environmental Technologies, Inc.
3138 Hatcher Mountain Road
300 John L Marshall Drive
Sevierville, TN 37862-8323
Phone: (865) 214-0350
E-mail: plutusceo@mail.com
(Mr. James Hatcher)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable until >170°F
2. Ventilation: Handle in a well-ventilated space. Local exhaust is recommended if TLV's are exceeded.
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid eye and (sensitive) skin contact. In case of contact, immediately flush with large amount of cool water of at least 5 minutes. Wear protective eye goggles when using any chemicals. Impermeable protective gloves are recommended for sensitive skin types. Protective clothing is not required. Rinse contaminated clothing, shoes, goggles, and gloves in simple tap water to remove any chemical residue. Avoid ingestion, breathing dusts, mists, or fumes. In case of ingestion drink several glasses of water. Do not induce vomiting. In case of inhalation, move affected person to fresh air.
- 4.a. Maximum storage temperature: 160°F

- 4.b. Minimum storage temperature: -8°F
- 4.c. Optimum storage temperature range: 40°F – 110°F
- 4.d. Temperatures of phase separations and chemical changes: No phase separations will occur.

V. SHELF LIFE

Unlimited if left in unopened containers stored at 40°F - 110°F and away from direct sunlight.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: SHEEN-MAGIC® recommended treatment is light misting of contaminated surface. Heavier hydrocarbons such as crude oil should be boomed or vacuumed away as much as possible before application of the SHEENMAGIC®. Treatment of fouled beach areas should have SHEEN-MAGIC® sprayed on all contaminated surfaces. Incidental wave action or rainfall will enhance coverage and penetration by SHEEN-MAGIC®. Any remaining hydrocarbons may then be effectively vacuumed or wiped away from the treated surfaces. Aerial application should be delivered at height and air speed that will create air shear necessary to deliver droplets as per nozzle manufacturer's recommendations. Mist spray from surface vehicles may be delivered from power fogger units. Hand sprayers are generally used for small treatment areas.
2. Concentration/Application Rate: One ounce per 50 square yards of surface is the normal treatment for diesel spills. Heavier hydrocarbon sheens may require additional treatment to remove the contaminant.
3. Conditions for Use: SHEEN-MAGIC® works in all weather conditions that allow hydrocarbon penetration. SHEEN-MAGIC® should be used as soon as the temperature and weather conditions allow delivery to the spill area. Heavier concentrations may be required when the temperature/humidity will cause rapid evaporation of the spray.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
SHEEN-MAGIC®	Menidia beryllina	183.00 96-hr
	Mysidopsis bahia	161.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	4.57 96-hr
	Mysidopsis bahia	3.04 48-hr
SHEEN-MAGIC®	Menidia beryllina	7.82 96-hr
	Mysidopsis bahia	5.75 48-hr
No. 2 Fuel Oil (1:10)	Menidia beryllina	11.70 96-hr
	Mysidopsis bahia	5.36 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point, ASTM D-93: >170°F
2. Pour Point, ASTM D-97: -22°C
3. Viscosity, ASTM D-88: 11SFS@ 100°F
4. Specific Gravity, ASTM D-1298: 1.0127 @ 60°F
5. pH: 8.10
6. Surface Active Agents: Confidential
7. Solvents: Confidential
8. Additives: Confidential
9. Solubility: Soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.005
Cadmium	<0.0008
Chromium	0.026
Copper	0.023
Lead	0.085
Mercury	<0.007
Nickel	<0.003
Zinc	0.231
Cyanide	0.200
Chlorinated Hydrocarbons	ND

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**3/16/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-35
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JUNE 16, 2008
“PROCLEANS”

I. NAME, BRAND, OR TRADEMARK
PROCLEANS
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Eximco International, Inc.
5250 Gulfton, #2-B
Houston, TX 77081
Phone: updated information required
E-mail: updated information required
(Mr. Nat Brown)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Eximco International, Inc.
5250 Gulfton, #2-B
Houston, TX 77081
Phone: updated information required
E-mail: updated information required
E-mail:
(Mr. Nat Brown)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.
2. Ventilation: Normal.
3. Skin and eye contact; protective clothing; treatment in case of contact: Flush contaminated eyes thoroughly with water for 15 minutes, and get medical attention. Remove contaminated clothing, wash exposed area with soap and water, and wash clothing before use. Get medical attention if irritation develops. Get medical attention if ingested. No medical attention is necessary if inhaled.
- 4.a. Maximum storage temperature: 130°F
- 4.b. Minimum storage temperature: 35°F
- 4.c. Optimum storage temperature range: 50°F to 100°F
- 4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

Approximately 2 years at recommended temperatures if unopened.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Apply specified dilute solution using fire hoses or heated pressure washers onto the contaminated solid surface of the spill.
2. Concentration/Application Rate: Use ten parts water to one part product. Dilution rates may be adjusted to suit different job conditions. Apply 10 to 15 gallons of diluted PROCLEANS to one cubic yard of contamination.
3. Conditions for Use: May be used with fresh or salt water. Warmer temperatures may improve results. Most effective if used on solid surfaces such as shoreline beaches and rocks contaminated with light and medium weight crude oils and refined petroleum products.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
PROCLEANS	Menidia beryllina	83.73 96-hr
	Mysidopsis bahia	83.98 48-hr
No. 2 Fuel Oil	Menidia beryllina	7.41 96-hr
	Mysidopsis bahia	11.68 48-hr
PROCLEANS & No. 2 Fuel Oil (1:10)	Menidia beryllina	4.78 96-hr
	Mysidopsis bahia	11.68 48-hr
Reference Toxicant (CuSO ₄)	Menidia beryllina	0.73 96-hr
	Mysidopsis bahia	0.77 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >186°F
2. Pour Point: 34.6°F
3. Viscosity: 2.41 cST @ 104°F
4. Specific Gravity: 1.01 @ 25°C
5. pH: 6.8
6. Surface Active Agents: Anionic and nonionic
7. Solvents: None.
8. Additives: None
9. Solubility in Water: NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.690
Cadmium	ND
Chromium	ND
Copper	ND
Lead	ND
Mercury	ND
Nickel	ND
Zinc	0.738
Cyanide	ND
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-36
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: MARCH 30, 2009
“SPILLCLEAN”
SPILLCLEAN [“Concentrate”]
(aka, FIREMAN’S BRAND SPILLCLEAN)

I. NAME, BRAND, OR TRADEMARK

SPILLCLEAN

SPILLCLEAN [“Concentrate”] = 30% Active Ingredients and 70% Water

(aka, FIREMAN’S BRAND SPILLCLEAN)

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Super Sat Ventures, Inc.

S96 W34577 Jericho Drive

Eagle, WI 53119

Phone: (414) 840-9223

E-mail: dwk@ssvinc.com

(Mr. Daniel W. Klein)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Super Sat Ventures, Inc.

S96 W34577 Jericho Drive

Eagle, WI 53119

Phone: (414) 840-9223

E-mail: dwk@ssvinc.com

(Mr. Daniel W. Klein)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: >210°F

2. Ventilation: General room ventilation is expected to be satisfactory.

3. Skin and eye contact; protective clothing; treatment in case of contact: Product may cause mild skin irritation. Wear impervious gloves, safety goggles, and full cover clothes. Eye wash and safety shower should be accessible. If eye contact, flush immediately with water for at least 15 minutes. If skin contact, wash with soap and water. If swallowed, give two glasses of water (do not induce vomiting). Seek medical attention for eye and skin contact and ingestion.

4.a. Maximum storage temperature: <210°F

4.b. Minimum storage temperature: >32°F

4.c. Optimum storage temperature range: 50°F – 70°F

4.d. Temperatures of phase separations and chemical changes: <32°F and >210°F

V. SHELF LIFE

3 years. Avoid extreme heat and store in a dry, cool area.

VI. RECOMMENDED APPLICATION PROCEDURES

Please note:

SPILLCLEAN comes in two forms “Concentrate” and “Original Formula.” SPILLCLEAN [“Concentrate”] is 30% Active Ingredients and 70% Water while SPILLCLEAN [“Original Formula”] is 10% Active Ingredients and 90% Water.

SPILLCLEAN [“Concentrate”] and SPILLCLEAN [“Original Formula”] are for on land and surface use only. They should not be used around or near bodies of water when there is a reasonable chance of mixing in with water. Once the contaminant/SPILLCLEAN [“Concentrate”] solution mixes with the body of water, “control” of the contaminant will be lost since SPILLCLEAN is water soluble.

SPILLCLEAN is a formula designed to solubilize and emulsify oil and oil-type products such as motor oil, gasoline, diesel fuel, and transmission fluid. When such products are accidentally spilled and need to be cleaned up from hard surfaces such as streets and driveways, SPILLCLEAN is an effective material to use. Being a surfactant-type material, SPILLCLEAN allows the spilled contaminant to be emulsified and then lifted and separated from the hard surface. The resulting spill/contaminant can then be picked up, vacuumed up, or flushed with water, all in accordance with federal, state, and local regulations.

1. Application Method: SPILLCLEAN [“Concentrate”] 30% Active Ingredients and 70% Water – squeeze product directly around outside perimeter of oil/gasoline/antifreeze spill using squeeze bottle container. This process is designed to “contain” the contaminant and keep it from migrating down a hard surface like a city street, parking lot, or garage floor. SPILLCLEAN [“Concentrate”] is more viscous than oil/gasoline, and will “hold” the contaminant in place. Once the contaminant is contained, the user can apply SPILLCLEAN [“Original Formula”] over the “body” of the contaminant if the spill is large (over 2 gallons). If the spill is small (less than 2 gallons), the user can apply either SPILLCLEAN [“Concentrate”] or SPILLCLEAN [“Original Formula”] to the “body” of the contaminant spill. Using a broom or broom-like applicator, sweep SPILLCLEAN in with the contaminant until thoroughly blended in place. The original bright red color of SPILLCLEAN [“Concentrate”] and SPILLCLEAN [“Original Formula”] will dissipate when it is thoroughly mixed with the contaminant.

SPILLCLEAN [“Original Formula”] 10% Active Ingredients and 90% Water – apply over the “body” of the contaminant if the spill is large (over 2 gallons). If the spill is small (less than 2 gallons), the user can apply SPILLCLEAN [“Concentrate”] or SPILLCLEAN [“Original Formula”] to the “body” of the contaminant spill. SPILLCLEAN [“Original Formula”] is designed to “attach” to a contaminant and remove it from a hard surface like a city street, parking lot, or garage floor. It is recommended to be used on any size contaminant spill, large or small. This product is designed to penetrate into the surface pores and molecularly “attach” with the contaminant, thus making the contaminant “water soluble.” The contaminant can be removed

from the pores (of the asphalt, concrete, epoxy surface, etc.) with a 60psi water supply. The user can then dispose of the resulting mixture according to regulations. This product can be applied using a vast number of different applicators, especially with regard to firefighting equipment. Using a broom or broom-like applicator, sweep SPILLCLEAN in with the contaminant until thoroughly blended in place. The original bright red color of SPILLCLEAN [“Concentrate”] and SPILLCLEAN [“Original Formula”] will dissipate when it is thoroughly mixed with the contaminant.

When SPILLCLEAN’S bright red color has dissipated (upon mixing) with the contaminant, it can be wiped clean with a rag or wet-vacuumed, collected, and disposed of according to EPA, federal, state, and local regulations. Additionally, a dry sorbent may be applied to the resulting SPILLCLEAN/contaminant/water mixture, shoveled up and disposed of according to applicable regulations.

2. Concentration/Application Rate: For Surface and Land Application Only:
SPILLCLEAN [“Concentrate”] 30% Active Ingredients and 70% Water – for spills less than 2 gallons squeeze a one-half inch ribbon of straight product around the perimeter of the oil/gasoline spill, followed by an “X” pattern over the body of the spill. For spills greater than 2 gallons squeeze a one-half inch ribbon of straight product around the perimeter of the oil/gasoline spill. The general purpose of SPILLCLEAN [“Concentrate”] is to “contain” the contaminant from migrating, and therefore should not be diluted with water during application.

SPILLCLEAN [“Original Formula”] 10% Active Ingredients and 90% Water – concentration rate is based on equipment used and disposal method. Typical usage will be (0 to 100 parts water) plus 1 part SPILLCLEAN [“Original Formula”] all applied to 1 part contaminant (oil/gasoline spill).

The resulting mixture of SPILLCLEAN and oil must be disposed of in accordance with EPA, federal, state, and local agencies that regulate disposal of contaminant. The resulting SPILLCLEAN contaminant mixture should be wet-vacuumed up and placed in a proper container and disposed.

3. Conditions for Use:

Water Salinity: Water soluble, not applicable for use on water

Water Temperature: >32°F and <120°F

Types of Pollutants: Automobile motor oil, gasoline, diesel fuel, and transmission fluid

Ages of Pollutants: 0 to 20 years old

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
SPILLCLEAN [“Concentrate”]	Menidia beryllina	24.30 96-hr
	Mysidopsis bahia	10.00 48-hr

No. 2 Fuel Oil	Menidia beryllina	6.60 96-hr
	Mysidopsis bahia	2.20 48-hr
SPILLCLEAN ["Concentrate"] & No. 2 Fuel Oil (1:10)	Menidia beryllina	3.30 96-hr
Reference Toxicant (SDS)	Mysidopsis bahia	1.30 48-hr
	Menidia beryllina	8.90 96-hr
	Mysidopsis bahia	10.70 48-hr

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: SPILLCLEAN ["Concentrate"] = >210°F
2. Pour Point: SPILLCLEAN ["Concentrate"] = 27.0°F
3. Viscosity: SPILLCLEAN ["Concentrate"] = 6400cPs@25°C
4. Specific Gravity: SPILLCLEAN ["Concentrate"] = 1.030
5. pH: SPILLCLEAN ["Concentrate"] = 7.20
6. Surface Active Agents: Confidential
7. Solvents: Confidential
8. Additives: Confidential
9. Solubility: Water soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.02
Cadmium	<0.007
Chromium	<0.01
Copper	<0.01
Lead	<0.02
Mercury	<0.00003
Nickel	<0.01
Zinc	<0.01
Cyanide	0.137
Chlorinated Hydrocarbons	<0.01

TECHNICAL PRODUCT BULLETIN #SW-37
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: MARCH 15, 2010
“TXCHEM HE-1000™”

I. NAME, BRAND, OR TRADEMARK

TXCHEM HE-1000™

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Texas EnviroChem, Inc.

17890 Airfield Lane

Pearland, TX 77581

Phone: (713) 806-4099

(Mr. Pete Franks)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Texas EnviroChem, Inc.

17890 Airfield Lane

Pearland, TX 77581

Phone: (713) 806-4099

(Mr. Pete Franks)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Not flammable

2. Ventilation: Recommended, respirator in confined area

3. Skin and eye contact; protective clothing; treatment in case of contact:

Wear rubber gloves and eye protection. If eye contact, wash eyes thoroughly for 15 minutes; including upper and lowers lids, and seek medical attention. For skin contact, irritation is possible, wash with soap and water for 15 minutes. If irritation persists, seek medical attention.

4.a. Maximum storage temperature: 95°F

4.b. Minimum storage temperature: 32°F

4.c. Optimum storage temperature range: 75°F

4.d. Temperatures of phase separations and chemical changes: No phase changes have been observed.

V. SHELF LIFE

One year in a sealed container.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: TXCHEM HE-1000™ is applied by pressure sprayer, heated pressure washer, fire hoses or mixing on or into hydrocarbon contaminated media.

2. Concentration/Application Rate: TXCHEM HE-1000™ should be diluted to a one (1) part concentrated chemical to ten (10) parts water solution. Apply ten to fifteen gallons of diluted solution to one cubic yard of contaminated media. Agitate to slurry. Dilution rate may change due to level of hydrocarbon contamination. Please see manufacturer's instructions for additional application dilutions. Excess washing solution should be disposed of according to local, state, and federal regulations.

3. Conditions for Use: Pollutants should be of hydrocarbon in nature. Greater results occur at ambient temperatures greater than 50°F. Fresh or salt water can be used with no performance change.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
TXCHEM HE-1000™	Menidia beryllina	91.33 96-hr
	Mysidopsis bahia	65.52 48-hr
No. 2 Fuel Oil	Menidia beryllina	5.84 96-hr
	Mysidopsis bahia	2.17 48-hr
TXCHEM HE-1000™ & No. 2 Fuel Oil (1:10)	Menidia beryllina	7.07 96-hr
	Mysidopsis bahia	2.11 48-hr
Reference Toxicant (SLS)	Menidia beryllina	15.27 96-hr
	Mysidopsis bahia	12.84 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

- Flash Point: >210°F
- Pour Point: 23.0°F
- Viscosity: 1.99cSt
- Specific Gravity: 0.999
- pH: 7.20
- Surface Active Agents: Confidential
- Solvents: NA
- Additives: Confidential
- Solubility: NA

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND
Cadmium	ND
Chromium	0.0366

Copper	0.0402
Lead	0.0189
Mercury	ND
Nickel	0.0125
Zinc	0.29
Cyanide	<0.05
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-38
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: MAY 11, 2010
“NOKOMIS 5-W”

I. NAME, BRAND, OR TRADEMARK

NOKOMIS 5-W

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Mar-Len Supply, Inc.

23159 Kidder Street

Hayward, CA 94545

Phone: (510) 782-3555

Fax: (510) 782-2032

E-mail: marlensupply@yahoo.com

(Mrs. Shirley Winter or Mr. Curt Winter)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Mar-Len Supply, Inc.

23159 Kidder Street

Hayward, CA 94545

Phone: (510) 782-3555

Fax: (510) 782-2032

E-mail: marlensupply@yahoo.com

(Mrs. Shirley Winter or Mr. Curt Winter)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (water based)

2. Ventilation: No special requirements

3. Skin and eye contact; protective clothing; treatment in case of contact: In case of eye contact, flush with water; in case of skin contact, wash with water; and, if swallowed drink water to dilute and induce vomiting.

4.a. Maximum storage temperature: 212°F

4.b. Minimum storage temperature: 32°F

4.c. Optimum storage temperature range: 50°F

4.d. Temperatures of phase separations and chemical changes: NA

V. SHELF LIFE

15 years or more if stored correctly in plastic drums.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: NOKOMIS 5-W is a concentrated liquid, non-hazardous cleaner. Can be

used full strength or diluted with fresh or salt water. NOKOMIS 5-W is marketed in plastic containers.

2. Concentration/Application Rate: Dilution ratios are determined by the individual cleaning application. For washing equipment contaminated with soluble crude and/or bunker fuel oil use a 5:1 cleaning solution. Spray or brush onto surface, agitate with a stiff bristle brush, and rinse with fresh or salt water. For pressure washing, pre-spray surface with concentrate and allow to dwell on surface one to ten minutes (depending on age of oil). For shoreline areas and beaches with rocky, breakwaters contain the area of beach sand and gravel by creating a sand bather around a small contaminated area. Spray contaminated area with a 10:1 solution. Add salt or freshwater, agitate surface to help release oil from sand. Allow time for oil to surface and recover oil. To clean larger tidal rock surfaces, apply 5:1 or 20 percent mixture of NOKOMIS 5-W. Spray solution onto rocks with a garden type pump sprayer. Agitate with a stiff bristle brush. Allow to dwell on surface until surface looks soluble. Contain with a boom or use oil absorbent pads to recover oil.

3. Conditions for Use: Fresh or salt water can be used.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
NOKOMIS 5-W	Menidia beryllina	10.46 96-hr
	Mysidopsis bahia	21.52 48-hr
No. 2 Fuel Oil	Menidia beryllina	4.25 96-hr
	Mysidopsis bahia	2.11 48-hr
NOKOMIS 5-W	Menidia beryllina	3.07 96-hr
	Mysidopsis bahia	2.24 48-hr
No. 2 Fuel Oil (1:10)	Menidia beryllina	13.01 96-hr
	Mysidopsis bahia	9.05 48-hr
Reference Toxicant (SLS)	Menidia beryllina	13.01 96-hr
	Mysidopsis bahia	9.05 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: None
2. Pour Point: 28°F
3. Viscosity: 31.00 cps
4. Specific Gravity: 1.0065 g/cc
5. pH: 10.4
6. Surface Active Agents: Confidential
7. Solvents: None
8. Additives: None
9. Solubility: Completely water soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.037
Cadmium	<0.050
Chromium	<0.050
Copper	<0.050
Lead	<0.025
Mercury	<0.0064
Nickel	<0.050
Zinc	1.7
Cyanide	0.042
Chlorinated Hydrocarbons	<0.500

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**8/23/2012
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-39
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 02, 2010
“G-CLEAN OSC-1809”

I. NAME, BRAND, OR TRADEMARK
G-CLEAN OSC-1809
(aka, OIL SPILL CLEANUP)
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Green Earth Technologies
1136 Celebration Boulevard
Celebration, FL 34347
Phone: (330) 540-4220
Fax: (815) 331-0931
E-mail: mlukco@getg.com
E-mail: jloch@getg.com
Website: www.getg.com
(Mr. Michael Lukco)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Green Earth Technologies
1136 Celebration Boulevard
Celebration, FL 34347
Phone: (330) 540-4220
Fax: (815) 331-0931
E-mail: mlukco@getg.com
E-mail: jloch@getg.com
Website: www.getg.com
(Mr. Michael Lukco)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: No special requirements
3. Skin and eye contact; protective clothing; treatment in case of contact: As defined by OSHA's Hazard Communication Standard, this product is non-hazardous with no evidence of adverse effects. No personal protection or exposure controls.
- 4.a. Maximum storage temperature: 140°F continuous up to 5 days
- 4.b. Minimum storage temperature: 35°F

4.c. Optimum storage temperature range: 50°F to 98°F

4.d. Temperatures of phase separations and chemical changes: May begin freezing at or below 25°F as product begins to thaw. Mix product with agitator until product becomes homogenous.

V. SHELF LIFE

Five to ten years in sealed polydrums or totes (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Product may be applied to any surface for removal of oils. Select proper dilution depending on product types and material surface prior to application. For treatment of large areas, properly diluted product may be applied by spraying with a pressure washer, portable fire pump or any other suitable pump with seawater or freshwater suction that is equipped with a chemical inductor or feed pump. For smaller areas, properly diluted product may be applied with scrubber, mop, cloth or damp sponge. Apply liberally, adjusting dilution on site as necessary.

2. Concentration/Application Rate: For heavily weathered oil on rocks, a diluted solution of 3 parts water to 1 part product is recommended. For heavily weathered oil on beaches/sand, a diluted solution of 5 parts water to 1 part product is ideal. For tar balls, no dilution is necessary and it is suggested to apply directly at full strength. For removing oil from vegetation, a diluted solution of 10/20 parts water to 1 part product is preferred. Product may be diluted with either salt water or fresh water. Warmer waters (greater than 78°F) and/or good agitation during application will require less product.

3. Conditions for Use: Best results are obtained by allowing diluted solution to soak for at least 30 minutes to soften the oil deposits. Reapplication may be necessary in severely contaminated areas. A sorbent boom or vacuum suction equipment should be positioned to collect the washed off effluent. When proper containment equipment is in place and a soaking period of at least 30 minutes has been achieved, a diluted solution of 20 parts water and 1 part product should be applied at mid-pressure (approximately 100 PSI). Adjust the pressure and angle of the hose sprayer to achieve optimum results, adjusting dilution as necessary on site. Product and effluent should be vacuumed up or absorbed in absorbent boom and disposed of according to EPA guidelines.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
G-CLEAN OSC-1809	Menidia beryllina	11.49 96-hr
	Mysidopsis bahia	7.32 48-hr
No. 2 Fuel Oil	Menidia beryllina	2.51 96-hr
	Mysidopsis bahia	2.24 48-hr
G-CLEAN OSC-1809 & No. 2 Fuel Oil (1:10)	Menidia beryllina	6.05 96-hr
	Mysidopsis bahia	2.51 48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.25 96-hr
	Mysidopsis bahia	11.71 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >93°C
2. Pour Point: -16°F
3. Viscosity: 60.77 at 40°C
4. Specific Gravity: 1.029 @60°F
5. pH: 11.3
6. Surface Active Agents: Nonionic, Surfactants, PROPRIETARY
7. Solvents: Plant-based, PROPRIETARY
8. Additives: None
9. Solubility: Completely water soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.004
Cadmium	<0.002
Chromium	2.004
Copper	0.068
Lead	<0.004
Mercury	<1 µg/L
Nickel	0.0132
Zinc	0.0136
Cyanide	<0.25
Chlorinated Hydrocarbons	<5.00

LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:

3/16/2016
7/27/2022

TECHNICAL PRODUCT BULLETIN #SW-40
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 06, 2010
“GREEN BEAST™ OIL SPILL & ODOR REMEDIATOR”
(aka, GREEN BEAST WASHING AGENT; ALL PURPOSE CLEANER & REMEDIATOR)

I. NAME, BRAND, OR TRADEMARK
GREEN BEAST™ OIL SPILL & ODOR REMEDIATOR
(aka, GREEN BEAST WASHING AGENT; ALL PURPOSE CLEANER & REMEDIATOR)
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
BioFusion Corporation
310 Godwin Avenue
Ridgewood, NJ 07450
Phone: updated information required
Fax: updated information required
E-mail: updated information required
Website: updated information required
(Mr. David Gubb)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Brightside Products, LLC	MSC Industrial Supply Company, Inc.
310 Godwin Avenue	75 Maxess Road
Ridgewood, NJ 07450	Melville, NY 11747
Phone: updated information required	Phone: (800) 645-7270
Fax: updated information required	Website: www.mscdirect.com
E-mail: updated information required	
(Mr. David Gubb)	

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: No special requirements
3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing required; however, goggles are recommended. If eye or skin irritation occurs, flush with plenty of water.
- 4.a. Maximum storage temperature: 120°F
- 4.b. Minimum storage temperature: 35°F
- 4.c. Optimum storage temperature range: 40°F to 113°F
- 4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

Unlimited in sealed polydrums or totes (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: The diluted composition of the present formulation is preferably applied to a surface to be cleaned under pressure (i.e., power washing), but will work well poured directly onto the contaminated area. It is advantageous to apply the diluted final composition at high pressure, above 500 psi, but it is not required.

2. Concentration/Application Rate: For treating hydrocarbons on beaches, rocks, and hard surfaces the final composition is diluted 1:15 with fresh or sea water and is applied to the hydrocarbons at a rate of about 4 gallons for 1000 square feet of contaminated area. For spills which are of heavy consistency, the diluted mixture is preferably applied at a rate of about 1.3 gallons for 1000 square feet of contaminated area and the diluted final composition is preferably applied over a period of three consecutive days. Residue should be collected and disposed of in accordance with local, state, and federal practices and laws.

3. Conditions for Use: The composition of the present formulation is diluted into water, preferably at a temperature of about 38°F to about 60°F. While the composition is active below about 38°F, the activity is slightly reduced. The composition is also active at temperatures above about 60°F; however, at these elevated temperatures the composition is less stable and is denatured at a greater rate than at lower temperatures. Preferably, the diluted compositions of the present formulation are used immediately after the dilution into about 38°F to 60°F water.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
Product	Menidia beryllina	29.18 96-hr
	Mysidopsis bahia	30.42 48-hr
No. 2 Fuel Oil	Menidia beryllina	2.51 96-hr
	Mysidopsis bahia	2.24 48-hr
Product & No. 2 Fuel Oil (1:10)	Menidia beryllina	7.15 96-hr
	Mysidopsis bahia	2.24 48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.25 96-hr
	Mysidopsis bahia	11.71 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >85°C

2. Pour Point: +26°F

3. Viscosity: 3.87 at 40°C
4. Specific Gravity: 0.9986 @60°F
5. pH: 4.5
6. Surface Active Agents: Anionic and Nonionic, PROPRIETARY SURFACTANTS
7. Solvents: None
8. Additives: Nutrient and Protein Package, PROPRIETARY
9. Solubility: Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.0088
Cadmium	<0.002
Chromium	0.1752
Copper	0.0360
Lead	<0.004
Mercury	<1 µg/L
Nickel	<0.010
Zinc	0.0840
Cyanide	<0.010
Chlorinated Hydrocarbons	<5.00

TECHNICAL PRODUCT BULLETIN #SW-41
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 13, 2010
“TULXA”

I. NAME, BRAND, OR TRADEMARK

TULXA

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Grupo Arthuriana S.A. de C.V.

Cuernavaca No. 43

Colonia Condesa, Delegación Cuauhtémoc

Mexico, Distrito Federal C.P. 06140

Phone: 01 52 (55) 52 41 11 90

Fax: 01 52 (55) 53 61 13 54

E-mail: sgarcia@arthuriana.com.mx, sgarcia@onsite.com.mx or bescorcia@arthuriana.com.mx,
bescorcia@onsite.com.mx

Website: www.grupoarthuriana.com.mx

(Ms. Susana Garcia Ballesteros)

(Ms. Bertha Escorcia Rodriguez)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Grupo Arthuriana S.A. de C.V.

Cuernavaca No. 43

Colonia Condesa, Delegación Cuauhtémoc

Mexico, Distrito Federal C.P. 06140

Phone: 01 52 (55) 52 41 11 90

Fax: 01 52 (55) 53 61 13 54

E-mail: sgarcia@arthuriana.com.mx, sgarcia@onsite.com.mx or bescorcia@arthuriana.com.mx,
bescorcia@onsite.com.mx

Website: www.grupoarthuriana.com.mx

(Ms. Susana Garcia Ballesteros)

(Ms. Bertha Escorcia Rodriguez)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)

2. Ventilation: Wear protective mask.

3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid contact with eyes, in case of contact rinse with fresh water. Do not ingest. If swallowed do not induce vomiting and contact a doctor immediately. Use normal protective equipment for handling powder, such as a mask or eye shield. If eye or skin irritation occurs, flush with plenty of fresh

water.

4.a. Maximum storage temperature: 104°F or 40°C

4.b. Minimum storage temperature: 52°F or 20°C

4.c. Optimum storage temperature range: 77°F or 25°C and 95°F or 35°C

4.d. Temperatures of phase separations and chemical changes: >104°F or 40°C

V. SHELF LIFE

Two years if stored in dry, fresh environment.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Tulxa can be applied using conventional spraying equipment using low to moderate pressure. Tulxa can be applied directly to any surfaces coated with oil (e.g., beaches, rocks, plants).

2. Concentration/Application Rate: Tulxa can be diluted with fresh water up to a ratio of 1:200. Higher concentration of Tulxa may be required for weathered oils. Optimum concentration should be determined on site based on the type and age of the oil being removed. The product is fully miscible with water with minimal mixing.

3. Conditions for Use: It is recommended to do a test to measure the amount of oils removed and check the time and dilution at which the fats are separated. The product should completely separate the oils in 25 minutes. Although, it may be necessary to let the mixture stay in contact with surface for a longer period of time depending on the type and age of the oil. Residue should be collected and disposed of in accordance with local, state, and federal practices and laws.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
TULXA	Menidia beryllina	16.50 96-hr
	Mysidopsis bahia	11.33 48-hr
No. 2 Fuel Oil	Menidia beryllina	4.94 96-hr
	Mysidopsis bahia	1.31 48-hr
TULXA & No. 2 Fuel Oil (1:10)	Menidia beryllina	6.08 96-hr
	Mysidopsis bahia	2.24 48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.19 96-hr
	Mysidopsis bahia	10.53 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >185°F

2. Pour Point: 22°F

3. Viscosity: 30.77 cSt @ 40°C

4. Specific Gravity: 1.0263 @60°F
5. pH: 5.0
6. Surface Active Agents: NA
7. Solvents: NA
8. Additives: None
9. Solubility: Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.002
Cadmium	<0.001
Chromium	0.4436
Copper	0.0034
Lead	<0.002
Mercury	<1 µg/L
Nickel	<0.005
Zinc	0.0278
Cyanide	<0.013
Chlorinated Hydrocarbons	<1.00

TECHNICAL PRODUCT BULLETIN #SW-42
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 28, 2010
“MARINE GREEN CLEAN™”

I. NAME, BRAND, OR TRADEMARK

MARINE GREEN CLEAN™

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

AGS Solutions, Inc.

5647 Nunn Street

Houston, TX 77087

Phone: (713) 645-4933

Fax: (713) 645-4903

E-mail: agssolutionsinc@gmail.com

Website: www.agstx.com

(Mrs. Linda Whiteley)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

AGS Solutions, Inc.

5647 Nunn Street

Houston, TX 77087

Phone: (713) 645-4933

Fax: (713) 645-4903

E-mail: agssolutionsinc@gmail.com

Website: www.agstx.com

(Mrs. Linda Whiteley)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable

2. Ventilation: Respiratory protection is not considered necessary for normal use. If exposure to vapors or mists is possible, such as is a fire emergency, NIOSH approved respiratory protection for organic vapors should be used. Mechanical ventilation is not normally required.

3. Skin and eye contact; protective clothing; treatment in case of contact: In case of contact with eyes, wash thoroughly with plenty of clean water. Seek medical attention if irritation develops.

Rubber protective gloves should be used if prolonged use of product is anticipated.

4.a. Maximum storage temperature: 100°F

4.b. Minimum storage temperature: 0°F

4.c. Optimum storage temperature range: 33°F to 100°F

4.d. Temperatures of phase separations and chemical changes: >100°F

V. SHELF LIFE

Shelf life is ≥ 2 years. The product may lose its effectiveness at temperatures $>140^{\circ}\text{F}$. Make sure bulk containers are properly vented. Drums and similar containers should be kept closed. Store in steel or plastic containers.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: For general use, apply product by spray, mop, or with standard steam and pressure wash cleaning equipment. It can also be applied using a foam generator, or any convenient sprayer. Product can be used as is or by using heat and pressure or mechanical scrubbing. Rinse thoroughly with fresh water for a residue-free surface. In direct applications, foaming will be most effective as it will allow more contact time for the product to work. In a typical foam cleaning application operation the surface to be cleaned will be thoroughly covered with foam and allowed to stand for several minutes. The foam is rinsed away with clean water using a hot pressure of low pressure washer. Product can be applied with a variety of spraying or washing equipment, depending upon the type and scale of the shoreline or beach to be cleaned. For large areas such as beaches, the product can be sprayed from water trucks or other vehicles equipped with pumps, hoses, and nozzles to aerially deliver cleaner. On smaller oily surfaces, the product can be applied with hand sprayers or portable pumps may be used to spray directly onto oily surfaces. Dose rates may vary depending on type and amount of petroleum spilled, and other site conditions such as water, temperatures, and porosity of shoreline. Cold weather applications will require more contact time before initiating recovery. The treated product can be removed by several means including but not limited to: sorbent pads, oil skimmers, collection booms, use of vacuum trucks, berm collecting, drumming, frac tanks, or other appropriate containment and collection mechanism.

2. Concentration/Application Rate: For spills on shorelines and beaches, the product can be used undiluted up to 14% dilution with fresh water. After application, the product should be allowed to penetrate and dissolve the oily surface for up to 30 minutes, longer is preferable – if possible, to maximize contact time. For light cleaning, use up to 1:50 parts product to water. For heavy cleaning, use up to 1:14 parts product to water.

3. Conditions for Use: Product can be used in fresh or salt water, sand beaches, gravel, cobble, coarse sand and rocky shores, public beaches, and other sensitive or high impact sites.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
MARINE GREEN CLEAN™	Menidia beryllina	46.00 96-hr
	Mysidopsis bahia	89.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	18.00 96-hr
	Mysidopsis bahia	22.00 48-hr
MARINE GREEN CLEAN™ & No. 2 Fuel Oil (1:10)	Menidia beryllina	34.00 96-hr
	Mysidopsis bahia	45.00 48-hr
Reference Toxicant (DSS)	Menidia beryllina	1.06 96-hr
	Mysidopsis bahia	0.97 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: NA
2. Pour Point: 30°F
3. Viscosity: 77.2 cSt @ 25°C
4. Specific Gravity: 1.032 @ 70°F
5. pH: 11-12.5
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL
8. Additives: None
9. Solubility: Completely soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.648
Cadmium	0.030
Chromium	0.143
Copper	0.154
Lead	<0.025
Mercury	<0.013
Nickel	0.357
Zinc	2.540
Cyanide	<0.02
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-43
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 28, 2010
“MARINE GREEN CLEAN PLUS™”

I. NAME, BRAND, OR TRADEMARK
MARINE GREEN CLEAN PLUS™
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
AGS Solutions, Inc.
5647 Nunn Street
Houston, TX 77087
Phone: (713) 645-4933
Fax: (713) 645-4903
E-mail: agssolutionsinc@gmail.com
Website: www.agstx.com
(Mrs. Linda Whiteley)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
AGS Solutions, Inc.
5647 Nunn Street
Houston, TX 77087
Phone: (713) 645-4933
Fax: (713) 645-4903
E-mail: agssolutionsinc@gmail.com
Website: www.agstx.com
(Mrs. Linda Whiteley)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable
2. Ventilation: Respiratory protection is not considered necessary for normal use. If exposure to vapors or mists is possible, such as is a fire emergency, NIOSH approved respiratory protection for organic vapors should be used. Mechanical ventilation is not normally required.
3. Skin and eye contact; protective clothing; treatment in case of contact: In case of contact with eyes, wash thoroughly with plenty of clean water. Seek medical attention if irritation develops. Rubber protective gloves should be used if prolonged use of product is anticipated.
- 4.a. Maximum storage temperature: 100°F
- 4.b. Minimum storage temperature: 0°F
- 4.c. Optimum storage temperature range: 33°F to 100°F
- 4.d. Temperatures of phase separations and chemical changes: >100°F

V. SHELF LIFE

Shelf life is ≥ 2 years. The product will not lose its effectiveness unless the temperatures is $>140^{\circ}\text{F}$. Make sure bulk containers are properly vented. Drums and similar containers should be kept closed. Store in steel or plastic containers.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: For general use, apply product by spray, mop, or with standard steam and pressure wash cleaning equipment. It can also be applied using a foam generator, or any convenient sprayer. Product can be used as is or by using heat and pressure or mechanical scrubbing. Rinse thoroughly with fresh water for a residue-free surface. In direct applications, foaming will be most effective as it will allow more contact time for the product to work. In a typical foam cleaning application operation the surface to be cleaned will be thoroughly covered with foam and allowed to stand for several minutes. The foam is rinsed away with clean water using a hot pressure or low pressure washer. Product can be applied with a variety of spraying or washing equipment, depending upon the type and scale of the shoreline or beach to be cleaned. For large areas such as beaches, the product can be sprayed from water trucks or other vehicles equipped with pumps, hoses, and nozzles to aerially deliver cleaner. On smaller oily surfaces, the product can be applied with hand sprayers or portable pumps may be used to spray directly onto oily surfaces. Dose rates may vary depending on type and amount of petroleum spilled, and other site conditions such as water, temperatures, and porosity of shoreline. Cold weather applications will require more contact time before initiating recovery. The treated product can be removed by several means including but not limited to: sorbent pads, oil skimmers, collection booms, use of vacuum trucks, berm collecting, drumming, frac tanks, or other appropriate containment and collection mechanism.

2. Concentration/Application Rate: For spills on shorelines and beaches, the product can be used undiluted up to 14% dilution with fresh water. After application, the product should be allowed to penetrate and dissolve the oily surface for up to 30 minutes, longer is preferable – if possible, to maximize contact time. For light cleaning, use up to 1:200 parts product to water. For heavy cleaning, use up to 1:14 parts product to water.

3. Conditions for Use: Product can be used in fresh or salt water, sand beaches, gravel, cobble, coarse sand and rocky shores, public beaches, and other sensitive or high impact sites.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
MARINE GREEN CLEAN PLUS™	Menidia beryllina	28.00 96-hr
	Mysidopsis bahia	53.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	18.00 96-hr
	Mysidopsis bahia	23.00 48-hr
MARINE GREEN CLEAN PLUS™	Menidia beryllina	30.00 96-hr
& No. 2 Fuel Oil (1:10)	Mysidopsis bahia	32.00 48-hr
Reference Toxicant (DSS)	Menidia beryllina	1.06 96-hr
	Mysidopsis bahia	0.97 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: NA
2. Pour Point: 28°F
3. Viscosity: 80.2 cSt @ 25°C
4. Specific Gravity: 8.6 @70°F
5. pH: 11-12.5
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL
8. Additives: CONFIDENTIAL
9. Solubility: Completely soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.827
Cadmium	0.025
Chromium	0.078
Copper	0.062
Lead	<0.025
Mercury	<0.013
Nickel	0.220
Zinc	1.990
Cyanide	<0.02
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-44
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: AUGUST 5, 2010
UPDATED LISTING LETTER DATE: MARCH 1, 2023
“CLEANGREEN® PLANET WASH”

I. NAME, BRAND, OR TRADEMARK
CLEANGREEN® PLANET WASH
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
U.S. AG, LLC
P.O. Box 368
Hogansville, GA 30230
Phone: (706) 637-1111
E-mail: carl@unitedstatesag.com
Website: www.unitedstatesag.com
(Mr. Carl Schneider)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
U.S. AG, LLC
7054 Lone Oak Road
Hogansville, GA 30230
Phone: (706) 637-1111
E-mail: carl@unitedstatesag.com
Website: www.unitedstatesag.com
(Mr. Carl Schneider)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: No special requirements.
3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing required, however, goggles are recommended. If eye or skin irritation occurs, flush with plenty of fresh water.
- 4.a. Maximum storage temperature: 120°F continuous, 140°F up to 5 days
- 4.b. Minimum storage temperature: 35°F
- 4.c. Optimum storage temperature range: 40°F to 120°F
- 4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

5 years in sealed polydrums or totes (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Product may be applied to any oil coated surface, such as beaches, equipment, rocks, etc. A variety of pumps or sprayers may be used for direct application to contaminates, back-pack, drum pumps, pick-up sprayers, etc.
2. Concentration/Application Rate: Where ever higher oil concentrations occur use approximately a 1:10 dilution ratio (product:water). Lightly soiled areas will require a 1:10 to 1:30 ratio.
3. Conditions for Use: Residue from surface washing should be collected and disposed of according to local, state, and federal regulations. The collection of residue can be determined on a site by site basis based on best practices of the area.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
CLEANGREEN® PLANET WASH	Menidia beryllina	136.10 96-hr
	Mysidopsis bahia	70.70 48-hr
No. 2 Fuel Oil	Menidia beryllina	3.35 96-hr
	Mysidopsis bahia	2.24 48-hr
CLEANGREEN® PLANET WASH & No. 2 Fuel Oil (1:10)	Menidia beryllina	4.73 96-hr
	Mysidopsis bahia	2.24 48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.25 96-hr
	Mysidopsis bahia	10.53 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >93°C
2. Pour Point: +25°F
3. Viscosity: 3.72 @40°C
4. Specific Gravity: 1.0691 @70°F
5. pH: 9.9
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL
8. Additives: CONFIDENTIAL
9. Solubility: Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.0265
Cadmium	<0.005
Chromium	0.0985
Copper	<0.0150
Lead	<0.0100
Mercury	0.0005
Nickel	<0.0250
Zinc	0.2455
Cyanide	<0.300
Chlorinated Hydrocarbons	<5.0

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**8/05/2010
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-45
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: AUGUST 5, 2010
“SOC-10”

I. NAME, BRAND, OR TRADEMARK
SOC 10 (SURFACE OIL CLEANER)
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Oil Treatment International AG
Seestrasse 5
CH-6300 Zug
Switzerland
Phone: updated information required
Fax: updated information required
(Mr. Paul Schuler, CEO)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Eco-Oil Treatment Technologies Corporation
18 Poppy Hills
Laguna Niguel, CA 92677
Phone: (949) 903-40336 (24-Hour)
E-mail: EcoOilTreatment@gmail.com
(Mr. William Azzalino)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (water based)
2. Ventilation: No special requirements.
3. Skin and eye contact; protective clothing; treatment in case of contact: In case of eye contact, flush with water. In case of skin contact, wash with water. If swallowed, drink water to dilute and induce vomiting.
- 4.a. Maximum storage temperature: 60°C
- 4.b. Minimum storage temperature: 0°C
- 4.c. Optimum storage temperature range: 10°C to 30°C
- 4.d. Temperatures of phase separations and chemical changes: 85°C

V. SHELF LIFE

2 years or more if stored correctly in plastic drums and at recommended temperatures.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Product may be applied by manual or mechanical means including but not limited to: hand operated spraying flask, spraying equipment and jet spraying equipment. Application mixture, once applied, should be washed with water or any suitable type for desired end result after about 3 minutes. Application mixture can be applied without further action or may be scrubbed, rubbed, or abraded as desired until diluted hydrocarbons have been removed from soil, sand, or rocks.
2. Concentration/Application Rate: Product should be applied at a 1:12 product to water ratio: 1:12 (1 oz of SOC 10 concentrated:11 oz water or 1 ml SOC 10 concentrated to 11 ml water).
3. Conditions for Use: Product may be used in fresh, river, brackish, or salt water of any temperature above 35°F. Optimum temperature for normal contamination is 25°C for heavy or aged oil. Product is suitable for use on crude oils and petroleum products that retain the majority of their VOCs including oil slicks, oil sheens, oil emulsions, and oil spills. It is not suitable for use on tar balls or other tar masses, or tar sands. For in-situ washing of sands, soils, and vegetation, a lined recovery trench may be built down slope to recover any residue. As washing occurs, pump residue from trench and dispose according to federal, state, and local regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
SOC 10	Menidia beryllina	20,007 96-hr
	Mysidopsis bahia	9,639 48-hr
No. 2 Fuel Oil	Menidia beryllina	3.76 96-hr
	Mysidopsis bahia	2.04 48-hr
SOC 10 & No. 2 Fuel Oil (1:10)	Menidia beryllina	6.31 96-hr
	Mysidopsis bahia	2.24 48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.19 96-hr
	Mysidopsis bahia	10.53 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 122°F
2. Pour Point: 29°F
3. Viscosity: 1.261 cps @40°C
4. Specific Gravity: 0.9970 g/cc @60°F
5. pH: 7.3
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: None
8. Additives: None
9. Solubility: Completely water soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.050
Cadmium	<0.035
Chromium	<0.025
Copper	<0.050
Lead	<0.060
Mercury	0.0005
Nickel	<0.050
Zinc	0.052
Cyanide	<0.150
Chlorinated Hydrocarbons	<1.0

TECHNICAL PRODUCT BULLETIN #SW-46
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: AUGUST 17, 2010
“BIOGRASS EXTRA[®]”

I. NAME, BRAND, OR TRADEMARK

BIOGRASS EXTRA[®]

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Química del Desierto, S. De R.L. de C.V.

Madrid 2001-A

Col. Mirador

Chihuahua City, Chihuahua, Mexico C.P. 31205

Phone: +52-1-614-110-2650

E-mail: erich.wolf@biograssextra.com

Website: www.biograssextra.com

(Ing. Erich Wolf)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

HRD Ecological Equations LLC

1417 Palma Plaza

Austin, Texas, 78703

Phone: (512) 789-4881

E-mail: info@biograssextra.com

(Mr. Howard Reed)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous).
2. Ventilation: No special requirements.
3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing required; however goggles are recommended. In case of eye irritation, flush with plenty of fresh water.
- 4.a. Maximum storage temperature: 120°F continuous, 140°F up to 5 days
- 4.b. Minimum storage temperature: 35°F
- 4.c. Optimum storage temperature range: 40°F to 120°F
- 4.d. Temperatures of phase separations and chemical changes: Mix well before use if outside the 60-85°F range.

V. SHELF LIFE

Two years minimum.

VI. RECOMMENDED APPLICATION PROCEDURES

Recommended application procedures depending on concentration of contaminants, water salinity levels, water temperature, and the type and age of the contaminant.

There are two means of application: power spraying or direct application.

a. Application via power spraying: Use of a power washer to spray the contaminated surface.

The action may be improved by warming the product during use.

b. Application via direct application: Remove contaminated soil, sand, etc. into a container.

Irrigate the affected ground with the product and let it soak in. Agitate the mixture of water/product/ground and add additional water to float the contaminant off of the surface. A layer of product-contaminant will form which may be physically separated from the soil. The oil in this layer may be separated by dehydration or pumping to prepare the contaminant for disposal or reclamation. The clean soil or sand may be returned to its original environment.

The residue should be removed and disposed of as required by local, state, or federal regulations. The on-site coordinator can determine the best way to recover the residue based on the spill type, surface, and environment of the area.

Concentrations: The concentration of the BIOGRASS® EXTRA product to be used depends on the density of the contaminant. Normally the product is used in a one-to-one proportion with the contaminant.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
BIOGRASS® EXTRA	Menidia beryllina	548.66 96-hr
	Mysidopsis bahia	703.43 48-hr
No. 2 Fuel Oil	Menidia beryllina	2.51 96-hr
	Mysidopsis bahia	2.24 48-hr
BIOGRASS® EXTRA & No. 2 Fuel Oil (1:10)	Menidia beryllina	2.54 96-hr
	Mysidopsis bahia	2.24 48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.25 96-hr
	Mysidopsis bahia	11.71 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >93°C
2. Pour Point: 21.0°F
3. Viscosity: 1.37 cSt @40°C
4. Specific Gravity: 1.0253 @60°F
5. pH: 7.1
6. Surface Active Agents: Anionic and nonionic, proprietary, surfactants
7. Solvents: Water
8. Additives: Sodium phosphate dibasic, sodium chloride
9. Solubility: Miscible in water and some solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.0702
Cadmium	0.0024
Chromium	0.0174
Copper	0.0158
Lead	0.0086
Mercury	<0.001
Nickel	0.0580
Zinc	0.3092
Cyanide	<0.010
Chlorinated Hydrocarbons	<1.0

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**4/04/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-47
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: AUGUST 25, 2010
“ENVIRONMENTAL 1 CRUDE OIL CLEANER”

I. NAME, BRAND, OR TRADEMARK
ENVIRONMENTAL 1 CRUDE OIL CLEANER
(aka, ENVIRONMENTAL 1 WASHING AGENT)
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Environmental 1, LLC
P.O. Box 9
Jackson, TN 38302
Phone: (615) 269-0506
Fax: (615) 269-0025
E-mail: info@environmental-one.com
E-mail: mfb@environmental-one.com
Website: www.environmental-one.com
(Ms. Mary Frances Blankenship, President)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Environmental 1, LLC
P.O. Box 9
Jackson, TN 38302
Phone: (615) 269-0506
Fax: (615) 269-0025
E-mail: info@environmental-one.com
E-mail: mfb@environmental-one.com
Website: www.environmental-one.com
(Ms. Mary Frances Blankenship, President)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable, no hazards or restrictions
2. Ventilation: No special requirements.
3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing required; however goggles are recommended if used with a pressure washer. If eye or skin irritation occurs, flush with plenty of fresh water.
- 4.a. Maximum storage temperature: 140°F
- 4.b. Minimum storage temperature: 35°F

- 4.c. Optimum storage temperature range: 40°F to 120°F
 4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

Unlimited in sealed polydrums or totes (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURES

ENVIRONMENTAL 1 CRUDE OIL CLEANER cleans oil from solid surfaces such as beaches, rocks, machines, buildings, tools, and other hard surfaces.

1. Spray ENVIRONMENTAL 1 CRUDE OIL CLEANER on oil surface to be cleaned with a drum pump sprayer or for smaller jobs use a hand pump sprayer.
2. On areas of heavy oil accumulation use product directly on the spill, or for areas of lighter accumulation use a 1:10 to 1:30 dilution ratio (product:water).
3. The oil and cleaner form a loose emulsion that can be rinsed away. Oil displaced from hard surfaces can be skimmed from the rinse water, absorbed with an oil absorbent, or removed via commercial waste removal.
4. May be used with fresh or salt water in normal climatic temperatures.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
ENVIRONMENTAL 1 CRUDE	Menidia beryllina	22.68 96-hr
OIL CLEANER	Mysidopsis bahia	16.27 48-hr
No. 2 Fuel Oil	Menidia beryllina	2.24 96-hr
	Mysidopsis bahia	0.99 48-hr
ENVIRONMENTAL 1 CRUDE	Menidia beryllina	2.19 96-hr
OIL CLEANER & No. 2 Fuel Oil (1:10)	Mysidopsis bahia	0.43 48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.25 96-hr
	Mysidopsis bahia	11.71 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >93°C
2. Pour Point: +26.0°F
3. Viscosity: 3.34 cSt @ 40°C
4. Specific Gravity: 1.01 @ 15°C
5. pH: 6.2
6. Surface Active Agents: Anionic, nonionic, zwitterionic surfactants
7. Solvents: None
8. Additives: Preservative

9. Solubility: Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.0021
Cadmium	<0.0010
Chromium	<0.0030
Copper	<0.0030
Lead	<0.0020
Mercury	<0.0005
Nickel	<0.0050
Zinc	<0.0030
Cyanide	<0.010
Chlorinated Hydrocarbons	<5.00

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**3/16/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-48
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: OCTOBER 4, 2010
“SANDKLENE 950”

I. NAME, BRAND, OR TRADEMARK
SANDKLENE 950
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
MDEChem, Inc.
923 10th Street PMB 101
Floresville, TX 78114
Phone: updated information required
E-mail: updated information required
Website: www.mdechem.com
(Mr. Paul Sack)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Imperial Petroleum, Inc. 101 NW 1 st Street #213 Evansville, IN 47708 Phone: (812) 867-1433 E-mail: Jwilsonx1@aol.com (Mr. Jeff Wilson)	<u>Mailing Address:</u> Imperial Petroleum, Inc. P.O. Box 1006 Evansville, IN 47706 (Mr. Jeff Wilson)
--	---

Archer Petroleum Corp.
490-580 Hornby St.
Vancouver, Canada V6C 3B6
604-683-7588
(Mr. Colin Bowkett)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: Normal
3. Skin and eye contact; protective clothing; treatment in case of contact: Wear chemically impervious gloves. No other special equipment or clothing is required; however, goggles are recommended. If eye or skin irritation occurs, flush with plenty of water.
- 4.a. Maximum storage temperature: 120°F continuous, 140°F up to 5 days
- 4.b. Minimum storage temperature: 35°F

- 4.c. Optimum storage temperature range: 40°F to 120°F
 4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

Unlimited in sealed drums or totes (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: SANDKLENE 950 is most effective in enclosed systems using centrifuges, shearing devices, or similar high speed equipment to process material. Under these conditions, SANDKLENE 950 and water are recycled continuously. In smaller applications on solid surfaces, SANDKLENE 950 may be applied with sprayers using water diluted product directly onto solid oil coated surfaces.
2. Concentration/Application Rate: Oil contaminated sands are placed in an enclosed chamber with a solution of SANDKLENE 950 and water. The concentration of SANDKLENE 950 in water ranges from about 0.15% to about 1.0%. The total volume of solution is 350 gallons per 3 cubic yards of contaminated sand. The mixture is agitated at an elevated temperature in the range of 100°F to 150°F. The actual treatment rate will vary within the recommended range, depending upon the nature of sand, the nature of the oil, and the percentage of oil content.
3. Conditions for Use: The water and oil parts are separated from the sand. The water part is continuously recycled, the oil is recovered, and the sand can be disposed according to federal, state, and local regulations. Dose rates and SANDKLENE 950 concentrations will vary with the type and amount of petroleum present, the extent of weathering, and other site specific conditions, including temperature and time available to let the solution contact the oil.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
SANDKLENE 950	Menidia beryllina	1768.73 96-hr
	Mysidopsis bahia	1263.78 48-hr
No. 2 Fuel Oil	Menidia beryllina	8.95 96-hr
	Mysidopsis bahia	2.41 48-hr
SANDKLENE 950& No. 2 Fuel Oil (1:10)	Menidia beryllina	4.48 96-hr
	Mysidopsis bahia	2.24 48-hr
Reference Toxicant (DLS)	Menidia beryllina	12.25 96-hr
	Mysidopsis bahia	11.71 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >93°C
2. Pour Point: +10°F
3. Viscosity: 3.69 cSt @ 40°C

4. Specific Gravity: 1.2806 @60°F
5. pH: 9.4
6. Surface Active Agents: None
7. Solvents: None
8. Additives: None
9. Solubility: Completely soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.540
Cadmium	<0.209
Chromium	1.100
Copper	<0.205
Lead	<0.494
Mercury	0.0009
Nickel	<0.274
Zinc	<0.204
Cyanide	<1.150
Chlorinated Hydrocarbons	<0.100

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**3/03/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-49
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: NOVEMBER 10, 2010
“DE-SOLV-IT CLEAN AWAY APC SUPER CONCENTRATE”

I. NAME, BRAND, OR TRADEMARK
DE-SOLV-IT CLEAN AWAY APC SUPER CONCENTRATE
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Orange-Sol Blending and Packaging
1400 N Fiesta Boulevard
Gilbert, AZ 85233
Phone: (800) 877-7771
Fax: (480) 497-0444
E-mail: updated information required
Website: www.orange-sol.com
(Mr. Albert Farnsworth or
Mr. Jack Farnsworth at (480) 319-0141)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Bell Tech
Master Distributor
P.O. Box 2198
Valdez, AK 99686
Phone: (907) 602-0111
Fax: (907) 835-4535
E-mail: bellenterprise@cvinternet.net
(Mr. Randy Bell)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-combustible
2. Ventilation: No special requirements
3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment of clothing required; however, goggles are recommended where splash is potential. If eye or skin irritation occurs, flush with ample fresh water.
- 4.a. Maximum storage temperature: 210°F
- 4.b. Minimum storage temperature: 34°F
- 4.c. Optimum storage temperature range: 55°F to 90°F

4.d. Temperatures of phase separations and chemical changes: There are no known phase separations, chemical changes, or other alterations that will change the effectiveness of the product.

V. SHELF LIFE

Two (2) years in sealed drums or totes (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: DE-SOLV-IT CLEAN AWAY APC SUPER CONCENTRATE can be used on all oil coated surfaces including sand and rocks through a detergency mechanism. Product should be used with handheld sprayers or for larger applications applied with truck mounted sprayers. Remove contamination with DE-SOLV-IT CLEAN AWAY APC SUPER CONCENTRATE, followed by a rinse.
2. Concentration/Application Rate: For oil spill removal and heavy duty cleaning, dilute product with water using a 1:1 ratio.
3. Conditions for Use: DE-SOLV-IT CLEAN AWAY APC SUPER CONCENTRATE can be used in salt or fresh water, with no limitations as to usage within the optimum temperature parameters (application may be made at or above 35°F, with optimum above 48°F). Cleaning of oil soaked areas should be done in a contained area and residue should be collected. For sand or vegetation cleaning, a berm may be constructed down slope that will collect the residue for disposal. All disposal residues should be done according to federal, state, and local regulations. In general, the technique used for collection of the oil/soap residue should be determined by the onsite contractor based on the environment of the area to be cleaned and the equipment and materials available for collection. Cleanup residue should be collected and disposed of in accordance with local, state, and federal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
DE-SOLV-IT CLEAN AWAY APC SUPER CONCENTRATE	Menidia beryllina	20.95 96-hr
	Mysidopsis bahia	30.95 48-hr
No. 2 Fuel Oil	Menidia beryllina	4.07 96-hr
	Mysidopsis bahia	0.86 48-hr
DE-SOLV-IT CLEAN AWAY APC SUPER CONCENTRATE & No. 2 Fuel Oil (1:10)	Menidia beryllina	6.42 96-hr
	Mysidopsis bahia	0.69 48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.04 96-hr
	Mysidopsis bahia	8.19 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >93°C
2. Pour Point: +20°F
3. Viscosity: 3.1 cSt @ 40°C
4. Specific Gravity: 1.024 @60°F
5. pH: 9.03
6. Surface Active Agents: PROPRIETARY
7. Solvents: PROPRIETARY
8. Additives: Yes
9. Solubility: 100 percent

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<1.0
Cadmium	<0.5
Chromium	<0.5
Copper	<2.0
Lead	<1.0
Mercury	<0.005
Nickel	<1.0
Zinc	<2.5
Cyanide	0.08
Chlorinated Hydrocarbons	<0.05

LISTING CHANGES PENDING;
VERIFICATION BY MANUFACTURER AND EPA REQUIRED

TECHNICAL PRODUCT BULLETIN #SW-50
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: NOVEMBER 17, 2010
"EO ALL PURPOSE SOAP-LAVENDER"

I. NAME, BRAND, OR TRADEMARK
EO ALL PURPOSE SOAP-LAVENDER
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
EO Products/Small World Trading Company
90 Windward Way
San Rafael, CA 94901
Phone: (415) 945-1900
Fax: (415) 945-7117
E-mail: kimberly@eoproducts.com or sam@eoproducts.com
Website: www.eoproducts.com
(Ms. Kimberly Luce or Mr. Sam Borri)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
EO Products/Small World Trading Company
90 Windward Way
San Rafael, CA 94901
Phone: (415) 945-1900
Fax: (415) 945-7117
E-mail: kimberly@eoproducts.com or
sam@eoproducts.com
Website: www.eoproducts.com
(Ms. Kimberly Luce or Mr. Sam Borri)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: Normal
3. Skin and eye contact; protective clothing; treatment in case of contact: Rinse thoroughly after use. Avoid eye contact. In case of such contact, immediately flush with large amounts of cool water for at least 15 minutes. Consult a physician if irritation develops. Protective gloves are recommended for extended or prolonged contact (e.g., immersing hands). Wear safety glasses if the method of use presents the likelihood of eye contact. Do not ingest. In case of ingestion, consult a physician.
- 4.a. Maximum storage temperature: 45°C

- 4.b. Minimum storage temperature: 4°C
 4.c. Optimum storage temperature range: 22°C to 30°C
 4.d. Temperatures of phase separations and chemical changes: Phase separation may occur at <15°C (but will restore to original condition at optimum temperature).

V. SHELF LIFE

Three (3) years (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: EO ALL PURPOSE SOAP may be applied by pouring, spraying (when diluted 1:4), dispensing equipment, or by scrubbing machines.
2. Concentration/Application Rate: Apply EO ALL PURPOSE SOAP full strength (undiluted) to surface area by pouring or with dispensing equipment concentrating on areas with heaviest contamination first. Apply diluted (1:4 dilution rate) EO ALL PURPOSE SOAP with sprayer. Agitate and scrub well. Rinse thoroughly. For heavily contaminated surfaces, EO ALL PURPOSE SOAP should always be used full strength (undiluted). For average to light contamination, EO ALL PURPOSE SOAP may be diluted from 2x-10x with water.
3. Conditions for Use: During cleaning, contain the oil soaked area and collect residue. For sand and vegetation cleaning, a berm may be constructed down slope that will collect the residue for disposal. All disposal of residue should be done according to federal, state, and local regulations. In general, the technique used for the collection of the oil/soap residue should be determined by the on-site contractor based on the environment of the area to be cleaned, and equipment and materials available for collection.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
EO ALL PURPOSE SOAP	Menidia beryllina	21.33 96-hr
No. 2 Fuel Oil	Mysidopsis bahia	83.65 48-hr
	Menidia beryllina	8.95 96-hr
	Mysidopsis bahia	2.41 48-hr
EO ALL PURPOSE SOAP & No. 2 Fuel Oil (1:10)	Menidia beryllina	3.14 96-hr
	Mysidopsis bahia	2.37 48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.04 96-hr
	Mysidopsis bahia	8.19 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >93°C

2. Pour Point: +24°F
3. Viscosity: 349.5 cSt @ 40°C
4. Specific Gravity: 1.0208 @60°F
5. pH: 5.88
6. Surface Active Agents: PROPRIETARY
7. Solvents: PROPRIETARY
8. Additives: PROPRIETARY
9. Solubility: Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.540
Cadmium	<0.209
Chromium	0.202
Copper	<0.205
Lead	<0.494
Mercury	<0.000388
Nickel	5.99
Zinc	<0.204
Cyanide	<1.15
Chlorinated Hydrocarbons	<2.0

TECHNICAL PRODUCT BULLETIN #SW-51
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: DECEMBER 7, 2010
“DYNAMIC GREEN™”

I. NAME, BRAND, OR TRADEMARK

DYNAMIC GREEN™

Type of Product: Surface Washing Agent (Water-based)

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Wechem, Inc.

5734 Susitna Drive

Harahan, LA 70123

Phone: (800) 426-0512

Phone: (504) 733-1152

Fax: (504) 733-2218

E-mail: mwisecarver@wechem.com or lhernandez@wechem.com

Website: www.wechem.com

(Mr. Mike Wisecarver)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Wechem, Inc.

5734 Susitna Drive

Harahan, LA 70123

Phone: (800) 426-0512

Phone: (504) 733-1152

Fax: (504) 733-2218

E-mail: mwisecarver@wechem.com or lhernandez@wechem.com

Website: www.wechem.com

(Mr. Mike Wisecarver)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)

2. Ventilation: Not required.

3. Skin and eye contact; protective clothing; treatment in case of contact: Wear protective gloves that are chemical resistant, rubber. In case of skin contact, wash with soap and water. If irritation develops seek medical attention. Wear safety glasses/goggles for eye protection. In case of eye contact flush with water for 15 minutes. If irritation develops seek medical attention.

4.a. Maximum storage temperature: 140°F

4.b. Minimum storage temperature: 34°F

4.c. Optimum storage temperature range: >50°F and <100°F

4.d. Temperatures of phase separations and chemical changes: <35°F and >100°F.

V. SHELF LIFE

DYNAMIC GREEN™ has a shelf life of 6-10 years in sealed poly drums or totes (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Product may be applied to any surface for removal of oils. The product can be applied through power washers, garden type sprayers, fire pump or any other portable pump with seawater or freshwater suction that is equipped with a chemical inductor or feed pump. For smaller areas properly diluted DYNAMIC GREEN™ may be applied with sponge, mop, scrub brush or cloth. Apply liberally, adjusting dilution on site if necessary.
2. Concentration/Application Rate: For heavily weathered oil on rocks, a diluted solution of 4 parts water to 1 part product is recommended. For heavily weathered oil on beaches/sand a diluted solution of 7 parts water to 1 part product is effective. For removing oil from vegetation, a diluted solution of 10/20 parts water to 1 part product is preferred. Product is effective in fresh or salt water.
3. Conditions for Use: Allow diluted product to soak for 20-30 minutes to soften and lift oil from surface. Reapplication may be necessary for severely contaminated areas. Vacuum suction equipment and sorbent boom or pads should be used to collect the washed effluent. When proper containment equipment is in place and a soak time of 20 minutes has been achieved, a diluted solution of 20 parts water to 1 part product should be applied through a pressure washer or flushing device to remove oils. Product and oil should be vacuumed up or absorbed with absorbent boom and disposed of according to EPA guidelines.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
DYNAMIC GREEN™	Menidia beryllina	106.00 96-hr
	Mysidopsis bahia	66.60 48-hr
No. 2 Fuel Oil	Menidia beryllina	13.00 96-hr
	Mysidopsis bahia	3.16 48-hr
EO ALL PURPOSE	Menidia beryllina	6.85 96-hr
SOAP & No. 2 Fuel Oil (1:10)	Mysidopsis bahia	3.30 48-hr
Reference Toxicant (SDS)	Menidia beryllina	2.67 96-hr
	Mysidopsis bahia	9.14 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >200°F
2. Pour Point: -16°F
3. Viscosity: <10 cSt @ 78°F
4. Specific Gravity: 1.01 @77°F
5. pH: 7.5
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL
8. Additives: CONFIDENTIAL
9. Solubility: Infinitely miscible

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.25
Cadmium	<0.25
Chromium	<0.25
Copper	<0.25
Lead	<0.25
Mercury	<2.00
Nickel	<0.25
Zinc	<0.25
Cyanide	<0.50
Chlorinated Hydrocarbons	ND

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**8/29/2012
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-52
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: DECEMBER 9, 2010
“VERU-SOLVE™ MARINE 200 HP”

I. NAME, BRAND, OR TRADEMARK
VERU-SOLVE™ MARINE 200 HP
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
VeruTEK® Technologies
65 West Dudley Town Road, Suite 100
Bloomfield, CT 06002
Phone: updated information required
Fax: updated information required
E-mail: updated information required
Website: updated information required
(Ms. Bethany McAvoy)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
VeruTEK® Technologies
65 West Dudley Town Road, Suite 100
Bloomfield, CT 06002
Phone: updated information required
Fax: updated information required
E-mail: updated information required
Website: updated information required
(Ms. Bethany McAvoy)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: Use in a well ventilated area.
3. Skin and eye contact; protective clothing; treatment in case of contact: Prevent eye contact, wear safety glasses or goggles. If eye contact occurs remove contact lenses at once. Flush with water for at least 15 minutes. If irritation persists seek medical attention. Prevent skin contact, nitrile gloves are recommended. Boots, aprons, or bodysuits should be worn as necessary. Contact with product may cause slight redness. Prolonged or repeated exposure may cause drying of skin. If skin contact occurs wash affected area with copious amounts of soap and water. Respiratory protection is not normally required. If adequate ventilation is unavailable use NIOSH approved air-purifying respirator with organic vapor cartridge or canister. The product is not likely toxic. If ingestion occurs DO NOT induce vomiting. Rinse mouth thoroughly with

water. Offer water to drink. DO NOT administer anything by mouth to an unconscious person.

4.a. Maximum storage temperature: Should not exceed 110°F (43.3°C)

4.b. Minimum storage temperature: Above 41°F (5°C)

4.c. Optimum storage temperature range: Between 41°F and 110°F (5°C to 43.3°C)

4.d. Temperatures of phase separations and chemical changes: Stable. There is no known temperature within the maximum and minimum storage temperature that would cause phase separation, chemical changes, or other known alterations to the effectiveness of the product.

V. SHELF LIFE

Indefinite, product will not degrade over time.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: VERU-SOLVE™ MARINE 200 HP is an aqueous based liquid without solids that can be readily applied through standard spray equipment. VERU-SOLVE™ MARINE 200 HP is suited for treating oil shorelines, sensitive environments, and for treating access limited areas. VERU-SOLVE™ MARINE 200 HP may be applied directly to oil on shoreline, beaches, rocks, or marsh surfaces by agricultural or standard sprayers attached to all terrain vehicles (ATVs), or workboats equipped with spray booms. The preferred and most effective method of application is to use a low-volume, low-pressure pump.

2. Concentration/Application Rate: The product can be applied undiluted to the spilled oil.

VERU-SOLVE™ MARINE 200 HP should be applied as droplets, not fogged or atomized.

System Calibration – Spray systems should be calibrated to insure accurate application rates for successful application and dosage control.

3. Conditions for Use: VERU-SOLVE™ MARINE 200 HP is sprayed directly on oil coated materials; and can be used on fresh or aged oil or oil combinations. Application may be limited at sub-freezing temperatures (<31°F) without inclusion of antifreeze additives. VERU-SOLVE™ MARINE 200 HP can be applied at temperatures above freezing without notable changes in viscosity with increasing temperature. Application is not affected by increasing salinity. VERU-SOLVE™ MARINE 200 HP can be used at temperatures above freezing and at temperatures above 70°F. VERU-SOLVE™ MARINE 200 HP will separate the oil and water from the sand or soiled surface. Cleaning of oil soaked surfaces should be done in a contained area and residue should be collected. For sand or vegetation cleaning, a berm may be constructed down slope that will collect the residue for disposal. Oil that has separated from sand or vegetation may be recovered from the substrate and collected for disposal. All disposal of residue should be done in accordance with federal, state, and local regulations. In general, the technique used for the collection of the oil/product residue should be determined by the On-Scene Coordinator based on the environment of the area to be cleaned, equipment and materials available for collection, and disposal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
VERU-SOLVE™	Menidia beryllina	418.32 96-hr
MARINE 200 HP	Mysidopsis bahia	76.98 48-hr
No. 2 Fuel Oil	Menidia beryllina	13.36 96-hr
	Mysidopsis bahia	1.94 48-hr
VERU-SOLVE™	Menidia beryllina	10.67 96-hr
MARINE 200 HP & No. 2 Fuel Oil (1:10)	Mysidopsis bahia	2.51 48-hr
Reference Toxicant (SLS)	Menidia beryllina	13.36 96-hr
	Mysidopsis bahia	12.08 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >93°C
2. Pour Point: +18°F
3. Viscosity: 1.77391 cSt @ 40°C
4. Specific Gravity: 1.017 @60°F
5. pH: 7.01
6. Surface Active Agents: PROPRIETARY
7. Solvents: None
8. Additives: None
9. Solubility: Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.0025
Cadmium	<0.0010
Chromium	0.0326
Copper	0.0093
Lead	<0.0020
Mercury	0.00109
Nickel	0.0077
Zinc	0.0165
Cyanide	<0.010
Chlorinated Hydrocarbons	<0.025

TECHNICAL PRODUCT BULLETIN #SW-53
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JANUARY 26, 2011
“NATURAMA G3 A-5”

I. NAME, BRAND, OR TRADEMARK

NATURAMA G3 A-5

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Green Life Development, Inc.

5112 W. Charleston Boulevard, Suite C

Las Vegas, NV 89146

Mobile: (702) 355-5102

Fax: (702) 448-6977

E-mail: david@greenlifedevelopment.com

Website: www.greenlifedevelopment.com

(Mr. David A. Levy)

Merlin-Tao Ltd.

65 Yigal Alon Street POB 91

Tel Aviv, Israel 67443

Phone: 972-3-562-8020

Fax: 972-3-562-8021

E-mail: asaf@merlin-tao.com

Website: www.merlin-tao.com

(Mr. Asaf Yaari, CEO)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Green Life Development, Inc.

5112 W. Charleston Boulevard, Suite C

Las Vegas, NV 89146

Mobile: (702) 355-5102

Fax: (702) 448-6977

E-mail: david@greenlifedevelopment.com

Website: www.greenlifedevelopment.com

(Mr. David A. Levy)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)

2. Ventilation: No special requirements.

3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing is required; however, goggles are recommended. If eye or skin irritation occurs, flush with plenty of water.

4.a. Maximum storage temperature: 120°F continuous, 140°F up to 5 days

4.b. Minimum storage temperature: 35°F

4.c. Optimum storage temperature range: 40°F to 120°F

4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

NATURAMA G3 A-5 has unlimited shelf life in sealed poly drums.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Product may be applied by any method (e.g., drum pump, pressurized spray applicator, brush, or aqueous wash tank), depending on the surface; and type and viscosity of the oil/contamination to be treated.
2. Concentration/Application Rate: The dilution ratio depends on the amount and type of contamination to be removed. For light contamination areas a 1:6 dilution ratio (product to fresh/salt water) with a 2-3 minutes wait. For heavier/thick/burnt contamination, the exact ratio should be determined by the field coordinator but a general starting point of 20-25% should remove most contamination (grease, burnt oil, diesel, tar, etc.) after a contact time of 10-15 minutes before rinsing with water/steam.
3. Conditions for Use: Cleanup residue must be collected and should be disposed of in accordance with local, state, and federal regulations. Where possible, the product/oil mixture can be recovered and processed using an oil separator system or a stagnant tank. A circulating wash tank fitted with an oil separator or filter system extends the life of NATURAMA G3 A-5 by weeks, greatly impacting the waste reduction.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
NATURAMA G3 A-5	Menidia beryllina	577.68 96-hr
	Mysidopsis bahia	482.97 48-hr
No. 2 Fuel Oil	Menidia beryllina	2.39 96-hr
	Mysidopsis bahia	0.32 48-hr
NATURAMA G3 A-5 & No. 2 Fuel Oil (1:10)	Menidia beryllina	3.68 96-hr
	Mysidopsis bahia	2.24 48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.25 96-hr
	Mysidopsis bahia	12.08 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >93°C
2. Pour Point: +28°F
3. Viscosity: 1.3628 cSt @ 40°C
4. Specific Gravity: 1.006 @60°F
5. pH: 8.39
6. Surface Active Agents: PROPRIETARY
7. Solvents: PROPRIETARY
8. Additives: None
9. Solubility: Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.0092
Cadmium	<0.002
Chromium	0.0262
Copper	<0.006
Lead	0.0062
Mercury	0.0005
Nickel	<0.01
Zinc	<0.0166
Cyanide	0.014
Chlorinated Hydrocarbons	<26.30

TECHNICAL PRODUCT BULLETIN #SW-54
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: FEBRUARY 25, 2011
“SAFE KLEEN”

I. NAME, BRAND, OR TRADEMARK

SAFE KLEEN

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Anti Slip Solutions Ltd

Beauchamp House

402/403 Stourpout Road

Kidderminster, Worcestershire

DY12 1AB, UK

Phone: 44 (0) 345-222-5613

E-mail: info@safe-grip.co.uk

(Mr. Dan Bayliss)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

V4 Distributing

507 West Bird Avenue

Nampa, ID 83686

Phone: (208) 571-8596

E-mail: info@v4distributing.com

(Mr. Todd Vitek)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: IMO Non-flammable (DOT: Non-hazardous)

2. Ventilation: Provide adequate ventilation.

3. Skin and eye contact; protective clothing; treatment in case of contact: Chemical eye goggles should be worn. In case of contact with eyes, rinse immediately with plenty of clean water for at least 15 minutes and seek medical advice. PVC or rubber gloves are recommended. Use protective clothing. Remove contaminated clothing and wash with soap and water.

4.a. Maximum storage temperature: 130°F

4.b. Minimum storage temperature: 40°F

4.c. Optimum storage temperature range: >40°F to <130°F

4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

Five years if stored in tightly closed containers under dry conditions within temperature range.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: For general use apply the product by spray, brush, mop, or standard pressure washing equipment.
2. Concentration/Application Rate: SAFE KLEEN is a concentrated liquid that can be used either as supplied or diluted with hot or cold, fresh or salt water. For small spills dilute 1:3 (product to water) and apply as described. For larger spills prepare a solution of SAFE KLEEN diluted with 50 percent water and apply as described. Concentrations may be adjusted to take account of temperatures, types and age of oil/contaminant and other local site conditions. Surface contact time will also be dependent on temperature. For low temperatures and conditions of heavy contamination extend the contact time, where possible agitation of the product during application time will assist the efficiency of the cleaning. Thoroughly rinse with water.
3. Conditions for Use: Response personnel can determine the best method to collect residue, which can include, but is not limited to, oil skimmers, collecting booms, vacuum equipment, absorbent materials, and other appropriate containment and collecting mechanisms. The cleanup residue should be collected and disposed of in accordance with local, state, and federal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Materials Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
SAFE KLEEN	Menidia beryllina	170.00	96-hr
	Mysidopsis bahia	258.00	48-hr
No. 2 Fuel Oil	Menidia beryllina	3.30	96-hr
	Mysidopsis bahia	6.20	48-hr
SAFE KLEEN & No. 2 Fuel Oil (1:10)	Menidia beryllina	2.60	96-hr
	Mysidopsis bahia	6.50	48-hr
Reference Toxicant (SDS)	Menidia beryllina	7.60	96-hr
	Mysidopsis bahia	16.90	48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: NA; water-based product
2. Pour Point: NA; water-based product
3. Viscosity: 2.33 cSt @ 40°C
4. Specific Gravity: 1.060 @68°F
5. pH: 11.5-13.0
6. Surface Active Agents: PROPRIETARY
7. Solvents: None
8. Additives: PROPRIETARY
9. Solubility: Totally soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.31
Cadmium	<0.16
Chromium	<0.16
Copper	<0.16
Lead	<0.16
Mercury	<0.025
Nickel	<0.16
Zinc	<0.16
Cyanide	ND
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-55
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: FEBRUARY 25, 2011
“CORIBA 700 SR”
(aka, CORIBA 700 ER, CORIBA 700 OS)

I. NAME, BRAND, OR TRADEMARK
CORIBA 700 SR
(aka, CORIBA 700 ER, CORIBA 700 OS)
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Coriba Technologies, LLC
5708 Cadron Creek
North Little Rock, AR 72116
Phone: (501) 834-2972
E-mail: ronrios@bellsouth.net
(Mr. Harvey G. Cobb)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
MLU Services
573 Hawthorne Avenue
Athens, GA 30606
Phone: (706) 569-7300
Fax: (706) 425-0300
(Mr. Billy Ulm)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable
2. Ventilation: Normal (contains ammonia)
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid eye contact due to possible mild eye irritation. In case of eye contact, flush eyes with water for at least 15 minutes. In the case of skin contact, flush with water for at least 15 minutes. If irritation occurs and persists, obtain medical attention. Protective clothing is not normally required.
- 4.a. Maximum storage temperature: 100°F
- 4.b. Minimum storage temperature: 33°F
- 4.c. Optimum storage temperature range: 33°F - 100°F
- 4.d. Temperatures of phase separations and chemical changes: Does not separate.

V. SHELF LIFE
Two years unopened minimum.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: CORIBA 700 SR is covered by U.S. Patent #7678201 (issued on March 16, 2010). The process is designed to remove and recover oil from sand. The product does not react with or alter the oil. Contaminated sand is transferred into a standard sand washer filled with 700 SR. The product is an aqueous solution that, upon contact, reduces the interfacial tension between the oil and the sand. The oil no longer adheres to the sand and is free to float to the surface of the processor and is removed with an auger. The cleaned sand is dried in a centrifuge and the collected liquid is recycled back to the processor. The product has a high vapor pressure and evaporates from the sand leaving no residue or contamination. The separated oil is transferred to a conical vertical tower where it concentrates at the surface and is siphoned off to be used as a fuel or sent to a refinery for further processing. The process solution that collects in the conical tower is recycled back to the processor. The clean, dry sand can be disposed as appropriate. Any sand that collects in the bottom of the conical tower is sent back through the processor. The process can be set up on a beach, waste treatment facility or on a barge for treating sensitive areas like barrier islands. The process chemical is not designed to come into contact with any body of water. There process is not designed to treat contaminated water. The process does not consume the process chemical. Any chemical that remains after the sand has been cleaned can be returned to the manufacturer or sent to an appropriate waste treatment facility.
2. Concentration/Application Rate: CORIBA 700 SR is used at full strength. It is delivered in aqueous solution. The application rate is 200 gallons/ton of oil-contaminated sand.
3. Conditions for Use: CORIBA 700 SR can be applied to contaminated sand as long as the sand mixture is not frozen.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Materials Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
CORIBA 700 SR	Menidia beryllina	1470.00	96-hr
	Mysidopsis bahia	3810.00	48-hr
No. 2 Fuel Oil	Menidia beryllina	11.10	96-hr
	Mysidopsis bahia	3.29	48-hr
CORIBA 700 SR & No. 2 Fuel Oil (1:10)	Menidia beryllina	22.80	96-hr
	Mysidopsis bahia	3.58	48-hr
Reference Toxicant (SDS)	Menidia beryllina	5.70	96-hr
	Mysidopsis bahia	9.04	48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 102°F
2. Pour Point: 200°F
3. Viscosity: 1.0 cps
4. Specific Gravity: 0.981
5. pH: 11.4
6. Surface Active Agents: None
7. Solvents: None
8. Additives: PROPRIETARY
9. Solubility: Miscible with water

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.05
Cadmium	<0.002
Chromium	0.031
Copper	0.25
Lead	0.02
Mercury	<0.01
Nickel	<0.01
Zinc	0.25
Cyanide	<0.1
Chlorinated Hydrocarbons	<0.1

TECHNICAL PRODUCT BULLETIN #SW-56
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: FEBRUARY 25, 2011
“CORIBA 713 SR”
(aka, CORIBA 713 ER, CORIBA 713 OS)

I. NAME, BRAND, OR TRADEMARK
CORIBA 713 SR
(aka, CORIBA 713 ER, CORIBA 713 OS)
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Coriba Technologies, LLC
5708 Cadron Creek
North Little Rock, AR 72116
Phone: (501) 834-2972
E-mail: ronrios@bellsouth.net
(Mr. Harvey G. Cobb)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
MLU Services
573 Hawthorne Avenue
Athens, GA 30606
Phone: (706) 569-7300
Fax: (706) 425-0300
(Mr. Billy Ulm)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable
2. Ventilation: Normal (contains ammonia)
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid eye contact due to possible mild eye irritation. Use chemical safety goggles and/or full face shield where splashing is possible. In case of eye contact, flush eyes with water for at least 15 minutes. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. In the case of skin contact, flush with water for at least 15 minutes. If irritation occurs and persists, obtain medical attention. Protective clothing is not normally required.
- 4.a. Maximum storage temperature: 100°F
- 4.b. Minimum storage temperature: 33°F
- 4.c. Optimum storage temperature range: 33°F - 100°F
- 4.d. Temperatures of phase separations and chemical changes: Does not separate.

V. SHELF LIFE

Two years unopened minimum.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: CORIBA 713 SR is covered by U.S. Patent #7678201 (issued on March 16, 2010). The process is designed to remove and recover oil from sand. The product does not react with or alter the oil. Contaminated sand is transferred into a standard sand washer filled with 713 SR. The product is an aqueous solution that, upon contact, reduces the interfacial tension between the oil and the sand. The oil no longer adheres to the sand and is free to float to the surface of the processor and is removed with an auger. The cleaned sand is dried in a centrifuge and the collected liquid is recycled back to the processor. The product has a high vapor pressure and evaporates from the sand leaving no residue or contamination. The separated oil is transferred to a conical vertical tower where it concentrates at the surface and is siphoned off to be used as a fuel or sent to a refinery for further processing. The process solution that collects in the conical tower is recycled back to the processor. The clean, dry sand can be disposed as appropriate. Any sand that collects in the bottom of the conical tower is sent back through the processor. The process can be set up on a beach, waste treatment facility or on a barge for treating sensitive areas like barrier islands. The process chemical is not designed to come into contact with any body of water. There process is not designed to treat contaminated water. The process does not consume the process chemical. Any chemical that remains after the sand has been cleaned can be returned to the manufacturer or sent to an appropriate waste treatment facility.
2. Concentration/Application Rate: CORIBA 713 SR is used at full strength. It is delivered in aqueous solution. The application rate is 200 gallons/ton of oil-contaminated sand.
3. Conditions for Use: CORIBA 713 SR can be applied to contaminated sand as long as the sand mixture is not frozen. The process is effective at ambient temperature.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Materials Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
CORIBA 713 SR	Menidia beryllina	1070.00	96-hr
	Mysidopsis bahia	2350.00	48-hr
No. 2 Fuel Oil	Menidia beryllina	11.10	96-hr
	Mysidopsis bahia	3.29	48-hr
CORIBA 713 SR & No. 2 Fuel Oil (1:10)	Menidia beryllina	9.55	96-hr
	Mysidopsis bahia	4.04	48-hr
Reference Toxicant (SDS)	Menidia beryllina	5.70	96-hr
	Mysidopsis bahia	9.04	48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 212°F
2. Pour Point: 220°F
3. Viscosity: 1.0 cps
4. Specific Gravity: 0.997
5. pH: 11.0
6. Surface Active Agents: None
7. Solvents: None
8. Additives: PROPRIETARY
9. Solubility: Miscible with water

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.05
Cadmium	<0.002
Chromium	0.031
Copper	0.25
Lead	0.02
Mercury	<0.01
Nickel	<0.01
Zinc	0.25
Cyanide	<0.1
Chlorinated Hydrocarbons	<0.1

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**7/19/2021
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-57
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: MAY 11, 2011
“JEP-MARINE CLEAN”
(aka, ECOVOOM-MARINE)

I. NAME, BRAND, OR TRADEMARK
JEP-MARINE CLEAN
(aka, ECOVOOM-MARINE)
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Nuance Solutions*
900 E. 103rd Street, Suite D
Chicago, IL 60628
Phone: (800) 621-8553
Fax: (800) 621-1276
(Mr. Neil Houtsma)
*(*Nuance Solutions is the manufacturer for Jubilee Environmental Products, product owner)*

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS	
Jubilee Environmental Products	Restored Cleaner LLC
406 S. Boulder, Suite 820	2475 Fairfield Avenue
Tulsa, OK 74103	Bridgeport, CT 06605
Phone: (918) 277-1113	Phone: (203) 335-9555
Fax: (918) 296-3997	Fax: (203) 335-9550
E-mail: jubilinc@aol.com	E-mail: info@restoredcleaner.com
Sales and Inquiries:	Sales and Inquiries:
Phone: (918) 277-1113	Phone: (203) 335-9555
Fax: (918) 296-3997	Fax: (203) 335-9550
E-mail: jubilinc@aol.com	E-mail: info@restoredcleaner.com
(Mr. Thomas J. Rhein, President)	(Mr. Colton Amster)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable
2. Ventilation: Normal.
3. Skin and eye contact; protective clothing; treatment in case of contact: Respiratory protection not required under normal conditions. Protect against generated mists using protective clothing in order to minimize contact (i.e., boots, apron, face shield). Use safety glasses/goggles during handling and application to prevent eye contact. Wear rubber/PVC gloves to prevent skin

contact.

4.a. Maximum storage temperature: 90°F

4.b. Minimum storage temperature: 40°F

4.c. Optimum storage temperature range: 40 – 90°F; product freezes at 32°F

4.d. Temperatures of phase separations and chemical changes: 120°F

V. SHELF LIFE

In unopened containers, shelf life is minimum 2 years.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Product may be diluted with fresh or salt water, and may be applied to any type of surfaces that have been coated with oil or other petroleum-based substances resulting from a spill (e.g., beaches, rocks). Manual pump sprayers should be used to presoak the contaminated areas, and pressure washers should be used to agitate the contaminated areas after a presoak has been applied.

2. Concentration/Application Rate: Shoreline Cleaning – presoak the surface needing to be cleaned, using a manual pump sprayer, with a dilution rate of one (1) part to three (3) parts water for approximately 10 to 15 minutes, without letting the product dry or evaporate. After the contaminated areas have been presoaking for the allotted time, run a dilution rate of one (1) part product to fifteen (15) parts water, through a pressure washer directly onto the contaminant.

3. Conditions for Use: Option temperature range for use is 45 to 212°F. When the contaminants have been released, they can be removed using sorbent pads, suction booms or skimmers, and hauled away and disposed of according to local, state, and federal law. It is recommended that for older or crustier contaminants higher pressure and stronger dilutions be used.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Materials Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
JEP-MARINE CLEAN	Menidia beryllina	88.40	96-hr
	Mysidopsis bahia	153.90	48-hr
No. 2 Fuel Oil	Menidia beryllina	2.70	96-hr
	Mysidopsis bahia	1.63	48-hr
JEP-MARINE CLEAN & No. 2 Fuel Oil (1:10)	Menidia beryllina	3.58	96-hr
	Mysidopsis bahia	2.32	48-hr
Reference Toxicant (SDS)	Menidia beryllina	8.84	96-hr
	Mysidopsis bahia	14.90	48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >100°C

2. Pour Point: -14°C
3. Viscosity: 1.1 cSt
4. Specific Gravity: 1.041
5. pH: 11.2
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: Water
8. Additives: CONFIDENTIAL
9. Solubility: Miscible with water

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.004
Cadmium	0.084
Chromium	0.082
Copper	0.138
Lead	<0.025
Mercury	<0.0012
Nickel	<0.025
Zinc	0.219
Cyanide	0.01
Chlorinated Hydrocarbons	<0.01

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**9/27/2012
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-58
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JUNE 28, 2011
“ETHOS CLEAN”

I. NAME, BRAND, OR TRADEMARK
ETHOS CLEAN
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
MAG7 Venture Group, LLC, DBA MAG7 Technologies
1 Lepage Place, Suite 100
Syracuse, NY 13206
Phone: updated information required
Fax: updated information required
E-mail: updated information required
Website: updated information required
(Mr. Greg Goodell or Mr. Trevor Quig)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
MAG7 Venture Group, LLC, DBA MAG7 Technologies
1 Lepage Place, Suite 100
Syracuse, NY 13206
Phone: updated information required
Fax: updated information required
E-mail: updated information required
Website: updated information required
(Mr. Greg Goodell or Mr. Trevor Quig)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable
2. Ventilation: Move subject to fresh air. If breathing is difficult, obtain medical help.
3. Skin and eye contact; protective clothing; treatment in case of contact: Wash affected skin area with water. Consult physician if irritation persists. Skin irritation will not occur with most users. Flush eyes with a large amount of water for at least 15 minutes. Consult physician if irritation persists. Wear safety glasses and neoprene or rubber gloves during application.
- 4.a. Maximum storage temperature: 120°F
- 4.b. Minimum storage temperature: 35°F
- 4.c. Optimum storage temperature range: 40°F to 120°F
- 4.d. Temperatures of phase separations and chemical changes: NA. Phase separation will not

occur within the storage range. Product should be stored out of direct sunlight unless it is in an Ultraviolet (UV) light resistant container.

V. SHELF LIFE

2 years in a sealed (unopened) container (tote, drum, pail) as delivered. 1 year in an opened container).

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Apply ETHOS CLEAN to oil or contaminant with sprayer, pressure washer, mop, sponge, brush, or rags. Application times will depend on the level of contaminant with a minimum of 30 minutes recommended soak time. The required soak time to remove oil will vary with oil density and degree of weathering. ETHOS CLEAN separates the oil from the physical surface to allow the oil to be sprayed off with a water rinse. ETHOS CLEAN should be mixed into soil applications to increase the effectiveness and reduce the application time.

2. Concentration/Application Rate: Pure concentrate can be used for heavy contamination. Dilution ratios for most applications range from 2 to 1 (parts water to parts ETHOS CLEAN) to 10 to 1 (parts water to parts ETHOS CLEAN). Dilution ratios are dependent on the contamination level and application with heavier crude oil spills requiring a lower dilution ratio. Dilutions up to 50 to 1 (parts water to parts ETHOS CLEAN) can be used for lighter contaminations and cleaning. Rinse with water after usage for residue free surface. Surface cleaning typically requires 5 to 1 or 10 to 1 dilution ratio. These dilution ratios will require 1 gallon of ETHOS CLEAN per 250 square feet of surface area. These dilution ratios can be used in many applications including shorelines, rocks, and beaches.

3. Conditions for Use: Salt or fresh water (temperature ranges from 35°F to 120°F). Oil or contaminant can be skimmed from the water or rinsed and captured into collection containers and disposed of per local, state, and federal regulations.

<u>Dilution</u>	<u>Intended Use</u>
2:1	Heavy contamination such as oil spills
5:1	Direct application to heavily soiled areas

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Materials Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
ETHOS CLEAN	Menidia beryllina	3960.00	96-hr
	Mysidopsis bahia	4510.00	48-hr
No. 2 Fuel Oil	Menidia beryllina	26.30	96-hr
	Mysidopsis bahia	4.86	48-hr
ETHOS CLEAN & No. 2 Fuel Oil (1:10)	Menidia beryllina	25.00	96-hr
	Mysidopsis bahia	5.00	48-hr
Reference Toxicant (SDS)	Menidia beryllina	2.23	96-hr
	Mysidopsis bahia	7.93	48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 142°F
2. Pour Point: 30°F
3. Viscosity: 32 SUS @60°F
4. Specific Gravity: 1.1664 @60°F
5. pH: 11.6
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL
8. Additives: CONFIDENTIAL
9. Solubility: Complete in water

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND
Cadmium	0.0813
Chromium	0.240
Copper	0.201
Lead	14.5
Mercury	5.0 (ppb)
Nickel	2.12
Zinc	ND
Cyanide	ND
Chlorinated Hydrocarbons	ND

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**9/27/2012
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-59
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JUNE 28, 2011
“OSR-10”

I. NAME, BRAND, OR TRADEMARK

OSR-10

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

MAG7 Venture Group, LLC, DBA MAG7 Technologies

1 Lepage Place, Suite 100

Syracuse, NY 13206

Phone: updated information required

Fax: updated information required

E-mail: updated information required

Website: updated information required

(Mr. Greg Goodell or Mr. Trevor Quig)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

MAG7 Venture Group, LLC, DBA MAG7 Technologies

1 Lepage Place, Suite 100

Syracuse, NY 13206

Phone: updated information required

Fax: updated information required

E-mail: updated information required

Website: updated information required

(Mr. Greg Goodell or Mr. Trevor Quig)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable

2. Ventilation: Move subject to fresh air. If breathing is difficult, obtain medical help.

3. Skin and eye contact; protective clothing; treatment in case of contact: Wash affected skin area with water. Consult physician if irritation persists. Skin irritation will not occur with most users. Flush eyes with a large amount of water for at least 15 minutes. Consult physician if irritation persists. Wear safety glasses and neoprene or rubber gloves during application.

4.a. Maximum storage temperature: 120°F

4.b. Minimum storage temperature: 35°F

4.c. Optimum storage temperature range: 40°F to 120°F

4.d. Temperatures of phase separations and chemical changes: NA. Phase separation will not

occur within the storage range. Product should be stored out of direct sunlight unless it is in an Ultraviolet (UV) light resistant container.

V. SHELF LIFE

2 years in a sealed (unopened) container (tote, drum, pail) as delivered. 1 year in an opened container).

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Apply OSR-10 to oil or contaminant with sprayer, pressure washer, mop, sponge, or brush. Application times will depend on the level of contaminant with a minimum of 10 minutes recommended soak time. The required soak time to remove oil will vary with oil density and degree of weathering. OSR-10 separates the oil from the physical surface to allow the oil to be sprayed off with a water rinse. OSR-10 should be mixed into soil applications and agitated to increase the effectiveness and reduce the application time.

2. Concentration/Application Rate: Dilution ratios for most applications range from 2 to 1 (parts water to parts OSR-10) to 15 to 1 (parts water to parts OSR-10). Dilution ratios are dependent on the contamination level and application with heavier crude oil spills requiring a lower dilution ratio. Rinse with water after usage for residue free surface. Surface cleaning typically requires 5 to 1 or 10 to 1 dilution ratio. These dilution ratios will require 1 gallon of OSR-10 per 300 square feet of surface area. These dilution ratios can be used in many applications including shorelines, rocks, and beaches.

3. Conditions for Use: Salt or fresh water (temperature ranges from 35°F to 120°F). Oil or contaminant can be skimmed from the water or rinsed and captured into collection containers and disposed of per local, state, and federal regulations.

<u>Dilution</u>	<u>Intended Use</u>
2:1	Heavy/severe contamination such as oil spills
5:1 to 10:1	Moderate contamination
15:1 to 30:1	Light contamination

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Materials Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
OSR-10	Menidia beryllina	385.00	96-hr
	Mysidopsis bahia	399.00	48-hr
No. 2 Fuel Oil	Menidia beryllina	26.30	96-hr
	Mysidopsis bahia	4.86	48-hr
OSR-10 & No. 2 Fuel Oil (1:10)	Menidia beryllina	16.00	96-hr
	Mysidopsis bahia	4.77	48-hr
Reference Toxicant (SDS)	Menidia beryllina	2.23	96-hr
	Mysidopsis bahia	7.93	48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 143°F
2. Pour Point: 20°F
3. Viscosity: 37 SUS @60°F
4. Specific Gravity: 1.1672 @60°F
5. pH: 11.5
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL
8. Additives: CONFIDENTIAL
9. Solubility: Complete in water

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND
Cadmium	ND
Chromium	0.209
Copper	0.150
Lead	7.57
Mercury	6.8 (ppb)
Nickel	1.20
Zinc	ND
Cyanide	ND
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-60
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 13, 2011
“ACCELL CLEAN® SWA”

I. NAME, BRAND, OR TRADEMARK
ACCELL CLEAN® SWA
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Advanced BioCatalytics Corporation
18010 Skypark Circle, #130
Irvine, California 92614-6456
Office Phone: (949) 771-0209
General E-mail: info@abiocat.com
Website: www.abiocat.com
Product Management:
Mobile: (949) 981-6510
E-mail: cpodella@abiocat.com
(Mr. Carl Podella)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Advanced BioCatalytics Corporation
18010 Skypark Circle, #130
Irvine, California 92614-6456
Office Phone: (949) 771-0209
General E-mail: info@abiocat.com
Website: www.abiocat.com
Product Management:
Mobile: (949) 981-6510
E-mail: cpodella@abiocat.com
(Mr. Carl Podella)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable
2. Ventilation: Use in well-ventilated area.
3. Skin and eye contact; protective clothing; treatment in case of contact: Protective clothing is recommended. Avoid eye contact. In case of eye contact, immediately flush with large amounts of water for at least 15 minutes. Get prompt medical attention. Avoid direct contact with skin and clothing. In case of skin contact, immediately flush with large amounts of water. Remove contaminated clothing, including shoes, after flushing has begun. If irritation persists, seek medical attention. For open systems where contact is likely, wear long sleeve shirt, chemical resistant gloves, and protective chemical goggles.

- 4.a. Maximum storage temperature: 130°F/55°C
- 4.b. Minimum storage temperature: 30°F/-1°C
- 4.c. Optimum storage temperature range: 40°F to 100°F/4°C to 38°C
- 4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

The shelf life of unopened drums of ACCELL CLEAN® SWA is unlimited. Containers should always remain capped when not in use to prevent contamination and evaporation.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Spray ACCELL CLEAN® SWA onto oil-contaminated shorelines, mangroves, or seagrasses full strength as applied. Allow to soak for 15-30 minutes. Rocks may be scrubbed with a stiff bristle brush where appropriate. Rinse with fresh or salt water as appropriate. For weathered crude oil on sand, transfer oil-contaminated sand to sand washing equipment. Agitate sand/ACCELL CLEAN® SWA solution. ACCELL CLEAN® SWA will lift the oil from the sand due to its low interfacial tension. Remove water from sand by centrifuge.
2. Concentration/Application Rate: Recommended application rate is 1 gallon per 100 square feet, dependent on the amount of oil and the degree of weathering. For weathered crude oil from sand, prepare a cleaning solution of 0.25%-2.0% ACCELL CLEAN® SWA using fresh or salt water.
3. Conditions for Use: Collect the oil/product residue from the water's surface using skimmers, absorbent pads, or other conventional means. Dispose of used, clean up residue in accordance with local, state, and federal regulations. Dispose of clean sand as appropriate and ACCELL CLEAN® SWA solution can be recycled after centrifuge.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Materials Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
ACCELL CLEAN® SWA	Menidia beryllina	24.12	96-hr
	Mysidopsis bahia	59.46	48-hr
No. 2 Fuel Oil	Menidia beryllina	17.13	96-hr
	Mysidopsis bahia	2.92	48-hr
ACCELL CLEAN® SWA & No. 2 Fuel Oil (1:10)	Menidia beryllina	12.25	96-hr
	Mysidopsis bahia	2.25	48-hr
Reference Toxicant (DDS)	Menidia beryllina	10.00	96-hr
	Mysidopsis bahia	29.00	48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >180°F/82°C

2. Pour Point: 10°F/-12°C
3. Viscosity: 68 SUS @60°F
4. Specific Gravity: 1.0141 @60°F
5. pH: 8.12
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: CONFIDENTIAL
8. Additives: CONFIDENTIAL
9. Solubility: Soluble in fresh or seawater

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<1.00
Cadmium	<0.50
Chromium	<1.00
Copper	<2.50
Lead	<1.00
Mercury	<0.020
Nickel	<4.00
Zinc	<6.00
Cyanide	<1.00
Chlorinated Hydrocarbons	ND

LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:

10/19/2016
7/27/2022

TECHNICAL PRODUCT BULLETIN #SW-61
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: OCTOBER 13, 2011
“EPA OIL FIELD SOLUTION™”
(aka, HYDRO-CLEAN™, GLOBAL ENVIRONMENTAL CLEANER™, AWAN PRA OIL
FIELD SOLUTION™)

I. NAME, BRAND, OR TRADEMARK

EPA OIL FIELD SOLUTION™

(aka, HYDRO-CLEAN™, GLOBAL ENVIRONMENTAL CLEANER™, AWAN PRA OIL
FIELD SOLUTION™)

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Environmental Protection Associates, Inc.

2578 Enterprise Road, Suite 141

Orange City, FL 32763

Phone: updated information required

E-mail: updated information required

Website: updated information required

(Mr. Nathan Hall)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

International Green Building Group, Inc.

10800 Main Street, Suite 150

Fairfax, VA 22030

Phone: (202) 300-8324

E-mail: info@internationalgreenbuildinggroup.com

Website: updated information required

AWAN International General Trading

P.O. Box 75352

Kingdom of Bahrain

Phone: 973-173-111-28

Fax: 973-172-950-05

E-mail: james@awanpra.com

Website: www.awangroups.com

Website: updated information required

(Mr. James Gard)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)

2. Ventilation: No special requirements.

3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing required; however goggles are recommended. If eye or skin irritation occurs, flush with plenty of fresh water.

4.a. Maximum storage temperature: 120°F continuous, 140°F up to 5 days

4.b. Minimum storage temperature: 35°F

4.c. Optimum storage temperature range: 40°F to 120°F

4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

Unlimited in sealed polydrums or totes (as delivered). Avoid direct sunlight.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: Product may be applied to surfaces for removal of oils. Select proper dilution depending on material surface prior to application. For treatment of large areas, properly diluted product may be applied by spraying with a pressure washer, portable fire pump, or any other suitable pump with seawater or freshwater suction that is equipped with a chemical inductor or feed pump. For smaller areas, properly diluted product may be applied with scrubber, mop, cloth or damp sponge. Apply liberally, adjusting dilution on site as necessary. For shorelines, mangroves, and seagrasses product is sprayed directly on the oiled rocky surfaces full strength as supplied. After a soak time of zero to 30 minutes, the cleaner and oil released from the shoreline surface can be collected and disposed. The soak time may vary with temperature, oil density, and degree of weathering.

2. Concentration/Application Rate: For heavily weathered oil on rocks, a diluted solution of 3 parts water to 1 part product is recommended. For heavily weathered oil on beaches/sand, a diluted solution of 5 parts water to 1 part product is ideal. For removing oil from vegetation, a diluted solution of 10-20 parts water to 1 part product is preferred. Product may be diluted with either salt or fresh water. Warmer water (greater than 78°F) and/or good agitation during application will require less of the product.

3. Conditions for Use: Best results are obtained by allowing diluted solution to soak for at least 30 minutes to soften the oil deposits. Reapplication may be necessary in severely contaminated areas. A sorbent boom or vacuum suction equipment should be positioned to collect the washed off effluent. When proper containment equipment is in place and a soaking period of at least 30 minutes has been achieved, a diluted solution of 20 parts water and 1 part product should be applied at mid-pressure (approximately 100 PSI). Adjust pressure and angle of the hose sprayer to achieve optimum results, adjusting the dilution as necessary on site. Product and effluent should be vacuumed up or absorbed in absorbent boom and disposed of according to local, state, and federal regulations. EPA Oil Field Solution™ is useful on shorelines using fresh or salt water. It can be used on all types of oil including heavily weathered and emulsified (“chocolate mousse”) containing up to 50 percent water.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Materials Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
EPA OIL FIELD SOLUTION™	Menidia beryllina	113.76	96-hr
	Mysidopsis bahia	114.60	48-hr
No. 2 Fuel Oil	Menidia beryllina	3.00	96-hr
	Mysidopsis bahia	1.41	48-hr
EPA OIL FIELD SOLUTION™ & No. 2 Fuel Oil (1:10)	Menidia beryllina	2.94	96-hr
	Mysidopsis bahia	1.12	48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.25	96-hr
	Mysidopsis bahia	12.06	48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >95°F
2. Pour Point: -2°F
3. Viscosity: 1.137368 SUS @40°F
4. Specific Gravity: 1.11 @60°F
5. pH: 13.4
6. Surface Active Agents: Nonionic, proprietary, surfactants
7. Solvents: Proprietary
8. Additives: None
9. Solubility: Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.200
Cadmium	<0.0600
Chromium	<0.300
Copper	<0.300
Lead	<0.200
Mercury	<1.00 (ug/l)
Nickel	<0.500
Zinc	2.31
Cyanide	<0.0100
Chlorinated Hydrocarbons	<250 (ug/l)

TECHNICAL PRODUCT BULLETIN #SW-62
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: MARCH 5, 2012
“PETROMAX PSC 3”
(aka, PETROMAX SOIL CLEANING AND WASHING AGENT)

I. NAME, BRAND, OR TRADEMARK
PETROMAX PSC 3
(aka, PETROMAX SOIL CLEANING AND WASHING AGENT)
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Alfaluz S.A.
Potosí 1517
Carrasco, Montevideo
Uruguay
Phone: 598-2-604-1006
Unites States: (305) 600-4927
Fax: (508) 256-8318
E-mail: svonbergen@alfaluz.net
Website: www.alfaluz.net
(Mr. Scot von Bergen)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Alfaluz Inc.
1875 Post Oak Park Drive, Suite 523
Houston, Texas 77027
Phone: (832) 272-1816
Fax: (508) 256-8138
E-mail: mvonbergen@alfaluz.net
(Mrs. Marina von Bergen)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-hazardous)
2. Ventilation: No special requirements.
3. Skin and eye contact; protective clothing; treatment in case of contact: No special equipment or clothing required; however, goggles are recommended. If eye or skin irritation occurs, flush with plenty of fresh water.
- 4.a. Maximum storage temperature: 120°F continuous, 140°F up to 5 days
- 4.b. Minimum storage temperature: 35°F
- 4.c. Optimum storage temperature range: 40°F to 120°F
- 4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

Unlimited when stored in unopened, sealed 5 gallon containers, 55 gallon drums, polydrums, and totes.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: PETROMAX PSC 3's mechanism of action is to reverse the charge of the particles (sand) holding the hydrocarbons, in such a way that the hydrocarbons and the particles reject each other thus allowing the hydrocarbons to be easily separated, removed, and collected. This is because the separated hydrocarbons maintain their globular integrity and are not dispersed nor solubilized into the water column.

PETROMAX PSC 3 is applied via hydroblaster directly to the contaminated sand/soil and as it becomes fluidized it is sucked through a four inch hose into a mobile containment tank set up for the purpose at the job site. The contaminated material is cleaned through a three phase separation process:

- a) Solids Recovery: Once in the containment tank, the cleaned sand and soil particles precipitate immediately to the bottom, from which they are extracted via a slew-valve to secondary containment. Any entrained water within this containment is further recovered for reuse according to local, state, and federal regulations.
- b) Oil Recovery: During this process the hydrocarbons float to the surface of the tank and are removed by skimming. These removed hydrocarbons are collected and are sent to a refinery for processing.
- c) PETROMAX PSC 3/Water Recovery: This leaves only the used PETROMAX PSC 3/water solution in the tank, which can be reused or disposed of according to local, state, and federal regulations. The remaining water may contain some light particles in suspension. These particles are easily precipitated into cake residues which are then collected. The cake residues typically contain a water content below 10%. They can be dried in open air pits with plastic protection underneath or in 15 yard roll-off containers. Any contaminated water should be collected and sent to a standard water treatment facility.

2. Concentration/Application Rate: PETROMAX PSC 3 should be applied via hydroblaster lance with minimum 3200 psi pressure and 4-15 gallons per minute flow depending on material to be treated. For smaller spills, a smaller hydroblaster sprayer may be used, mixing fresh or salt water according to availability, and depending on the oil composition and viscosity in the contaminated sand and soil being treated. For large scale soil remediation and cleaning of soils and sands contaminated with heavy crude, direct PETROMAX PSC 3 directly on the spill (contaminated) material using a hydroblaster lance at a minimum pressure of 3500 psi, with a dilution ratio of approximately 1:10 (product:water). Lighter oil soil contamination will require a 1:20 to 1:30 product to water dilution ratio with pressures at 2800 psi minimum. Warmer water (greater than 70°F) may require less PETROMAX PSC 3.

3. Conditions for Use: A sorbent boom should be positioned during use to contain any runoff and the collected material should be disposed of according to local, state, and federal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Materials Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
PETROMAX PSC 3	Menidia beryllina	20332.19	96-hr
	Mysidopsis bahia	13460.87	48-hr
No. 2 Fuel Oil	Menidia beryllina	1.90	96-hr
	Mysidopsis bahia	1.68	48-hr
PETROMAX PSC 3 & No. 2 Fuel Oil (1:10)	Menidia beryllina	1.99	96-hr
	Mysidopsis bahia	1.00	48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.25	96-hr
	Mysidopsis bahia	12.35	48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >185°F
2. Pour Point: +22°F
3. Viscosity: 1.5 cst @40°C
4. Specific Gravity: 1.08 @60°F
5. pH: 13.23
6. Surface Active Agents: Anionic, proprietary
7. Solvents: None
8. Additives: Proprietary
9. Solubility: Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.121
Cadmium	0.332
Chromium	0.067
Copper	<0.100
Lead	0.197
Mercury	<0.50 (ug/l)
Nickel	<0.100
Zinc	<0.100
Cyanide	<0.010
Chlorinated Hydrocarbons	<5.00 (ug/l)

TECHNICAL PRODUCT BULLETIN #SW-63
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 12, 2012
“GREEN TECHNOLOGIES SOLUTIONS-OIL RECOVERY (GTS-OR)”

I. NAME, BRAND, OR TRADEMARK
GREEN TECHNOLOGIES SOLUTIONS-OIL RECOVERY (GTS-OR)
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
International Technologies and Services, Inc.
29258 Palos Verdes Drive East
Rancho Palos Verdes, CA 90275
Phone: (310) 749-4487
E-mail: pirladybug@itsenvironmental.com
Website: www.ITSEnvironmental.com
(Ms. Pilar Ortega)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
International Technologies and Services, Inc.
29258 Palos Verdes Drive East
Rancho Palos Verdes, CA 90275
Phone: (310) 749-4487
E-mail: pirladybug@itsenvironmental.com
Website: www.ITSEnvironmental.com
(Ms. Pilar Ortega)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable
2. Ventilation: Handle in well ventilated space.
3. Skin and eye contact; protective clothing; treatment in case of contact: Product may cause minor irritation, so avoid eye and skin contact by wearing protective goggles, impermeable protective gloves, and protective clothing while handling the product. Wash contaminated clothing with soap and water, and dry prior to reuse. In case of contact, flush with large amounts of water for at least 15 minutes. Product may harmful if inhaled. In case of inhalation, move affected person to fresh air, and call a physician. Product may be harmful if swallowed. In case of ingestion, induce vomiting, give water, and call a physician.
- 4.a. Maximum storage temperature: 120°F
- 4.b. Minimum storage temperature: 30°F
- 4.c. Optimum storage temperature range: >50°F to <100°F
- 4.d. Temperatures of phase separations and chemical changes: None

V. SHELF LIFE

One year minimum when stored between 50°F and 100°F.

VI. RECOMMENDED APPLICATION PROCEDURES

1. Application Method: GTS-OR may clean oil from beaches, rocks, riprap, pilings, and seawalls. GTS-OR application method can be adjusted depending on the scale and type of area to be cleaned. For large areas, GTS-OR can be sprayed from water trucks or water boats equipped with pumps, hoses, and nozzles to deliver the product as an aerial spray. The pump should be equipped with a chemical inductor or feed pump. In smaller applications, GTS-OR can be applied directly onto oiled surfaces using a pressure washer, steam powered unit, fire hose, or chemical boom sprayer with nozzles at mid-pressure (i.e., approximately 100 PSI) that produce a shearing action. For small applications, the product may be applied with mops, cloth, or damp sponges. For application in tidally influenced areas and to maximize contact time, GTS-OR should be applied during ebb tide (i.e., receding). Oil trapped between rocks or in crevices may be released over several days, requiring containment devices to be left in place.

2. Concentration/Application Rate: For heavily weathered oil on rocks, a diluted solution of 15 parts water to 1 part product is recommended. For heavily weathered oil on beaches/sand, a diluted solution of 10 parts water to 1 part product is ideal. For lightly-to-moderately oiled shorelines, mangroves, and seagrasses, the product should be sprayed directly to the affected surface at a 1:20 dilution ratio; a 1:10 dilution ratio is preferred for heavily oiled areas.

3. Conditions for Use: GTS-OR may be used in freshwater, estuarine, and marine environments. In all applications, the product may be diluted with either salt or fresh water, and the mixture should be allowed to penetrate and dissolve weathered petroleum for at least 30 minutes. Cold weather applications will require more contact time. Reapplication may be necessary for heavily oiled areas. The product may be used on both lighter oils (e.g., No. 2 Fuel Oil) and heavy ends (e.g., crude oil, No. 6 Fuel Oil). Prior to application, booms, oil skimmers, or other appropriate containment and collection mechanism should be deployed and operational. Collected product and oil mixture should be disposed of according to local, state, and federal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Materials Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>	
GTS-OR	Menidia beryllina	3930	96-hr
	Mysidopsis bahia	916	48-hr
No. 2 Fuel Oil	Menidia beryllina	8.16	96-hr
	Mysidopsis bahia	4.47	48-hr
GTS-OR & No. 2 Fuel Oil (1:10)	Menidia beryllina	5.77	96-hr
	Mysidopsis bahia	2.18	48-hr
Reference Toxicant (SDS)	Menidia beryllina	1.24	96-hr
	Mysidopsis bahia	4.77	48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: 171°F
2. Pour Point: 35°F
3. Viscosity: 8.5 cSt @40°C
4. Specific Gravity: 1.009 @60°F
5. pH: 9.0
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: None
8. Additives: CONFIDENTIAL
9. Solubility: Soluble in water

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.0084
Cadmium	<0.004
Chromium	0.00064
Copper	0.180
Lead	0.00025
Mercury	<0.00010
Nickel	0.0012
Zinc	0.017
Cyanide	<0.200
Chlorinated Hydrocarbons	<2.5

TECHNICAL PRODUCT BULLETIN #SW-64
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JULY 9, 2013
“SIMPLE GREEN® 2013 Reformulation”

I. NAME, BRAND, OR TRADEMARK
SIMPLE GREEN® 2013 REFORMULATION
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Sunshine Makers, Inc.
15922 Pacific Coast Highway
Huntington Beach, CA 92649
Phone: (800) 228-0709
Phone: (562) 795-6000
Fax: (562) 592-3830
E-mail: LLorincz@simplegreen.com
(Ms. Laura Lorincz)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Sunshine Makers, Inc.
15922 Pacific Coast Highway
Huntington Beach, CA 92649
Phone: (800) 228-0709
Phone: (562) 795-6000
Fax: (562) 592-3830
E-mail: LLorincz@simplegreen.com
(Ms. Laura Lorincz)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.
2. Ventilation: Not expected to cause respiratory irritation. However, use in well ventilated areas. If adverse effect occurs, move to fresh air.
3. Skin and eye contact; protective clothing; treatment in case of contact: Not expected to cause eye irritation. However, use protective glasses if splashing or spray-back is likely. If adverse effect occurs, flush eyes with water. Not expected to cause skin irritation. However, dermally sensitive users may experience dry skin and should use protective gloves. If adverse effect occurs, rinse skin with water. General hygiene considerations include washing hands thoroughly after handling and before eating or drinking. Ensure adequate ventilation. Keep out of reach of children. If ingested, drink plenty of water to dilute.
- 4.a. Maximum storage temperature: 109°F
- 4.b. Minimum storage temperature: 41°F

4.c. Optimum storage temperature range: 42°F to 108°F

4.d. Temperatures of phase separations and chemical changes: SIMPLE GREEN® is stable and phase separation will not occur at temperatures within the maximum and minimum storage temperatures. If separation occurs, mix the product for reconstitution.

V. SHELF LIFE

SIMPLE GREEN® has a 5-year shelf life. Keep away from heat, sparks, open flame and direct sunlight. Do not pierce any part of the container. Keep container tightly closed. Keep in a cool dry area. Avoid prolonged exposure to direct sunlight. Do not store at temperatures above 109°F (42.7°C).

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Spray or apply on oily surfaces (e.g., beaches, rocks, shorelines, pilings, etc.).

2. Concentration/Application Rate:

a) Mix SIMPLE GREEN® in clean water at recommended concentration for strength of surface being cleaned:

Degree that Surface is Covered in Oil	Concentration of Simple Green®
HEAVY – fresh, thick, viscous oil; porous surfaces	Full strength to 25%
MEDIUM – weathered, thinner coats of oil; non-porous surfaces – use pressure washer equipment	25% to 10%
LIGHT – very light oil film; non-porous surfaces	Less than 10%

b) Apply SIMPLE GREEN® or diluted solution of Simple Green® to oiled surface via sponge, mop, coarse spray, foaming applicator, or pressure washer.

c) Whenever possible, allow several minutes (5-10) of contact time to loosen oil. Do not allow product to dry on the surface or it will be difficult to remove.

d) Wash and scrub as necessary.

e) Rinse cleansed surfaces with clean water. Whenever possible, rinse should enter a pretreatment system (e.g., clarifier, oil/water separator, municipal sanitary sewer) before repurposing.

3. Conditions for Use: SIMPLE GREEN® can be used in freshwater, estuarine, and marine environments at all temperatures. Prior to application, booms, oil skimmers, or other appropriate containment and collection mechanism should be deployed and operational. Collected product and oil mixture should be disposed of according to local, state, and federal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
SIMPLE GREEN®	Menidia beryllina	735.00 96-hr
	Mysidopsis bahia	541.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	26.40 96-hr
	Mysidopsis bahia	3.37 48-hr

SIMPLE GREEN® & No. 2 Fuel Oil (1:10)	Menidia beryllina	28.50 96-hr
	Mysidopsis bahia	5.05 48-hr
Reference Toxicant (DSS)	Menidia beryllina	1.69 96-hr
	Mysidopsis bahia	6.60 48-hr

NOTE: This toxicity data was derived using the concentrated product. See Section VI of this bulletin for information regarding the manufacturer's recommendations for concentrations and application rates for field use.

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

SIMPLE GREEN® contains no microorganisms, enzymes, or biological material.

IX. PHYSICAL PROPERTIES

- Flash Point (ASTM 92): 98°C
No Flash Point seen at or below 212°F (ASTM 93)
- Pour Point: 0°C
- Viscosity: <2.0 mm²/s at 40°C
- Specific Gravity: 1.0283 g/ml at 60°F
- pH: 9.0
- Surface Active Agents: CONFIDENTIAL
- Solvents: None
- Additives: CONFIDENTIAL
- Solubility: 100% soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.0031
Cadmium	<0.0005
Chromium	0.013
Copper	<0.0025
Lead	<0.0005
Mercury	0.0016
Nickel	0.0054
Zinc	0.016
Cyanide	<0.08
Chlorinated Hydrocarbons	<5

TECHNICAL PRODUCT BULLETIN #SW-65
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: JANUARY 23, 2014
“NONTOX™ SURFACE WASHING AGENT”

I. NAME, BRAND, OR TRADEMARK
NONTOX™ SURFACE WASHING AGENT
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Bio-Organic Catalyst, Inc. (wholly owned subsidiary of Neozyme International, Inc.)
711 West 17th Street, Suite E-6
Costa Mesa, CA 92627
Phone: (949) 515-1301
Phone: (800) 982-8676
Fax: (949) 515-1314
E-mail: parker@bio-organic.com
Website: www.bio-organic.com
(Mr. Parker Dale, President)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Government Logistics Solutions	Rolling Hills Construction and Demolition
3540 Chaneyville Road	Recycling Center
Owings, MD 20736	6990 Rolling Hills Road
Phone: (410) 286-0098	Pensacola, FL 32505
Fax: (301) 812-2878	Phone: (850) 477-2687
(Mr. Charles M. Baker, Retired USAF (SMSgt sel), President)	(Mr. John Levitan – Mobile (850) 497-2724)
(Kelly Davis – (240) 691-3946)	(Mr. Scott Miller – Mobile (850) 723-5715)
	(Mr. Charlie Davidson – Mobile (850) 776-2852)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: >93°C
2. Ventilation: None required. No respiratory protection required.
3. Skin and eye contact; protective clothing; treatment in case of contact: The use of protective eyewear and rubber gloves is recommended under good manufacturing practices.
- 4.a. Maximum storage temperature: 55°C
- 4.b. Minimum storage temperature: 2°C
- 4.c. Optimum storage temperature range: 25°C to 40°C
- 4.d. Temperatures of phase separations and chemical changes: No phase separations or chemical changes observed under optimum storage temperatures.

V. SHELF LIFE

A minimum of two (2) years.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: For general use apply the product by spray, mop or with standard steam and pressure wash cleaning equipment. It can also be applied using a foam generator or any convenient sprayer. Product can be used as is or by using heat and pressure or mechanical scrubbing. Rinse thoroughly with salt or fresh water for a residue-free surface. For direct applications foaming will be most effective as it will allow more contact time for the product to work. In a foam-cleaning application operation, the surface to be cleaned will be thoroughly covered with foam and allowed to stand for several minutes. The foam is rinsed away with clean water using a high pressure washer. The product can be applied with a variety of spraying or washing equipment, depending on the type and scale of the shoreline or beach to be cleaned. For large areas, such as beaches, the product can be sprayed from water trucks or other vehicles equipped with pumps, hoses and nozzles to aerially deliver the product. On smaller oily surfaces, the product can be applied with hand sprayers or portable pumps may be used to spray directly onto the contaminated areas.

2. Concentration/Application Rate: For spills on shorelines and beaches, the product can be used at a dilution of 1:17 parts product to water using salt or fresh water. After application, the product should be allowed to penetrate and dissolve the oily surface for up to 30 minutes. Longer is preferable to maximize contact time. For light cleaning use a ratio up to 1:50 parts product to water. For heavy cleaning use a ratio up to 1:17 parts product to water. Dose rates may vary depending on type and amount of petroleum spilled, and other site conditions such as water, temperatures and porosity of shoreline. Cold weather applications will require more contact time before initiating recovery.

3. Conditions for Use: The product can be used on sand beaches, gravel, cobble, and coarse sand and rocky shores. Water salinity should not negatively impact product use. Water temperatures below 2°C may impact application. Aged or highly viscous concentrations of hydrocarbons may require presoaking prior to removal. The treated product can be collected and removed by several means including, but not limited to, sorbent pads, oil skimmers, collection booms, or other appropriate containment and collection mechanism. All oily water mixtures should follow disposal procedures in accordance with current local, state and federal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

Material Tested	Species	LC50 (ppm)
NONTOX™ SURFACE WASHING AGENT	Menidia beryllina	203.04 96-hr
	Mysidopsis bahia	316.23 48-hr
No. 2 Fuel Oil	Menidia beryllina	2.51 96-hr
	Mysidopsis bahia	2.24 48-hr
NONTOX™ SURFACE WASHING AGENT & No. 2 Fuel Oil (1:10)	Menidia beryllina	3.29 96-hr
	Mysidopsis bahia	2.19 48-hr
Reference Toxicant (SLS)	Menidia beryllina	12.25 96-hr
	Mysidopsis bahia	12.08 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

2. Flash Point (ASTM 92): >93°C

2. Pour Point: 2.22°C

3. Viscosity: 2.3373 cST @ 40°C

4. Specific Gravity: 1.005 at 68°F

5. pH: 3.46

6. Surface Active Agents: CONFIDENTIAL

7. Solvents: None

8. Additives: CONFIDENTIAL

9. Solubility: 100% soluble

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.0100
Cadmium	<0.0050
Chromium	0.1515
Copper	0.1530
Lead	<0.0100
Mercury	<0.5000 ug/L
Nickel	<0.0250
Zinc	4.781
Cyanide	<0.0100
Chlorinated Hydrocarbons	<2.50

**LAST COMMUNICATION WITH MANUFACTURER:
LAST ATTEMPT:**

**3/16/2016
7/27/2022**

TECHNICAL PRODUCT BULLETIN #SW-66
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: MAY 7, 2015
"FORMULA 206-1x BIO-WASH™"
(aka, CAST OFF™, FORMULA 206-1x)

I. NAME, BRAND, OR TRADEMARK
FORMULA 206-1X BIO-WASH™
(aka, CAST OFF™, FORMULA 206-1x)
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Natural Soap Formulas, Inc.
3200 S Andrews Avenue, Suite 113
Fort Lauderdale, FL 33316
Phone: updated information required
E-mail: updated information required
(Ms. Kaylin D'Aire)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Natural Soap Formulas, Inc.
3200 S Andrews Avenue, Suite 113
Fort Lauderdale, FL 33316
Phone: updated information required
E-mail: updated information required
(Ms. Kaylin D'Aire)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable (DOT: Non-Hazardous)
2. Ventilation: Normal ventilation is adequate. No respiratory protection is required. If respiratory irritation or distress occurs, remove exposed person to fresh air. Seek medical attention if respiratory irritation or distress continues.
3. Skin and eye contact; protective clothing; treatment in case of contact: Protective eyewear is advisable for operator's comfort. If eye irritation occurs, flush eyes with water. After initial flushing, removal any contact lenses and continue flushing for 1 minute. Please seek medical attention, if eye irritation symptoms persist or if there are additional concerns. Wash hands after handling. If ingested, drink 2-4 glasses of water and allow the product to pass through the digestive system naturally. Ingesting large amounts may cause gastrointestinal distress due to emulsification of grease and oil in the digestive tract. Please seek medical attention, if symptoms persist or if there additional concerns.

- 4.a. Maximum storage temperature: 120°F continuous, 130°F up to 5 days
- 4.b. Minimum storage temperature: 30°F
- 4.c. Optimum storage temperature range: 40°F to 110°F
- 4.d. Temperatures of phase separations and chemical changes: Stable

V. SHELF LIFE

5 years in sealed poly drums or IBC totes (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: FORMULA 206-1x BIO-WASH™ may be applied to hard surfaces including beaches, shorelines, and rocks; specifically to aid in the removal of oil and oil saturated soiling. Product may be applied by spray, high pressure wash, mop, scrub brush, cloth or sponge. Once applied to target surface, allow for a 5 to 30 minute dwell time, the product may be agitated using suitable physical methods (i.e., scrubbing to increase effectiveness). For large areas such as shorelines, product can be applied by vehicle or boat; spraying from fire eduction systems or boom system, hand-held or backpack sprayers, garden type sprayers, or from hoses attached to small pumps through power washers, fire pump or other portable pump with suction that is equipped with a chemical inductor or feed pump. After application, the removal of oil or oil saturated soiling can be done by rinsing with water where practicable followed by removal with physical methods, such as sorbent pads, mop or vacuum application to prevent contamination to open water. Ensure boom containment continues to be in place during oil/product removal procedures.

2. Concentration/Application Rate: FORMULA 206-1x BIO-WASH™ is typically diluted with using tap-water at ambient temperature; and can be diluted with sea water or any other suitable field expedient water source. The product is not affected by salinity or hard water dilution. Apply using a typical dilution ratio of 1:10 in the first instance. Product dilution varies with the severity of the contamination, contaminant viscosity, area of application and porosity, and nature of the surface to be decontaminated. A dilution ratio ranging from 1:5 to 1:200 is recommended for this product, there is no specific application rate; however, for large area application, 15 to 50 U.S. gallons per acre can be considered optimal. During application, the rate and concentration of the product can be adjusted to suit the cleaning effect desired.

3. Conditions for Use: FORMULA 206-1x BIO-WASH™ is most effective on hydrocarbon and bio-organic soiling on hard surfaces including beaches, shorelines, and rocks. A sorbent boom or other containment equipment should be positioned prior and remain in place during product use to collect runoff from application and removal operations. Collect and contain runoff from oil/product mixture and dispose of such material in accordance with local, state, and federal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
FORMULA 206-1x BIO-WASH™	Menidia beryllina	157.00 96-hr
	Mysidopsis bahia	123.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	3.60 96-hr
	Mysidopsis bahia	5.80 48-hr
FORMULA 206-1x BIO-WASH™ & No. 2 Fuel Oil (1:10)	Menidia beryllina	3.90 96-hr
	Mysidopsis bahia	4.10 48-hr
Reference Toxicant (SDS)	Menidia beryllina	10.00 96-hr
	Mysidopsis bahia	19.00 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

- Flash Point (ASTM 93): 130°F
- Pour Point (D2500): 30°F
- Viscosity (ASTM D88): 26 SUS @ 100°F
- Specific Gravity (ASTM D1217): 1.0137 g/ml at 60°F
- pH (EPA 9040C): 10.6
- Surface Active Agents: Natural fatty acid soaps
- Solvents: Hydrofurfuryl Alcohol
- Additives: NA
- Solubility: Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	ND
Cadmium	ND
Chromium	0.0173
Copper	0.115
Lead	ND
Mercury	ND
Nickel	0.160
Zinc	0.556
Cyanide	ND
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-67
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: AUGUST 3, 2015
“RHAMNOWASH 10”

I. NAME, BRAND, OR TRADEMARK
RHAMNOWASH 10
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Rhamnolipid, Inc.
511 West Bay Street, Suite 350
Tampa, FL 33606
Phone: (917) 576-7381
Direct: (704) 564-6445
E-mail: greccosg@rhamnolipid.com
Website: <http://www.rhamnolipid.com>
(Mr. Samuel G. Grecco)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Rhamnolipid Companies, Inc.
511 West Bay Street, Suite 350
Tampa, FL 33606
Phone: (917) 576-7381
Direct: (704) 564-6445
E-mail: kdesanto@rhamnolipid.com
Website: <http://www.rhamnolipid.com>
(Mr. Keith DeSanto)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: IMO, Non-flammable; DOT, Non-Hazardous
2. Ventilation: Inhalation causes irritation. Use in properly ventilated areas, with approved respiratory mask and goggles. Avoid creating mist where possible. If inhaled, allow plenty of fresh air and loosen clothing around neck. Contact physician immediately.
3. Skin and eye contact; protective clothing; treatment in case of contact: Exposure to skin can cause irritation if person has a history of dermal allergic reaction. Limit exposure and use rubber gloves. Wash with soap and water. If product comes in contact with the eyes, excess redness and swelling of the conjunctiva may occur. Causes moderate to severe irritation, which is experienced as discomfort or pain, excessive blinking and tear production, with marked excessive redness and swelling. Corneal injury may occur. Immediately flush with water for at least 15 minutes. DO NOT remove contact lenses, if worn. Obtain medical attention without delay, preferably from an ophthalmologist. To avoid eye contact, wear goggles or a face shield.

Ingestion of product can lead to nausea or diarrhea. If ingested, give two glasses of water to dilute product. DO NOT induce vomiting. Contact physician immediately. Treat as you would any chemical or biological material. Always wash hands thoroughly after use. Follow product sheets and SDS instructions.

4.a. Maximum storage temperature: 105°F

4.b. Minimum storage temperature: 35°F

4.c. Optimum storage temperature range: 35°F to 75°F

4.d. Temperatures of phase separations and chemical changes: Phase separation may occur over time, but mild agitation will reconstitute mixture.

V. SHELF LIFE

The shelf life of unopened containers (i.e., drums, totes, etc.) of RHAMNOWASH 10 exceeds five (5) years. Containers should always be capped when not in use to prevent spillage and/or contamination.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: RHAMNOWASH 10 can remove oil (e.g., crude, different grades of fuel oil, gasoline, and other petrochemicals) from soil, shorelines, sandy beaches, mangroves, or sea grasses. The product may be applied by hand or using mechanical sprayers, pressure washers, or mechanical soil washing equipment. After a soak time of approximately 30 minutes to 3 to 4 hours (depending on the nature of the spill repeat as necessary), the residual mixture may be recovered using conventional methods. Actual cleaning time will likely depend on the environmental conditions, chemistry of the spilled oil, and the cleaning method employed.

2. Concentration/Application Rate: On heavy oils, use RHAMNOWASH 10 (neat) directly on the spill, or use a 1:100 dilution ratio (product:water) depending on the nature of the oil (e.g., crude vs refined) and environmental conditions (e.g., warm vs cold water). Lighter oils may need a 1:100 to 1:1000 dilution ratios depending on the oil's specific gravity and environmental conditions. RHAMNOWASH 10 maintains its surfactant properties at high levels of dilution, and works best when diluted with water (can use either saltwater or freshwater).

3. Conditions for Use: RHAMNOWASH 10 can be applied on oiled surfaces and shorelines in both freshwater and saltwater. Water temperatures less than 65°F may require higher dilution rates. Sorbent booms, oil skimmers, or other containment equipment should be positioned prior to and remain in place during product use to collect runoff from application and removal operations. Collect and contain runoff from oil/product mixture and dispose of such material in accordance with local, state, and federal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
RHAMNOWASH 10	Menidia beryllina	76.64 96-hr
	Mysidopsis bahia	164.61 48-hr

No. 2 Fuel Oil	Menidia beryllina	10.85 96-hr
	Mysidopsis bahia	2.27 48-hr
RHAMNOWASH 10 & No. 2 Fuel Oil (1:10)	Menidia beryllina	13.70 96-hr
	Mysidopsis bahia	2.15 48-hr
Reference Toxicant (SDS)	Menidia beryllina	7.52 96-hr
	Mysidopsis bahia	5.47 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point (ASTM D-56): >100°C
2. Pour Point (ASTM D-97): 2.6°C
3. Viscosity (ASTM D-445): 2.02 cst @ 40°C
4. Specific Gravity (ASTM D1298): 1.009 at 60°F
5. pH (ASTM D-1293): 6.5
6. Surface Active Agents: Anionic and nonionic, proprietary surfactants
7. Solvents: None
8. Additives: None
9. Solubility: Miscible

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.250
Cadmium	<0.099
Chromium	<0.250
Copper	<0.740
Lead	<0.200
Mercury	<0.0033
Nickel	<0.200
Zinc	<5.000
Cyanide	<2.500
Chlorinated Hydrocarbons	<5.000

TECHNICAL PRODUCT BULLETIN #SW-68
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: AUGUST 22, 2016
“ADP-7”

I. NAME, BRAND, OR TRADEMARK

ADP-7

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Petro-Green, Inc.

3952 Candlenut Lane

Dallas, TX 75244

Phone: updated information required

E-mail: adp7@petro-green.com

E-mail: michael.paddock@petro-green.com

Website: www.petro-green.com

(Mr. Michael Paddock)

Mailing Address

Petro-Green, Inc.

P.O. Box 814665

Dallas, TX 75381

(Mr. Michael Paddock)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Petro-Green, Inc.

3952 Candlenut Lane

Dallas, TX 75244

Phone: updated information required

E-mail: adp7@petro-green.com

E-mail: michael.paddock@petro-green.com

Website: www.petro-green.com

(Mr. Michael Paddock)

Mailing Address

Petro-Green, Inc.

P.O. Box 814665

Dallas, TX 75381

(Mr. Michael Paddock)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-Flammable (DOT: Non-Hazardous)

2. Ventilation: In most instances there will be no special requirements. However, if exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive pressure supplied air respirators may be required for high airborne contaminant concentrations.

3. Skin and eye contact; protective clothing; treatment in case of contact: First Aid: Skin/Body Contact – Wash off immediately with soap and water while removing all contaminated clothing and shoes. Wash all before reuse. Consult physician if irritation persists. Eyes – Immediately flush with plenty of water. After initial flushing, remove contact lenses if present and continue flushing for at least 15 minutes. If symptoms persist contact physician. Ingestion – Rinse mouth. Drink plenty of water. Do NOT induce vomiting. If symptoms persist contact physician.

Inhalation – Move to fresh air. If breathing is irregular or stopped administer artificial respiration. Call physician.

4.a. Maximum storage temperature: 120°F continuous, 140°F up to 5 days

4.b. Minimum storage temperature: 26°F

4.c. Optimum storage temperature range: 40°F to 110°F

4.d. Temperatures of phase separations and chemical changes: Stable within storage temperature range.

V. SHELF LIFE

Unlimited in sealed poly drums (as delivered).

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: For spills on soils, sandy or rocky areas: ADP-7 can be pre-mixed into water, or educed into a water flow, to be sprayed directly onto the oil spill.

2. Concentration/Application Rate: For spills on land: Typical dilution is one gallon of ADP-7 diluted with 42 gallons of water (approximately 2.4% concentration). Higher water temperatures (over 78°F) and/or good agitation during application will allow you to reduce the concentration strength. Aged or asphaltic spills may be more resistant to removal. Heating the solution to 150°F in a hot water washing rig, or a common oil field “hot oiler” truck will increase effectiveness.

3. Conditions for Use: ADP-7 is effective in salt water or fresh water, with no limitations as to usage within optimum temperature parameters (application may be made at or above 35°F, with optimum above 48°F). A sorbent boom or other containment equipment should be positioned prior to product application and should remain in place during product use to collect runoff from application and removal operations. The oil/product residue should be collected and removed from the site. Collection process should be determined by onsite coordinator based on practices of the area. Residue should be disposed of according to local, state and federal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
ADP-7	Menidia beryllina	20.28 96-hr
	Mysidopsis bahia	22.36 48-hr
No. 2 Fuel Oil	Menidia beryllina	17.46 96-hr
	Mysidopsis bahia	5.30 48-hr
ADP-7 & No. 2 Fuel Oil (1:10)	Menidia beryllina	14.10 96-hr
	Mysidopsis bahia	3.24 48-hr
Reference Toxicant (SDS)	Menidia beryllina	3.42 96-hr
	Mysidopsis bahia	7.81 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point (ASTM D-56): >212°F
2. Pour Point (ASTM D-97): 21°F
3. Viscosity (ASTM D-445): 81.4 cst @ 40°C
4. Specific Gravity (ASTM D-287): 1.0985 at 60°F
5. pH (ASTM D-1293): 9.9
6. Surface Active Agents: Anionic and nonionic
7. Solvents: Confidential
8. Additives: Confidential
9. Solubility: Miscible in oil, water, and solvents

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.485
Cadmium	<0.243
Chromium	<0.243
Copper	<0.485
Lead	<0.585
Mercury	<3.26 µg/L
Nickel	<0.485
Zinc	<0.485
Cyanide	<0.115
Chlorinated Hydrocarbons	<2.00

TECHNICAL PRODUCT BULLETIN #SW-69
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
ORIGINAL LISTING DATE: SEPTEMBER 7, 2016
“WATER WORKS™ HEAVY DUTY DEGREASER CONCENTRATE”
(aka, HEAVY DUTY DEGREASER CONCENTRATE)

I. NAME, BRAND, OR TRADEMARK
WATER WORKS™ HEAVY DUTY DEGREASER CONCENTRATE
(aka, HEAVY DUTY DEGREASER CONCENTRATE)
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Keteca USA, Inc.
4280 W. Opportunity Way
Phoenix, AZ 85086
Phone: (602) 278-7789
Fax: (602) 535-1305
E-mail: sales@ketecausa.com
E-mail: kparks@ketecausa.com
Web site: www.ketecawaterworks.com
(Ms. Kathy Parks)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Keteca USA, Inc.
4280 W. Opportunity Way
Phoenix, AZ 85086
Phone: (602) 278-7789
Fax: (602) 535-1305
E-mail: sales@ketecausa.com
E-mail: kparks@ketecausa.com
Web site: www.ketecawaterworks.com
(Ms. Kathy Parks)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-Flammable (DOT: Non-Hazardous)
2. Ventilation: No special requirements.
3. Skin and eye contact; protective clothing; treatment in case of contact: Avoid contact with eyes, slight irritation may result. Wear splash goggles or full face-shield and have eye washing equipment available in areas where potential is high for eye contact. Skin contact will not cause irritation in the majority of users. If eye or skin irritation occurs, flush with plenty of fresh water. No special precautions or additional protective equipment are required during handling or use.

Water Works™ Heavy Duty Degreaser Concentrate is provided with a Safety Data Sheet.

4.a. Maximum storage temperature: 100°F continuous, 110°F up to 5 days, keep away from direct sun light.

4.b. Minimum storage temperature: 35°F

4.c. Optimum storage temperature range: >32°F to <100°F

4.d. Temperatures of phase separations and chemical changes: Stable and phase separation will not occur at temperatures within the storage temperature range.

V. SHELF LIFE

12 months from date of manufacturer in unopened original packaging (as delivered). Containers should always remain closed when not in use to prevent contamination and evaporation.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Product may be applied to rocks, shoreline, and beaches for removal of oil. Select proper dilution depending on product types and contaminated material surface prior to application. For treatment of large areas, properly diluted product may be applied by spraying with a pressure washer, portable fire pump or any other suitable pump with seawater or freshwater suction that is equipped with a chemical inductor or feed pump. For smaller areas, properly diluted product may be applied with scrubber, mop, cloth or damp sponge. Apply liberally, adjusting dilution on site as necessary.

2. Concentration/Application Rate: For heavily weathered oil on rocks, applying concentrated or diluted solution at 5 parts water to 1 part product is recommended. For heavily weathered oil on beaches/sand, a diluted solution of 2 parts water to 1 part product is ideal. For tar balls, no dilution is necessary and applying product at full strength is recommended. For removing oil from vegetation, a diluted solution of 10-20 parts water to 1 part product is preferred. Product may be diluted with either saltwater or freshwater. Warmer waters (greater than 78°F) and/or good agitation during application will require less product.

3. Conditions for Use: Can be used in freshwater, estuarine, and marine environments at all temperatures. Prior to application, booms, oil skimmers, or other appropriate containment and collection mechanism should be deployed and operational. Collected product and oil mixture should be disposed of according to local, state, and federal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
WATER WORKS™ HEAVY DUTY DEGREASER CONCENTRATE	Menidia beryllina	68.70 96-hr
	Mysidopsis bahia	91.70 48-hr
No. 2 Fuel Oil	Menidia beryllina	11.53 96-hr
	Mysidopsis bahia	2.10 48-hr
WATER WORKS™ HEAVY DUTY DEGREASER CONCENTRATE &	Menidia beryllina	14.60 96-hr

No. 2 Fuel Oil (1:10)
Reference Toxicant (SDS)

Mysidopsis bahia
Menidia beryllina
Mysidopsis bahia

2.27 48-hr
7.68 96-hr
5.27 48-hr

b. Effectiveness: NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point (ASTM D-56): >212°F
2. Pour Point (ASTM D-97): 26°F
3. Viscosity (ASTM D-445): 2.66 cst @ 40°C
4. Specific Gravity (ASTM D-1298): 1.0728 at 60°F
5. pH (ASTM D-1293): 9.4
6. Surface Active Agents: Proprietary surfactants
7. Solvents: None
8. Additives: None
9. Solubility: Soluble in water

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.001
Cadmium	<0.001
Chromium	<0.005
Copper	<0.01
Lead	0.0163
Mercury	<0.0002
Nickel	0.0167
Zinc	0.025
Cyanide	0.21
Chlorinated Hydrocarbons	6.22

TECHNICAL PRODUCT BULLETIN #SW-70
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: MARCH 05, 2019
“X4JH2000”

I. NAME, BRAND, OR TRADEMARK

X4JH2000

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

X4 Environmental Inc.

14702 Jersey Shore Drive

Houston, TX 77047

Phone: (281) 846-6003

E-mail: benlux.tam@x4environmental.com

(TszFung Benlux Tam)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

X4 Environmental Inc.

14702 Jersey Shore Drive

Houston, TX 77047

Phone: (281) 846-6003

E-mail: benlux.tam@x4environmental.com

(TszFung Benlux Tam)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable

2. Ventilation: Recommend using a respirator in confined areas.

3. Skin and eye contact; protective covering; treatment in case of contact: Wear rubber gloves and eye protection. In case of eye contact, wash eyes thoroughly for 15 minutes including upper and lower lids; and seek medical attention. In case of skin contact, irritation is possible; wash with soap and water for 15 minutes. If irritation persists, seek medical attention.

4.a. Maximum storage temperature: 95°F

4.b. Minimum storage temperature: 32°F

4.c. Optimum storage temperature range: 75°F

4.d. Temperatures of phase separations and chemical changes: No phase changes have been observed.

V. SHELF LIFE

One year in a sealed container; and six months for an opened container.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: X4JH2000 is applied by spraying apparatus or mixing on or into media

- using excavator and 2-inch discharge hose, fire nozzle, or water pump; and water trucks.
2. Concentration/Application Rate: X4JH2000 is a water-based chemical. Use a ratio of 1 to 1.5 U.S. gallons of X4JH2000 to 10 parts water (i.e., tap, salt or fresh water) per cubic yard of contaminated media.
 3. Conditions for Use: Ambient temperature should be above 50°F. Water salinity and age of hydrocarbon pollutants are not a condition of use. Prior to application, use oil spill absorbent, boom and/or pad to prevent X4JH2000 from run off into ditches, creeks, and waterways. Place collected booms, pads, and absorbents in black 55-gallon poly-bags, use duct tape to seal, and then place bags in hazardous waste container for disposal. Collected containment materials should be disposed of according to local, state, and federal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
X4JH2000	Menidia beryllina	145.89 96-hr
	Mysidopsis bahia	40.26 48-hr
No. 2 Fuel Oil	Menidia beryllina	18.82 96-hr
	Mysidopsis bahia	1.49 48-hr
X4JH2000 & No. 2 Fuel Oil (1:10)	Menidia beryllina	18.59 96-hr
	Mysidopsis bahia	2.07 48-hr
Reference Toxicant (SLS)	Menidia beryllina	4.64 96-hr
	Mysidopsis bahia	8.42 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point (ASTM D-56): >220°F
2. Pour Point (ASTM D-57): +28°F
3. Viscosity (ASTM D-445): 4.99cSt at 40°C
4. Specific Gravity (ASTM D-1298): 1.06 at 60°F
5. pH (ASTM D-1293): 4.69
6. Surface Active Agents: HS Code 340211 anionic organic surface-active agents
7. Solvents: Not applicable
8. Additives: Not applicable
9. Solubility in Water: Not applicable

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.050
Cadmium	<0.025
Chromium	<0.050
Copper	<0.100
Lead	<0.050
Mercury	<0.010
Nickel	<0.050
Zinc	0.461
Cyanide	<0.025
Chlorinated Hydrocarbons	<1.000

TECHNICAL PRODUCT BULLETIN #SW-71
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: JUNE 30, 2020
“TASMANIA C-CLENZ”

I. NAME, BRAND, OR TRADEMARK
TASMANIA C-CLENZ
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Head Office Physical Address

Tasmania Limited
104 Forest Drive
La Lucia, 4051, Durban, South Africa
(Mr. John Webster, CEO)

Headquarter's Office Postal Address

Tasmania Limited
P.O. 242
Umhlanga Rocks, 4320, Durban, South Africa
(Mr. John Webster, CEO)

Product Management

Office: (+27) 562-9490
Mobile: (+27) 82-775-6555
U.S. Number: (904) 352-7195
E-mail: john.webster@tasmanialimited.com
Website: www.tasmanialimited.com
(Mr. John Webster, CEO)

U.S. Postal Address

Tasmania Limited
1958 East Peachtree Street
Nashville, AR 71852
Phone: (936) 777-4270
E-mail: moxxyoil@gmail.com
(Mr. Jeff Parker)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Skyfirm SA (Pty) Ltd
Nicol Grove Office Park
William Nicol Drive
Johannesburg, 2191, South Africa
Mobile: (+27) 76-280-0624
E-mail- martin@skyfirmsa.com
(Mr. Martin Schnuir)

Sam Jariri
6314 Washington Blvd
Arlington, VA 22205
Office: (202) 664-9250
E-mail: sam.jariri@tasmanialimited.com
(Mr. Sam Jariri)

Tasmania Limited
6 Lauderdale, 50 Chartwell Drive
Umhlanga Rocks, 4015, South Africa
Mobile: (+27) 71-419-1421
E-mail: russ@tasmanialimited.com
(Mr. Russell Parsons)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: IMO – Non-flammable; DOT – Non-hazardous.
2. Ventilation: Handle in well ventilated space, local exhaust is recommended if threshold limit values are exceeded. If used in a confined area, wear a respirator. If used outdoors, no special equipment is needed.
3. Skin and eye contact; protective covering; treatment in case of contact: Use good normal hygiene and avoid contact with skin and eyes. Wear rubber or vinyl gloves when applying the product. Impermeable protective gloves are recommended for sensitive skin types. If contact is made, wash with soap and water. Contact may cause redness, edema and drying of skin. Seek medical attention if irritation develops. Wear protective eye goggles at all times. If in contact with eyes, flush with water for 15 minutes and seek medical attention. Rinse contaminated clothing, shoes, goggles and gloves in simple tap water to remove any chemical residue. In case of ingestion, give water and call a doctor or medical professional. Remove to fresh air.
- 4.a. Maximum storage temperature: 160°F
- 4.b. Minimum storage temperature: -25°F
- 4.c. Optimum storage temperature range: 60-90°F
- 4.d. Temperatures of phase separations and chemical changes: Temperature fluctuations will not cause separation or deterioration of the product. There are no chemical changes to the product at either the maximum or minimum temperature, the product is stable and will not undergo phase separation of ingredients or stratification of contents over time.

V. SHELF LIFE

The shelf life of an unopened TASMANIA C-CLENZ drum is 3 years. In case of opened drums, shelf life is 2 years. Keep product away from direct sunlight.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: TASMANIA C-CLENZ is for land use only. There are no application restrictions. The preferred application method is to apply the product over pollutant or stained area with a hand sprayer, pressure sprayer or a heated pressure spray unit. For the first application of TASMANIA C-CLENZ to shoreline contamination, use cold water/low pressure washing (<50 PSI) to remove any liquid oil that has adhered to the substrate, pooled on the surface or become trapped in vegetation. The average soak time of light oil contamination is 15-30 minutes. The average soak time of heavy oil contamination is 30-45 minutes, which allows the viscous oil deposits to soften. The actual soak time may vary with temperature, oil density and degree of weathering. The product starts to work on breaking the physical bond between the oil and the surface to be cleaned. In the case of heavy oil on the rocks or oil displaced into crevices, use warm water and moderate to high pressure washing with a temperature of 90°F and 100 PSI. When accessible or applicable, a work boat with mounted spray booms can be used to spray the product on the shoreline. Personnel can also apply the product with a hand sprayer or pressure sprayer.
2. Concentration/Application Rate: For heavily contaminated oil on rocks, use a full strength solution (non-diluted). For heavily weathered oil on beaches and rocks, a dilution of 5 parts water and 1 part product is ideal. For light contamination on the rocks, beaches and sand, a

dilution of 10 parts water and one part product is used. Product can be diluted with either fresh or salt water. For removing oil from vegetation, a diluted solution of 15 parts water and one part product is preferred. Application rate is 1 gallon of product per square foot of surface area.

3. Conditions for Use: Used for cleaning petroleum fractions from shoreline, beaches and rocks. The water temperature can vary from 30-140°F. Best results are obtained by allowing either the non-diluted or diluted product to soak for 15-45 minutes depending on the severity of the pollutant on the area and whether the oil is weathered or is heavy oil. Adjust the pressure angle of the sprayer for optimal results. TASMANIA C-CLENZ can be used for contamination with all types of oil including heavily weathered and emulsified to light oil fractions, only the dilution amount will be adjusted. In the case of high temperatures above 75°F, use full strength TASMANIA C-CLENZ as the temperature and humidity will cause rapid evaporation of the spray. Greater results occur at ambient temperatures greater than 50°F. The salinity of the water has no effect on the performance of the product. Prior to application, use booms to prevent the product and oil mixture from entering open water. The product and oil mixture can be removed by either vacuum, skimmers or oil absorbents being applied in the boomed off area. The product and oil mixture, along with containment materials, should be disposed of according to local, state, and federal regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
TASMANIA C-CLENZ	Menidia beryllina	141.16 96-hr
	Mysidopsis bahia	34.27 48-hr
No. 2 Fuel Oil	Menidia beryllina	6.17 96-hr
	Mysidopsis bahia	2.11 48-hr
TASMANIA C-CLENZ & No. 2 Fuel Oil (1:10)	Menidia beryllina	5.24 96-hr
	Mysidopsis bahia	1.93 48-hr
Reference Toxicant (SDS)	Menidia beryllina	3.47 96-hr
	Mysidopsis bahia	8.75 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point (ASTM D-56): >100°C
2. Pour Point (ASTM D-97): +26°C
3. Viscosity (ASTM D-445): 2.299cSt at 60°F
4. Specific Gravity (ASTM D-287): 0.9678 at 60°F
5. pH: 7.0
6. Surface Active Agents: Confidential

7. Solvents: Confidential
8. Additives: Confidential
9. Solubility in Water: 100%

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.275
Cadmium	0.122
Chromium	0.0406
Copper	0.272
Lead	0.154
Mercury	0.0132
Nickel	0.0154
Zinc	0.195
Cyanide	0.00198
Chlorinated Hydrocarbons	0.00050

TECHNICAL PRODUCT BULLETIN #SW-72
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: MAY 17, 2021
“GOLD CREW® TC”

I. NAME, BRAND, OR TRADEMARK

GOLD CREW® TC

(aka, TRAFFIC COLLISION, SPILL CLEANUP AGENT)

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Gold Crew Products & Services, LLC

P.O. Box 2039

Orange, CA 92869

Mobile: (714) 318-5997

E-mail: jfigueira@goldcrew.net

E-mail: jfigueira@ecscheme.com

(Mr. Jim Figueira)

ECS

5713 Wollochet Drive NW, Suite B

Gig Harbor, WA 98332

Phone: (253) 263-8040

E-mail: egrubbs@ecscheme.com

Website: www.ecscheme.com

(Mr. Ed Grubbs)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

ECS

5713 Wollochet Drive NW, Suite B

Gig Harbor, WA 98332

Phone: (253) 263-8040

E-mail: egrubbs@ecscheme.com

Website: www.ecscheme.com

(Mr. Ed Grubbs)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.

2. Ventilation: Normal.

3. Skin and eye contact; protective clothing; treatment in case of contact: Good hygiene practices should always be followed. Wear impervious gloves for solutions or where contact is repeated. Avoid contact with eyes, skin, and clothing. Handle in accordance with good industrial hygiene and safety practices. For eye contact, flush with water and get medical attention if required. For skin contact, remove contaminated clothing and wash exposed area, and wash clothing before next use. If irritation develops get medical attention. If ingested, get medical attention.

4.a. Maximum storage temperature: When above 120°F, keep container closed and stored in a cool dark place. Evaporation may change product's characteristics.

4.b. Minimum storage temperature: Product will freeze below 25°F. No phase separation will occur. If frozen, thaw, and stir well.

4.c. Optimum storage temperature range: 25°F to 120°F. Use normal storage conditions, but store away from incompatible materials.

4.d. Temperatures of phase separations and chemical changes: No separation at any temperature between 32-120°F. No tendency to “layer out” or separate, standing for 30 days. No separation of layering after freezing.

V. SHELF LIFE

2 years (unopened); and 1 year (opened).

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Gold Crew® TC’s mechanism of action desorbs or strips the hydrocarbon off the surface of the solid through surface tension reduction enhanced with physical agitation.

The action is not a chemical reaction.

2. Concentration/Application Rate: For small hard surface area, active wash: Apply undiluted through hand pump sprayer. Apply to cover immediate work area. Use scrub brush to agitate. Use appropriate sorbent material to pick up and contain. For releasing from hard surface using presoak and/or power wash action: Boom off immediate work area. Use undiluted as presoak. Apply to cover the focused work area. Work on a test area first to determine site specific application. For crude oil, allow up to a 20-minute presoak. For medium distillates, allow 10 (±) minutes. For light distillates, allow 5 minutes. Times may vary depending on weather conditions/oil viscosity and site-specific conditions. After determining and applying the solution for presoak, wash down the area in the following manner: Gold Crew® TC should be used through a power washer or through a steam powered unit at 1 to 5 percent eduction rate to decrease the water’s surface tension and enhance power washing effectiveness. Wash to boomed containment area and remove by absorbent or skimmer. Dispose of waste material according to federal, state, and local regulations. For power wash with no presoak, used undiluted through power washer for crude and heavy oils. For lighter distillate’s dilute 50:50 with water. Follow containment and recovery methods.

3. Conditions for Use: Equally effective with salt or fresh water. Product will freeze in very low temperature but when thawed, will not affect performance.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
GOLD CREW® TC	Menidia beryllina	630.00 96-hr
	Mysidopsis bahia	503.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	8.77 96-hr
	Mysidopsis bahia	3.00 48-hr
GOLD CREW® TC & No. 2 Fuel Oil (1:10)	Menidia beryllina	5.65 96-hr
	Mysidopsis bahia	4.25 48-hr
Reference Toxicant (SDS)	Menidia beryllina	1.90 96-hr
	Mysidopsis bahia	9.03 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >200
2. Pour Point: 32°F
3. Viscosity: 1.52 cst @ 71°F (22°C); 1.213 cst @ 104°F (40°C)
4. Specific Gravity: 1.002
5. pH: 8.78 (±0.01)
6. Surface Active Agents: CONFIDENTIAL.
7. Solvents: None.
8. Additives: CONFIDENTIAL.
9. Solubility in Water: Complete.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	0.0343
Cadmium	<0.0020
Chromium	<0.0050
Copper	0.0166
Lead	<0.0060
Mercury	<0.0008
Nickel	<0.0050
Zinc	<0.0200
Cyanide	<0.0050
Chlorinated Hydrocarbons	ND

TECHNICAL PRODUCT BULLETIN #SW-73
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: SEPTEMBER 29, 2021
“DE-OIL-IT INDUSTRIAL STRENGTH CONCENTRATE”

I. NAME, BRAND, OR TRADEMARK
DE-OIL-IT INDUSTRIAL STRENGTH CONCENTRATE
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Greenworld Innovations Corp.
3813 Highgate Drive
Valrico, FL 33594
Phone: (407) 574-3898
Fax: (813) 413-6073
E-mail: info@gwi.world
Website: www.deoilit.com
(Mr. Ron McCarthy, CEO, or Mr. Danny Schillaci, COO)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Greenworld Innovations Corp.
3813 Highgate Drive
Valrico, FL 33594
Phone: (407) 574-3898
Fax: (813) 413-6073
E-mail: info@gwi.world
Website: www.deoilit.com
(Mr. Ron McCarthy, CEO, or Mr. Danny Schillaci, COO)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.
2. Ventilation: No mechanical ventilation required; fresh air supply recommended for inside confined spaces.
3. Skin and eye contact; protective clothing; treatment in case of contact: May cause eye irritation, manufacturer recommends use of goggles during application. In case of eye contact, flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. For skin contact, wash exposed skin with soap and water. If redness, itching or a burning sensation develops get medical attention.
- 4.a. Maximum storage temperature: 120°F continuous, 140°F up to 5 days.
- 4.b. Minimum storage temperature: 35°F.
- 4.c. Optimum storage temperature range: 40°F to 120°F.
- 4.d. Temperatures of phase separations and chemical changes: Stable; however, avoid freezing

application solution (concentrated product diluted with water) to avoid possible separation.

V. SHELF LIFE

The shelf life of unopened containers is unlimited. Containers should remain capped when not in use to prevent contamination or evaporation. Activated concentrate (i.e., product diluted with water) has unlimited shelf life if kept capped.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Product is to be used in diluted form and works just as well with fresh or salt water. This product works well with all types of oils contaminating shorelines, beaches, and rocks. Dilute to 30:1 (this is the application solution comprised of 30 parts water and one part product), spray on surface areas, and allow to soak time for 15 minutes before rinsing with water. For stubborn oil cleanup, after soaking scrub with brush before rinsing. Spraying means using mechanical methods such as a pump that can deliver 30 psi or greater. Rinsing is best performed with a pressure washer if available. Prior to application, use booms to prevent the product and oil mixture from entering open water. Water run-off can be collected by a vacuum apparatus as surface tension of the treated oil is reduced making pick up efforts easier (should not stick to vacuuming). The product and oil mixture, along with containment materials, should be disposed of according to local, state, and federal regulations.

2. Concentration/Application Rate: The volume of an application solution for shoreline cleanup means adding water (30 parts) to product (one part) and is dependent on size of cleanup area. In general the calculation of application solution (water plus product) volume in gallons is $(\text{Length} \times \text{Width}) \times (0.08)$ – scale is in feet. As an example, a boundary of contaminated shoreline measuring 50 feet x 12 feet, would be 600 square feet. Then $600 \text{ square feet} \times 0.08 = 48 \text{ gallons}$, at 30:1 dilution ratio this would be 1.5 gallons of product and 46.5 gallons of water. Water does not need to be filtered and can be salt or fresh.

3. Conditions for Use: Outside air temperature of 50°F to 125°F is optimal; otherwise, there is no specific restrictions outside this range other than avoid freezing of application solution. Water temperature for activating the application solution produces optimal performance between 95°F to 125°F; otherwise, there is no specific restrictions outside this range other than avoid freezing application solution. Water source for application solution can be fresh, or a non-potable source such as natural sources (i.e., lakes, ocean). Ambient water temperature at source of oil spill should be above 35°F. Do not freeze product, possible separation could occur. Manufacturer resting time of dilution application solution includes:

- When creating a diluted application solution according to a selected dilution ratio, the combined solution of water and product needs to rest.
- Resting time of 30 minutes to one hour stabilizing at ambient temperature to which you are to apply the application solution is optimal.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
DE-OIL-IT INDUSTRIAL	Menidia beryllina	144.59 96-hr
STRENGTH CONCENTRATE	Mysidopsis bahia	76.64 48-hr
No. 2 Fuel Oil	Menidia beryllina	10.55 96-hr
	Mysidopsis bahia	3.90 48-hr
PRODUCT &	Menidia beryllina	4.65 96-hr
No. 2 Fuel Oil (1:10)	Mysidopsis bahia	4.13 48-hr
Reference Toxicant (DSS)	Menidia beryllina	3.98 96-hr
	Mysidopsis bahia	8.36 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >212°F
2. Pour Point: 26°F
3. Viscosity: 1.505 cSt @ 40°C
4. Specific Gravity: 1.1959 @ 60°F
5. pH: 12.9
6. Surface Active Agents: Anionic and nonionic surfactants, proprietary
7. Solvents: CONFIDENTIAL.
8. Additives: CONFIDENTIAL.
9. Solubility in Water: High solubility in water.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.050
Cadmium	<0.025
Chromium	<0.015
Copper	<0.050
Lead	<0.050
Mercury	<1.00 ug/L
Nickel	<0.050
Zinc	0.249
Cyanide	0.0774
Chlorinated Hydrocarbons	<0.005

TECHNICAL PRODUCT BULLETIN #SW-74
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: NOVEMBER 17, 2021
“ECOGREEN”

I. NAME, BRAND, OR TRADEMARK
ECOGREEN

Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT

Rose Rock Products, LLC

P.O. Box 721926

Oklahoma City, OK 73172

Phone: (405) 883-1095

E-mail: Ken.Murphy@RoseRockEnv.com

Website: www.RoseRockEnv.com

(Mr. Ken Murphy, CEO)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS

Rose Rock Products, LLC

P.O. Box 721926

Oklahoma City, OK 73172

Phone: (405) 883-1095

E-mail: Ken.Murphy@RoseRockEnv.com

Website: www.RoseRockEnv.com

(Mr. Ken Murphy, CEO)

EcoTec, LLC

3 Nancy Court, Suite 4

Wappingers Falls, NY 12590

Phone: (845) 897-0003

E-mail: WJordan@EcoTecLLC.com

Website: www.EcoTecLLC.com

(Mr. Wyatt Jordan)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.

2. Ventilation: Always keep exposure below permissible exposure limits. In general, dilution ventilation is a satisfactory health hazard control for this substance. However, if conditions of use create discomfort to the worker, a local exhaust system should be considered.

3. Skin and eye contact; protective clothing; treatment in case of contact: As prescribed in the OSHA Standard for Personal Protective Equipment (29 CFR 1910.132), employers must perform a Hazard Assessment for all workplaces to determine the need for, and selection of, proper protective equipment for each task performed. For skin and eye contact, use good normal hygiene and avoid contact with skin and eyes. For prolonged or repeated handling, use impervious gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boots are recommended. Wear face shield, safety glasses, or chemical goggles are recommended for field application and product handling. If contact with eyes, flush with water for 15 minutes and see medical attention if irritation develops. For contact with skin, wash area with soap and water. May cause redness and drying of skin. Seek medical attention if

irritation develops. In case of ingestion, seek medical attention. Not considered an inhalation risk.

4.a. Maximum storage temperature: 120°F.

4.b. Minimum storage temperature: Freeze temperature is 32°F. No deterioration in performance is expected as a result of freezing. Thaw product and mix thoroughly prior to use.

4.c. Optimum storage temperature range: 35°F to 120°F.

4.d. Temperatures of phase separations and chemical changes: Temperature fluctuations will not cause separation or deterioration of product. Product blend is stable and will not undergo phase separation of ingredients or stratification of contents over time.

V. SHELF LIFE

Unlimited shelf life (unopened), product should be used within 12 months of opening.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: Dilute product with water prior to use. Apply diluted product via manual pressure applicator (i.e., hand pump), or other delivery equipment, to impacted surfaces. Allow product to soak prior to rinse/recovery if heavily saturated with oil. On hard surfaces, product may be applied and agitated with a brush or other physical means prior to recovery of effluent. Product may also be pre-mixed and used in a batch tank or through an eduction/metering system for flushing and recovery operations. Any common pressure washer, either hot or cold, will be effective for proper application at recommended dilutions of ECOGREEN. Proper containment contingencies should be deployed prior to application of ECOGREEN solution to stranded oils on impacted substrates to ensure adequate recovery of treated oils.

2. Concentration/Application Rate: ECOGREEN is a concentrated product and must be diluted prior to use. Concentrations vary based upon type of oil and degree of surface saturation. For Light Ends (i.e., gas condensate/gasoline) a 1% to 2% solution may be used to flush area to containment. Note: A higher concentration solution of 5% to 6% should be used if flammable vapor presents an explosion hazard. For Lighter Oils (i.e., Diesel Fuel, #2 Fuel Oil) a 3% solution may be used to flush impacted areas to containment. For Heavy Ends (i.e., Crude Oil, #6 Fuel Oil) a 6% solution of ECOGREEN should be applied and allowed to soak into containment/substrate for up to an hour to allow for release of oil. The surface should then be flushed to containment with a 1% to 3% solution of ECOGREEN. Product may be used as noted above through any pressure or steam equipment. The use of a “hot” unit is recommended when oils are at low temperature or have been weathered.

3. Conditions for Use: ECOGREEN may be diluted with hard, soft, brackish, salt, or most waters of sufficient quality for operations. Upon proper application as noted above, all treated fluids should be flushed and/or directed to proper containment and recovery. Affected shorelines and other surfaces should be isolated with containment booms and/or sorbent materials prior to treatment to avoid release of treated fluids to open waters. Diversion of swales and temporary catchment sumps may be used for vacuum recovery of treated effluents. All recovered fluids should be disposed of in accordance with all federal, state, and local regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
ECOGREEN (neat)	Menidia beryllina	111.00 96-hr
	Mysidopsis bahia	104.00 48-hr
No. 2 Fuel Oil	Menidia beryllina	11.30 96-hr
	Mysidopsis bahia	1.74 48-hr
ECOGREEN & No. 2 Fuel Oil (1:10)	Menidia beryllina	5.73 96-hr
	Mysidopsis bahia	1.84 48-hr
Reference Toxicant (SDS)	Menidia beryllina	1.76 96-hr
	Mysidopsis bahia	4.24 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS

NA

IX. PHYSICAL PROPERTIES

1. Flash Point: >230°F
2. Pour Point: 32.0°F
3. Viscosity: 4.403 cSt @ 104°F
4. Specific Gravity: 1.015 @ 60°F
5. pH: 8.3
6. Surface Active Agents: CONFIDENTIAL.
7. Solvents: CONFIDENTIAL.
8. Additives: CONFIDENTIAL.
9. Solubility in Water: Complete.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.500
Cadmium	<0.100
Chromium	<0.250
Copper	<0.500
Lead	<0.300
Mercury	<0.151
Nickel	<0.250
Zinc	<1.250
Cyanide	<1.000
Chlorinated Hydrocarbons	All < Method Quantification Limit

TECHNICAL PRODUCT BULLETIN #SW-75
USEPA, OEM REGULATIONS IMPLEMENTATION DIVISION
LISTING DATE: FEBRUARY 16, 2023
“ABLUOL OSASA H/C”

I. NAME, BRAND, OR TRADEMARK
ABLUOL OSASA H/C
Type of Product: Surface Washing Agent

II. NAME, ADDRESS, AND TELEPHONE NUMBER OF MANUFACTURER/CONTACT
Taiwan Surfactant Corporation
8Fl., No. 11, Sec. 1
Chung Shan North Road
Taipei, 104, Taiwan
Phone: 886-2-25410022
E-mail: twsa@twsa.com.tw
Website: <https://www.taiwan-surfactant.com/>
(Mr. Lun Hsieh)

III. NAME, ADDRESS, AND TELEPHONE NUMBER OF PRIMARY DISTRIBUTORS
Taiwan Surfactant Corporation
8Fl., No. 11, Sec. 1
Chung Shan North Road
Taipei, 104, Taiwan
Phone: 886-2-25410022
E-mail: twsa@twsa.com.tw
Website: <https://www.taiwan-surfactant.com/>
(Mr. Lun Hsieh)

IV. SPECIAL HANDLING AND WORKER PRECAUTIONS FOR STORAGE AND FIELD APPLICATION

1. Flammability: Non-flammable.
2. Ventilation: Normal ventilation, use of a respirator in confined areas is recommended.
3. Skin and eye contact; protective clothing; treatment in case of contact: As in handling any industrial chemical, the standard precautions of wearing chemical-resistant gloves and eye protection are recommended. Additional precautions include using non-sparking tools and avoiding exposure to aerosol vapor.
- 4.a. Maximum storage temperature: 212°F.
- 4.b. Minimum storage temperature: 32°F
- 4.c. Optimum storage temperature range: 68°F.
- 4.d. Temperatures of phase separations and chemical changes: May begin freezing below 25°F as product begins to get turbid. Stir until product becomes homogenous. No chemical changes.

V. SHELF LIFE

Two years (unopened). After confirming there is no contamination in opened barrels, opened barrels will have a shelf life of two years.

VI. RECOMMENDED APPLICATION PROCEDURE

1. Application Method: ABLUOL OSASA H/C is water-based formulation. The product is used to remove oil from hard surfaces such as shorelines, rock, and sand. Prior to application of ABLUOL OSASA H/C, collection booms, oil skimmers, sorbent pads, or other appropriate containment and collection mechanism must be deployed and operational. Apply diluted product via manual pressure washer, spraying tools, or hand pumps.

2. Concentration/Application Rate: ABLUOL OSASA H/C is a highly concentrated product and must be diluted with water (salt or fresh) before use. Dilution ratios vary depending on the specific conditions of the contaminated site. The dilution ratio is approximately 1:80 to 1:100 (product:water). The application ratio of this diluted product to oil is approximately 1:10. For shorelines and rock, ABLUOL OSASA H/C is to be used in approximately a 1:80 to 1:100 dilution ratio (product:water). ABLUOL OSASA H/C is sprayed directly on the oiled rocky shorelines or rock. A dilution of ABLUOL OSASA H/C with warm waters (up to 176°F or 80°C) during application will enhance its washing effect on shorelines and rocks. After applying the diluted ABLUOL OSASA H/C by hand or spraying tools, soaking for approximately 10 minutes, the washing work can be started. Application of pressure washer will accelerate the washing process. For use on sand, ABLUOL OSASA H/C is to be used in approximately a 1:80 to 1:100 dilution ratio (product:water) under stirring. Oil will separate from sand and float on the surface of spray water for timely collection or adsorption.

3. Conditions for Use: Do not mix the product with any other cleaner or allow other cleaners to contact surfaces while using ABLUOL OSASA H/C. ABLUOL OSASA H/C does not contain petroleum distillates. The product works well with all types of oils and with salt or fresh water. Use booms or other containments prior application of ABLUOL OSASA H/C to prevent the product/oil mixture from reaching open water. Collect, remove, and dispose of product/oil mixture from site according to federal, state, and local regulations.

VII. TOXICITY AND EFFECTIVENESS

a. Toxicity:

<u>Material Tested</u>	<u>Species</u>	<u>LC50 (ppm)</u>
ABLUOL OSASA H/C	Menidia beryllina	19.80 96-hr
	Mysidopsis bahia	28.10 48-hr
No. 2 Fuel Oil	Menidia beryllina	6.22 96-hr
	Mysidopsis bahia	1.41 48-hr
ABLUOL OSASA H/C No. 2 Fuel Oil (1:10)	Menidia beryllina	3.33 96-hr
	Mysidopsis bahia	1.32 48-hr
Reference Toxicant (SDS)	Menidia beryllina	1.69 96-hr
	Mysidopsis bahia	4.64 48-hr

b. Effectiveness:

NA

VIII. MICROBIOLOGICAL ANALYSIS
NA

IX. PHYSICAL PROPERTIES

1. Flash Point: No flash
2. Pour Point: -21°C
3. Viscosity: 161 cSt @ 40°C
4. Specific Gravity: 1.102 @ 60°F
5. pH: 4.93
6. Surface Active Agents: CONFIDENTIAL
7. Solvents: Water
8. Additives: CONFIDENTIAL
9. Solubility in Water: Soluble in fresh and salt water.

X. ANALYSIS FOR HEAVY METALS, CYANIDE, AND CHLORINATED
HYDROCARBONS

<u>Compound</u>	<u>Concentration (ppm)</u>
Arsenic	<0.50
Cadmium	<0.10
Chromium	<0.25
Copper	<0.50
Lead	<0.30
Mercury	<0.0136
Nickel	<0.25
Zinc	<1.25
Cyanide	<1.00
Chlorinated Hydrocarbons	Non Detect