

Chapter 62-296
Stationary Sources - Emission Standards

62-296.100 Purpose and Scope.

- (1) The Department of Environmental Protection adopts this chapter to establish emission limiting standards and compliance requirements for stationary sources of air pollutant emissions.
- (2) The chapter includes emission limitations for specific categories of facilities and emissions units, and it establishes reasonably available control technology requirements. Where work practice standards, including requirements for specific types of pollution control equipment, are provided for in this chapter, such standards shall be of the same force and effect as emission limiting standards. The emission limiting and work practice standards of Rule 62-296.320, F.A.C., and Rules 62-296.401 through 62-296.480, F.A.C., are applicable statewide. The reasonably available control technology requirements are established for specific areas as set forth in Rules 62-296.500, 62-296.600, and 62-296.700, F.A.C.
- (3) A facility or emissions unit subject to any standard or requirement of 40 C.F.R. Part 60, 61, 63 or 65, adopted and incorporated by reference at Rule 62-204.800, F.A.C. shall comply with such standard or requirement. Nothing in this chapter shall relieve a facility or emissions unit from complying with such standard or requirement, provided, however, that where a facility or emissions unit is subject to a standard established in this chapter, such standard shall also apply.
- (4) Words and phrases used in this chapter, unless clearly indicated otherwise, are defined at Rule 62-210.200, F.A.C.

History: New 11-23-94, Amended 3-13-96, 10-6-2008.

62-296.100

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	12/21/1994	6/16/1999	64 FR 32346
1 st Revision	4/15/1996	6/16/1999	64 FR 32346
2 nd Revision	7/1/2011	10/6/2017	82 FR 46682

62-296.320 General Pollutant Emission Limiting Standards.

- (1) Volatile organic compounds emissions or organic solvents emissions.
No person shall store, pump, handle, process, load, unload or use in any process or installation, volatile organic compounds or organic solvents without applying known and existing vapor emission control devices or systems deemed necessary and ordered by the Department.
- (2) Objectionable Odor Prohibited - No person shall cause, suffer, allow or permit the discharge of air pollutants which cause or contribute to an objectionable odor.
- (3) Industrial, Commercial, and Municipal Open Burning Prohibited. Open burning in connection with industrial, commercial, or municipal operations is prohibited, except when:
 - (a) Open burning is determined by the Department to be the only feasible method of operation and is authorized by an air permit issued pursuant to Chapter 62-210 or 62-213, F.A.C.; or
 - (b) An emergency exists which requires immediate action to protect human health and safety; or
 - (c) A county or municipality would use a portable air curtain incinerator to burn yard trash generated by a hurricane, tornado, fire or other disaster and the air curtain incinerator would otherwise be operated in accordance with the permitting exemption criteria of Rule 62-210.300(3), F.A.C.
- (4) General Particulate Emission Limiting Standards. The following emission limiting standards shall apply to emissions units of particulate matter not subject to a particulate emission limit or opacity limit set forth in or established elsewhere in this chapter.
 - (a) Process Weight Table.
 1. Applicability. The emission limitations set forth in Rule 62-296.320(4)(a)2., F.A.C., below, shall apply to any emissions unit which processes raw materials to produce a finished product through a chemical or physical change, except emissions units which:
 - a. Burn fuel to produce heat or power by indirect heating where the products of combustion do not come in contact with the process materials.
 - b. Burn refuse.
 - c. Salvage materials by burning.
 2. Particulate Matter Emissions Standard - No person shall cause, let, permit, suffer or allow the emission of particulate matter through a stack or vent, from any emissions unit subject to this rule in total quantities in excess of the amount shown in Table 296.320-1. Interpolation of the data in Table 296.320-1 for the process weight rates up to 30 tons per hour shall be accomplished by use of the equation: $E = 3.59P^{0.62}$, where P is less than or equal to 30 tons per hour. Interpolation and extrapolation of the data for process weight rates in excess of 30 tons per hour shall be accomplished by use of the equation: $E = 17.31P^{0.16}$, where P is greater than 30 tons per hour. In both equations: E = emissions in pounds per hour and P = process weight rate in tons per hour.

PROCESS WEIGHT TABLE
TABLE 296.320-1

Rate (Tons Per Hour)	Emission Rate (Pounds Per Hour)
.025	0.36
.050	0.56
.250	1.52
.50	2.34
2.50	6.34
5	9.74
10	14.97
30	29.57
40	31.23
60	33.33
80	34.90
100	36.17
200	40.41
500	46.79

3. Particulate Matter Emissions Test Method and Procedures. All particulate matter emissions tests performed pursuant to the requirements of this rule shall comply with the following provisions.
 - a. Emissions units incorporating a scrubber for control of particulate matter shall use the following test methods.
 - (i) Citrus Plants. The test method for particulate emissions shall be EPA Method 5, as described in 40 C.F.R Part 60, Appendix A-3, adopted and incorporated by reference at Rule 62-204.800, F.A.C. An acetone wash shall be used. The minimum sample volume shall be 32 dry standard cubic feet.
 - (ii) All Others. The test method for particulate emissions shall be EPA Method 5, as described at 40 C.F.R. Part 60, Appendix A-3, adopted and incorporated by reference at Rule 62-204.800, F.A.C. An acetone wash shall be used.
 - b. Emissions units incorporating dry controls for control of particulate matter shall use the following test methods.
 - (i) Phosphate Processing. The test method for particulate emissions shall be EPA Method 5, as described at 40 C.F.R. Part 60, Appendix A-3, adopted and incorporated by reference at rule 62-204.800, F.A.C. An acetone wash shall be used. The minimum sample volume shall be 30 dry standard cubic feet.
 - (ii) All Others. The test method for particulate emissions shall

be EPA Method 17, with an acetone wash and an average stack temperature below 275 degrees Fahrenheit, or EPA Method 5 with an acetone wash. EPA Method 17 is described at 40 C.F.R. Part 60, Appendix A-6; and EPA Method 5 is described at 40 C.F.R. Part 60, Appendix A-3. These test methods are adopted and incorporated by reference at Rule 62-204.800, F.A.C.

- c. Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.
- (b) General Visible Emissions Standard.
1. No person shall cause, let, permit, suffer or allow to be discharged into the atmosphere the emissions of air pollutants from any activity, the density of which is equal to or greater than 20 percent opacity.
 2. Notwithstanding Rule 62-296.320(4)(b)1., F.A.C., above, the owner or operator of an emissions unit subject to the general visible emission standard may request the Department to establish a higher visible emissions standard for that emissions unit. The owner or operator may request that a visible emissions standard be established at that level at which the emissions unit will be able, as indicated by compliance tests, to meet the opacity standard at all times during which the emissions unit is meeting the applicable particulate matter standard. The Department shall establish such a standard, through the permitting process, if it finds that:
 - a. The emissions unit was in compliance with the applicable particulate emission standard while a compliance test was being conducted but failed to comply with the general visible emissions standard during the test;
 - b. The emissions unit and associated air pollution control equipment were operated and maintained in a manner to minimize the opacity emissions during the compliance test; and
 - c. The emissions unit and associated air pollution control equipment were incapable of being adjusted or operated in such a manner as to meet the opacity standard.
 3. If the presence of uncombined water is the only reason for failure to meet visible emission standards given in this rule, such failure shall not be a violation of this rule.

4. All visible emissions tests performed pursuant to the requirements of this rule shall comply with the following provisions.
 - a. The test method for visible emissions shall be EPA Method 9, as described at 40 C.F.R. Part 60, Appendix A-4, adopted and incorporated and adopted by reference at Rule 62-204.800, F.A.C.
 - b. Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.
- (c) Unconfined Emissions of Particulate Matter.
1. No person shall cause, let, permit, suffer or allow the emissions of unconfined particulate matter from any activity, including vehicular movement; transportation of materials; construction, alteration, demolition or wrecking; or industrially related activities such as loading, unloading, storing or handling; without taking reasonable precautions to prevent such emissions.
 2. Any permit issued to a facility with emissions of unconfined particulate matter shall specify the reasonable precautions to be taken by that facility to control the emissions of unconfined particulate matter.
 3. Reasonable precautions include the following:
 - a. Paving and maintenance of roads, parking areas and yards.
 - b. Application of water or chemicals to control emissions from such activities as demolition of buildings, grading roads, construction, and land clearing.
 - c. Application of asphalt, water, oil, chemicals or other dust suppressants to unpaved roads, yards, open stock piles and similar activities.
 - d. Removal of particulate matter from roads and other paved areas under the control of the owner or operator of the facility to prevent reentrainment, and from buildings or work areas to prevent particulate from becoming airborne.
 - e. Landscaping or planting of vegetation.
 - f. Use of hoods, fans, filters, and similar equipment to contain, capture and/or vent particulate matter.
 - g. Confining abrasive blasting where possible.
 - h. Enclosure or covering of conveyor systems.
 4. In determining what constitutes reasonable precautions for a particular facility, the Department shall consider the cost of the control technique or work practice, the environmental impacts of the technique or practice, and the degree of reduction of emissions expected from a particular technique or practice.

History: Formerly 17-2.620, 17-296.320, Amended 1-1-96, 3-13-96, 10-6-08, 7-10-14.

62-296.320

Date Submitted	Date Approved	Federal
----------------	---------------	---------

	to EPA	by EPA	Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	6/16/1999	64 FR 32346
2 nd Revision	4/15/1996	6/16/1999	64 FR 32346
3 rd Revision	4/1/2022	1/22/2024	89 FR 3886

62-296.340 Best Available Retrofit Technology.

(1) Applicability. This rule applies to all BART-eligible sources as defined at 40 CFR 51.301, adopted and incorporated by reference at Rule 62-204.800, F.A.C. Failure of the Department to include a particular BART eligible source on any list of BART-eligible sources it produces does not relieve the owner or operator of such source from responsibility to comply with the requirements of this rule.

(2) Definitions. For the purposes of this rule:

1. All definitions at 40 CFR 51.301 shall apply, including the definition of "Best Available Retrofit Technology (BART)" contained therein.

2. The term "CAIR Program" shall mean the requirements of 40 CFR 52.540 and 52.541, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or it shall have the meaning given at Rule 62-210.200, F.A.C., whichever is applicable.

3. The term "Class I area" shall mean any mandatory Class I federal area where visibility is an important value, as set forth at 40 CFR Part 81, Subpart D, adopted and incorporated by reference at Rule 62-204.800, F.A.C.

(3) Requirements.

(a) Unless exempted under subsection 62-296.340(5), F.A.C., the owner or operator of a BART-eligible source shall install, operate, and maintain BART, as determined by the Department, for each emissions unit and each pollutant for which a BART determination is required.

1. The Department shall determine BART for all BART-eligible sources in accordance with the criteria of 40 CFR 51.308(e) and the procedures and guidelines contained in 40 CFR Part 51, Appendix Y, each adopted and incorporated by reference at Rule 62-204.800, F.A.C.

2. The pollutants for which a BART determination is required are those pollutants identified as visibility-impairing pollutants in 40 CFR Part 51, Appendix Y, excluding volatile organic compounds, ammonia, and ammonia compounds, except that:

a. A BART determination shall not be required for sulfur dioxide or for nitrogen oxides if the BART-eligible source has the potential to emit less than 40 tons per year of such pollutant(s), or for PM₁₀ if the BART-eligible source has the potential to emit less than 15 tons per year of such pollutant.

b. A BART determination shall not be required for sulfur dioxide or for nitrogen oxides for any electric generating unit at a BART-eligible source that is subject to the CAIR Program.

(b) The Department shall articulate the basis for its BART determination(s) in an air construction permit.

1. The owner or operator of a BART-eligible source subject to the requirement for BART determination under paragraph 62-296.340(3)(a), F.A.C., shall perform a BART evaluation for each emissions unit comprising the BART-eligible source and for each pollutant for which a BART determination is required. The BART evaluation shall be performed in accordance with the criteria of 40 CFR 51.308(e) and the procedures and guidelines contained in 40 CFR Part 51. Appendix Y. The BART evaluation and proposed BART determination(s) shall be submitted to the Department in an application for an air construction permit not later than January 31, 2007.

2. The air construction permit issued by the Department shall require the owner or operator of the BART-eligible source to comply with BART as expeditiously as practicable, but not later than December 31, 2013. Such permit shall also require an operation and maintenance plan for any control equipment required by the BART determination.

3. Before taking final agency action on any air construction permit application to establish its BART determination(s), the Department shall comply with all applicable provisions of Rule 62-110.106, F.A.C., and, in its intent to issue, provide an opportunity for public comment which shall include at a minimum the following:

a. Pursuant to Chapter 119, Florida Statutes, a complete file available for public inspection at its Tallahassee offices which includes the information submitted by the owner or operator, exclusive of confidential records under Section 403.111, Florida Statutes, and the Department's preliminary BART determination(s);

b. A 30-day period for submittal of public comments; and

c. A notice, by advertisement in a newspaper of general circulation in the county affected, specifying the nature and location of the BART-eligible source and the location of the information specified in sub-subparagraph 62-296.340(3)(b)3.a., F.A.C., and notifying the public of the opportunity for submitting comments. The notice shall be prepared by the Department and published by the applicant in accordance with all applicable provisions of Rule 62-110.106, F.A.C., except that the applicant shall cause the notice to be published no later than thirty (30) days prior to final agency action.

(4) Optional Reasonable Progress Evaluation. An electric generating unit that is part of a BART-eligible source and also subject to the CATR Program shall not be subject to further emissions reductions to meet Florida's reasonable progress goal for 2018 for any Class I area pursuant to the requirements of 40 CFR 51.308(d)(1), provided that the owner or operator:

(a) Performs a unit-specific BART evaluation for sulfur dioxide and nitrogen oxides in accordance with the criteria of 40 CFR 51.308(e) and the procedures and guidelines contained in 40 CFR Part 51. Appendix Y. and submits such evaluation and proposed BART-equivalent

emission limitations for sulfur dioxide and nitrogen oxides to the Department in an application for an air construction permit; and

(b) Accepts an air construction permit wherein the Department establishes BART-equivalent emission limitations for sulfur dioxide and nitrogen oxides for the unit.

(c) In establishing BART-equivalent emission limitations pursuant to this subsection, the Department shall use the criteria of 40 CFR 51.308(e) and the procedures and guidelines contained in 40 CFR Part 51, Appendix Y, each adopted and incorporated by reference at Rule 62-204.800, F.A.C.

(d) The air construction permit issued by the Department shall require the owner or operator of the unit to comply with the BART-equivalent emission limitations as expeditiously as practicable, but not later than December 31, 2013, if the permit is issued on or before December 31, 2008; or the earlier of December 31, 2017, or the date five years after permit issuance, if the permit is issued after December 31, 2008.

(e) Before taking final agency action on any air construction permit application to establish its BART-equivalent emission limitations, the Department shall provide opportunity for public comment in accordance with the provisions of subparagraph 62-296.340(3)(b)3., F.A.C.

(f) BART-equivalent emission limitations for sulfur dioxide and nitrogen oxides established pursuant to this subsection are separate and distinct from the BART requirements of subsection 62-296.340(3). F.A.C. Noncompliance with a BART-equivalent emission limitation established pursuant to this subsection shall not constitute noncompliance with BART.

(5) Exemptions.

(a) A BART-eligible source may demonstrate that it is exempt from the requirement for BART determination for all pollutants by documenting that:

1. The sum of its potential emissions of sulfur dioxide, nitrogen oxides, and particulate matter (expressed as equivalent tons of sulfur dioxide or nitrogen oxides in terms of its light extinction efficiency) is less than 500 tons per year and the source is located greater than 50 kilometers from all Class I areas; or

2. The sum of its potential emissions of sulfur dioxide, nitrogen oxides, and particulate matter (expressed as equivalent tons of sulfur dioxide or nitrogen oxides in terms of its light extinction efficiency) is less than 1,000 tons per year and the source is located greater than 100 kilometers from all Class I areas.

(b) A BART-eligible source comprising only electric generating units that are subject to the CAIR Program and other emissions units that emit no visibility-impairing pollutants other than

particulate matter may demonstrate that it is exempt from the requirement for BART determination for all pollutants by documenting that:

1. Its potential emissions of particulate matter (expressed as equivalent tons of sulfur dioxide or nitrogen oxides in terms of its light extinction efficiency) are less than 500 tons per year and the source is located greater than 50 kilometers from all Class I areas; or
2. Its potential emissions of particulate matter (expressed as equivalent tons of sulfur dioxide or nitrogen oxides in terms of its light extinction efficiency) are less than 1,000 tons per year and the source is located greater than 100 kilometers from all Class I areas.

(c) If unable to claim exemption pursuant to paragraph 62-296.340(5)(a) or (b), F.A.C., a BART-eligible source may demonstrate that it is exempt from the requirement for BART determination for all pollutants by performing an individual source attribution analysis in accordance with the procedures contained in 40 CFR Part 51. Appendix Y. A BART-eligible source is exempt from BART determination requirements if its contribution to visibility impairment, as determined below, does not exceed 0.5 deciviews above natural conditions in any Class I area.

1. For electric generating units subject to the CAIR Program, the source attribution analysis need only consider particulate matter emissions (including primary sulfate) for comparison with the contribution threshold.
2. For all other units, the source attribution analysis shall consider sulfur dioxide, nitrogen oxides, and particulate matter emissions collectively for comparison with the contribution threshold.

(d) If the owner or operator of a BART-eligible source requests exemption from the requirement for BART determination for all pollutants by submitting its source attribution analysis or other supporting documentation to the Department not later than January 31, 2007, and the Department ultimately grants such exemption, the requirement for submission of an air construction permit application pursuant to subparagraph 62-296.340(3)(b) 1., F.A.C., shall not apply. If the Department denies such exemption, the owner or operator shall submit an application for air construction permit containing a BART evaluation and proposed BART determination(s) to the Department not later than January 31, 2007, or thirty (30) days after receipt of the Department's denial, whichever is later.

Specific Authority 403.061, 403.087 FS. Law Implemented 403.03 1, 403.061, 403.087 FS.
History – New

62-296.340

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	3/19/2010	8/29/2013	78 FR 53250

62-296.401 Incinerators.

- (1). Any incinerator with a charging rate of less than 50 tons per day.
 - (a) No visible emission (5 percent opacity) except that visible emissions not exceeding 20 percent opacity are allowed for up to three minutes in any one hour period.
 - (b) No objectionable odor allowed.
 - (c) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - 1. The test method for visible emissions shall be DEP Method 9, incorporated in Chapter 62-297, F.A.C.
 - 2. Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.
- (2) Existing incinerators, other than those which are operated or utilized for the disposal or treatment of biological waste, with a charging rate equal to or greater than 50 tons per day.
 - (a) Particulate matter - 0.1 grains per standard cubic foot dry gas corrected to 50 percent excess air.
 - (b) No objectionable odor allowed.
 - (c) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - 1. The test method for particulate emissions shall be EPA Method 5, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 30 dry standard cubic feet. EPA Method 3 or 3A using Orsat analysis is required for percent excess air correction.
 - 2. Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.
 - (d) Calculations Correcting Concentrations to 50% Excess Air (EA), EPA Method 3, Section 1.2. When correcting a pollutant emission concentration to 50% excess air, pursuant to this rule, the following equation shall be used:

$$Cs_{50} = \frac{Cs(100 + \%EA)}{150} \qquad \text{Equation 296.401-1}$$

where: Cs₅₀ is the pollutant concentration at 50% excess air;
Cs is the pollutant concentration computed at standard conditions on a dry basis; and
%EA is calculated by equation 296.401-2:

$$\%EA = \frac{(\%O_2 - 0.5\%CO) * 100}{0.264\%N_2 - (\%O_2 - 0.5\%CO)} \qquad \text{Equation 296.401-2}$$

- (3) New incinerators, other than those which are operated or utilized for the disposal or treatment of biological waste, with a charging rate equal to or greater than 50 tons per

day.

- (a) Particulate matter - .08 grains per standard cubic foot dry gas corrected to 50 percent excess air.
- (b) No objectionable odor allowed.
- (c) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - 1. The test method for particulate emissions shall be EPA Method 5, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 30 dry standard cubic feet. EPA Method 3 or 3A using Orsat analysis is required for percent excess air correction.
- (d) Calculations Correcting Concentrations to 50% Excess Air (EA), EPA Method 3, Section 1.2. When correcting a pollutant emission concentration to 50% excess air, pursuant to this rule, the following equation shall be used:

$$Cs_{50} = \frac{Cs(100 + \%EA)}{150} \quad \text{Equation 296.401-1}$$

where: Cs_{50} is the pollutant concentration at 50% excess air;
 Cs is the pollutant concentration computed at standard conditions on a dry basis; and
 $\%EA$ is calculated by equation 296.401-2:

$$\%EA = \frac{(\%O_2 - 0.5\%CO) * 100}{0.264\%N_2 - (\%O_2 - 0.5\%CO)} \quad \text{Equation 296.401-2}$$

- 2. Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.
- (4) Biological Waste Incineration Facilities. The following requirements apply to all biological waste incineration facilities. This rule does not apply to human remains for which a DHRS death certificate has been issued, that are disposed of by a person licensed under the provisions of Chapter 470, F.S.
- (a) Facilities with a capacity equal to or less than 500 pounds per hour used solely for the incineration of dead animals.
 - 1. Particulate matter emissions shall not exceed 0.080 grains per dry standard cubic foot of flue gas, corrected to 7% O_2 .
 - 2. Facilities subject to this rule shall incinerate only dead animals and, if applicable, the bedding and the remains associated with the animals placed in leak proof containers. Containers may contain up to 0.5 percent by weight chlorinated plastics. Plastic bags used for the incineration of animals shall be nonchlorinated and no less than 3 mils thick.
 - a. If containers are incinerated, documentation from the manufacturers certifying that they are composed of 0.5 percent or

less by weight chlorinated plastics must be kept on-file at the site for the duration of their use and for at least two years after their use. This documentation must also be submitted with any permit renewal application.

- b. If plastic bags are incinerated, documentation must be provided to prove that the bags are nonchlorinated and no less than 3 mils thick.
3. Facilities subject to this rule shall not incinerate dead animals which were used for biomedical or commercial experimentation. No other material, including biohazardous waste as defined in Rule 62-210.200, F.A.C., shall be incinerated.
- (b) Facilities with a capacity equal to or less than 500 pounds per hour that are not used solely for the incineration of dead animals.
 1. Particulate matter emissions shall not exceed 0.100 grains per dry standard cubic foot of flue gas, corrected to 7% O₂.
 2. Hydrochloric Acid (HCl) emissions shall not exceed 4.0 pounds per hour.
- (c) Facilities with a capacity greater than 500 pounds per hour, but less than or equal to 2,000 pounds per hour.
 1. Particulate matter emissions shall not exceed 0.030 grains per dry standard cubic foot of flue gas, corrected to 7% O₂.
 2. Hydrochloric acid (HCl) emissions shall not exceed 4.0 pounds per hour; or shall be reduced by 90% by weight on an hourly average basis.
- (d) Facilities with a capacity greater than 2000 pounds per hour.
 1. Particulate matter emissions shall not exceed 0.020 grains per dry standard cubic foot of flue gas, corrected to 7% O₂.
 2. Hydrochloric acid (HCl) emissions shall not exceed 50 parts per million by volume, dry basis, corrected to 7% O₂ on a three hour average basis; or shall be reduced by 90% by weight on an hourly average basis.
- (e) All facilities unless otherwise noted are subject to the following design, operating, monitoring and operator training requirements.
 1. Any incinerator with a capacity equal to or less than 500 pounds per hour used solely for the incineration of dead animals for which a complete application for a permit to construct a new unit was received by the Department on or after August 30, 1989, shall provide design calculations to confirm a sufficient volume in the secondary (or last) chamber combustion zone to provide for at least a 1.0 second gas residence time at 1800 degrees Fahrenheit. The actual operating temperature of the secondary (or last) chamber combustion zone shall be no less than 1600 degrees Fahrenheit throughout the combustion process in the primary chamber. Primary chamber and stack shall not be used in calculating this residence time. Combustion in the primary chamber shall not begin unless the secondary (or last) chamber combustion zone temperature is equal to or greater than 1600 degrees Fahrenheit.
 2. Any incinerator with a capacity equal to or less than 500 pounds per hour

used solely for the incineration of dead animals for which a complete application for a permit to construct a new unit was received by the Department prior to August 30, 1989, shall provide design calculations to confirm a sufficient volume in the secondary (or last) chamber combustion zone to provide for at least a 1.0 second gas residence time at 1600 degrees Fahrenheit. The actual operating temperature of the secondary (or last) chamber combustion zone shall be no less than 1400 degrees Fahrenheit throughout the combustion process in the primary chamber. Primary chamber and stack shall not be used in calculating this residence time. Combustion in the primary chamber shall not begin unless the secondary (or last) chamber combustion zone temperature is equal to or greater than 1400 degrees Fahrenheit.

3. Any incinerator that is not used solely for the incineration of dead animals or any incinerator with a capacity greater than 500 pounds per hour shall operate with a combustion zone design temperature of no less than 1800 degrees Fahrenheit for at least a 1.0 second gas residence time in the secondary (or last) combustion chamber. Primary chamber and stack shall not be utilized in calculating this residence time.
4. Mechanically fed facilities shall incorporate an air lock system to prevent opening the incinerator to the room environment. The volume of the loading system shall be designed to prevent overcharging thereby assuring complete combustion of the waste.
5. Carbon monoxide (CO) emissions shall not exceed 100 parts per million by volume, dry basis, corrected to 7% O₂ on an hourly average basis.
6. Incineration or ignition of waste shall not begin until the secondary (or last) combustion chamber temperature requirement is attained. All air pollution control and continuous emission monitoring equipment shall be operational and functioning properly prior to the incineration or ignition of waste and until all the wastes are incinerated. The secondary (or last) combustion chamber temperature requirement shall be maintained until the wastes are completely combusted.
7. Radioactive waste may not be burned in an incinerator subject to this rule unless the incinerator has been issued a Department of Health and Rehabilitative Services (DHRS) license to incinerate radioactive waste or the waste is of such quantity to be exempt in accordance with DHRS Rule 10D-91 or 10D-104.003, F.A.C.
8. Hazardous waste may not be burned in an incinerator subject to this rule unless the incinerator has been issued a hazardous waste permit by the Department or the waste is of such quantity to be exempt in accordance with Chapter 62-730, F.A.C.
9. Any operators of incinerators with a capacity equal to or less than 500 pounds per hour used solely for the incineration of dead animals shall be trained by the equipment manufacturer's representatives or an equivalent state-approved organization.

- a. The content of the training program shall be submitted to the Department for approval. Construction permit applicants shall submit a training program, or reference a previously submitted training program, with the construction permit application. The training shall provide a basic understanding of the principles of the combustion process, provide instruction on the operation and maintenance of the incinerator, and increase awareness of regulation requirements and safety concerns. Training programs shall be a minimum of 8 hours of instruction. Training programs shall at a minimum include hands-on experience involving start-up, operation of at least one incineration cycle, shut-down of equipment, and one full cycle of preventative maintenance actions. The Department shall approve training programs which meet, at a minimum, the criteria set forth in the EPA Medical Waste Incinerator Operator Training Program Course Handbook EPA 453/B-93-018 and Instructor's Guide EPA 453/B-93-019.
 - b. A copy of the training certificate for each operator having satisfactorily completed the Department-approved training program must be submitted to the Department within 15 days of training. If the emissions unit is modified to the extent that a Department construction permit is required, the operators shall be retrained to operate the modified unit. Owners of new and modified emissions units shall submit copies of the operator training certificates within 15 days after completion of initial compliance test.
 - c. An operator's certificate must be kept on file at the facility for the duration of the operator's employment and for an additional two years after termination of employment. The owner shall not allow the incinerator to be operated unless it is operated by an operator who has satisfactorily completed the required training program.
10. Any operator of an incinerator that is not used solely for the incineration of dead animals or any operator of an incinerator with a capacity greater than 500 pounds per hour shall be trained by the equipment manufacturer's representative or an equivalent state-approved organization.
- a. The content of the training program shall be submitted to the Department for approval. Construction permit applicants shall submit a training program, or reference a previously submitted training program, with the construction permit application. The training shall provide a basic understanding of the principles of the combustion process, provide instruction on proper operating practices and procedures, and increase awareness of regulation requirements and safety concerns. Training programs shall be minimum of 16 hours of instruction. The Department shall approve training programs which meet, at a minimum, the criteria

set forth in the EPA Medical Waste Incinerator Operator Training Program Course Handbook EPA 453/B-93-018 and Instructor's Guide EPA 453/B-93-019.

- b. A copy of the training certificate for each operator having satisfactorily completed the Department-approved training program must be submitted to the Department within 15 days of training. If the incinerator is modified to the extent that a Department construction permit is required, the operators shall be retrained to operate the modified incinerator. Owners of new and modified incinerators shall submit copies of the operator training certificates within 15 days after completion of the initial compliance test.
 - c. An operator's certificate must be kept on file at the facility for the duration of the operator's employment and for an additional two years after termination of employment. The owner shall not allow the incinerator to be operated unless it is operated by an operator who has satisfactorily completed the required training program.
- (f) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
- 1. The test method for visible emissions shall be DEP Method 9, incorporated in Chapter 62-297, F.A.C.
 - 2. The test method for carbon monoxide shall be EPA Method 10, incorporated and adopted by reference in Chapter 62-297, F.A.C.
 - 3. The test method for oxygen shall be EPA Method 3 or 3A, incorporated and adopted by reference in Chapter 62-297, F.A.C.
 - 4. The test method for particulate emissions shall be EPA Method 5 or 26A, incorporated and adopted by reference in Chapter 62-297, F.A.C.
 - 5. The test method for hydrochloric acid shall be EPA Method 26, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 30 dry standard cubic feet.
 - 6. Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.
- (g) Frequency of Testing.
- 1. Facilities with a capacity equal to or less than 500 pounds per hour shall demonstrate compliance as follows.
 - a. New and existing facilities shall demonstrate individual emissions unit compliance with the visible emissions standard upon initial compliance and annually thereafter.
 - b. New and existing facilities shall demonstrate individual emissions unit compliance with the remaining applicable standards upon initial compliance and prior to renewing the operation permit.
 - 2. New and existing facilities with a capacity greater than 500 pounds per hour shall demonstrate individual source compliance with the applicable standards upon initial compliance and annually thereafter.

- (h) Compliance Demonstration. Facilities with a capacity equal to or less than 500 pounds per hour used solely for the incineration of dead animals may demonstrate compliance with the carbon monoxide and particulate emissions standards by submission of a test report for an identical (same make, model, and permitted capacity) crematory unit operating in compliance with a valid Department air permit and tested pursuant to that permit. The test data in the test report must be less than five years old and may or may not be obtained from the unit that is being permitted.
- (i) Continuous Emissions Monitoring Requirements. Each owner or operator of a biological waste incineration facility shall install, operate, and maintain in accordance with the manufacturer's instructions continuous emission monitoring equipment.
 - 1. The monitors shall record the following operating parameters.
 - a. Secondary (or last) combustion chamber exit temperature.
 - b. Oxygen (for facilities with a capacity greater than 500 pounds per hour).
 - 2. A complete file of all measurements, including continuous emissions monitoring system, monitoring device, and performance testing measurements; all continuous emissions monitoring system performance evaluations; all continuous emissions monitoring system or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; and all other information required, shall be recorded in a permanent legible form available for inspection. The file shall be retained for at least two years following the date of such measurements, maintenance, reports and records.
- (5) Human Crematories. The following requirements apply to all human crematory facilities.
 - (a) Particulate matter emissions shall not exceed 0.080 grains per dry standard cubic foot of flue gas, corrected to 7% O₂.
 - (b) Carbon Monoxide (CO) emissions shall not exceed 100 parts per million by volume, dry basis, corrected to 7% O₂ on an hourly average basis.
 - (c) Crematory units for which a complete application for a permit to construct a new unit was received by the Department on or after August 30, 1989, shall provide design calculations to confirm a sufficient volume in the secondary chamber combustion zone to provide for at least a 1.0 second gas residence time at 1800 degrees Fahrenheit. The actual operating temperature of the secondary chamber combustion zone shall be no less than 1600 degrees Fahrenheit throughout the combustion process in the primary chamber. Primary chamber and stack shall not be used in calculating this residence time. Cremation in the primary chamber shall not begin unless the secondary chamber combustion zone temperature is equal to or greater than 1600 degrees Fahrenheit.
 - (d) Crematory units for which construction began or for which a complete application for a permit to construct a new unit was received by the Department prior to August 30, 1989, shall provide design calculations to confirm a sufficient volume in the secondary chamber combustion zone to provide for at least a 1.0 second gas

residence time at 1600 degrees Fahrenheit. The actual operating temperature of the secondary chamber combustion zone shall be no less than 1400 degrees Fahrenheit throughout the combustion process in the primary chamber. Primary chamber and stack shall not be used in calculating this residence time. Cremation in the primary chamber shall not begin unless the secondary chamber combustion zone temperature is equal to or greater than 1400 degrees Fahrenheit.

- (e) Human crematories shall cremate only dead human bodies with appropriate containers. The bodies may be clothed. The containers may contain up to 0.5 percent by weight chlorinated plastics as demonstrated by manufacturer's data sheet. If containers are incinerated, documentation from the manufacturers certifying that they are composed of 0.5 percent or less by weight chlorinated plastics must be kept on-file at the site for the duration of their use and for at least two years after their use. This documentation must also be submitted with any permit renewal applications. No other material, including biohazardous waste as defined in Rule 62-210.200, F.A.C., shall be incinerated.
- (f) All crematory operators shall be trained by the equipment manufacturer's representatives or another qualified organization.
 - 1. The content of the training program shall be submitted to the Department for approval. Construction permit applicants shall submit a training program or reference a previously approved training program with the construction permit application. The training shall provide a basic understanding of the principles of the combustion process, provide instruction on the operation and maintenance of the crematory unit, and increase awareness of regulation requirements and safety concerns. Training programs shall be a minimum of 8 hours of instruction. Training programs shall at a minimum include hands-on experience involving start-up, operation of at least one cremation, shut-down of the equipment, and one full cycle of preventive maintenance actions. The Department shall approve training programs which meet, at a minimum, as are applicable to cremation, the criteria set forth in the EPA Medical Waste Incinerator Operator Training Program Course Handbook EPA 453/B-93-018 and Instructor's Guide EPA 453/B-93-019.
 - 2. A copy of the training certificate for each operator having satisfactorily completed the Department-approved training program must be submitted to the Department within 15 days of training. If the crematory unit is modified to the extent that a Department construction permit is required, the operators shall be retrained to operate the modified unit. Owners of new and modified emissions units shall submit copies of the operator training certificates within 15 days after completion of initial compliance test.
 - 3. An operator's certificate must be kept on file at the facility for the duration of the operator's employment and for an additional two years after termination of employment. The owner shall not allow the crematory to be operated unless it is operated by an operator who has satisfactorily

- completed the required training program.
- (g) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - 1. The test method for visible emissions shall be DEP Method 9, incorporated in Chapter 62-297, F.A.C.
 - 2. The test method for carbon monoxide shall be EPA Method 10, incorporated and adopted by reference in Chapter 62-297, F.A.C.
 - 3. The test method for oxygen shall be EPA Method 3, incorporated and adopted by reference in Chapter 62-297, F.A.C.
 - 4. The test method for particulate emissions shall be EPA Method 5, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 30 dry standard cubic feet.
 - 5. Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.
 - (h) Operation During Compliance Test. Testing of emissions shall be conducted with the source operating at the maximum permitted capacity.
 - (i) Frequency of Testing.
 - 1. New and existing facilities shall demonstrate individual source compliance with the visible emissions standard upon initial compliance and annually thereafter.
 - 2. New and existing facilities shall demonstrate individual source compliance with the remaining applicable standards upon initial compliance and prior to renewing the operating permit.
 - (j) Compliance Demonstration. Facilities may demonstrate compliance with the carbon monoxide and particulate emissions standards by submission of a test report for an identical (same make, model, and permitted capacity) crematory unit operating in compliance with a valid Department air permit and tested pursuant to that permit. The test data in the test report must be less than five years old and may or may not be obtained from the unit that is being permitted.
 - (k) Continuous Emissions Monitoring Requirements. Each crematory facility shall install, operate, and maintain continuous monitors to record temperature at the point or beyond where 1.0 second gas residence time is obtained in the secondary chamber combustion zone in accordance with the manufacturer's instructions. A complete file of all measurements, including continuous monitoring system, monitoring device, and performance testing measurements; all continuous monitoring system performance evaluations; all continuous monitoring system or monitoring device calibration checks; and any adjustments, preventive maintenance, and corrective maintenance performed on these systems or devices, shall be recorded in a permanent legible form available for inspection. Continuous temperature monitoring documentation shall include operator name, operator indication of when cremation in the primary chamber begins, date, time, and temperature markings. The file shall be retained for at least two years following the recording of such measurements, maintenance, reports, and records.
- (6) Any air curtain incinerator, new or existing, located at a landfill for any time period or at

any other site for more than six months.

- (a) Outside of startup periods, no visible emissions (5 percent opacity or less) shall be allowed, except that an opacity of up to 20 percent shall be permitted for not more than three minutes in any one hour.
- (b) During startup periods, which shall not exceed the first 30 minutes of operation, an opacity of up to 35 percent, averaged over a six-minute period, shall be allowed.
- (c) The general excess emissions rule, Rule 62-210.700, F.A.C., to handle startups, shutdowns, and malfunctions, shall not apply to air curtain incinerators.
- (d) The following dimensions for the pit must be strictly adhered to: no more than 12 feet wide, between 8 and 15 feet deep, and no longer than the length of the manifold. The pit shall not be dug within a previously active portion of the landfill.
- (e) The only materials that can be burned in an air curtain incinerator are wood wastes consisting of trees, logs, large brush, stumps relatively free of soil, unbagged leaves and yard trash, tree surgeon debris, and clean dry lumber such as pallets.
- (f) The burning of sawdust, paper, trash, tires, garbage, plastics, liquid wastes, chemically treated or painted wood, and other similar materials is expressly prohibited.
- (g) Only virgin oil, natural gas, or liquefied petroleum gas may be used to start the fire. The use of waste oil, chemicals, gasoline, or tires is expressly prohibited.
- (h) In no case shall an air curtain incinerator be started before sunrise. For refractory lined air curtain incinerators, charging must have completely stopped before sunset. For all other air curtain incinerators, charging must have completely stopped two hours before sunset.
- (i) In no case shall the permitted burning rate, in tons per day, exceed the value obtained by dividing the number 100,000 by the permitted number of days that burning will be authorized to take place.
- (j) New air curtain incinerators must be located at least three hundred (300) feet from any pre-existing occupied building located off site. Air curtain incinerators existing as of October 1, 1986, must be located at least two hundred (200) feet from any occupied building located off site. The Department may issue a permit for an air curtain incinerator which does not meet this setback if the applicant submits with the application a signed affidavit from the owner(s) of all occupied buildings within the setback area that waives the setback requirement.
- (k) Air curtain incinerators used at landfills may not be operated within one thousand (1000) feet of any active portion of the landfill unless the air curtain incinerator is separated from the active portion of the landfill by a controlled gate or check-in station.
- (l) The material shall not be loaded into the air curtain incinerator such that it will protrude above the air curtain.
- (m) Ash shall not be allowed to build up in the pit to higher than 1/3 the pit depth or to the point where the ash begins to impede combustion, whichever occurs first.

- (n) A detailed operation and maintenance guide must be available to the operators at all times, and the permittee must provide the proper training to all operators before they work at the incinerator. The Department may request a copy of this guide.
- (o) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - 1. The test method for visible emissions shall be DEP Method 9, incorporated in Chapter 62-297, F.A.C.
 - 2. Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.600(1), Amended 10-14-92, 12-02-92; Formerly 17-296.401; Amended 11-23-94, 1-1-96, 3-13-96.

62-296.401

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	06/16/1999	64 FR 32346
2 nd Revision	04/15/1996	06/16/1999	64 FR 32346

62-296.402 Sulfuric Acid Plants.

- (1) (Reserved).
- (2) Existing Plants.
 - (a) Florida portion of the Jacksonville, Florida - Brunswick, Georgia, Interstate Air Quality Control Region as defined in 40 CFR Section 81.91.
 1. Visible Emissions - ten percent opacity.
 2. (Reserved)
 3. Acid Mist - 0.5 pounds per ton of 100 percent acid produced.
 - (b) All other areas of the State of Florida.
 1. Visible Emissions - ten percent opacity.
 2. (Reserved)
 3. Acid Mist - 0.3 pounds per ton of 100 percent acid produced.
- (3) New Plants.
 - (a) Visible emissions - ten percent opacity.
 - (b) (Reserved)
 - (c) Acid Mist - 0.15 pounds per ton of 100 percent acid produced.
- (4) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) The test method for visible emissions shall be DEP Method 9, incorporated in Chapter 62-297, F.A.C.
 - (b) The test method for acid mist/sulfur dioxide shall be EPA Method 8, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 40 dry standard cubic feet.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.
- (5) Continuous Emissions Monitoring Requirements. Each owner or operator of a sulfuric acid plant shall install, calibrate, operate and maintain a continuous monitoring system for continuously monitoring the pollutants specified in this subsection. Performance specifications, location of monitor, data requirements, data reduction and reporting requirements, shall conform with the requirements in: 40 CFR Part 51, Appendix P, adopted and incorporated by reference in Rule 62-204.800(2), F.A.C., and 40 CFR Part 60, Appendix B, adopted by reference in Rule 62-204.800(7), F.A.C., for existing and new emissions units provided, however, any alternative procedures (as specified in s. 3.9, 40 CFR Part 51, Appendix P) or Special Considerations (as specified in s. 6.0, 40 CFR Part 51, Appendix P) shall be incorporated in the Department's air permit for the emissions unit and submitted to the U.S. Environmental Protection Agency as a proposed revision to the State Implementation Plan.
 - (a) Facilities greater than 300 tons per day production capacity, expressed as 100% acid, shall install continuous monitoring systems for the measurement of sulfur dioxide emissions for each sulfuric acid emission source.
 - (b) Where two or more emissions units emit through a common stack, continuous monitoring systems, if required, shall be installed on each emissions unit prior to combination of the emission.
- (6) Semi-annual Reporting Requirements. The owners or operators of facilities for which

monitoring is required shall submit to the Department a written report of emissions in excess of emission limiting standards as set forth in Rule 62-296.402, F.A.C., for each semi-annual period. Each semi-annual report shall cover the 6-month periods of January 1 – June 30 and July 1 – December 31. The reports shall be submitted by the 60th day following the end of each calendar half (i.e., March 1st and August 29th of every year). The nature and cause of the excessive emissions shall be explained. This report does not relieve the owner or operator of the legal liability for violations. All recorded data shall be maintained on file by the owner or operator for a period of two years.

History: Formerly 17-2.600(2); Formerly 17-296.402; Amended 11-23-94, 1-1-96, 3-13-96.

62-296.402

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	11/23/1992	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	6/16/1999	64 FR 32346
2 nd Revision	4/15/1996	6/16/1999	64 FR 32346
3 rd Revision	9/30/2022	8/4/2023	88 FR 51702

62-296.403 - Phosphate Processing.

Fluorides (water soluble or gaseous atomic weight 19) expressed as pounds of fluoride per ton of phosphate materials input to the system expressed as tons of P₂O₅.

- (1) New Plants or Plant Sections.
 - (a) Wet process phosphoric acid production and auxiliary equipment - 0.02 pounds.
 - (b) Run-of-pile triple super phosphate (TSP) mixing belt and den and auxiliary equipment - 0.05 pounds.
 - (c) Run-of-pile TSP curing or storage process and auxiliary equipment - 0.12 pounds.
 - (d) Granular triple super phosphate (GTSP) production and auxiliary equipment.
 - 1. GTSP made by granulating run-of-pile TSP - 0.06 pounds.
 - 2. GTSP made from phosphoric acid and phosphate rock slurry - 0.15 pounds.
 - (e) GTSP storage and auxiliary equipment - 0.05 pounds.
 - (f) Diammonium phosphate production and auxiliary equipment - 0.06 pounds.
 - (g) Calcining or other thermal phosphate rock processing and auxiliary equipment excepting phosphate rock drying and defluorinating - 0.05 pounds.
 - (h) Defluorinating phosphate rock by thermal processing and auxiliary equipment - 0.37 pounds.
 - (i) All plants, plant sections or unit operations and auxiliary equipment not listed in paragraphs (a) through (h) above must use the best available control technology.
- (2) Existing plants or plant sections shall comply with Rule 62-296.403(1), F.A.C., no later than July 1, 1975; or existing plant complexes with an operating wet process phosphoric acid section (including any items in Rule 62-296.403(1)(a) through (f), F.A.C.) and other plant sections processing or handling phosphoric acid or products of phosphoric acid processing, total emissions from the entire complex shall not exceed 0.4 pounds per ton of P₂O₅ input to the wet process phosphoric acid section.
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) The test method for fluoride emissions shall be EPA Method 13A or EPA Method 13B, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 30 dry standard cubic feet.
 - (b) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.600(3); Formerly 17-296.403; Amended 11-23-94, 1-1-96, 3-13-96.

62-296.403

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	6/16/1999	64 FR 32346
2 nd Revision	4/15/1996	6/16/1999	64 FR 32346

62-296.404 Kraft (Sulfate) Pulp Mills and Tall Oil Plants.

- (1) New plants.
 - (a) Particulate Matter - three pounds per each 3000 pounds of black liquor solids fed.
 - (b) Total Reduced Sulfur (TRS) - one ppm expressed as H₂S on the dry basis or 0.03 pounds per 3000 pounds black liquor solids fed, whichever is more restrictive.
- (2) Existing plants.
 - (a) Particulate Matter - three pounds per each 3000 pounds of black liquor solids fed.
 - (b) Visible emission limits for kraft pulp mill sources equipped with wet scrubbers shall be effective only if the visible emission measurement can be made without being substantially affected by plume mixing or moisture condensation. If the Department determines that visible emissions exceed 20 percent opacity, a special compliance test may be required in accordance with Rule 62-297.570, F.A.C., Kraft (Sulfate) Pulp Mills and Tall oil Plants.
- (4) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) Kraft Recovery Furnaces.
 1. The test method for visible emissions shall be EPA Method 9, incorporated and adopted by reference in Chapter 62-297, F.A.C.
 2. The test method for particulate emissions shall be EPA Method 5, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 32 dry standard cubic feet. For EPA Method 5, the filter temperature must not exceed 320 degrees Fahrenheit. EPA Method 17 may be used if stack temperature is less than 400 degrees Fahrenheit. An adjustment of 0.004 grains per dry standard cubic foot shall be added to the test results when using Method 17. A water wash shall be used with either method.
 3. The test method for TRS shall be EPA Method 16 or EPA Method 16A or EPA Method 16B, incorporated and adopted by reference in Chapter 62-297, F.A.C. EPA Method 16 or EPA Method 16A pursuant to Rule 62-297.401(16), F.A.C., shall be required for instrument certification and compliance testing.
 - (b) Lime Kilns and Calciners.
 1. The particulate emissions test method for scrubber controlled emissions units shall be EPA Method 5, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 32 dry standard cubic feet. A water wash shall be used.
 2. The particulate emissions test method for dry control emissions units shall be EPA Method 5, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 32 dry standard cubic feet. A acetone wash shall be used.
 3. The test method for TRS shall be EPA Method 16 or EPA Method 16A or EPA Method 16B, incorporated and adopted by reference in Chapter 62-297, F.A.C. EPA Method 16 or EPA Method 16A pursuant to Rule

- 62-297.401(16), F.A.C., shall be required for instrument certification and compliance testing.
- (c) Smelt Dissolving Tank Vents.
1. The particulate emissions test method for scrubber controlled emissions units shall be EPA Method 5, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 32 dry standard cubic feet. A water wash shall be used.
 2. The particulate emissions test method for dry control emissions units shall be EPA Method 5, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 32 dry standard cubic feet. A acetone wash shall be used.
 3. The test method for TRS shall be EPA Method 16 or EPA Method 16A or EPA Method 16B, incorporated and adopted by reference in Chapter 62-297, F.A.C. EPA Method 16 or EPA Method 16A pursuant to Rule 62-297.401(16), F.A.C., shall be required for instrument certification and compliance testing.
- (d) The TRS test method for tall oil plants shall be EPA Method 16 or EPA Method 16A or EPA Method 16B, incorporated and adopted by reference in Chapter 62-297, F.A.C. EPA Method 16 or EPA Method 16A pursuant to Rule 62-297.401(16), F.A.C., shall be required for instrument certification and compliance testing.
- (e) Other Combustion Devices used to Incinerate TRS.
1. The particulate emissions test method for scrubber controlled emissions units shall be EPA Method 5, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 32 dry standard cubic feet. A water wash shall be used.
 2. The particulate emissions test method for dry control emissions units shall be EPA Method 5, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 32 dry standard cubic feet. A acetone wash shall be used.
 3. The test method for TRS shall be EPA Method 16 or EPA Method 16A or EPA Method 16B, incorporated and adopted by reference in Chapter 62-297, F.A.C. EPA Method 16 or EPA Method 16A pursuant to Rule 62-297.401(16), F.A.C., shall be required for instrument certification and compliance testing.
- (f) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.
- (5) Continuous Emissions Monitoring Requirements. Each owner or operator of a kraft (sulfate) pulp mill or tall oil plant shall install continuous monitoring systems for monitoring total reduced sulfur (TRS) emissions, or the performance of total reduced sulfur air pollution control systems as specified in this subsection.
- (a) Straight kraft recovery furnaces, whether new or old design, cross recovery furnaces, lime kilns and calciners, shall be equipped with total reduced sulfur continuous emissions monitoring systems as specified in Rule 62-296.404(5)(b), F.A.C. All digester systems and multiple effect evaporator systems, shall be

equipped with total reduced sulfur continuous emissions monitoring systems as specified in Rule 62-296.404(5)(b), F.A.C. (Continuous Emission Monitoring), if a technology other than incineration is used.

(b) Continuous determination of total reduced sulfur emissions.

1. A total reduced sulfur continuous emissions monitoring system shall be installed, calibrated, certified and operated pursuant to all of the following provisions:
 - a. The continuous emissions monitoring system shall monitor and record the concentration of total reduced sulfur (TRS) emissions on a dry basis and the percentage of oxygen by volume on a dry basis.
 - b. The continuous emissions monitoring system shall complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each successive 15-minute period.
 - c. The continuous emissions monitoring system shall be located downstream of the control device such that representative measurements of process parameters can be obtained.
 - d. The continuous emissions monitoring system shall be located, installed and certified pursuant to the provisions of 40 CFR Part 60, Appendix B, Performance Specification 2 and Performance Specification 3, and 40 CFR Part 60, Appendix B, Performance Specification 5, which are adopted by reference in Rule 62-296.800, F.A.C. The exception is that the phrase "or other approved alternative" in s. 3.2 of Performance Specification 5 is not adopted. For the purposes of compliance testing and certification of continuous emissions monitoring systems, 40 CFR Part 60, Appendix A, Reference Method 16 and Method 16A adopted by reference in Rule 62-296.800, F.A.C., 62.204.800 par (7) F.A.C. are to be used.
 - e. The continuous emissions monitoring system shall be in continuous operation, except when the emissions unit is not operating, or during system breakdowns, repairs, calibration checks, and zero and span adjustments.
 - f. During any initial compliance tests conducted pursuant to Rule 62-296.404, F.A.C., or within 30 days thereafter, and at such times as there is reason to believe the system does not conform to the performance specifications under this rule (for example, equipment repairs, replacements, excessive drift and such), the owner or operator of any affected emissions unit shall conduct continuous monitoring system performance evaluations and furnish the Department, within sixty days thereof, two copies of a written report of the results of such tests. These continuous emissions monitoring systems performance evaluations shall be conducted in accordance with the requirements and procedures contained in

Rule 62-296.404(5)(b)1.d., F.A.C.

- g. The continuous emissions monitoring system shall have a maximum span value not to exceed:
 - (i) A total reduced sulfur concentration of 30 ppm for the total reduced sulfur continuous emissions monitoring system on any new design direct-fired kraft recovery furnace that is not direct-fired, new design suspension-burning kraft recovery furnace, incinerator, digester system or multiple effect evaporator system.
 - (ii) A total reduced sulfur concentration of 50 ppm for the total reduced sulfur continuous emissions monitoring system on any old design kraft recovery furnace, new design kraft recovery furnace that is not direct-fired, new design direct-fired suspension-burning kraft recovery furnace, cross recovery furnace, lime kiln or calciner.
 - (iii) 20 percent oxygen for the continuous oxygen monitoring system.
 - h. The continuous emissions monitoring system shall be checked by the owner or operator in accordance with a written procedure at least once daily and after any maintenance to the system. The owner or operator shall check the zero (or low level value between 0 and 20 percent of span value) and span (90 to 100 percent of span value) calibration drifts. The zero and span shall be adjusted, as a minimum, whenever the 24-hour zero drift or 24-hour span drift exceeds two times the limits of the applicable performance specifications referenced in Rule 62-296.404(5)(b)1.d., F.A.C. The system must allow the amount of excess zero and span drift measured at the 24-hour interval checks to be recorded and quantified.
2. The owner or operator of any total reduced sulfur emissions unit who is required to install a total reduced sulfur continuous emissions monitoring system pursuant to Rule 62-296.404(5)(a), F.A.C., shall:
- a. Reduce all data to one-hour averages for each 60-minute period beginning on the hour. One-hour averages shall be computed from a minimum of four data points equally spaced over each one-hour period. Data recorded during periods of system breakdowns, repairs, calibration checks, and zero and span adjustments shall not be included in the computation. Either an arithmetic or integrated average shall be used. The data output of the continuous emissions monitoring system may, at the owner's or operator's option, include a numerical format showing individual numerical readings and averages in addition to the required strip chart format with legible ink tracings and calibration information. All data output shall be clearly and properly identified by the operator. All system

- breakdowns, repairs, calibration checks, span adjustments and periods of excess emissions shall legibly appear on all data output.
- b. Calculate and record on a daily basis the 12-hour average total reduced sulfur concentrations for two consecutive 12-hour periods of each operating day. Each 12-hour average shall be determined as the arithmetic mean of the appropriate 12 contiguous one-hour average total reduced sulfur concentrations provided by the continuous emissions monitoring system.
 - c. Calculate and record on a daily basis 12-hour average oxygen concentrations for two consecutive 12-hour periods of each operating day. These 12-hour averages shall correspond to the 12-hour average total reduced sulfur concentrations from Rule 62-296.404(5)(b)2.b., F.A.C., and shall be determined as an arithmetic mean of the appropriate 12 contiguous one-hour average oxygen concentrations provided by each continuous emissions monitoring system.
 - d. Correct all 12-hour average total reduced sulfur (TRS) concentrations using the following equation:

$$C_{corr} = C_{meas} (21 - X)/(21 - Y)$$

where: C_{corr} = the TRS concentration corrected for oxygen.

C_{meas} = the TRS concentration uncorrected for oxygen.

X = the volumetric oxygen concentration in percentage that the measured TRS concentration is to be corrected to (8 percent for all recovery furnaces and 10 percent for all lime kilns, incinerators or other devices, except those emissions units subject to Rule 62-296.404(3)(a)2., F.A.C., and Rule 62-296.404(3)(b), F.A.C., which shall be corrected to the actual oxygen content of the untreated flue gas stream).

Y = the measured 12-hour average volumetric oxygen concentration.

- e. The data shall be rounded to the same number of significant digits as the standard.
- (c) Incinerators subject to Rule 62-296.404(3)(f), F.A.C., shall be equipped with devices to continuously monitor temperature at the point of combustion and oxygen.
The temperature devices shall be certified by the manufacturer to be accurate to within ± 1 percent of the temperature being measured. The oxygen monitors shall be certified by the manufacturer to be accurate to within 0.1 percent oxygen by volume.
 - (d) The owner or operator of any kraft pulp mill shall provide the Department with a list of physical and chemical parameters for each regulated total reduced sulfur

emissions unit that is not required to be equipped with a total reduced sulfur continuous monitor, which will be regularly monitored to demonstrate that the emissions unit is being operated in a manner that can reasonably be expected to result in compliance with the applicable total reduced sulfur emission limiting standards. The owner or operator shall provide information showing the correlation between the specific magnitudes of the specific surrogate parameters and the associated emissions of total reduced sulfur. The owner or operator shall recommend the frequency and method of monitoring for each parameter. The Department shall issue notice to the company pursuant to Rule 62-103, F.A.C., that specifies the parameters that are to be monitored, the frequency of monitoring, and the parameter limits that must be maintained. The parameters, parameter limits and frequency of monitoring shall become a modification to the permit for each affected emissions unit. Excess emissions shall be deemed to occur if the parameters exceed the parameter limits specified in the permit. Such parameter limits may be in the form of the applicable total reduced sulfur emission standard, if an equation is used that estimates the 12-hour average total reduced sulfur emission rate based on the surrogate parameter values during each 12-hour averaging period; or the parameter limits may be in the form of specific parameter values that are not to be exceeded (or dropped below) more often than a specified period of time during each 12-hour averaging period.

- (6) Quarterly Reporting Requirements. The owner or operator of any digester system, multiple effect evaporator system, condensate stripper system, tall oil plant, kraft recovery furnace, lime kiln, calciner or other emissions unit subject to the provisions of Rule 62-296.404(5), F.A.C. (Continuous Monitoring Requirements), shall submit a written total reduced sulfur emissions and surrogate parameter data report to the Department postmarked by the 30th day following the end of each calendar quarter.
- (a) The report shall include the following information:
1. The magnitude of excess emissions and the date and time of commencement and completion of each time period in which excess emissions occurred.
 2. Specific identification of each period of excess emissions that occurs including startups, shutdowns, and malfunctions of the affected emissions unit. An explanation of the cause of each period of excess emissions, and any corrective action taken or preventive measures adopted. Excess emissions shall be all 12-hour periods for which the appropriate surrogate parameter data or total reduced sulfur continuous emissions monitoring data indicates that an applicable 12-hour average total reduced sulfur emission limiting standard for the emissions unit was exceeded.
 3. The date and time identifying each period during which each continuous emissions monitoring system used to measure total reduced sulfur emissions or surrogate parameters was inoperative except for zero and span checks, and the nature of the system repairs or adjustments.
 4. When no excess emissions have occurred or the continuous emissions monitoring system(s) have not been operative, or have been repaired or

adjusted, such information shall be stated in the report.

- (b) Any owner or operator subject to the provisions of Rule 62-296.404(5) and (6), F.A.C., shall maintain a complete file of any measurements, including continuous emissions monitoring system, monitoring device, and performance testing measurements; any continuous emissions monitoring system performance evaluations; any continuous emissions monitoring system or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; and any other information required, recorded in a permanent legible form available for inspection. The file shall be retained for at least three years following the date of such measurements, maintenance, reports and records.
- (c) Evaluation of Excess Emissions. The Department shall consider periods of excess emissions from any kraft recovery furnace, lime kiln, calciner or any other regulated TRS emissions unit to be evidence of improper operation and maintenance of the monitored emissions unit provided that:
 - 1. For kraft recovery furnaces subject to the emissions limits of Rule 62-296.404(3)(c), F.A.C., the excess emissions occur during more than one percent of the total number of possible contiguous 12-hour periods of excess emissions in a calendar quarter rounded to the nearest whole number (excluding only the actual 12-hour periods during which a startup, shutdown or malfunction of the kraft recovery furnace occurred and only the actual 12-hour periods when the kraft recovery furnace was not operating), or
 - 2. For lime kilns and calciners subject to the emissions limits of Rule 62-296.404(3)(e), F.A.C., the excess emissions occur during more than two percent of the total number of possible contiguous 12-hour periods of excess emissions in a calendar quarter rounded to the nearest whole number (excluding only the actual 12-hour periods during which a startup, shutdown or malfunction of the lime kiln, calciner, or their control equipment occurred and only the actual 12-hour periods when the lime kiln or calciner was not operating), or
 - 3. For other regulated non-NSPS total reduced sulfur emissions units, the excess emissions as indicated by the appropriate surrogate parameters occur during more than one percent of the total number of possible contiguous 12-hour periods of excess emissions in a calendar quarter rounded to the nearest whole number (excluding only the actual 12-hour periods during which a startup, shutdown, or malfunction of the emissions unit or its control equipment occurred and only the actual 12-hour periods when the source was not operating), and
 - 4. The Department determines that the affected emissions unit, including air pollution control equipment, is not maintained and operated in a manner which is consistent with good air pollution control practice for minimizing emissions. Such determination shall be based on the failure of the owner or operator of the facility to provide records of maintenance and operation of the emissions unit and related equipment showing operation consistent

with good air pollution control practices. Good air pollution control practices shall include:

- a. Operation of all equipment within permit limits for loading rates and other process parameters,
 - b. An adequate preventive maintenance program based on manufacturer's recommendations or other accepted industry practices,
 - c. Training of personnel in the operation and maintenance of equipment,
 - d. Visual and instrument inspections of equipment on a regular basis, and
 - e. Maintenance of an adequate on-site, or readily available, supply of equipment for routine repairs.
- (d) The owner or operator of any kraft pulp mill or tall oil plant shall notify the Department in writing within fourteen days of the date on which periods of excess emissions exceed the percentages allowed by Rule 62-296.404(6)(c)1. through 3., F.A.C.

History: Formerly 17-2.600(4); Formerly 17-296.404; Amended 11-23-94, 1-1-96, 3-13-96.
62-296.404

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	06/16/1999	64 FR 32346
2 nd Revision	04/15/1996	06/16/1999	64 FR 32346

62-296.405 Existing Fossil Fuel Steam Generators with Greater than or Equal to 250 Million Btu Per Hour Heat Input.

(1) Applicability. Rule 62-296.405, F.A.C., applies to existing fossil fuel steam generators with greater than or equal to 250 MMBtu per hour heat input. For the purposes of this rule, “existing” means the emission unit was in existence, in operation, or under construction, or had received a permit to begin construction prior to January 18, 1972.

(2) Visible emissions – 20 percent opacity except for one six-minute period per one-hour period during which opacity shall not exceed 27 percent. Emissions units governed by this visible emission limit shall test for particulate emissions annually and as otherwise required by Chapter 62-297, F.A.C. Emissions units electing to test for particulate matter emissions quarterly shall be allowed visible emissions of 40 percent opacity. The results of such tests shall be submitted to the Department or local program, as specified in the facility’s permit. Upon demonstration that the particulate standard has been regularly complied with, the Secretary, upon petition by the applicant, shall reduce the frequency of particulate testing to no less than once annually.

(3) Particulate Matter – 0.1 pound per million Btu heat input, as measured by stack height . If compliance is demonstrated with a particulate matter continuous emission monitoring system, then compliance shall be determined on a heat-input weighted 30-operating day rolling average basis, including all periods of operation. Compliance is determined by first summing the total pounds of the pollutant in question emitted from the Unit during an operating day and the previous 29 operating days; second, sum the total heat-input to the Unit in MMBtu during the operating day and the previous 29 operating days; and third, divide the total number of pounds of the pollutant emitted during the 30 operating days by the total heat input during the 30 operating days. An operating day is defined as any day (midnight to midnight when fuel is fired).

(4) Sulfur Dioxide, as measured by fuel sampling. If compliance is demonstrated with a sulfur dioxide continuous emission monitoring system, then compliance shall be determined on a 24-hour block average including all periods of operation unless a different averaging period is specified below. Compliance is determined by calculating the arithmetic average of all valid hourly averages occurring within one day.

(a). Emissions units burning liquid fuel.

1. Emissions units in Duval County with a nameplate generating capacity of greater than 250 MW which commenced operation prior to August 1, 1977 – 1.98 pounds per million Btu heat input.

6. Escambia County, no emissions unit north of Interstate 10 with a rated heat input of 515 million Btu per hour or less for which a valid Department operating permit was issued prior to September 30, 1972 shall emit in the aggregate more than 57.5 tons per any 24 hour period.

7. Manatee County, emissions units with a nameplate generating capacity of

greater than 700 MW for which a valid Department operating permit was issued prior to January 1, 1979 – 1.1 pounds per million Btu heat input.

10. All other areas of the State – 2.75 pounds per million Btu heat input.

(b). Emissions units burning solid fuel.

3. Escambia County, emissions units north of Interstate 10 with a nameplate generating capacity of more than 50 MW which commenced operation prior to September 1, 1973 – 5.90 pounds per million Btu heat input.

(5) Nitrogen Oxides (expressed as NO₂) – as measured by stack test. If compliance is demonstrated with a nitrogen oxides continuous emission monitoring system, then compliance shall be based on a heat-input weighted 30-operating day rolling average basis, including all periods of operation. Compliance is determined by first summing the total pounds of the pollutant in question emitted from the Unit during operating day and the previous 29 operating days; and third, divide the total number of pounds of the pollutant emitted during the 30 operating days by the total heat input during the 30 operating days. An operating day is defined as any day (midnight to midnight) when fuel is fired.

(a). Duval County, emissions units with a nameplate generating capacity of greater than 450 MW which commenced operation prior to August 1, 1977 – 0.30 pounds per million Btu heat input.

(b). Manatee County, emissions units with a nameplate generating capacity of greater than 700 MW for which a valid Department operating permit was issued prior to January 1, 1979 – 0.30 pounds per million Btu heat input.

(d). Hillsborough County, emissions units with a nameplate generating capacity of greater than 400 MW which commenced operation after January 1, 1976 and prior to January 1, 1985 – 0.70 pounds per million Btu heat input.

(6) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.

(a). The test method for visible emissions shall be EPA Method 9, as described at 40 C.F.R. Part 60, Appendix A-4, adopted and incorporated by reference at Rule 62-204.800, F.A.C. In lieu of Method 9 testing, a transmissometer utilizing a 6-minute block average for opacity measurement may be used, provided such transmissometer is installed, certified, calibrated, operated and maintained in accordance with the provisions of 40 C.F.R. Part 75, as adopted and incorporated by reference at Rule 62-204.800, F.A.C.

(b). The test methods for particulate emissions shall be EPA Methods 17, 5, 5B, or 5F.

The minimum sample volume shall be 30 dry standard cubic feet. EPA Method 5 may be used with filter temperature at no more than 320 degrees Fahrenheit. For EPA Method 17, stack temperature shall be less than 375 degrees Fahrenheit. EPA Method 3 or 3A with Orsat analysis shall be used when the oxygen base F-factor computed according to EPA Method 19 is used in lieu of heat input. Acetone wash shall be used with EPA Method 5 or 17. Methods 3 and 3A are described at 40 C.F.R. Part 60, Appendix A-2; EPA Methods 5, 5B, and 5F are described at 40 C.F.R. Part 60, Appendix A-3; EPA Method 17 is described at 40 C.F.R. Part 60, Appendix A-6; and EPA Method 19 is described at 40 C.F.R. Part 60, Appendix A-7; adopted and incorporated by reference a Rule 62-204.800, F.A.C. In lieu of EPA Method 17, 5, 5B, or 5F, an emissions unit may demonstrate compliance using a particulate matter continuous emissions monitoring system that meets the requirements of Performance Specification 11, adopted and incorporated by reference in Rule 62-204.800, F.A.C.

(c). The test methods for sulfur dioxide emissions shall be EPA Methods 6, 6A, 6B or 6C, as described at 40 C.F.R. Part 60, Appendix A-4, adopted and incorporated by reference at Rule 62-204.800 F.A.C. Fuel sampling and analysis may be used as an alternate sampling procedure if such a procedure was incorporated in the operation permit for the emissions unit prior to April 23, 1985. Otherwise, fuel sampling and analysis may be used if the emissions unit obtains an alternate procedure under the provisions of Rule 62-297.620, F.A.C. Such alternate procedure shall become a condition of the emissions unit's permit. The Department will retain the authority to require EPA Method 6 or 6C if it has reason to believe that exceedances of the sulfur dioxide emissions limiting standard are occurring. Results of an approved fuel sampling and analysis program or continuous emissions monitoring program shall have the same effect as EPA Method 6 test results for purposes of demonstrating compliance or noncompliance with sulfur dioxide standards.

(d). The test method for nitrogen oxides shall be a nitrogen oxides continuous emissions monitor meeting the requirements of 40 C.F.R. Part 75, as adopted and incorporate by reference in Rule 62-204.800, FA.C.

(e). Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

(7) Continuous Emissions Monitoring Requirements. Each owner or operator of an emissions unit subject to subsection 62-296.405(1), F.A.C., shall install, calibrate, operate and maintain a continuous monitoring system for continuously monitoring the pollutants specified in this subsection. Performance specifications, location of monitor, 419 data requirements, data reduction and reporting requirements shall conform with the requirements of 40 C.F.R. Part 51, Appendix P, adopted and incorporated by reference in subsection 62-204.800(2), F.A.C., and 40 C.F.R. Part 60, Appendix B, adopted by reference in subsection 62-204.800(7), F.A.C., for existing and new emissions units provided, however, any alternative procedure (as specified in Section 3.9, 40 C.F.R. Part 51, Appendix P) or special consideration (as specified in Section 6.0, 40 C.F.R. Part 51, Appendix P) shall be incorporated in the Department's air permit for the

emissions unit and submitted to the U.S. Environmental Protection Agency as a proposed revision to the State Implementation Plan.

(a). Existing fossil fuel steam generators with more than 250 million BTU per hour heat input and with a capacity factor of greater than 30 percent for the latest year of record or as otherwise documented to the Department by the owner or operator, shall install continuous monitoring systems as set forth in this subparagraph. Any reactivated or previously exempted unit whose operated capacity factor for the previous six months is greater than 30 percent must install continuous monitoring systems as set forth in this subparagraph no later than twelve months following the previous six month period of achieving a capacity factor greater than 30 percent.

1. Opacity. All emissions units as set forth in subparagraph 62-296.405(1)(f)1., F.A.C., shall install continuous monitoring systems for monitoring opacity. Exempted are:

(a) Emissions units burning only gas, oil, or gas and oil which comply with the applicable state visible emission limiting standard without the use of emission control equipment.

(b) Any emissions unit using a wet scrubber.

2. Sulfur dioxide. All emissions units as set forth in subparagraph 62-296.405(1)(f)1., F.A.C., shall install sulfur dioxide continuous monitoring equipment on units which have installed sulfur dioxide control equipment. Those emissions units not having an operating flue gas desulfurization device may monitor sulfur dioxide emissions by fuel sampling and analysis according to methods approved by EPA.

3. Nitrogen Oxides. All new emissions units as set forth in subparagraph 62-296.405(1)(f)1., F.A.C., with more than 1000 million BTU per hour heat input shall, during construction, install continuous monitoring systems for monitoring nitrogen oxides.

4. Oxygen or Carbon Dioxide. A continuous monitoring system shall be installed at each emissions unit, as set forth in subparagraph 62-296.405(7)(a), F.A.C., where measurements of oxygen or carbon dioxide in the flue gas are utilized to convert either sulfur dioxide or nitrogen oxides continuous emission monitoring data to units of the emission limiting standards for proof of compliance as set forth in subsection 62-296.405 F.A.C.

(b). The exemption from opacity monitoring under sub-subparagraph 62-296.405(7)(a)1.a., F.A.C., shall not apply to any emissions unit which has been found to be in violation of the visible emission limiting standard pursuant to administrative

proceedings conducted under Chapter 120, Florida Statutes, or judicial proceedings after January 1, 1978. No later than ninety days following the date an order establishing such violation becomes final, the owner or operator of such emissions unit shall submit to the Department a proposed compliance schedule for installing a continuous opacity monitoring system. Following incorporation of a compliance schedule into the emission unit's air permit, the owner or operator shall install the continuous monitoring system in accordance with the schedule.

(8) Semi-annual Reporting Requirements. The owners or operators of facilities for which monitoring is required shall submit to the Department a written report of emissions in excess of emission limiting standards as set forth in Rule 62-206.405, F.A.C., for each semi-annual period. Each semi-annual report shall cover the 6-month periods of January 1-June 30 and July 1-December 31. The reports shall be submitted by the 60th day following the end of each calendar half (i.e., March 1st and August 29th of every year). The nature and cause of the excessive emissions shall be explained. This report does not relieve the owner or operator of the legal liability for violations. All recorded data shall be maintained on file by the Source for a period of two years.

(9) For the purposes of this rule, nameplate generating capacity means the manufacturer's capacity rating of electrical generating output (expressed in Mwe) as designed.

History: Formerly 17-2.600(5); Amended 6-29-93; Formerly 17-296.405; Amended 11-23-94, 1-1-96, 3-13-96, 3-2-99, 7-10-14.

62-296.405

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	7/02/1993	4/14/1994	59 FR 17696
2 nd Revision	12/21/1994	6/16/1999	64 FR 32346
3 rd Revision	4/15/1996	6/16/1999	64 FR 32346
4 th Revision	6/23/99 & 7/1/2011	10/6/2017	82 FR 46682
5 th Revision	4/1/2022	8/4/2023	88 FR 51702
6th Revision	9/30/2022	8/4/2023	88 FR 51702

62-296.406 Fossil Fuel Steam Generators with Less than 250 Million Btu per Hour Heat Input.

The following standards apply to new and existing emissions units, except for emissions units that would otherwise be exempt from permitting pursuant to subsection 62-210.300(3), F.A.C., and emissions units that would otherwise be considered insignificant pursuant to subparagraph 62-213.300(2)(a)1., or paragraph 62-213.430(6)(b), F.A.C. These standards apply unless otherwise specified by rule, or by order or permit issued by the Department prior to July 15, 1989.

- (1) Visible Emissions – shall not exceed 20 percent opacity except for one six-minute period per one-hour period during which opacity shall not exceed 27percent . An opacity of 30 percent opacity shall be allowed for sources rated at 241 million Btu per hour heat input for which a valid Department operating permit was issued prior to October 1, 1972 in Escambia County, while burning fuel oil in conjunction with waste material derived from waste streams previously discharged into underground wells.
- (2) Particulate Matter - Best available control technology.
- (3) Sulfur Dioxide - Best available control technology.

History: Formerly 17-2.600(6); Amended 6-29-93; Formerly 17-296.406; Amended 11-23-94, 3-13-96, 3-2-99, 7-10-14, 11-5-20.

62-296.406

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	7/02/1993	4/14/1994	59 FR 17696
2 nd Revision	12/21/1994	6/16/1999	64 FR 32346
3 rd Revision	4/15/1996	6/16/1999	64 FR 32346
4 th Revision	6/23/1999 & 7/1/2011	10/6/2017	82 FR 46682
5 th Revision	4/1/2022	1/22/2024	89 FR 3886

62-296.408 Nitric Acid Plants.

These limits are applicable to new and existing emissions units producing weak nitric acid (50 to 70 percent) by pressure or atmospheric pressure process.

- (1) Visible emissions - 10 percent opacity.
- (2) Nitrogen Oxides - 3 pounds per ton of acid produced (100 percent basis).
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) The test method for visible emissions shall be DEP Method 9, incorporated in Chapter 62-297, F.A.C.
 - .(Reserved)
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.600(8); Formerly 17-296.408; Amended 11-23-94, 1-1-96.

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	1/11/93	10/20/94	59 FR 52916
1 st Revision	12/21/1994	06/16/1999	64 FR 32346
2 nd Revision	9/30/2022	8/4/2023	88 FR 51702

62-296.409 Sulfur Recovery Plants.

These limits are applicable to plants recovering sulfur from crude oil gas.

- (1) New Plants - 0.004 pounds of sulfur dioxide per pound of sulfur input to the recovery system or 0.004 pounds of sulfur dioxide per pound of sulfur removed from an oil well.
- (2) Existing Plants (for which a valid Department Construction permit was issued prior to July 1, 1973) - 0.08 pounds of sulfur dioxide per pound of sulfur input to the recovery system or 0.08 pounds of sulfur dioxide per pound of sulfur removed from crude oil or gas processed.
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) The test method for sulfur dioxide shall be EPA Method 6, incorporated and adopted by reference in Chapter 62-297, F.A.C. The minimum sample volume shall be 0.71 dry standard cubic feet. Two 20 minute samples (± 5 minutes) per run required.
 - (b) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.600(9); Formerly 17-296.409; Amended 11-23-94.

62-296.409

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	6/16/1999	64 FR 32346

62-296.410 Carbonaceous Fuel Burning Equipment.

- (1) Emissions units for which a valid Department operation or Construction permit was issued prior to July 1, 1974.
 - (a) Burners with a capacity less than 30 million Btu per hour heat input - Visible emissions with a density of Number 1 on the Ringelmann Chart (20 percent opacity) except that emissions with a density of Number 2 (40 percent opacity) are permissible for not more than two minutes in any one. hour.
 - (b) Burners with a capacity equal to or greater than 30 million Btu per hour heat input.
 - 1. Visible emissions - Visible emissions with a density of Number 1.5 on the Ringelmann Chart (30 percent opacity) except that a density of Ringelmann Number 2 (40 percent opacity) is permissible for not more than two minutes in any one hour.
 - 2. Particulate Matter - 0.3 pounds per million Btu of heat input of carbonaceous fuel plus 0.1 pounds per million Btu heat input of fossil fuel.

- (2) New Emissions Units.
 - (a) Burners of capacity less than 30 million Btu per hour total heat input - Ringelmann Number 1 (20 percent opacity) except that a density of Ringelmann Number 2 (40 percent opacity) is permissible for not more than two minutes in any one hour.
 - (b) Burners of capacity equal to or greater than 30 million Btu per hour total heat input.
 - 1. Visible Emissions - Number 1.5 on the Ringelmann Chart (30 percent opacity) except that a density of Ringelmann Number 2 (40 percent opacity) is permissible for not more than two minutes in any one hour.
 - 2. Particulate Matter - 0.2 pounds per million Btu of heat input of carbonaceous fuel plus 0.1 pounds per million Btu heat input of fossil fuel.

- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) The test method for visible emissions shall be DEP Method 9, incorporated in Chapter 62-297, F.A.C.
 - (b) The test method for particulate emissions shall be EPA Method 5, incorporated and adopted by reference in Chapter 62-297, F.A.C.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.600(10); Formerly 17-296.410; Amended 11-23-94, 1-1-96.

62-296.410

Date Submitted	Date Approved	Federal
----------------	---------------	---------

	to EPA	by EPA	Register
Original Reg	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	06/16/1999	64 FR 32346

62-296.412 Dry Cleaning Facilities.

- (1) All new and existing perchloroethylene dry cleaning facilities are subject to the requirements (including compliance deadlines) of the national emission standard for perchloroethylene dry cleaning facilities at 40 CFR Part 63, Subpart M, adopted and incorporated by reference in Rule 62-204.800(9), F.A.C. Until compliance is achieved with the requirements of 40 CFR Part 63, Subpart M, existing (as of December 9, 1991) perchloroethylene dry cleaning facilities with a solvent consumption of 1,475 gallons per year or more must also comply with the requirements of Rule 62-296.412(2), F.A.C. The requirements of Rule 62-296.412(2), F.A.C., shall not apply to any perchloroethylene dry cleaning facility after it has achieved compliance with the requirements of 40 CFR Part 63, Subpart M.
- (2) The owner or operator of any existing perchloroethylene dry cleaning facility as specified in Rule 62-296.412(1), F.A.C., with total rated dryer capacity of 10 pounds of articles or greater, shall:
 - (a) Vent the entire dryer exhaust through a carbon adsorption system or refrigerated condensation unit which meets the following conditions:
 1. The dryer/condenser system must be closed to the atmosphere at all times except when articles are being loaded or unloaded through the door of the machine; and
 2. The dryer/condenser system must not vent to the atmosphere until the air-vapor stream temperature on the outlet side of the refrigerated condenser is equal to or less than 45 degrees Fahrenheit.
 - (b) Emit no more than 100 parts per million by volume of organic compounds from the dryer control device before dilution;
 - (c) Cook or treat all diatomaceous earth filters so that the residue contains 55 pounds or less of organic compounds per 220 pounds of wet waste material;
 - (d) Reduce the organic compounds from all solvent stills to 132 pounds or less per 220 pounds of wet waste material;
 - (e) Drain all filtration cartridges in the filter housing for at least 24 hours before discarding the cartridge; or dry all drained cartridges without emitting organic compounds to the atmosphere; and
 - (f) Repair all perceptible leaks of organic compounds within three working days or, if repair parts are necessary, order such parts within three working days.
 - (g) Keep monthly records of solvent consumption.
- (3) New or existing (as of October 1, 1986) perchloroethylene dry cleaning facilities, located outside of ozone nonattainment or air quality maintenance areas as defined in Chapter 62-204, F.A.C., and their respective metropolitan statistical areas, with total rated dryer capacity equal to or greater than 10 pounds of articles shall be exempt from the requirements of Rule 62-296.412(2), F.A.C., if the owner or operator demonstrates to the Department that the solvent mileage (pounds of articles cleansed per drum of solvent consumed) is equal to or greater than 20,000 or 15,000 pounds of articles cleansed per 52-gallon drum of perchloroethylene consumed for new or existing facilities, respectively. Such facilities are not exempt from the requirements of the national emission standard for perchloroethylene dry cleaning facilities promulgated in 40 CFR

- Part 63 and adopted by reference in Rule 62-204.800(9), F.A.C.
- (4) Petroleum solvent dry cleaning facilities, located in areas designated as air quality maintenance areas for ozone under Rule 62-204.340, F.A.C., (including the respective metropolitan statistical areas) and all such facilities located in ozone attainment areas, with solvent consumption equal to or greater than 9,750 and 15,000 gallons per year, respectively, shall comply with the following:
- (a) Each affected petroleum solvent dry cleaning dryer that is installed at a petroleum dry cleaning plant shall be a solvent recovery dryer. The solvent recovery dryer(s) shall be properly installed, operated, and maintained.
 - (b) Each affected petroleum solvent filter that is installed at a petroleum dry cleaning plant shall be a cartridge filter. Cartridge filters shall be drained in their sealed housings for at least eight hours prior to their removal.
 - (c) Each owner or operator of an affected petroleum solvent dryer shall include leak inspection and leak repair cycle information in the operating manual and on a clearly visible label posted on each affected facility. Such information should state: "To protect against fire hazards, loss of valuable solvents and emissions of solvent to the atmosphere, periodic inspection of this equipment for evidence of leaks and prompt repair of any leaks is required. The equipment must be inspected every 15 days and all vapor or liquid leaks be repaired within the subsequent 15 day period."
 - (d) Keep monthly records of solvent consumption.
- (5) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
- (a) Leak Detection. Liquid leakage shall be detected by visual inspection of the sources identified in p. 6-3 of EPA 450/2-78-050, incorporated and adopted by reference in Chapter 62-297, F.A.C.
 - (b) The concentration of organic compounds in the filter residue, per Rule 62-296.412(1)(c), F.A.C., shall be determined using ASTM 322-67, 1972.
 - (c) The mass reduction of organic compounds from solvent stills shall be determined using EPA Method 21, incorporated and adopted by reference in Chapter 62-297, F.A.C.
 - (d) The concentration of organic compounds in the exhaust vent of single bed carbon adsorbers shall be determined per the equipment specifications in "RACT Compliance for Carbon Adsorbers," Task No. 119, or stack test per Attachment 3 of EPA 450/2-78-041, incorporated and adopted by reference in Chapter 62-297, F.A.C.
 - (e) The concentration of organic compounds in the exhaust vent of multiple bed carbon adsorbers and others shall be determined using the equipment specifications per the manufacturer's specifications, or stack testing per Attachment 3 of EPA 450/2-78-041, incorporated and adopted by reference in Chapter 62-297, F.A.C.
 - (f) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.600(12); Formerly 17-296.412; Amended 11-23-94, 4-18-95, 1-1-96, 3-

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	6/16/1999	64 FR 32346
2 nd Revision	4/24/1995	4/25/1996	61 FR 18259
3 rd Revision	4/15/1996	6/16/1999	64 FR 32346
4 th Revision	7/22/1996	1/16/2003	68 FR 2204
5 th Revision	3/11/2010	10/6/2017	82 FR 46682

62-296.414 Concrete Batching Plants.

The following requirements apply to emissions units producing concrete and concrete products by batching or mixing cement and other materials. This rule also applies to facilities processing cement and other materials for the purposes of producing concrete, and to equipment used to mix cement and soil for onsite soil augmentation or stabilization.

- (1) Stack emissions. Emissions from silos, weigh hoppers (batchers), and other enclosed storage and conveying equipment shall be controlled to the extent necessary to limit visible emissions to 5 percent opacity.
- (2) Unconfined Emissions. The owner or operator shall take reasonable precautions to control unconfined emissions from hoppers, storage and conveying equipment, conveyor drop points, truck loading and unloading, roads, parking areas, stockpiles, and yards as required by paragraph 62-296.320(4)(c), F.A.C. For concrete batching plants the following shall constitute reasonable precautions:
 - (a) Management of roads, parking areas, stockpiles, and yards, which shall include one or more of the following:
 1. Paving and maintenance of roads, parking areas, and yards.
 2. Application of water or environmentally safe dust-suppressant chemicals when necessary to control emissions
 3. Removal of particulate matter from roads and other paved areas under control of the owner or operator to mitigate re-entrainment, and from building or work areas to reduce airborne particulate matter.
 4. Reduction of stockpile height or installation of wind breaks to mitigate wind entrainment of particulate matter from stock piles.
 - (b) Use of spray bar, chute, or partial enclosure to mitigate emissions at the drop point to the truck.
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this subsection shall comply with the following requirements.
 - (a) The reference test method for visible emissions shall be EPA Method 9, as described at 40 CFR, Part 60, Appendix A-4, adopted and incorporated by reference at Rule 62-204.800, F.A.C.
 - (b) Test procedures shall conform to the procedures specified in Rule 62-297.310, F.A.C. All test results shall be reported to the Department in accordance with the provisions of Rule 62-297.310, F.A.C.
 - (c) Visible emissions tests of silo dust collector exhaust points shall be conducted while loading the silo at a rate that is representative of the normal silo loading rate. The minimum loading rate shall be 25 tons per hour unless such rate is unachievable in practice. If emissions from the weigh hopper (batcher) operation are also controlled by the silo dust collector, the batching operation shall be in operation during the visible emissions test. The batching rate during the emissions test shall be representative of the normal batching rate and duration. Each test report shall state the actual silo loading rate during emissions testing and, if applicable, whether or not batching occurred during emissions testing.
 - (d) If emissions from the weigh hopper (batcher) operation are controlled by a dust collector which is separate from the silo dust collector, visible emissions tests of

the weigh hopper (batcher) dust collector exhaust point shall be conducted while batching at a rate that is representative of the normal batching rate and duration. Each test report shall state the actual batching rate during emissions testing.

- (4) Frequency of Testing.
- (a) The owner or operator of any concrete batching plant using an air general permit shall have a visible emissions test conducted for stack emissions referenced in subsection 62-296.414(1), F.A.C., no later than sixty (60) days after commencing initial operation, and annually thereafter.
 - (b) The owner or operator of any concrete batching plant operating under the authority of an air construction permit or air operation permit shall have a visible emissions test conducted for stack emissions referenced in subsection 62-296.414(1), F.A.C., prior to submitting the application for an initial air operation permit, and annually thereafter.

History: Formerly 17-2.600(14); Formerly 17-296.414; Amended 11-23-94, 1-1-96, 11-13-97, 1-10-07, 7-10-14, 11-5-20.

62-296.414

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	1/11/1993	10/20/94	59 FR 52916
1 st Revision	12/21/1994	6/16/1999	64 FR 32346
2 nd Revision	4/15/1996	6/16/1999	64 FR 32346
3 rd Revision	7/1/2011	10/6/2017	82 FR 46682
4 th Revision	4/01/2022	12/6/2023	88 FR 76137

62-296.415 Soil Thermal Treatment Facilities.

This rule prescribes air pollution control requirements for soil thermal treatment facilities. Soil thermal treatment facilities are only authorized to treat petroleum contaminated soil as defined in Chapter 62-775, F.A.C., Soil Thermal Treatment Facilities. The following requirements apply to soil thermal treatment facilities.

(1) Volatile Organic Compounds (VOC).

- (a) A soil thermal treatment facility shall be designed and operated to expose the organic vapors from the soil during thermal treatment to one of the following combinations:

Minimum Temperature (Fahrenheit)		Minimum Time (seconds)
1,500	and	1.0
1,600	and	0.5
1,800	and	0.3

The minimum temperature shall be determined by a continuous temperature monitor pursuant to the applicable continuous emissions monitoring requirements of Rule 62-296.415(6), F.A.C. When soil is being treated, the minimum temperature shall be met or exceeded at all times except for 4 minutes in any 60 minute period, provided that the temperature does not fall below 100 degrees Fahrenheit of the required minimum temperature for the corresponding residence time. The minimum residence time shall be met or exceeded at all times while soil is being treated.

- (b) The average carbon monoxide (CO) emissions shall not exceed 100 parts per million (ppm) by volume, dry basis, during all 60-consecutive-minute periods of plant operation. The average CO emissions is the arithmetic mean of all CO concentration measurements during any consecutive 60 minutes of plant operation that were recorded by the continuous emissions monitor required pursuant to subsection 62-296.415(6) , F.A.C.
- (c) A soil thermal treatment facility shall continually monitor the temperature and carbon monoxide content of the flue gases leaving the high temperature zone pursuant to the applicable continuous emissions monitoring requirements of Rule 62-296.415(6), F.A.C. Temperature and carbon monoxide monitors shall be co-located unless otherwise approved by the Department.
- (d) Soil thermal treatment facilities must possess an air permit authorizing the processing of soils containing polychlorinated biphenyls (PCBs), if soil contaminated with PCBs is to be thermally treated.
- (2) Visible Emissions. Visible emissions (VE) from a stack shall not exceed 5% opacity as determined by the test method specified in Rule 62-296.415(5), F.A.C. when thermally treating soil.
- (3) Particulate Matter Emissions. The particulate matter emissions shall not exceed 0.04 grains per dry standard cubic foot (gr/dscf) as determined by the test method specified in Rule 62-296.415(5), F.A.C.

(4) Unconfined Emissions.

A soil thermal treatment facility is subject to Rule 62-296.320, F.A.C., Unconfined Emissions of Particulate Matter. As a minimum, before and after thermal soil treatment is accomplished, unconfined emissions of particulate matter from the soil shall be controlled by application of water or containment.

(5) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.

(a) The test method for visible emissions shall be EPA Method 9, as described at 40 C.F.R. Part 60, Appendix A-4, adopted and incorporated by reference at Rule 62-204.800, F.A.C.

(b) The test method for particulate emissions shall be EPA Method 5, as described at 40 C.F.R. Part 60, Appendix A-3, adopted and incorporated by reference Rule 62-204.800, F.A.C. The minimum sample volume shall be 30 dry standard cubic feet.

(c) The test method for carbon monoxide shall be EPA Method 10, as described at 40 C.F.R. Part 60, Appendix A-4, adopted and incorporated by reference at Rule 62-204.800, F.A.C.

(d) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

(6) Continuous Emissions Monitoring Requirements. Any facility subject to this rule shall be equipped with instruments to continuously monitor and record the temperature and the carbon monoxide concentration of the flue gases leaving the high temperature zone, but before any dilution air is mixed with the flue gases. The temperature monitor shall be certified by the manufacturer to be accurate to within 1% of the temperature being measured. The temperature monitoring system shall be calibrated at least annually by the procedure recommended by the manufacturer. The calibration shall be at a minimum of three temperatures and over a range from 10% below to 10% above the designed flue gas hot zone temperature of the soil thermal treatment facility. Calibration records shall be kept for a minimum of three years. The carbon monoxide monitor shall be certified by the manufacturer to be accurate to within 10% of the carbon monoxide concentration by volume, mean value, or 5% of the applicable standard of 100 ppm, whichever is greater, as determined by EPA Test Method 10 as described at 40 CFR Part 60, Appendix A-4, adopted and incorporated by reference in Rule 62-204.800, F.A.C. The carbon monoxide continuous emission monitoring device shall be certified, calibrated, and operated according to Performance Specification 4 of 40 CFR Part 60, Appendix B, adopted and incorporated by reference in Rule 62-204.800, F.A.C., excluding Section 5.2, Calibration Drift Test Period, of Performance Specification 2.

History: New 11-17-92, Formerly 17-296.415; Amended 11-23-94, 1-1-96, 3-13-96, 7-10-14, 11-5-20.

62-296.415

Date Submitted to EPA	Date Approved by EPA	Federal Register
--------------------------	-------------------------	---------------------

62-296-49

Original Reg	11/23/1992	10/20/1994	59 FR 52916
1st Revision	12/21/1994	6/16/1999	64 FR 32346
2 nd Revision	4/15/1996	6/16/1999	64 FR 32346
3 rd Revision	4/01/2022	12/6/2023	88 FR 76139

62-296.418 Bulk Gasoline Plants.

(1) The owner or operator of a bulk gasoline plant that has begun operation prior to August 1, 2007, is located in Broward, Duval, Hillsborough, Miami-Dade, Orange, Palm Beach, or Pinellas County, and has an average annual daily throughput of more than 2,000 gallons (7,570 liters) shall comply with the following requirements.

(a) Gasoline shall not be loaded into a stationary storage tank at the bulk gasoline plant unless the storage tank is equipped for submerged filling, and such equipment is used as designed.

(b) Gasoline shall not be loaded into a gasoline cargo tank at the bulk gasoline plant unless the gasoline cargo tank is equipped for submerged filling, and such equipment is used as designed.

(2) The owner or operator of a bulk gasoline plant that begins operation on or after August 1, 2007, at any location in the state and with any throughput rate shall comply with the following requirements.

(a) Gasoline shall not be loaded into a stationary storage tank at the bulk gasoline plant unless the storage tank is equipped for submerged filling, and such equipment is used as designed.

(b) Gasoline shall not be loaded into a gasoline cargo tank at the bulk gasoline plant unless:

1. The gasoline cargo tank is equipped for submerged filling, and such equipment is used as designed;

2. The loading rack is equipped with a vapor collection and control system designed to minimize emissions of vapors displaced from the gasoline cargo tank during product loading; and

3. The loading rack vapor collection and control system is designed and operated to prevent any vapors collected at the loading rack from passing to another loading rack.

Rulemaking Authority 403.061 FS. Law Implemented 403.031, 403.061, 403.087 FS. History—New 5-9-07, Amended 3-11-10, 8-14-19

62-296.418

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	5/31/2007	6/1/2009	74 FR 26103
1 st Revision	7/01/11	10/6/2017	82 FR 46682
2 nd Revision	04/01/2022	12/6/2023	88 FR 76139

62-296.500 Reasonably Available Control Technology (RACT) Volatile Organic Compounds (VOC) and Nitrogen Oxides (NOx) Emitting Facilities.

- (1) Applicability.
 - (a) The specific emission limiting standards and other requirements of Rules 62-296.500 through 62-296.516, F.A.C., shall apply to each stationary VOC-emitting stationary emissions unit in Broward, Duval, Hillsborough, Miami-Dade, Orange, Palm Beach, or Pinellas County, except for any emission unit which has been or would be subject to Prevention of Significant Deterioration review or Preconstruction Review for Nonattainment Areas, pursuant to 40 CFR 52.21 as adopted and incorporated by reference in Rule 62-204.800, F.A.C., or Rule 17-2.17 (repealed), 17-2.500 (transferred), 17-2.510 (transferred), Rule 62-212.400 or 62-212.500, F.A.C.
 - (b) In addition to the applicable requirements of this rule the specific emission limiting standards and other requirements of Rule 62-296.570, F.A.C., shall apply in Broward, Dade, and Palm Beach Counties to major VOC-emitting facilities not regulated in whole under Rules 62-296.501 through 62-296.516, F.A.C., and major NOx-emitting facilities, except those new and modified major VOC- and NOx-emitting facilities which have been or would be subject to Prevention of Significant Deterioration review or Preconstruction Review for Nonattainment Areas, review pursuant to 40 CFR 52.21 , as adopted and incorporated by reference in Rule 62-204.800, F.A.C., or Rule 17-2.17 (repealed), 17-2.500 (transferred), 17-2.510 (transferred), Rule 62-212.400 or 62-212.500, F.A.C.
- (2) Permit, Recordkeeping, and Compliance Reporting Requirements.
 - (a) Permits - Special Considerations.
 1. Permits to construct or operate are required for all emission units subject to a specific emission limiting standard or other requirement of Rules 62-296.501 through 62-296.516, F.A.C., or Rule 62-296.570, F.A.C., except those emission units subject to Rule 62-296.512, F.A.C., Cutback Asphalt , or emissions units operating under an Air General Permit pursuant to Rule 62-210.310, F.A.C.
 2. Permits to operate shall contain conditions relating to operation, emission levels, control equipment, use of low solvent technology or other resource characteristics necessary to insure compliance with the applicable rules.
 - (b) Recordkeeping.
 1. An owner or operator of a stationary emission unit using adhesives, coating, solvents, and/or graphic arts materials and subject to a specific emission limiting standard or other requirement of Rules 62-296.501 through 62-296.516, F.A.C., or Rule 62-296.570, F.A.C., shall maintain daily records of operations for the most recent two year period. The records shall be made available to the local, state, or federal air pollution agency upon request. The records shall include, but not be limited to the following:
 - a. The rule number applicable to the operation for which the records are being maintained.

- b. The application method and substrate type (metal, plastic, paper, etc.).
 - c. The amount and type of adhesive, coatings (including catalyst and reducer for multicomponent coatings), solvent, and/or graphic arts material used at each point of application, including exempt compounds.
 - d. The VOC content as applied in each adhesive coating, solvent, and/or graphic arts material.
 - e. The date for each application of adhesive coating, solvent, and/or graphic arts material.
 - f. The amount of surface preparation, clean-up, wash-up of solvent including exempt compounds) used and the VOC content of each.
 - g. Oven temperature (where applicable).
2. VOC content shall be calculated using a percent solids basis (less water and exempt solvents) for adhesives, coating, and inks, using EPA Reference Method 24.
 3. VOC content and density of rotogravure publication inks shall be determined by EPA Reference Method 24A.
 4. The Department may accept, instead of the coating analysis methods required under Rules 62-296.500(2)(b)2. and 3., F.A.C., a certification by the coating manufacturer of the composition of the coating if it is supported by actual batch formulation records. The manufacturer's certification shall be consistent with EPA's document number 450/3-84-019, titled, "Procedures for Certifying Quantity of Volatile Organic Compounds Emitted by Paint, Ink, and other Coatings"" effective December 1984, herein adopted and incorporated by reference (<http://www.flrules.org/Gateway/reference.asp?No=Ref-10762>).
 5. When an emissions unit utilizes add-on controls to achieve compliance, documentation will be necessary to assure proper operation. Examples of some controls and related information are:
 - a. Thermal incinerator - combustion temperature, inlet and outlet VOC concentration from emission tests, how and when these concentrations were determined, destruction or removal efficiency, and manufacturer data.
 - b. Catalytic incinerator - exhaust gas temperature, change in temperature across catalyst bed, date of last change of catalyst bed, inlet and outlet VOC concentration from emission tests, how and when these concentrations were determined, destruction or removal efficiency, and manufacturer data.
 - c. Condenser - inlet temperature of cooling medium, outlet temperature of cooling medium, inlet and outlet VOC concentration from emission tests, how and when these concentrations were determined, removal efficiency, and manufacturer data.

- (c) Reporting. Annually, in accordance with a schedule and reporting format provided by the Department, the owner or operator of any emissions unit having a Department air operation permit and subject to a specific emission limitation under Rule 62-296.501 through 62-296.516, F.A.C., shall provide the Department with proof of compliance with such limitation. Compliance with the requirements of Rule 62-296.570, F.A.C., shall be demonstrated in accordance with the provisions of that rule.
- (3) Exceptions.
- (a) Emissions units which in combination with all other emissions units at the facility subject to the same specific emission limitation under Rule 62-296.501 through 62-296.516, F.A.C., emit VOC at rates of not more than 15 pounds (6.8 kilograms) in any one day and not more than 3 pounds (1.4 kilograms) in any one hour.
- (b) Emissions units used exclusively for chemical or physical analysis, or for the determination of product quality and commercial acceptance, provided:
1. The operation of the emissions unit is not an integral part of any production process; and
 2. The emissions from the emissions unit do not exceed 800 pounds (363 kilograms) in any one calendar month.
- (4) Consideration of Exempt Solvents - Compliance calculations for coatings containing solvents exempted under the definition of VOC shall be determined as follows:

Given the mass of VOC and mass of exempt solvent per unit volume of coating, determine the mass of VOC per unit volume of coating less exempt solvent.

Let x = mass of exempt solvent per unit volume of coating
 y = mass of VOC per unit volume of coating
 d = density of exempt solvent
 z = mass of VOC per unit volume of coating less exempt solvent.

Then
 $z = [y / (1 - x/d)]$ or

If more than one solvent is present and the individual volumes and densities are known, use:

$$d = \frac{d_1V_1 + d_2V_2 + \dots + d_nV_n}{V_1 + V_2 + \dots + V_n}$$

where

V = volume of each component solvent

- (5) Compliance may be demonstrated for surface coating and graphic arts facilities on a 24-hour weighted average basis for a single emissions unit point with a single emission limit.
- (6) Specific Emission Limitations. The specific volatile organic compounds emission limiting standards set forth in Rules 62-296.401 through 62-296.416, F.A.C., have been found to represent the application of RACT for each emissions unit category listed in those rules except for those emissions unit categories listed in Rules 62-296.501 through 62-296.516, F.A.C., and Rule 62-296.570, F.A.C. For those emissions unit categories the volatile organic compounds emission standards of Rules 62-296.501 through 62-296.516, F.A.C., and Rule 62-296.570, F.A.C., have been found to represent the application of RACT. Emission limitations for surface coating operations shall be expressed in units of pounds VOC/gallon of solids as applied rather than pounds VOC/gallon of coating (less water and exempt solvents) when crossline averaging or compliance using add-on control equipment such as incineration is involved. The method of calculating pounds VOC/gallon of solids as applied from the pounds VOC/gallon of coating is shown in Table 296.500-1.

TABLE 296.500-1
CALCULATION OF POUNDS VOC/GALLON OF SOLIDS
FROM POUNDS VOC/GALLON OF COATING

These calculations shall be determined as follows:

EXAMPLE CONVERSION

GIVEN: COATING OF 3 POUNDS VOC/GALLON OF COATING (LESS WATER AND EXEMPT SOLVENTS) AND VOC DENSITY OF 7.36 POUNDS VOC/GALLON.

PROBLEM: CONVERT POUNDS VOC/GALLON OF COATING TO POUNDS VOC/GALLON OF SOLIDS.

STEP 1 - WHAT IS THE VOLUME OF VOC IN 1 GALLON OF COATING?

$$\frac{3 \text{ pounds VOC}}{\text{gallons coating}} \times \frac{1 \text{ gallon VOC}}{7.36 \text{ pounds VOC}} = \frac{0.408 \text{ gallon VOC}}{\text{gallon coating}}$$

STEP 2 - WHAT IS THE VOLUME OF SOLIDS IN 1 GALLON COATING?

1 GALLON COATING - VOLUME VOC = VOLUME SOLIDS
1 - 0.408 = 0.592 GALLON SOLIDS

STEP 3 - HOW MANY GALLONS OF COATING DOES IT TAKE TO GET A GALLON OF SOLIDS?
(INVERSE OF STEP 2)

$$\frac{1 \text{ GALLON COATING}}{0.592 \text{ GALLON SOLIDS}} = \frac{1.689 \text{ GALLON COATING}}{\text{GALLON SOLIDS}}$$

STEP 4 - CONVERT 3 POUNDS VOC/GALLON OF COATING TO POUNDS VOC/GALLON OF SOLIDS

$$\frac{3 \text{ POUNDS VOC}}{\text{GALLON COATING}} \times \frac{1.689 \text{ GALLON COATING}}{\text{GALLON SOLIDS}} = \frac{5.07 \text{ POUNDS VOC}}{\text{GALLON SOLIDS}}$$

ANSWER: 3 POUNDS VOC/GALLON OF COATING (LESS WATER AND EXEMPT SOLVENTS) = 5.07 POUNDS VOC/GALLON OF SOLIDS

History: Formerly 17-2.650(1)-(1)(f), Amended 2-2-93, 4-17-94; Formerly 17-296.500; Amended 11-23-94, 1-1-96, 3-11-10, 8-14-19.

62-296.500

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	1/08/1993	1/11/1995	60 FR 2688
2 nd Revision	4/25/1994	1/11/1995	60 FR 2688
3 rd Revision	12/21/94	6/16/1999	64 FR 32346
4 th Revision	3/11/2010	10/6/2017	82 FR 46682
5 th Revision	04/01/2023	12/6/2023	88 FR 76139

62-296.501 Can Coating.

- (1) Applicability. The emission limiting standards set forth in Rule 62-296.501, F.A.C., will apply to:
 - (a) Coating applicators and ovens of sheet, can, or end coating lines involved in sheet basecoat (exterior and interior) and overvarnish;
 - (b) Two-piece can exterior (basecoat and overvarnish);
 - (c) Two- and three-piece can interior body spray;
 - (d) Two-piece can exterior end (spray or roll coat);
 - (e) Three-piece can side-seam and end sealing compound operation.
- (2) Emission Limiting Standards. No owner or operator of can coating lines subject to Rule 62-296.501, F.A.C., may cause, allow, or permit the discharge into the atmosphere of any volatile organic compounds in excess of the total discharge that would occur if each coating line complied with the emission limitations contained in Rule 62-296.501(2)(a) through (d), F.A.C. below. Compliance with these limitations for any given day's operation shall be determined by using the method contained in 45 FR 80824. A copy of the above referenced document is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., and may be inspected at the Department's Tallahassee office.
 - (a) 2.8 pounds per gallon of coating (0.34 kilograms per liter), excluding water, delivered to the coating applicator of:
 1. Sheet basecoat (exterior and interior) and overvarnish, or
 2. Two-piece can exterior (basecoat and overvarnish) operation.
 - (b) 4.2 pounds per gallon of coating (0.50 kilograms per liter), excluding water delivered to the coating applicator from two- and three-piece can interior body spray and two-piece can exterior end (spray or roll coat) operations.
 - (c) 5.5 pounds per gallon of coating (0.66 kilograms per liter), excluding water, delivered to the coating applicator from three-piece can side-seam spray operations.
 - (d) 3.7 pounds per gallon of coating (0.44 kilograms per liter) excluding water delivered to the coating applicator from can side-seams and end sealing compound operations.
- (3) Control Technology. The emission limits in Rule 62-296.501(2), F.A.C., shall be achieved by:
 - (a) The application of low solvent content coating technology; or,
 - (b) Incineration, provided that 90 percent of the volatile organic compounds (VOC measured as total combustible carbon) which enter the incinerator are oxidized to carbon dioxide and water.
- (4) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) Low Solvent Technology. The test method for volatile organic compounds shall be EPA Method 24 as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or EPA 450/3-84-019, Procedures for Certifying Quantity of Volatile Organic Compounds Emitted by Paint, Ink, and Other Coatings

<http://www.flrules.org/Gateway/reference.asp?No=Ref-04298>), hereby adopted and incorporated by reference or EPA 450/3-84-019,

(b) Add-on Control Device.

1. Destructive. The test method for volatile organic compounds shall be EPA Method 25 as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or Attachment 3 of EPA 450/2-78-041, Alternate Test Method for Direct Measurement of Total Gaseous Organic Compounds Using a Flame Ionization Analyzer adopted and incorporated by reference in Chapter 62-297, F.A.C.
2. Non-destructive. The test method for volatile organic compounds shall be EPA VOC Capture Efficiency Test Procedures as described at Rule 62-297.450, F.A.C. The sampling time for each capture efficiency test run shall be at least 8 hours, unless otherwise approved by the Department pursuant to Rule 62-297.620, F.A.C.

(c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)1., 17-296.501; Amended 11-23-94, 1-1-96, 7-10-14

62-296.501

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/194 & 04/15/96	6/16/1999	64 FR 32346
2 nd Revision	04/01/22	12/6/2023	88 FR 76139

62-296.502 Coil Coating.

- (1) Applicability. The emission limiting standard set forth in Rule 62-296.502, F.A.C., will apply to coating applicators, coating lines with or without ovens, and quench areas of coil coating lines involved in prime and topcoat or single-coat operations.
- (2) Emission Limiting Standard. No owner or operator of a coil coating line subject to Rule 62-296.502, F.A.C., may cause, allow, or permit the discharge into the atmosphere of any volatile organic compounds in excess of 2.6 pounds per gallon of coating (0.31 kilograms per liter), excluding water delivered to a coating applicator from prime and topcoat or single-coat operations.
- (3) Control Technology. The emission limit under Rule 62-296.502(2), F.A.C., shall be achieved by:
 - (a) The application of low solvent content coating technology; or
 - (b) Incineration, provided that 90 percent of the volatile organic compounds (VOC measured as a total combustible carbon) which enter the incinerator are oxidized to carbon dioxide and water.
- (4) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) Low Solvent Technology. The test method for volatile organic compounds shall be EPA Method 24 , as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or EPA 450/3-84-019, Procedures for Certifying Quantity of Volatile Organic Compounds Emitted by Paint, Ink, and Other Coatings (<http://www.flrules.org/Gateway/reference.asp?No=Ref-04298>), hereby adopted and incorporated by reference.
 - (b) Add-on Control Device.
 1. Destructive. The test method for volatile organic compounds shall be EPA Method 25 , as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or Attachment 3 of EPA 450/2-78-041, Alternate Test Method for Direct Measurement of Total Gaseous Organic Compounds Using a Flame Ionization Analyzer, adopted and incorporated by reference in Chapter 62-297, F.A.C.
 2. Non-destructive. The test method for volatile organic compounds shall be VOC Capture Efficiency Test Procedures as described at Rule 62-297.450 , F.A.C. The sampling time for each capture efficiency test run shall be at least 8 hours, unless otherwise approved by the Department pursuant to Rule 62-297.620, F.A.C.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)2., 17-296.502; Amended 11-23-94, 1-1-96, 7-10-14.

62-296.502

Date Submitted
to EPA

Date Approved
by EPA

Federal
Register

Recodification	1/11/1993	10/20/94	59 FR 52916
1 st Revision	12/21/1994&04/15/96	6/16/1999	64 FR 32346
2 nd Revision	04/01/22	12/6/2023	88 FR 76139

62-296.503 Paper Coating.

- (1) Applicability. The emission limiting standards set forth in Rule 62-296.503, F.A.C., will apply to roll, knife, or rotogravure coaters and drying ovens of paper coating lines. The following standards shall also apply to saturation operations.
- (2) Emission Limiting Standards. No owner or operator of a paper coating line subject to Rule 62-296.503, F.A.C., may cause, allow, or permit the discharge into the atmosphere of any volatile organic compounds in excess of 2.9 pounds per gallon of coating (0.35 kilograms per liter), excluding water, delivered to the coating applicator from a paper coating line.
- (3) Control Technology. The emission limit under Rule 62-296.503(2), F.A.C.; shall be achieved by:
 - (a) The application of low solvent content coating technology; or
 - (b) Incineration, provided that 90 percent of the volatile organic compounds (VOC measured as total combustible carbon) which enter the incinerator are oxidized to carbon dioxide and water.
- (4) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) Low Solvent Technology. The test method for volatile organic compounds shall be EPA Method 24, as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or EPA 450/3-84-019, Procedures for Certifying Quantity of Volatile Organic Compounds Emitted by Paint, Ink, and Other Coatings (<http://www.flrules.org/Gateway/reference.asp?No=Ref-04298>), hereby adopted and incorporated by reference. or EPA 450/3-84-019,
 - (b) Add-on Control Device.
 1. Destructive. The test method for volatile organic compounds shall be EPA Method 25, as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or Attachment 3 of EPA 450/ 2-78-041, Alternate Test Method for Direct Measurement of Total Gaseous Organic Compounds Using a Flame Ionization Analyzer, adopted and incorporated by reference in Chapter 62-297, F.A.C. or Attachment 3 of EPA 450/2-78-041, incorporated and adopted by reference in Chapter 62-297, F.A.C.
 2. Non-destructive. The test method for volatile organic compounds shall be VOC Capture Efficiency Test Procedures as described at Rule 62297.450 F.A.C. The sampling time for each capture efficiency test run shall be at least 8 hours, unless otherwise approved by the Department pursuant to Rule 62-297.620, F.A.C.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)3.,17-296.503; Amended 11-23-94, 1-1-96, 7/10/14

62-296.503

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994 & 04/15/96	6/16/1999	64 FR 32346
2 nd Revision	04/01/2022	12/6/2023	88 FR 76139

62-296.504 Fabric and Vinyl Coating.

- (1) Applicability. The emission limiting standards set forth in Rule 62-296.504, F.A.C., will apply to roll, knife, or rotogravure coaters and drying ovens of fabric and vinyl coating lines. The following standards shall also apply to saturation operations.
- (2) Emission Limiting Standards.
 - (a) No owner or operator of a fabric coating line or a vinyl coating line subject to Rule 62-296.504, F.A.C., may cause, allow, or permit the discharge into the atmosphere of any volatile organic compounds in excess of:
 1. 2.9 pounds per gallon of coating (0.35 kilograms per liter), excluding water, delivered to a coating applicator from a fabric coating line.
 2. 3.8 pounds per gallon of coating (0.46 kilograms per liter), excluding water, delivered to a coating applicator from a vinyl coating line.
- (3) Control Technology. The emission limits under Rule 62-296.504(2), F.A.C., shall be achieved by:
 - (a) The application of low solvent content coating technology; or
 - (b) Incineration, provided that 90 percent of the volatile organic compounds (VOC measured as total combustible carbon) which enter the incinerator are oxidized to carbon dioxide and water.
- (4) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) Low Solvent Technology. The test method for volatile organic compounds shall be EPA Method 24, as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or EPA 450/3-84-019, Procedures for Certifying Quantity of Volatile Organic Compounds Emitted by Paint, Ink, and Other Coatings (<http://www.flrules.org/Gateway/reference.asp?No=Ref-04298>), hereby adopted and incorporated by reference.
 - (b) Add-on Control Device.
 1. Destructive. The test method for volatile organic compounds shall be EPA Method 25 as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or Attachment 3 of EPA 450/2-78-041, Alternate Test Method for Direct Measurement of Total Gaseous Organic Compounds Using a Flame Ionization Analyzer, adopted and incorporated by reference in Chapter 62-297, F.A.C.
 2. Non-destructive. The test method for volatile organic compounds shall be VOC Capture Efficiency Test Procedures as described at Rule 62-297.450, F.A.C. The sampling time for each capture efficiency test run shall be at least 8 hours, unless otherwise approved by the Department pursuant to Rule 62-297.620, F.A.C.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)4. 17-296.504; Amended 11-23-94, 1-1-96, 7/10/14

62-296.504

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994&04/15/96	06/16/1999	64 FR 32346
2 nd Revision	04/01/22	12/6/2023	88 FR 76139

62-296.505 Metal Furniture Coating.

- (1) **Applicability.** The emission limiting standards set forth in Rule 62-296.505, F.A.C., will apply to the application areas, flash-off areas, and ovens of metal furniture coating lines involved in prime and topcoat or single-coating operations.
- (2) **Emissions Limiting Standards.** No owner or operator of a metal furniture coating line subject to Rule 62-296.505, F.A.C., may cause, allow, or permit the discharge into the atmosphere of any volatile organic compounds in excess of 3.0 pounds per gallon of coating (0.36 kilograms per liter), excluding water, delivered to the coating applicator from prime and topcoat or single-coat operations. Credit for transfer efficiency above the baseline of 60% for spray coating operations can be granted according to the following formula:

$$X = \frac{(TE)(Z)(Y)}{Y + (TE)(Z)}$$

Where

- X = allowable maximum VOC content (kg VOC/liter of coating less water)
- Y = density of the VOC in the maximum VOC content coating (kg/liter)
- Z = applicable emission limit (kg VOC/liter of coating solids deposited)
- TE = transfer efficiency

An EPA and state approved test method for determination of transfer efficiency above the baseline is required.

- (3) **Control Technology.** The emission limit under Rule 62-296.505(2), F.A.C., shall be achieved by:
 - (a) The application of low solvent content coating technology; or
 - (b) Incineration, provided that 90 percent of the volatile organic compounds (VOC measured as total combustible carbon) which enter the incinerator are oxidized to carbon dioxide and water.
- (4) **Test Methods and Procedures.** All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) **Low Solvent Technology.** The test method for volatile organic compounds shall be EPA Method 24, as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or EPA 450/3-84-019, Procedures for Certifying Quantity of Volatile Organic Compounds Emitted by Paint, Ink, and Other Coatings (<http://www.flrules.org/Gateway/reference.asp?No=Ref-04298>), hereby adopted and incorporated by reference.
 - (b) **Add-on Control Device.**
 1. **Destructive.** The test method for volatile organic compounds shall be EPA Method 25, as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or Attachment 3 of EPA 450/2-78-041, Alternate Test Method for Direct Measurement of Total Gaseous Organic Compounds Using a Flame Ionization Analyzer, adopted and incorporated by reference in Chapter

62-297, F.A.C.

2. Non-destructive. The test method for volatile organic compounds shall be EPA VOC Capture Efficiency Test Procedures as described at Rule 62-297.450, F.A.C. The sampling time for each capture efficiency test run shall be at least 8 hours, unless otherwise approved by the Department pursuant to Rule 62-297.620, F.A.C.

- (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)5.17-296.505; Amended 11-23-94, 1-1-96, 7/10/14

62-296.505

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994&04/15/96	06/16/1999	64 FR 32346
2 nd Revision	04/01/22	12/6/2023	88 FR 76139

62-296.506 Surface Coating of Large Appliances.

(1) Applicability.

- (a) The emission limiting standards set forth in Rule 62-296.506, F.A.C., shall apply to application areas, flash-off areas, and ovens of large appliance coating lines involved in prime, single, or topcoat coating operations. Credit for transfer efficiency above the baseline of 60% for spray coating operations can be granted according to the following formula:

$$X = \frac{(TE) (Z) (Y)}{Y + (TE) (Z)}$$

Where

- X = allowable maximum VOC content (kg VOC/liter of coating less water)
Y = density of the VOC in the maximum VOC content coating (kg/liter)
Z = applicable emission limit (kg VOC/liter of coating solids deposited)
TE = transfer efficiency

An EPA and state approved test method for determination of transfer efficiency above the baseline is required.

- (b) Rule 62-296.506, F.A.C., does not apply to the use of quick-drying lacquers for repair of scratches and nicks that occur during assembly, provided that the volume of coating does not exceed one quart (0.95 liters) in any one 8-hour period.
- (2) Emission Limiting Standard. No owner or operator of a large appliance coating line subject to Rule 62-296.506, F.A.C., may cause, allow or permit the discharge into the atmosphere of any volatile organic compounds in excess of 0.34 kilograms per liter of coating (2.8 pounds per gallon), excluding water, delivered to the coating applicator from prime, single, or topcoat coating operations.
- (3) Control Technology. The emission limit under Rule 62-296.506(2), F.A.C., shall be achieved by:
- (a) The application of low solvent content coating technology; or
- (b) Incineration, provided that 90 percent of the volatile organic compounds (VOC measured as total combustible carbon) which enter the incinerator are oxidized to carbon dioxide and water.
- (4) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
- (a) Low Solvent Technology. The test method for volatile organic compounds shall be EPA Method 24, as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or EPA 450/3-84-019, Procedures for Certifying Quantity of Volatile Organic Compounds Emitted by Paint, Ink, and Other Coatings (<http://www.flrules.org/Gateway/reference.asp?No=Ref-04298>), hereby adopted and incorporated by reference.
- (b) Add-on Control Device.
1. Destructive. The test method for volatile organic compounds shall be

EPA Method 25 , as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or Attachment 3 of EPA 450/2-78-041, Alternate Test Method for Direct Measurement of Total Gaseous Organic Compounds Using a Flame Ionization Analyzer, adopted and incorporated by reference in Chapter 62-297, F.A.C.

2. Non-destructive. The test method for volatile organic compounds shall be EPA VOC Capture Efficiency Test Procedures as described at Rule 62-297.450 , F.A.C. The sampling time for each capture efficiency test run shall be at least 8 hours, unless otherwise approved by the Department pursuant to Rule 62-297.620, F.A.C.
- (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)6.,17-296.506; Amended 11-23-94, 1-1-96,7/10/14

62-296.506

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994 & 04/15/96	06/16/1999	64 FR 32346
2 nd Revision	04/01/2022	12/6/2023	88 FR 76139

62-296.507 Magnet Wire Coating.

- (1) Applicability. The emission limiting standard set forth in Rule 62-296.507, F.A.C., shall apply to the ovens of magnet wire coating operations.
- (2) Emission Limiting Standards. No owner or operator of a magnet wire coating oven subject to Rule 62-296.507, F.A.C., may cause, allow, or permit the discharge into the atmosphere of any volatile organic compounds in excess of 1.7 pounds per gallon of coating (0.20 kilograms per liter), excluding water, delivered to the coating applicator from magnet wire coating operations.
- (3) Control Technology. The emission limit under Rule 62-296.507(2), F.A.C., shall be achieved by:
 - (a) The application of low solvent content coating technology; or
 - (b) Incineration, provided that 90 percent of the volatile organic compounds (VOC measured as total combustible carbon) which enter the incinerator are oxidized to carbon dioxide and water.
- (4) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) Low Solvent Technology. The test method for volatile organic compounds shall be EPA Method 24 , as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or EPA 450/3-84-019, Procedures for Certifying Quantity of Volatile Organic Compounds Emitted by Paint, Ink, and Other Coatings (<http://www.flrules.org/Gateway/reference.asp?No=Ref-04298>), hereby adopted and incorporated by reference.
 - (b) Add-on Control Device.
 1. Destructive. The test method for volatile organic compounds shall be EPA Method 25 , as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or Attachment 3 of EPA 450/2-78-041, Alternate Test Method for Direct Measurement of Total Gaseous Organic Compounds Using a Flame Ionization Analyzer, adopted and incorporated by reference in Chapter 62-297, F.A.C.
 2. Non-destructive. The test method for volatile organic compounds shall be VOC Capture Efficiency Test Procedures as described at Rule 62-297.450, F.A.C. The sampling time for each capture efficiency test run shall be at least 8 hours, unless otherwise approved by the Department pursuant to Rule 62-297.620, F.A.C.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)7.,17-296.507; Amended 11-23-94, 1-1-96, 7/10/14

62-296.507

Date Submitted
to EPA

Date Approved
by EPA

Federal
Register

Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994 & 04/15/96	6/16/1999	64 FR 32346
2 nd Revision	04/01/22	12/6/2023	88 FR 76139

62-296.508 Petroleum Liquid Storage.

- (1) Applicability.
 - (a) The control technology set forth in Rule 62-296.508, F.A.C., shall apply to all fixed roof storage vessels with capacities equal to or greater than 42,000 gallons (159,000 liters; nominal design 1,000 barrels (bbls.) containing petroleum liquids whose true vapor pressure is greater than 1.50 psia (10.3 kilopascals) but shall not be used if the petroleum liquid has a true vapor pressure of 11.0 psia (76 kilopascals) or greater under actual storage conditions.
 - (b) Rule 62-296.508, F.A.C., shall not apply to volatile petroleum liquid storage vessels:
 1. Equipped with external floating roofs before the effective date of this rule; or,
 2. Having capacities equal to or less than 420,000 gallons (1,590,000 liters; nominal design 10,000 bbls.) located at oil field production sites and used to store produced oil and condensate prior to lease custody transfer.
- (2) Control Technology. Except as provided under Rule 62-296.508(1)(b), F.A.C., no owner or operator of an affected emissions unit under Rule 62-296.508(1)(a), F.A.C., shall permit the use of such emissions unit unless:
 - (a) The emissions unit has been retrofitted with an internal floating roof equipped with a closure seal, or seals, to close the space between the roof edge and tank wall, or the emissions unit has been retrofitted with an equally effective alternative control; and,
 - (b) The emissions unit is maintained such that there are no visible holes, tears, or other openings in the seal or any seal fabric or materials; and,
 - (c) All openings, except stub drains are equipped with covers, lids, or seals such that:
 1. The cover, lid, or seal is in the closed position at all times except on demand for sampling, maintenance, repair, or necessary operational practices; and,
 2. Automatic bleeder vents are closed at all times except when the roof is floated off or landed on the roof leg supports; and,
 3. Rim vents, if provided, are set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting.
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) Internal Floating Roof and Roof Seals. The test method for volatile organic compounds shall be p. 6-2 of EPA 450/2-77-036, incorporated and adopted by reference in Chapter 62-297, F.A.C.
 - (b) Add-on Control Device.
 1. Destructive. The test method for volatile organic compounds shall be EPA Method 25 as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or Attachment 3 of EPA 450/2-78-041, Alternate Test Method for Direct Measurement of Total Gaseous Organic Compounds Using a Flame Ionization Analyzer, adopted and incorporated by reference in Chapter 62-297, F.A.C.

2. Non-destructive. The test method for volatile organic compounds shall be VOC Capture Efficiency Test Procedures as described at Rule 62-297.450, F.A.C. The sampling time for each capture efficiency test run shall be at least 8 hours, unless otherwise approved by the Department pursuant to Rule 62-297.620, F.A.C.
- (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)8.,17-296.508; Amended 11-23-94, 1-1-96, 10-6-08,7-10-14
62-296.508

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	06/16/1999	64 FR 32346
2 nd Revision	7/1/2011	10/6/2017	82 FR 46682
3 rd Revision	04/01/22	12/6/2023	88 FR 76139

62-296.510 Bulk Gasoline Terminals.

- (1) Applicability. The emission limiting standards or control technology set forth in Rule 62-296.510, F.A.C., applies to bulk gasoline terminals and the appurtenant equipment necessary to load the tank truck or trailer compartments.
- (2) Emission Limiting Standards. Emissions units affected under Rule 62-296.510(1), F.A.C., shall not allow mass emissions of volatile organic compounds from control equipment to exceed 4.7 grains per gallon (80 milligrams per liter) of gasoline loaded.
- (3) Control Technology. No person shall load gasoline into any tank, trucks or trailers from any bulk gasoline terminal unless:
 - (a) Displaced vapors are vented only to the-vapor control system; and,
 - (b) A means is provided to prevent liquid waste from the loading device to exceed the quantity specified for the self sealing coupler or adapter according to API regulation RP 1004 (or equivalent) upon the loading device being disconnected or when it is not in use (the above referenced are available from the American Petroleum Institute, 2101 Street N. W., Washington, D. C. 20037); and,
 - (c) All loading and vapor lines equipped with fittings are vapor tight; and,
 - (d) The bulk gasoline terminal is equipped with a properly installed and operated vapor control system complying with Rule 62-296.510, F.A.C., and which recovers vapors from the equipment being controlled or which directs all vapors to a combustion or incineration system.
- (4) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) Vapor Control Emissions. The test methods for volatile organic compounds shall be EPA Methods 2A and 2B, as described at 40 C.F.R. Part 60, Appendix A-1; and EPA Methods 25A and 25B, as described at 40 C.F.R. Part 60, Appendix A-7; adopted and incorporated by reference at Rule 62-204.800, F.A.C. Rule 62-297.440(2)(b)1.a., F.A.C., shall also apply.
 - (b) Equipment Vapor-Leak Detection. The test methods for volatile organic compounds shall be EPA Methods 21, as described at 40 C.F.R. Part 60, Appendix A-7; and EPA Method 27, as described at 40 C.F.R. Part 60, Appendix A-8; adopted and incorporated by reference at Rule 62-204.800, F.A.C. Subparagraph 62-297.440(2)(b)2.a., F.A.C., shall also apply.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)10.,17-296.510; Amended 11-23-94, 1-1-96, 7-10-14.
62-296.510

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994 & 04/15/96	06/16/1999	64 FR 32346
2 nd Revision	04/01/22	12/6/2023	88 FR 76139

62-296.511 Solvent Metal Cleaning.

(1) Applicability.

(a) The emission limiting standards and control technology set forth in Rule 62-296.511, F.A.C., shall apply to cold cleaning, open-top vapor degreasing, and conveyORIZED degreasing operations. All degreasing facilities using the following halogenated solvents are subject to the requirements (including compliance deadlines) of the national emission standard for halogenated solvent degreasers at 40 CFR Part 63, Subpart T, adopted and incorporated by reference in Rule 62-204.800.; carbon tetrachloride, chloroform, tetrachloroethylene, 1,1,1-trichloroethane, trichloroethylene, and methylene chloride. Until compliance is achieved with the requirements of 40 CFR Part 63, Subpart T, existing (as of November 29, 1993) halogenated solvent degreasing facilities must also comply with the requirements of this rule. The requirements of this rule shall not apply to any halogenated solvent degreasing facility after it has achieved compliance with the requirements of 40 CFR Part 63, Subpart T.

(b) The provisions of Rule 62-296.511, F.A.C., shall apply with the following exceptions:

1. Open-top vapor degreasers with an open area smaller than 10.8 square feet (one square meter) shall be exempt from Rule 62-296.511(3)(c), F.A.C.;
2. ConveyORIZED degreasers with an air/vapor interface smaller than 21.5 square feet (2.0 square meters) shall be exempt from Rule 62-296.511(4)(b), F.A.C.

(2) Cold Cleaning Control Technology. Except as provided under Rule 62-296.511(1), F.A.C., the owner or operator of a cold cleaning facility shall comply with each of the following requirements:

- (a) Equip the cleaner with a cover. The cover shall be so designed that it can be easily operated with one hand if:
 1. The solvent volatility is greater than 0.3 pounds per square inch (15 millimeters of mercury or 2 kilopascals) measured at 100 degrees Fahrenheit (38 degrees Celsius);
 2. The solvent is agitated;
 3. The solvent is heated.
- (b) Equip the cleaner with a facility for draining cleaned parts. The drainage facility shall be constructed internally so that parts are enclosed under the cover while draining if the solvent volatility is greater than 0.6 pounds per square inch (31 millimeters of mercury or 4.1 kilopascals) measured at 100 degrees Fahrenheit (38 degrees Celsius), except that the drainage facility may be external for the applications where an internal type cannot fit into the cleaning system.
- (c) Install one of the following control devices if the solvent volatility is greater than 0.6 pounds per square inch (31 millimeters of mercury or 4.1 kilopascals) measured at 100 degrees Fahrenheit (38 degrees Celsius), or if the solvent is heated above 120 degrees Fahrenheit (50 degrees Celsius):
 1. Freeboard that gives a freeboard ratio greater than or equal to 0.7; or,
 2. Water cover (solvent must be insoluble in and heavier than water); or,
 3. Other systems of equivalent control such as refrigerated chiller or carbon absorption.

- (d) Provided a permanent, conspicuous label summarizing the operating requirements.
 - (e) Store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, such that greater than 20 percent of the waste solvent (by weight) can evaporate into the atmosphere.
 - (f) Close the cover whenever parts are not being handled in the cleaner.
 - (g) Drain the cleaned parts for at least 15 seconds or until dripping ceases.
 - (h) If used, supply a solvent spray that is a solid fluid stream (not a fine, atomized, or shower-type spray) at a pressure which does not cause excessive splashing.
- (3) Open Top Vapor Degreaser Control Technology. Except as provided under Rule 62-296.511, F.A.C., the owner or operator of an open top vapor degreaser shall comply with each of the following requirements:
- (a) Equip the vapor degreaser with a cover that can be opened and closed easily without disturbing the vapor zone.
 - (b) Provide the following safety switches:
 1. A condenser flow switch and thermostat which shut off the heat if the condenser coolant is either not circulating or too warm; and,
 2. A spray safety switch which shuts off the spray pump if the vapor level drops more than 4 inches (10 centimeters) below the bottom condenser coil; and,
 3. A vapor level control thermostat which shuts off the heat when the vapor level rises too high.
 - (c) Install one of the following control devices:
 1. A freeboard ratio greater than or equal to 0.75, and a powered or mechanically assisted cover if the degreaser opening is greater than 10.8 square feet (1.0 square meter) or,
 2. Refrigerated chiller; or,
 3. An enclosed design (cover or door opens only when the dry part is actually entering or exiting the degreaser); or,
 4. A carbon adsorption system, with ventilation greater than or equal to 50 cubic feet per minute per square foot (15 cubic meters per minute per square meter) of air/vapor area (when cover is open), and exhausting less than 25 parts per million of solvent averaged over one complete adsorption cycle.
 - (d) Keep the cover closed at all times except when processing work loads through the degreaser.
 - (e) Minimize solvent carry out by:
 1. Racking parts to allow complete drainage; and,
 2. Moving parts in and out of the degreaser at less than 11 feet per minute (3.3 meters per minute); and,
 3. Holding the parts in the vapor zone at least 30 seconds or until condensation ceases; and,
 4. Decanting any pools of solvent on the cleaned parts before removal from the vapor zone; and,

5. Allowing parts to dry within the degreaser for at least 15 seconds or until visually dry.
 - (f) Not degrease porous or absorbent materials, such as cloth, leather, wood, or rope.
 - (g) Not occupy more than half of the degreaser's open-top area with a workload.
 - (h) Not load the degreaser to the point where the vapor level would drop more than 4 inches (10 centimeters) below the bottom condenser coil when the workload is removed from the vapor zone.
 - (i) Always spray below the vapor level.
 - (j) Repair solvent leaks immediately, or shut down the degreaser.
 - (k) Store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, such that greater than 20 percent of the waste solvent (by weight) can evaporate into the atmosphere.
 - (l) Not operate the cleaner so as to allow water to be visually detectable in solvent exiting the water separator.
 - (m) Not use ventilation fans near the degreaser opening, nor provide exhaust ventilation exceeding 66 cubic feet per minute per square foot (20 cubic meters-per minute per square meter) of degreaser open area, unless necessary to meet OSHA requirements.
 - (n) Provide a permanent, conspicuous label, summarizing the operating procedure of Rule 62-296.511(3)(d) through (1), F.A.C.
- (4) Conveyorized Degreaser Control Technology. Except as provided under Rule 62-296.511(1), F.A.C., the owner or operator of a conveyorized degreaser shall comply with the following requirements:
- (a) Not use work-place fans near the degreaser opening, nor provide exhaust ventilation exceeding 66 cubic feet per minute per square foot (20 cubic meters per minute per square meter) of degreaser opening, unless necessary to meet Occupational Safety and Health Administration (OSHA) requirements. OSHA regulations are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., and may be inspected at the Department's Tallahassee office.
 - (b) Install one of the following control devices:
 1. Refrigerated chiller; or,
 2. Carbon absorption system, with ventilation greater than or equal to 49 cubic feet per minute per square foot (15 cubic meters per square meter) of air/vapor area (when downtime covers are open), and exhausting less than 25 parts per million of solvent by volume averaged over a complete absorption cycle.
 - (c) Equip the cleaner with equipment, such as a drying tunnel or rotating (tumbling) basket, sufficient to prevent cleaned parts from carrying out solvent or liquid vapor.
 - (d) Provide the following safety switches:
 1. A condenser flow switch and thermostat which shut off the sump heat if the condenser coolant is either not circulating or too warm; and,
 2. A spray safety switch which shuts off the spray pump or the conveyor if

- the vapor level drops more than 4 inches (10 centimeters) below the bottom condenser coil; and,
3. A vapor level control thermostat which shuts off the heat when the vapor level rises too high.
- (e) Minimize openings during operation so that entrances and exits will silhouette workloads with an average clearance between-the parts and the edge of the degreaser opening of less than 4 inches (10 centimeters) or less than 10 percent of the width of the opening.
 - (f) Provide downtime covers for closing off the entrance and exit during shutdown hours.
 - (g) Minimize carryout emissions by:
 1. Racking parts for best drainage; and,
 2. Maintaining the vertical conveyor speed at less than 11 feet per minute (3.3 meters per minute).
 - (h) Store waste solvent only in covered containers and not dispose of waste solvent or transfer it to another party, such that greater than 20 percent of the waste solvent (by weight) can evaporate into the atmosphere.
 - (i) Repair solvent leaks immediately, or shut down the degreaser.
 - (j) Not operate the cleaner so as to allow water to be visually detectable in solvent exiting the water separator.
 - (k) Place downtime covers over entrances and exits of conveyORIZED degreasers immediately after the conveyors and exhausts are shutdown and do not remove them until just before a startup.
- (5) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
- (a) The test method for volatile organic compound emissions from the specified equipment shall be EPA Method 21, as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800 , F.A.C.
 - (b) The test method for non-halogenated organic solvent emissions from a destructive add-on control device shall be EPA Method 25, as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or Attachment 3 of EPA 450/2-78-041, Alternate Test Method for Direct Measurement of Total Gaseous Organic Compounds Using a Flame Ionization Analyzer, adopted and incorporated by reference in Chapter 62-297, F.A.C.
 - (c) The test method for organic solvent emissions from a non-destructive add-on control device shall be VOC Capture Efficiency Test Procedures as described at Rule 62297.450 , F.A.C. The sampling time for each capture efficiency test run shall be at least 8 hours, unless otherwise approved by the Department pursuant to Rule 62-297.620, F.A.C.
 - (d) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)12.,17-296.511; Amended 11-23-94, 1-1-96, 6-25-96, 10-7-96, 7-10-14, 11-5-20.

62-296.511

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994 & 04/15/96	06/16/1999	64 FR 32346
2 nd Revision	7/22/1996	1/16/2003	68 FR 2204
3 rd Revision	04/01/22	12/6/2023	88 FR 76139

62-296.512 Cutback Asphalt.

- (1) Applicability. The emission limiting control standards set forth in Rule 62-296.512(2), F.A.C., shall apply to the manufacture and use of cutback asphalts for paving or maintaining roads, streets, highways, and parking lots.
- (2) Control Standards. No person shall cause, allow, or permit the manufacture, mixing, storage, use, or application of cutback asphalts except where:
 - (a) Long-life storage of liquid asphalt is necessary; or,
 - (b) Stockpile storage of cold mixed asphaltic concrete patching material is necessary; or,
 - (c) The use or application at ambient temperature less than 50 degrees Fahrenheit (10 degrees Celsius) as determined by the nearest National Weather Service Station is necessary; or,
 - (d) The cutback asphalt is to be used solely as a penetrating prime coat; or,
 - (e) The cutback asphalt is to be used in a sand seal coat; or,
 - (f) The cutback asphalt is to be used as a tack coat in the routine maintenance of public roads, or the minor betterment of public roads.

History: Formerly 17-2.650(1)(f)13.,17-296.512; Amended 11-23-94, 1-1-96, 7-1014, 8-14-19.

62-296.512

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	06/16/1999	64 FR 32346
2 nd Revision	04/01/22	12/6/2023	88 FR 76139

62-296.513 Surface Coating of Miscellaneous Metal Parts and Products.

(1) Applicability.

- (a) The emission limiting standards set forth in Rule 62-296.513(2), F.A.C., shall apply to surface coating of the following metal parts and products:
1. Large farm machinery, such as harvesting, fertilizing and planting machines, tractors and combines;
 2. Small farm machinery, such as lawn and garden tractors, lawn mowers and rototillers;
 3. Small appliances, such as fans, mixers, blenders, crock pots, dehumidifiers and vacuum cleaners;
 4. Commercial machinery, such as office equipment, computers and auxiliary equipment, typewriters, calculators and vending machines;
 5. Industrial machinery, such as pumps, compressors, conveyor components, fans, blowers and transformers;
 6. Fabricated metal products, such as metal covered doors, frames, etc.; and,
 7. Any other industrial category which coats metal parts or products under the Standard Industrial Classification Code of Major Group 33 (primary metal industries), Major Group 34 (fabricated metal products), Major Group 35 (nonelectric machinery), Major Group 36 (electrical machinery), Major Group 37 (transportation equipment), Major Group 38 (miscellaneous instruments), and Major Group 39 (miscellaneous manufacturing industries). The Standard Industrial Classification Code is available from the superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402, and may be examined at the Department of Environmental Regulation, Tallahassee.
- (b) The provisions of Rule 62-296.513, F.A.C., shall not apply to the surface coating of the following metal parts and products:
1. Automobiles and light-duty trucks;
 2. Metal cans;
 3. Flat metal sheets and strips in the form of rolls or coils;
 4. Magnet wire for use in electrical machinery;
 5. Metal furniture;
 6. Large appliances;
 7. Exterior of airplanes;
 8. Automobile refinishing;
 9. Customized top coating of automobiles and trucks if production is less than 35 vehicles per day;
 10. Exterior of marine vessels; and,
 11. Aerospace parts and products coating operations that are either:
 - a. Facilities classified as area sources that comply with primer, topcoat, and specialty coating VOC control requirements of 40 CFR Part 63, Subpart GG, as adopted and incorporated by reference in Rule 62-204.800, F.A.C.; or
 - b. Facilities classified as major sources that are subject to 40 CFR Part 63,

Subpart GG, as adopted and incorporated by reference in Rule 62-204.800, F.A.C.

- (c) The provisions of Rule 62-296.513, F.A.C., apply to the application area (s), flashoff area(s), air and forced air dryer(s), and oven(s) used in the surface coating of the metal parts and products listed in Rule 62-296.513(1)(a), F.A.C. These provisions also apply to prime coat, top coat, and single coat operations. Credit for transfer efficiency above the baseline of 60% for spray coating operations can be granted according to the following formula:

$$X = \frac{(TE)(Z)(Y)}{Y + (TE)(Z)}$$

Where

X = allowable maximum VOC content (kg VOC/liter of coating less water)

Y = density of the VOC in the maximum VOC content coating (kg/liter)

Z = applicable emission limit (kg VOC/liter of coating solids deposited)

TE = transfer efficiency

An EPA and state approved test method for determination of transfer efficiency above the baseline is required.

(2) Emission Limiting Standards

- (a) No owner or operator of a coating line for miscellaneous metal parts and products shall cause, allow, or permit the discharge into the atmosphere of any volatile organic compounds in excess of:
1. 4.3 pounds per gallon of coating (0.52 kilograms per liter), excluding water, delivered to a coating applicator that applies clear coatings;
 2. 3.5 pounds per gallon of coating (0.42 kilograms per liter), excluding water, delivered to a coating applicator in a coating application system that is air dried or forced warm air dried at temperatures up to 194 degrees Fahrenheit (90 degrees Celsius);
 3. 3.5 pounds per gallon of coating (0.42 kilograms per liter), excluding water, delivered to a coating applicator that applies extreme performance coatings; or,
 4. 3.0 pounds per gallon of coating (0.36 kilograms per liter), excluding water, delivered to a coating applicator for all other coatings and coating application systems.
- (b) If more than one emission limitation in Rule 62-296.513(2)(a), F.A.C., applies to a specific coating, then the least stringent emission limitation shall be applied.
- (c) All volatile organic compound emissions from solvent washings shall be considered in the emission limitations in Rule 62-296.513(2)(a), F.A.C., unless the solvent is directed into containers that prevent evaporation into the atmosphere.

(3) Control Technology. The emission limits in Rule 62-296.513(2)(a), F.A.C., shall be achieved by:

- (a) The application of low solvent coating technology; or,

- (b) Incineration, provided that 90 percent of the volatile organic compounds (VOC measured as total combustible carbon) which enter the incinerator are oxidized to carbon dioxide and water.
- (4) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) Low Solvent Technology. The test method for volatile organic compounds shall be EPA Method 24 , as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or EPA 450/3-84-019, Procedures for Certifying Quantity of Volatile Organic Compounds Emitted by Paint, Ink, and Other Coatings (<http://www.flrules.org/Gateway/reference.asp?No=Ref-04298>, hereby adopted and incorporated by reference.
 - (b) Add-on Control Device.
 - 1. Destructive. The test method for volatile organic compounds shall be EPA Method 25 , as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or Attachment 3 of EPA 450/2-78-041, Alternate Test Method for Direct Measurement of Total Gaseous Organic Compounds Using a Flame Ionization Analyzer, adopted and incorporated by reference in Chapter 62-297, F.A.C.
 - 2. Non-destructive. The test method for volatile organic compounds shall be EPA VOC Capture Efficiency Test Procedures as described at Rule 62-297.450 , F.A.C. The sampling time for each capture efficiency test run shall be at least 8 hours, unless otherwise approved by the Department pursuant to Rule 62-297.620, F.A.C.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)14.,17-296.513; Amended 11-23-94, 1-1-96, 7-10-14, 06-16-22.

62-296.513

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994 & 04/15/96	06/16/1999	64 FR 32346
2 nd Revision	04/01/22	12/6/2023	88 FR 76139
3 rd Revision	10/12/22	9/27/2024	89 FR 79147

62-296.514 Surface Coating of Flat Wood Paneling.

- (1) Applicability.
 - (a) The emission limiting standards set forth in Rule 62-296.514(2), F.A.C., shall apply to all flat wood manufacturing and surface finishing facilities that manufacture the following products:
 1. Printed interior panels made of hardwood, plywood and thin particle board;
 2. Natural finish hardwood plywood panels, or
 3. Hardboard paneling with Class II finishes.
 - (b) The provisions stated in Rule 62-296.514(2), F.A.C., do not apply to the manufacture of exterior siding, tileboard, or particle board used as a furniture component.
- (2) Emission Limiting Standards. No owner or operator of a flat wood coating line subject to Rule 62-296.514, F.A.C., may cause, allow or permit the discharge into the atmosphere of any volatile organic compounds in excess of:
 - (a) 6.0 pounds per 1,000 square feet of coated finished product (2.9 kilograms per 100 square meters) from the coating of printed interior panels, regardless of the number of coats applied;
 - (b) 12.0 pounds per 1,000 square feet of coated finished product (5.8 kilograms per 100 square meters) from the coating of natural finish hardwood plywood panels, regardless of the number of coats applied; or,
 - (c) 10.0 pounds per 1,000 square feet of coated finished product (4.8 kilograms per 100 square meters) from the coating of Class II finishes on hardboard panels, regardless of the number of coats applied.
- (3) Control Technology. The emission limits in Rule 62-296.514(2), F.A.C., shall be achieved by:
 - (a) The application of low solvent coating technology; or,
 - (b) Incineration, provided that 90% of the volatile organic compounds (VOC measured as total combustible carbon) which enter the incinerator are oxidized to carbon dioxide and water.
- (4) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) Low Solvent Technology. The test method for volatile organic compounds shall be EPA Method 24 , as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or EPA 450/3-84-019, Procedures for Certifying Quantity of Volatile Organic Compounds Emitted by Paint, Ink, and Other Coatings (<http://www.flrules.org/Gateway/reference.asp?No=Ref-04298>), hereby adopted and incorporated by reference.
 - (b) Add-on Control Device.
 1. Destructive. The test method for volatile organic compounds shall be EPA Method 25 , as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or Attachment 3 of EPA 450/2-78-041, Alternate Test Method for Direct

Measurement of Total Gaseous Organic Compounds Using a Flame Ionization Analyzer, adopted and incorporated by reference in Chapter 62-297, F.A.C.

2. Non-destructive. The test method for volatile organic compounds shall be VOC Capture Efficiency Test Procedures as described at Rule 62-297.450, F.A.C. The sampling time for each capture efficiency test run shall be at least 8 hours, unless otherwise approved by the Department pursuant to Rule 62-297.620, F.A.C.

(c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)15.,17-296.514; Amended 11-23-94, 1-1-96, 7-10-14
62-296.514

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/9194	59 FR 52916
1 st Revision	12/21/1994 & 04/15/96	6/16/1999	64 FR 32346
2 nd Revision	04/01/22	12/6/2023	88 FR 76139

62-296.515 Graphic Arts Systems.

- (1) Applicability. The control technology and provisions set forth in Rule 62-296.515(2), F.A.C., shall apply to all packaging rotogravure, publication rotogravure, or flexographic printing operations whose prior to control potential to emit volatile organic compounds is equal to or more than 100 tons per year (90 megagrams per year).
- (2) Control Technology.
 - (a) No owner or operator of a packaging rotogravure, publication rotogravure, or flexographic printing operation subject to Rule 62-296.515, F.A.C., and employing solvent containing ink shall cause, allow or permit the operation of the facility unless:
 1. The volatile fraction of ink as it is applied to the substrate, contains 25 percent by volume or less of organic solvent and 75 percent by volume or water; or,
 2. The ink as it is applied to the substrate, less water, contains 60 percent by volume or more nonvolatile material; or,
 3. An incineration system is employed which oxidizes at least 90 percent of the volatile organic compounds (VOC measured as total combustible carbon) to carbon dioxide and water.
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) Low Solvent Technology. The test method for volatile organic compounds shall be EPA Method 24 or 24A as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or EPA 450/3-84-019, Procedures for Certifying Quantity of Volatile Organic Compounds Emitted by Paint, Ink, and Other Coatings (<http://www.flrules.org/Gateway/reference.asp?No=Ref-04298>), hereby adopted and incorporated by reference.
 - (b) Add-on Control Device.
 1. Destructive. The test method for volatile organic compounds shall be EPA Method 25 , as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or Attachment 3 of EPA 450/2-78-041, Alternate Test Method for Direct Measurement of Total Gaseous Organic Compounds Using a Flame Ionization Analyzer, adopted and with equipment specifications per Industrial Ventilation Manual, incorporated by reference in Chapter 62-297, F.A.C.
 2. Non-destructive. The test method for volatile organic compounds shall be VOC Capture Efficiency Test Procedures as described at Rule 62-297.450 , F.A.C. The sampling time for each capture efficiency test run shall be at least 8 hours, unless otherwise approved by the Department pursuant to Rule 62-297.620, F.A.C.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)16.,17-296.515; Amended 11-23-94, 1-1-96, 7-10-14.

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994 & 04/15/96	6/16/1999	64 FR 32346
2 nd Revision	04/01/22	12/6/2023	88 FR 76139

62-296.516 Petroleum Liquid Storage Tanks with External Floating Roofs.

(1) Applicability.

- (a) The control technology and provisions set forth in Rule 62-296.516(2), F.A.C., shall apply to all petroleum liquid storage vessels equipped with external floating roofs, having capacities equal to or greater than 42,000 gallons (159,000 liters, nominal design 1,000 barrels);
- (b) Rule 62-296.516(2), F.A.C., shall not apply to petroleum liquid storage vessels which:
 - 1. Are used to store waxy, heavy pour crude oil; or,
 - 2. Have capacities equal to or less than 420,000 gallons (1,590,000 liters, nominal 10,000 barrels) and are used to store crude oil and condensate prior to lease custody transfer; or,
 - 3. Contain a petroleum liquid with a true vapor pressure of less than 1.5 psia (10.15 kPa); or,
 - 4. Contain a petroleum liquid with a true vapor pressure of less than 4.0 psia (27.6 kPa) if such vessel is of welded construction and presently possesses a metallic-type shoe seal, a liquid-mounted foam seal, a liquid-mounted liquid-filled type of seal, or other closure device of demonstrated equivalence approved by the Department; or,
 - 5. Are of welded construction, equipped with a metallic-type shoe primary seal and with a secondary seal from the top of the shoe seal to the tank wall (shoe-mounted secondary seal).

(2) Control Technology.

- (a) No owner or operator of a petroleum liquid storage vessel subject to Rule 62-296.516, F.A.C., shall store a petroleum liquid in that vessel unless:
 - 1. The vessel has been fitted with a continuous secondary seal extending from the floating roof to the tank wall.(rim-mounted secondary seal); or another closure or device, approved by the Department, which is equally effective in controlling emissions; and,
 - 2. All seal closure devices meet the following requirements:
 - a. The seal(s) are intact and uniformly in place around the circumference of the floating roof between the floating roof and the tank wall; and,
 - b. There are no visible holes, tears, or other openings in the seal(s) or seal fabric, and
 - c. For vapor mounted (primary) seals, the accumulated area of gaps exceeding 1/8 inch (0.32 cm) in width between the secondary seal and the tank wall shall not exceed 1.0 square inch per foot of tank diameter (21.2 square centimeters per meter of tank diameter); and,
 - 3. All openings in the external floating roof, except for automatic bleeder vents, rim space vents, and leg sleeves, are:
 - a. Equipped with covers, seals, or lids in the closed position except when the openings are in actual use; and,
 - b. Equipped with projections in the tank which remain below the

- liquid surface at all times; and,
4. Automatic bleeder vents are closed at all times except when the roof is floating off or landed on the roof leg supports; and,
 5. Rim vents are set to open when the roof is being floated off the leg supports or at the manufacturer's recommended setting; and,
 6. Emergency roof drains are provided with slotted membrane fabric covers or equivalent covers which cover at least 90 percent of the area of the opening.
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
- (a) The test method for volatile organic compounds shall be EPA Method 21, as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C.; and as described in section 5.2 on p. 5-3 of EPA 450/2-78-047, adopted and incorporated by reference in Chapter 62-297, F.A.C.
 - (b) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(1)(f)17., 17-296.516; Amended 11-23-94, 1-1-96, 7-10-14
62-296.516

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994 & 04/15/96	06/16/1999	64 FR 32346
2 nd Revision	04/01/22	12/6/2023	88 FR 76139

62-296.570 Reasonably Available Control Technology (RACT) - Requirements for Major VOC- and NOx-Emitting Facilities.

- (1) Applicability.
 - (a) The requirements of this rule shall apply to those major VOC- and NOx-emitting facilities specified in Rule 62-296.500(1)(b), F.A.C.; specifically, to those VOC emissions units within such facilities which are not regulated for VOC under Rules 62-296.501 through 62-296.516, F.A.C., and those VOC and NOx emissions units which have not been exempted pursuant to Rule 62-296.500(1)(b), F.A.C., or by a specific provision of Rules 62-296.500 through 62-296.516, F.A.C.
 - (b) The requirements of this rule shall not apply to emissions units that would otherwise be exempt from the air permitting requirements of the Department pursuant to Rule 62-210.300(3), F.A.C., or that would otherwise be considered insignificant pursuant to Rule 62-213.300(2)(a)1., F.A.C., or Rule 62-213.430(6)(b), F.A.C.
- (2) Compliance Requirements. Emissions units subject to the requirements of this rule shall comply with the operation permit requirements of Rule 62-296.570(3), F.A.C., and the RACT emission limiting standards of Rule 62-296.570(4), F.A.C. If, pursuant to an air operation or construction permit, the owner or operator of a emissions unit subject to the requirements of this rule assumes (or has assumed) a more stringent NOx or VOC emissions limit than the RACT emissions limit established in Rule 62-296.570(4), F.A.C., for the applicable emissions unit category, compliance with the emissions unit's NOx or VOC emissions limit in its air operation or construction permit shall be considered compliance with RACT for purposes of this rule.
- (3) (Reserved).
- (4) RACT Emission Limiting Standards.
 - (a) Emissions Testing Dates and Monitoring.
 1. (Reserved).
 2. (Reserved).
 3. For units that are not equipped with a continuous emission monitoring system (CEMS) for NOx or VOCs, annual emission testing is required in accordance with applicable EPA Reference Methods as described in 40 C.F.R. Part 60, Appendices A-1 through A-8, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or other methods approved by the Department in accordance with the requirements of Rule 62-297.620, F.A.C., except as otherwise provided in Rule 62-296.570(4)(b), F.A.C. If required, such annual emission testing shall be conducted during each federal fiscal year (October 1 - September 30). Annual emissions testing while firing oil is unnecessary for units operating on oil for less than 400 hours in the current federal fiscal year.
 4. For units that are equipped with a CEMS, compliance shall be demonstrated based on a 30-day rolling average. The CEMs must meet the performance specifications contained in 40 Code of Federal Regulations Part 60, Appendix B, or 40 Code of Federal Regulations Part

75, hereby adopted and incorporated by reference.

- (b) Emission Limiting Standards.
1. (Reserved).
 2. (Reserved).
 3. (Reserved).
 4. (Reserved).
 5. Emissions of NO_x from any gas turbine shall not exceed 0.50 lb/million BTU while firing natural gas and 0.90 lb/million BTU while firing oil. Unless compliance is demonstrated using a CEMS, compliance shall be demonstrated by a stack test on one representative turbine unit within a facility if the turbines are substantially similar.
 6. Emissions of VOC and NO_x from carbonaceous fuel burning facilities, other than waste-to-energy facilities, shall not exceed 5.0 lbs/million BTU and 0.9 lb/million BTU, respectively.
 7. Emissions of NO_x from any oil-fired diesel generator shall not exceed 4.75 lb/million BTU.
 8. Emissions of NO_x from any cement plant shall not exceed 2.0 lb/million BTU.
 9. Emissions of NO_x from any other external combustion emissions unit subject to the requirements of this rule, and not covered in Rule 62-296.570(4)(b)1. through 8., F.A.C., shall not exceed 0.50 lb/million BTU. Emissions shall be determined annually in accordance with the applicable EPA Method from 40 C.F.R. Part 60, Appendix A-1 through A-8, adopted and incorporated by reference at Rule 62-204.800, F.A.C., or other method approved by the Department in accordance with the requirements of Rule 62-297.620, F.A.C.
 10. Emissions of VOC from resin coating operations shall be limited by the use of low-VOC resin or thermal oxidation of emissions from the purge cycle.
 11. Emissions of VOC from any emissions unit subject to this rule but specifically exempted from any of the control technology requirements of Rules 62-296.501, through 62-296.516, F.A.C., shall not exceed the applicable exemption criteria.
- (c) Startup, Shutdown, or Malfunction. The emission limits in this rule shall apply during periods of startup, shutdown, or malfunction as provided by Rule 62-210.700, F.A.C.

History: New 2-2-93; Amended 4-17-94; Formerly 17-296.570; Amended 11-23-94, 1-1-96, 3-2-99, 7-10-14, 06-23-22.

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	01/08/93	01/11/95	60 FR 2688

1 st Revision	04/25/94	01/11/95	60 FR 2688
2 nd Revision	12/21/1994	06/16/1999	64 FR 32346
3 rd Revision	4/15/1996	06/16/1999	64 FR 32346
4 th Revision	4/1/2022 & 9/30/2022	08/4/2023	88 FR 51702

62-296.600 Reasonably Available Control Technology (RACT) - Lead.

- (1) **Applicability.** Any new or existing lead processing operation that is located in an area designated under Chapter 62-275, F.A.C., as a lead nonattainment or air quality maintenance area, or in the area of influence of such an area, shall limit the emission of lead through the application of reasonably available control technology (RACT) as specified in Rules 62-296.601 through 62-296.605, F.A.C.
- (2) **Compliance Requirements.** Lead processing operations subject to the requirements of this rule shall comply with the permit requirements, operation and maintenance plan requirements, recordkeeping and reporting requirements, and compliance demonstration requirements of Rules 62-296.600(3) through 62-296.600(6), F.A.C., respectively, the general requirements of Rule 62-296.601, F.A.C., and the specific emission limiting standards of Rules 62-296.602 through 62-296.605, F.A.C. For existing facilities, compliance with these requirements shall be achieved as expeditiously as possible, in accordance with a schedule of compliance established in the permit required pursuant to this rule.
- (3) **Permit Requirements.** By September 30, 1994, the owner or operator of any existing facility subject to the requirements of this rule shall apply for a new or revised federally enforceable, as defined in Rule 62-210.200, F.A.C., air permit, pursuant to Chapter 62-4, F.A.C., addressing the requirements of this rule.
- (4) **Operation and Maintenance Plan.** In any application for a permit, the owner or operator of any facility subject to the requirements of this rule shall submit to the Department an operation and maintenance plan for the lead emissions control devices, collection systems, and processing systems. The operation and maintenance plan shall include quarterly inspection methods for the lead emissions control devices, including black light leak detection tests or broken bag detectors in the baghouses, to prevent reduced lead collection efficiency. Lead oxide handling operations with the potential to emit 200 pounds or less of lead per year shall be exempt from this operation and maintenance plan provision.
- (5) **Recordkeeping and Reporting.** The owner or operator of any facility subject to the requirements of this rule shall keep the following records for a minimum of two years, and make them available to any representative of the Department or an approved local air program upon request:
 - (a) Records of control equipment operating parameters.
 - (b) Maintenance records on the control equipment, including black-light tests, bag replacements, structural repairs, and motor replacements.
 - (c) Records of control system malfunctions or failures and corrective actions taken.
- (6) **Compliance Demonstration.** The owner or operator of any facility subject to an emissions limiting standard pursuant to Rule 62-296.602 through 62-296.605, F.A.C., shall demonstrate compliance with such limit by the initial compliance date established in the permit required pursuant to this rule, or in accordance with the terms of any construction permit addressing the requirements of this rule, and every five years thereafter unless a more frequent schedule is specified in the permit. Compliance shall be demonstrated as follows:
 - (a) Compliance with lead emission standards shall be demonstrated by EPA Method

12, adopted and incorporated by reference in Chapter 62-297, F.A.C.

- (b) Compliance with opacity standards shall be demonstrated by EPA Method 9, adopted and incorporated by reference in Chapter 62-297, F.A.C.

History: New: 8-8-94, Formerly 17-296.600, Amended 1-1-96, 3-13-96.

62-296.600

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	08/18/1994	9/18/1996	61 FR 49064
1 st Revision	4/15/1996	6/16/1999	64 FR 32346

62-296.601 Lead Processing Operations in General.

- (1) Applicability. The provisions of this rule shall apply to all lead processing operations as specified in Rule 62-296.600(1), F.A.C.
- (2) Prohibition.
 - (a) No owner or operator of a lead processing operation shall cause, allow, or permit the emissions of lead, including emissions of lead from vehicular movement, transportation of materials, construction, alteration, demolition or wrecking, or industrially-related activities such as loading, unloading, charging, melting, tapping, casting, storing or handling, unless reasonably available control technology is employed to control such lead emissions.
 - (b) Examples of measures that constitute RACT are:
 - 1. Paving, curbing, and maintaining roads, parking areas and yards which are routinely used by vehicular traffic.
 - 2. Applying water or chemicals to control emissions from such activities as demolition of buildings, grading roads, construction, and land clearing.
 - 3. Installing a permanent sprinkler system to continuously moisten open stock piles.
 - 4. Vacuuming the roads and other paved areas under the control of the owner or operator of the facility to prevent lead from becoming airborne.
 - 5. Landscaping or vegetating unpaved roads, parking areas and yards.
 - 6. Using hoods, fans, filters, and similar equipment to capture, contain, and control lead emissions.
 - 7. Enclosing or covering conveyor systems.
 - 8. Using walls or windbreaks to contain lead-bearing scrap, products, or raw materials.
 - (c) As part of any application for a permit, the owner or operator of any facility subject to the requirements of this rule shall submit to the Department a description of the reasonably available control technology that will be employed to meet the requirements of this section.

History: New 8-8-94, Formerly 17-296.601, Amended 1-1-96.

62-296.601

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	8/18/1994	9/18/1996	61 FR 49064

62-296.602 Primary Lead-Acid Battery Manufacturing Operations.

- (1) Emission Limiting Standards. No owner or operator of a primary lead-acid battery manufacturing operation subject to Rule 62-296.600, F.A.C., shall cause, allow, or permit the discharge into the atmosphere of lead in excess of the following emission standards, in grains of lead per dry standard cubic foot, nor shall visible emissions exceed the following standards, in percent opacity:
 - (a) Grid casting sources: 0.000176 grains and 0% opacity.
 - (b) Paste mixing sources: 0.00044 grains and 0% opacity.
 - (c) Three-process operation sources: 0.00044 grains and 0% opacity.
 - (d) Lead oxide manufacturing sources: 0.0005 grains and 0% opacity.
 - (e) Lead reclamation sources: 0.00198 grains and 5% opacity.
 - (f) Any other lead sources: 0.00044 grains and 0% opacity.
- (2) Collection Systems. Collection systems representing RACT shall be installed and operated to capture, contain, and control lead emissions resulting from all lead-emitting processes including charging, melting, tapping, and casting. No lead emissions shall be vented to the outside of any enclosed or partially enclosed process unless RACT is employed to control such emission.
- (3) Attainment Demonstration. As part of the initial application for the permit required pursuant to Rule 62-296.600(3), F.A.C., the owner or operator of a facility subject to the requirements of this rule shall demonstrate to the Department that, after the application of RACT, the facility shall not cause or contribute to a violation of the national ambient air quality standard for lead. The demonstration shall be made using air quality models as provided in 40 C.F.R. Part 51, Appendix W, adopted and incorporated by reference at Rule 62-204.800, F.A.C., and shall address both stack and fugitive emissions.

History: New 8-8-94, Formerly 17-296.602, Amended 1-1-96, 3-13-96, 7-10-14.

62-296.602

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	8/18/1994	9/18/1996	61 FR 49064
1 st Revision	4/15/1996	6/16/1999	64 FR 32346
2 nd Revision	4/1/2022	1/22/2024	89 FR 3886

62-296.603 Secondary Lead Smelting Operations.

- (1) Emission Limiting Standards. No owner or operator of a secondary lead smelting operation subject to Rule 62-296.600, F.A.C., shall cause, allow, or permit the discharge into the atmosphere of lead in excess of the following emission standards, in grains of lead per dry standard cubic foot, nor shall visible emissions exceed the following standards, in percent opacity:
 - (a) Blast and slag furnaces: 0.010 grains and 3% opacity at the exit point of the emissions control device.
 - (b) Blast furnace charging: 0.002 grains and 3% opacity at the exit point of the emissions control device.
 - 1. Visible emissions from the closed charge doors on the blast furnace shall not exceed 3% opacity during furnace operation.
 - 2. Visible emissions from the charge doors on the blast furnace shall not exceed 6% opacity during charging operation.
 - (c) Blast and slag furnaces, slag and product tapping: 0.002 grains and 3% opacity at the exit point of the emissions control device.
 - (d) Melt kettles and pot furnaces: 0.0002 grains and 3% opacity.
 - (e) Battery cracking operations: 3% opacity.
 - (f) Slag handling and processing operations: 0.0000333 grains and 3% opacity.
- (2) Collection Systems. Collection systems representing RACT shall be installed and operated to capture, contain, and control lead emissions resulting from the storage, transport, and processing of all lead-bearing materials and products at secondary lead smelting operations. No lead emissions shall be vented to the outside of any enclosed or partially enclosed process unless RACT is employed to control such emissions.
- (3) Attainment Demonstration. As part of the initial application for the permit required pursuant to Rule 62-296.600(3), F.A.C., the owner or operator of a facility subject to the requirements of this rule shall demonstrate to the Department that, after the application of RACT, the facility shall not cause or contribute to a violation of the national ambient air quality standard for lead. The demonstration shall be made using air quality models as provided in 40 C.F.R Part 51, Appendix W, adopted and incorporated by reference at Rule 62-204.800, F.A.C., and shall address both stack and fugitive emissions.

History: New 8-8-94, Formerly 17-296.603, Amended 1-1-96, 7-10-14.

62-296.603

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	08/18/1994	09/18/1996	61 FR 49064
1 st Revision	4/15/1996	06/16/1999	64 FR 32346
2 nd Revision	4/1/2022	1/22/2024	89 FR 3886

62-296.604 Electric Arc Furnace Equipped Secondary Steel Manufacturing Operations.

- (1) Emission Limiting Standards. No owner or operator of a secondary steel manufacturing operation subject to Rule 62-296.600, F.A.C., shall cause, allow or permit the discharge of lead into the atmosphere in excess of the following emission standards, in grains of lead per dry standard cubic foot as a weighted average of the exhaust from the entire control equipment system, nor shall visible emissions exceed the following standards, in percent opacity:
 - (a) Electric arc furnace control device: 0.0002 grains and 3% opacity.
 - (b) Melt shop building roof ventilators: 6% opacity.
- (2) Collection Systems. Collection systems representing RACT shall be installed and operated to capture, contain, and control lead emissions resulting from all lead-emitting processes including charging, melting, tapping, and casting. No lead emissions shall be vented to the outside of any enclosed or partially enclosed process unless RACT is employed to control such emission.
- (3) Attainment Demonstration. As part of the initial application for the permit required pursuant to Rule 62-296.600(3), F.A.C., the owner or operator of a facility subject to the requirements of this rule shall demonstrate to the Department that, after the application of RACT, the facility shall not cause or contribute to a violation of the national ambient air quality standard for lead. The demonstration shall be made using air quality models as provided in 40 C.F.R. Part 51, Appendix W, adopted and incorporated by reference at Rule 62-204.800, F.A.C., and shall address both stack and fugitive emissions.

History: New 8-8-94, Formerly 17-296.604, Amended 1-1-96, 7-10-14.

62-296.604

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	8/18/1994	9/18/1996	61 FR 49064
1 st Revision	4/15/1996	06/16/1999	64 FR 32346
2 nd Revision	4/1/2022	1/22/2024	89 FR 3886

62-296.605 Lead Oxide Handling Operations.

No owner or operator of a lead oxide handling operation subject to Rule 62-296.600, F.A.C., shall cause, allow, or permit visible emissions in excess of 3% opacity.

History: New 8-8-94, Formerly 17-296.605.

62-296.605

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Original Reg	8/18/1994	9/18/1996	61 FR 49064

62-296.700 Reasonably Available Control Technology (RACT) Particulate Matter.

(1) Applicability.

(a) Emissions of particulate matter shall be limited through the application of Reasonably Available Control Technology (RACT) for any emissions unit, issued an air permit on or before May 30, 1988, that emits particulate matter and is located in:

1. That portion of Hillsborough County which falls within the area of the circle having a centerpoint at the intersection of US 41 South and State Road 60 and a radius of 12 kilometers;

2. The downtown Jacksonville area in Duval County located within the following boundary lines: south and then west along the St. Johns River from its confluence with Long Branch Creek, to Main Street; north along Main Street to Eighth Street; east along Eight Street to Evergreen Avenue; north along Evergreen Avenue to Long Branch Creek; and east along Long Branch Creek to the St. Johns River; or

3. An area within 50 kilometers outside the boundary of such an area as described in subparagraph 62-296.700(1)(a)1. or 2., F.A.C., above.

(b) (Reserved)

(2) Exemptions. The following facilities and emissions unit are exempt from the provisions of this rule:

(a) Any facility with total maximum allowable emissions of particulate matter of less than 15 tons per year and 5 pounds per hour.

(b) Any facility whose owner or operator demonstrates to the Department that the impact within an area as described in subparagraph 62-296.700(1)(a)1. or 2., F.A.C., above, that of the total maximum allowable particulate matter emissions from such facility will not exceed 1 ug/m^3 , annual average, and 5 ug/m^3 , 24-hour average.

(c) Any emissions unit which has total allowable emissions of particulate matter of less than one ton per year.

(d) Any emissions unit of unconfined particulate matter which is located more than five kilometers outside the boundary of an area as described in subparagraph 62-296.700(1)(a)1. or 2., F.A.C., above.

(e) Any emissions unit of unconfined particulate matter from open stockpiling of materials, vehicular traffic and other emissions from roads and plant grounds, or construction activities.

(f) Any moveable drop transfer point where the discharge point and receiving point of the materials being handled must be moved in relationship to each other, either continuously or intermittently, such that enclosure of the drop transfer point with a device to control emissions of particulate matter is not practicable.

(g) Any emissions unit which as received a determination of Best Available Control Technology pursuant to Rule 17-2.630 (repealed) or 62-296.330 (repealed), F.A.C., or received a permit in connection with Rule 17-2.500 (transferred), 17-2-510 (transferred), 62-212.400 (Prevention of Significant Deterioration) or 62-

212.500 (Preconstruction Review of Nonattainment Areas), F.A.C.

- (3) Specific RACT Emission Limiting Standards for Stationary Emission Units. The specific particulate matter emission limiting standards set forth in Rules 62-296.401 through 62-296.414, F.A.C., have been found to represent the application of RACT for each emissions unit category listed in those rules except for those emissions unit categories listed in Rules 62-296.701 through 62-296.712, F.A.C. For those emissions unit categories the particulate matter emission standards in Rules 62-296.701 through 62-296.712, F.A.C., have been found to represent the application of RACT.
- (4) Maximum Allowable Emission Rates.
 - (a) Emissions Unit Data. The new or revised operating permit for each emissions unit subject to the provisions of this rule shall specify:
 1. The maximum heat input rate, charging rate, production rate, through-put rate, and/or materials handling rate, as appropriate;
The maximum heat input rate, charging rate, production rate, through-put rate, or materials handling-rate shall be the maximum rate at which the emissions unit is capable of being operated on a continuous basis.
 2. The maximum dry standard volumetric flow rate for each emission point, when applicable:
The maximum dry standard volumetric flow rate for each emissions unit or component emissions unit operation shall be the minimum dry standard volumetric flow rate that is necessary to safely and properly vent or operate the emissions unit when it is operated at its maximum continuous operating rate.
 3. The control device through which each gas stream is vented and the emission point from which each gas stream is discharged to the open air;

4. The height above ground, exit diameter, UTM coordinates, and nature of each emission point through which particulate is or may be vented;
 5. The exit gas temperature, actual volumetric flow rate and moisture content of each particulate bearing gas stream that is or may be vented to the open air;
 6. Pertinent operating or control equipment parameters, such as pH of scrubber solution, pressure drop in scrubber, pressure on spray nozzle, etc., when such information is needed to confirm the control device is operating normally;
 7. The permitted operating schedule (hrs./day, days/wk., wk./yr.)
- (b) Maximum Emission Rates. The new or revised operating permit for each emissions unit shall specify the maximum allowable emission rate for each emissions unit or group of commonly vented emissions units in accordance with the following provisions:
1. The maximum allowable emission rate expressed in lbs/hr, lbs/day and tons/yr (or other equivalent units) shall be determined for each emissions unit (for example, each drop transfer point, screening operation, kiln, or dryer) by applying the appropriate emission limitation contained in Rules 62-296.401 through 62-296.414, F.A.C., or Rules 62-296.701 through 62-296.712, F.A.C., to the maximum applicable emissions unit operation rate or dry standard volumetric flow rate and the permitted operating schedule as specified in the operating permit pursuant to the provisions of Rule 62-296.700(4)(a), F.A.C.
 2. If several emissions units are vented through a common control device or emission point, the maximum allowable emission rate for the common emission point shall be the sum of the individual maximum allowable emission rates for each emissions unit vented by the emission point.
 3. The owner or operator of a emissions unit or a group of emissions units that is subject to an emission limitation set forth in Rules 62-296.701 through 62-296.712, F.A.C., and that is vented through more than one emission point, shall, subject to the approval of the Department, prorate the total allowable emission for such emissions unit among all emission points that vent the affected emissions unit such that a specific maximum allowable emission rate is assigned to each emission point.

The operating permits for emissions units shall be revised in accordance with Rule 62-296.700(4), F.A.C., to reflect the maximum allowable emission rates for each emission point.
 4. The operating permit shall specify whether compliance shall be determined by measuring the emissions vented from each individual emissions unit or by measuring the emissions from the common emission point. In determining whether compliance shall be determined for each emissions unit individually or for a group of commonly vented emissions units at the common emission point, the department shall consider the following factors:
 - a. If all emissions units that are vented through a common emission point are subject to the same type of emission limiting standard

(i.e., grains per dry standard cubic foot (gr/dscf)) and are all part of the same system of unit operations such that when one emissions unit is in operation the other emissions units will also normally be in operation, the Department may specify that compliance be determined at the common point of emission.

- b. If the various emissions units that are vented through a common emission point are parts of different operating systems or are subject to different types of emission limiting standards (i.e., gr/dscf, lbs/ton of feed, lbs/MMBTU, percent opacity, etc.). The Department may specify that compliance with the various emission standards be determined separately for each emissions unit operation.
- (5) Circumvention. No owner or operator of an emissions unit subject to the requirements of Rules 62-296.401 through 62-296.414, F.A.C., or Rules 62-296.701 through 62-296.712, F.A.C., establishing maximum concentrations of emissions of particulate matter in the exhaust gas from the emissions unit shall circumvent the provisions of an applicable emission limitation by increasing the volume of gas in any exhaust or group of exhausts for the purpose of reducing the stack gas concentration. This includes allowing dilution air to enter the system through leaks, open vents, or similar means.
- (6) Operation and Maintenance Plan. The new or revised operating permit for each emissions unit subject to the provisions of this rule shall specify an operation and maintenance plan for the particulate control devices, the collection systems and the processing systems.
- (a) Air Pollution Control devices and collection systems. The plan shall include a schedule for the maintenance and inspection of each control device and collection system and a schedule for recording performance parameters of the control devices, collection systems and auxiliary equipment. Records of inspections, maintenance and performance data of control devices and auxiliary equipment shall be retained by the emissions unit for a minimum of two years and shall be made available to the Department upon request. The performance parameters shall include such physical, chemical or electrical characteristics as are applicable to the particular emissions unit and which are indicators of the condition, operating rates and efficiencies. Such parameters may include, but shall not be limited to, the following indicators for:
 - 1. Scrubbers
 - Pressure drop, total
 - Pressure drop, scrubber
 - Pressure drop, mist eliminator
 - Liquor feed rate
 - Liquor feed composition and pH
 - Liquor feed solids and undissolved solids contents
 - Water makeup rate
 - Fan(s) current at rated voltage
 - Pump(s) current at rated voltage
 - Gas flowrate
 - Gas temperatures, inlet and outlet (minimum)

2. Baghouses
 - Bag pressure drop
 - Gas flowrate: direct method preferred; indirect method acceptable
 - Air to cloth ratio
 - Bag Weave
 - Bag material
 - Gas temperature, inlet and outlet
 - Bag cleaning conditions:
 - Pulse: Air pressure
 - Shake: shaker motor current
 - Reverse: reverse air fan current
 - Bag cleaning cycle:
 - Shake: duration, frequency, and delay periods
 - Reverse: duration, frequency, and delay periods

3. Electrostatic Precipitators. The following information shall be recorded unless otherwise agreed to by the Department:

- Primary voltage
- Primary current
- Secondary current
- Spark rate

Additional information, including but not limited to the following, may be required to be included as descriptive information in the operation and maintenance plan, but shall not be required to be recorded routinely unless the Department determines that a precipitator's ability to achieve compliance with applicable emission limiting standards is questionable:

- Secondary voltage
- Rapper frequency, plate
- Rapper Vibrator frequency, wire
- Rapper duration, plate
- Rapper Vibrator duration, wire
- Gas temperature, inlet and outlet
- Estimated gas flowrate
- Static pressure

- (b) Control Equipment Data. The Operation and Maintenance plan shall include identification of control device(s) for each emissions unit subject to provisions of this rule including but not limited to the following appropriate design specifications and other descriptive data:

1. Manufacturer
2. Model name and number
3. Type: scrubber, baghouse, electrostatic precipitator, dry scrubber, etc.
4. Design flow rate (liquid and/or gas)
5. For EPS's: primary and secondary voltage and current
6. Efficiency rating at design capacity
7. Pressure drop
8. Liquid to gas ratio
9. Scrubbing liquor composition

- (c) Processing or Materials Handling Systems.
1. Appropriate parameters of processing or materials handling systems provide a measure of the rate of operations. The operation and maintenance plan shall include performance parameters which indicate the rate of operation, process weight through-put, the fuel or other energy source, the materials being processed or other physical or chemical characteristics, as applicable. Such parameters may include, but shall not be limited to the following:
 - a. Weight per unit time of raw materials input;
 - b. Process temperature or pressure;
 - c. Fuel or fuel mixture;
 - d. Chemical or physical data on product or raw materials;
 - e. Air to fuel ratio or percent excess oxygen;
 - f. Electrical power use rate by auxiliary equipment.
 2. The plan shall contain inspection and maintenance schedules including periodic assessments of the condition of manholes ducting, breaching, hoods, conveyor and elevator housing, loading sheds and other equipment, and a schedule for recording of performance parameter data.
- (d) Fossil Fuel Steam Generators. The operation and maintenance plan for fossil fuel steam generators may include, but shall not be limited to, the following:
- Steam flow
 - Fuel type (e.g., gas, oil, coal, or mixtures thereof)
 - Consumption rate for type(s) of fuel(s) burned
 - Fuel oil temperature (if applicable)
- (e) Records of inspection, maintenance and performance parameter data shall be retained for a minimum of two years and shall be made available to the Department upon request.

History: Formerly 17-2.650(2)(a)-(g); 17-296.700; Amended 11-23-94, 1-1-96, 8-14-19.
62-296.700

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/94	59 FR 52916
1 st Revision	12/21/1994	06/16/1999	64 FR 32346
2 nd Revision	4/15/1996	06/16/1999	64 FR 32346
3 rd Revision	4/1/2022	1/22/2024	89 FR 3886

62-296.702 Fossil Fuel Steam Generators.

- (1) Applicability. The emission limitations set forth in Rule 62-296.702, F.A.C., shall apply to fossil fuel steam generating facilities including one or more boilers which individually or in combination have a heat input greater than or equal to 30 million British thermal units per hour.
- (2) Emission Limitations.
 - (a) Particulate Matter. No owner or operator of a fossil fuel steam generator shall cause, permit, or allow the emission of particulate matter in excess of 0.10 pounds per million BTU except as provided for in Rules 62-296.405 or 62-296.406, F.A.C., and Rule 62-210.700
 - (b) Visible Emissions. No owner or operator of a fossil fuel fire4 steam generator shall allow visible emissions the density of which is greater than 20 percent opacity except as provided for in Rule 62-210.700, F.A.C., Excess Emissions, and in Rule 62-296.405, F.A.C., for fossil-fuel steam generators with a heat input of greater than 250 million BTU per hour.
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) The test method for visible emissions shall be EPA Method 9, as described at 40 C.F.R. Part 60, Appendix A-4, adopted and incorporated by reference at Rule 62-204.800, F.A.C. A transmissometer may be used and calibrated in accordance with 40 C.F.R. Part 60, Appendix B, , F.A.C.
 - (b) The test method for particulate matter emissions shall be EPA Method 17, as described and incorporated at 40 C.F.R. Part 60, Appendix A-6, EPA Method 5B as described at 40 C.F.R. Part 60, Appendix A-3; or EPA Method 5F, as described at 40 C.F.R. Part 60, Appendix A-3; adopted and incorporated by reference at Rule 62-204.800, F.A.C. The minimum sample volume shall be 30 dry standard cubic feet. EPA Method 5, as described at 40 C.F.R. Part 60, Appendix A-3, adopted and incorporated by reference at Rule 62-204.800, F.A.C., may be used with the filter temperature at no more than 320 degrees Fahrenheit. For EPA Method 17, stack temperature shall be less than 375 degrees Fahrenheit.. EPA Method 3 or 3A with Orsat analysis, as described at 40 C.F.R. Part 60, Appendix A-2, adopted and incorporated by reference at Rule 204.800, F.A.C., shall be used when oxygen based F factor computed according to EPA Method 19, as described at 40 C.F.R. Part 60, Appendix A-7, adopted and incorporated by reference at Rule 62-204.800, F.A.C., is used in lieu of heat input. Use Acetone wash with Method 5 or 17.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(2)(c)2; 17-296.702; Amended 11-23-94, 1-1-96, 7-10-14.

62-296.702

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	6/16/1999	64 FR 32346

2nd Revision
3rd Revision

4/15/1996
4/1/2022

6/16/1999
1/22/2024

64 FR 32346
89 FR 3886

62-296.704 Asphalt Concrete Plants.

- (1) Applicability. The emission limitations set forth in Rule 62-296.704, F.A.C., shall apply to any facility used to manufacture asphalt concrete by heating and drying aggregate and mixing with asphalt cements, excluding unloading and storage of raw materials.
- (2) Emission Limitations. No owner or operator of an asphalt concrete plant shall cause, permit, or allow the emission of particulate matter in excess of 0.06 gr/dscf, or visible emissions the density of which is greater than 20 percent opacity.
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) The test method for visible emissions shall be EPA Method 9, as described at 40 C.F.R. Part 60, Appendix A-4, adopted and incorporated by reference at Rule 62-204.800, F.A.C.
 - (b) The test method for particulate matter emissions shall be EPA Method 5 or EPA Method 5A, as described at 40 C.F.R. Part 60, Appendix A-3, adopted and incorporated by reference at Rule 62-204.800, F.A.C. The minimum sample volume shall be 30 dry standard cubic feet.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(2)(c)4.,17-296.704; Amended 11-23-94, 1-1-96, 7-10-14.

62-296.704

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	6/16/1999	64 FR 32346
2 nd Revision	4/15/1996	6/16/1999	64 FR 32346
3 rd Revision	4/1/2022	1/22/2024	89 FR 3886

62-296.705 Phosphate Processing Operations.

- (1) Applicability. The emission limitations set forth in Rule 62-296.705, F.A.C., shall apply to all unit operations and auxiliary equipment which are an integral part of the process used to manufacture the finished products specified in paragraphs (a) through(f) below, including reactors, dryers, coolers, concentrators, screens, elevators, conveyor belts, grinders, and other unit operations, which exist as part of the manufacturing system from the point of introduction of raw materials feed into the process to the point of discharge of the finished product to the storage materials handling system;
 - (a) Diammonium phosphate (DAP);
 - (b) Run of pile triple super phosphate (ROPTSP);
 - (c) Granular triple super phosphate (GTSP);
 - (d) Normal super phosphate (NSP);
 - (e) Monoammonium phosphate (MAP);
 - (f) Phosphate animal feed ingredient (AFI).
- (2) Emission Limitations.
 - (a) No owner or operator of a phosphate processing facility shall cause, permit or

allow total emissions of particulate matter from the affected unit operations and auxiliary equipment in excess of 0.30 pounds per ton of product or visible emissions the density of which is greater than 20 percent opacity from the above listed operations ((a) through (f)).

- (b) No owner or operator of a phosphate rock dryer or phosphate rock grinding operation which is not an integral part of the operations described in Rule 62-296.705(1)(a) through (f), F.A.C., shall cause, permit or allow total emissions of particulate matter from the dryer or grinder in excess of 0.20 lb/ton of products or visible emissions the density of which is greater than 20 percent opacity.
 - (c) No owner or operator of a concentrator which is part of a phosphate processing facility shall cause, permit or allow total emissions of particulate matter from the concentrator in excess of 15 pounds per hour or visible emissions the density of which is greater than 20 percent opacity.
 - (d) No owner or operator of a Diammonium Phosphate cooler producing less than 50 tons per hour of product shall cause, permit, or allow total emissions of particulate matter in excess of 0.60 pound per ton of product or visible emissions the density of which is greater than 20 percent opacity.
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
- (a) The test method for visible emissions shall be EPA Method 9, as described at 40 C.F.R. Part 60, Appendix A-4, adopted and incorporated by reference at Rule 62-204.800, F.A.C.
 - (b) The test method for particulate matter emissions shall be EPA Method 5 or EPA Method 5A, as described at 40 C.F.R. Part 60, Appendix A-3, adopted and incorporated by reference at Rule 62-204.800, F.A.C. The minimum sample volume shall be 30 dry standard cubic feet.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(2)(c)5., 17-296.705; Amended 11-23-94, 1-1-96, 7-10-14.

62-296.705

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/94	59 FR 52916
1 st Revision	12/21/1994	6/16/1999	64 FR 32346
2 nd Revision	4/15/1996	6/16/1999	64 FR 32346
3 rd Revision	4/1/2022	1/22/2024	89 FR 3886

62-296.707 Electric Arc Furnaces.

- (1) Applicability. The emission limitations set forth in Rule 62-296.707, F.A.C., shall apply to all furnaces that heat materials with electric arcs from carbon electrodes, including phosphorus electric arc furnaces.
- (2) Emission Limitations. No owner or operator of an electric arc furnace shall cause, permit, or allow emissions of particulate matter in excess of the following standards:

- (a) Phosphorus electric arc furnaces - 0.035 gr/dscf or any visible emissions (greater than five percent opacity) from a control device, except during tapping periods. No visible emissions greater than 60 percent opacity shall be allowed during the tapping period.
- (b) All other electric arc furnaces - 0.010 gr/dscf or any visible emissions (greater than five percent opacity) from a control device, except during charging and tapping periods. No visible emissions greater than 20 percent opacity shall be allowed from the shop during charging periods. No visible emissions greater than 40 percent opacity shall be allowed during tapping periods.
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) The test method for visible emissions shall be EPA Method 9, as described at 40 C.F.R. Part 60, Appendix A-4, adopted and incorporated by reference at Rule 62-204.800, F.A.C.
 - (b) The test method for particulate matter emissions shall be EPA Method 5 or EPA Method 5D, as described at 40 C.F.R. Part 60, Appendix A-3, adopted and incorporated by reference at Rule 62-204.800, F.A.C. The minimum sample volume shall be 30 dry standard cubic feet.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(2)(c)7., 17-296.707; Amended 11-23-94, 1-1-96, 7-10-14.

62-296.707

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	6/16/1999	64 FR 32346
2 nd Revision	4/15/1996	6/16/1999	64 FR 32346
3 rd Revision	4/1/2022	1/22/2024	89 FR 3886

62-296.708 Sweat or Pot Furnaces.

- (1) Applicability. The emission limitations set forth in Rule 62-296.708, F.A.C., shall apply to indirectly heated furnaces which are temperature controlled for the differential melting of scrap or combined metal products or which melt metals for coating or reclamation.
- (2) Emission Limitations. No owner or operator of a sweat or pot furnace shall cause, permit, or allow emissions of particulate matter in excess of 0.05 gr/dscf, or visible emissions greater than 10 percent opacity.
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) The test method for visible emissions shall be EPA Method 9, as described at 40 C.F.R. Part 60, Appendix A-4, adopted and incorporated by reference at Rule 62-204.800, F.A.C.
 - (b) The test method for particulate matter emissions shall be EPA Method 5, as described at 40 C.F.R. Part 60, Appendix A-3, adopted and incorporated by reference at Rule 62-204.800, F.A.C. The minimum sample volume shall be 30 dry standard cubic feet.
 - (c) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(2)(c)8., 17-296.708; Amended 11-23-94, 1-1-96, 7-10-14.

62-296.708

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	6/16/1999	64 FR 32346
2 nd Revision	4/15/1996	6/16/1999	64 FR 32346
3 rd Revision	4/1/2022	1/22/2024	89 FR 3886

62-296.711 Materials Handling, Sizing, Screening, Crushing and Grinding Operations.

- (1) Applicability. The emission limitations set forth in Rule 62-296.711, F.A.C., shall apply to the handling, sizing, screening, crushing, or grinding of the materials such as, but not limited to, cement, clinker, fly ash, coke, gypsum, shale, lime, sulfur, phosphatic materials, slag, and grain or grain products, including but not limited to the following types of operations:
 - (a) Loading or unloading of materials to or from such containers as railcars, trucks, ships, and storage structures;
 - (b) Conveyor systems other than portable conveyor systems;
 - (c) Storage of materials in storage structures, such as silos or enclosed bins, which have a storage capacity of fifty cubic yards or more;
 - (d) Crushing and/or grinding operations;
 - (e) Sizing and/or rescreening operations;
 - (f) Static drop transfer points where the discharge point and receiving point of the materials being handled are not moving in relationship to one another. The emission limitations set forth in Rule 62-296.711, F.A.C., shall not apply to emissions from materials handling, sizing, screening, crushing and grinding operations governed by Rule 62-296.705, F.A.C., Phosphate Process Operations or Rule 62-296.704, F.A.C., Asphalt Concrete Plants.
- (2) Emission Limitations.
 - (a) No owner or operator of an emissions unit governed by Rule 62-296.711, F.A.C., shall cause, permit, or allow any visible emissions (five percent opacity) from such emissions unit except that at the point where material is being discharged to the hold of a ship from a conveyor system. When the conveyor and/or hatch covering is moved, an opacity of 10 percent will be allowed.
 - (b) If, in order to comply with the requirements of paragraph (a) above, it is necessary to totally or partially enclose an operation and exhaust particulate laden gases through a vent or stack, emissions of particulate from such vent or stack shall not exceed 0.03 gr/dscf.
 - (c) An owner or operator may request the Department to determine that the emission standards of Rule 62-296.711(2)(a) and (b), F.A.C., do not constitute RACT for a facility. If the Department finds that the emission standards do not represent RACT, the Department shall make a determination of RACT for that facility.
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) The test method for visible emissions shall be EPA Method 9, as described at 40 C.F.R. Part 60, Appendix A-4, adopted and incorporated by reference at Rule 62-204.800, F.A.C.
 - (b) The test method for particulate matter emissions shall be EPA Method 5, as described at 40 C.F.R. Part 60, Appendix A-3, adopted and incorporated by reference at Rule 62-204.800, F.A.C. The minimum sample volume shall be 30 dry standard cubic feet.
 - (c) A visible emissions test indicating no visible emissions (5 percent opacity) may be submitted in lieu of a particulate stack test for materials handling emissions units subject to this rule, where the emissions unit is equipped with a baghouse.
 - (d) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(2)(c)11., 17-296.711; Amended 11-23-94, 1-1-96, 7/10/14.
62-296.711

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	6/16/1999	64 FR 32346
2 nd Revision	4/15/1996	6/16/1999	64 FR 32346
3 rd Revision	4/1/2022	1/22/2024	89 FR 3886

62-296.712 Miscellaneous Manufacturing Process Operations.

- (1) Applicability. The emission limitations and other requirements of Rule 62-296.712, F.A.C., shall apply to miscellaneous manufacturing process operations for which a specific RACT emission limitation has not been established in Rules 62-296.401 through 62-296.415, F.A.C., or Rules 62-296.701 through Rule 62-296.711, F.A.C., including but not limited to such operations as heat treating furnaces, waste heat evaporators, corebaking ovens, mixing kettles, blast furnaces, puddling furnaces, dryers, stills, roasters, and all other methods or forms of manufacturing or processing which emit particulate matter.
- (2) Emission Limitations. No owner or operator of a miscellaneous manufacturing process operation shall cause, permit, or allow emissions of particulate matter in excess of 0.03 gr/dscf, or any visible emissions greater than 5 percent opacity. However, the owner or operator may exceed these emission limits if he utilizes a pollution control device or system for control of particulate matter which has an actual particulate matter collection efficiency of at least 98 percent.

If Rule 62-296.712, F.A.C., is the least restrictive standard, the opacity standard for the emissions unit shall be the average opacity level achieved during the initial compliance* test which establishes compliance with the standard, plus 5 percent opacity.
- (3) Test Methods and Procedures. All emissions tests performed pursuant to the requirements of this rule shall comply with the following requirements.
 - (a) The test method for visible emissions shall be EPA Method 9, as described at 40 C.F.R. Part 60, Appendix A-4, adopted and incorporated by reference at Rule 62-204.800, F.A.C.
 - (b) The test method for particulate matter emissions shall be EPA Method 5, as described at 40 C.F.R. Part 60, Appendix A-3, adopted and incorporated by reference at Rule 62-204.800, F.A.C. The minimum sample volume shall be 30 dry standard cubic feet.
 - (c) A visible emissions test indicating no visible emissions (5 percent opacity) may be submitted in lieu of a particular stack test for materials handling emissions subject to this rule, where the emissions unit is equipped with a baghouse.
 - (d) Test procedures shall meet all applicable requirements of Chapter 62-297, F.A.C.

History: Formerly 17-2.650(2)(c)12., 17-296.712; Amended 11-23-94, 1-1-96, 7-10-14.

62-296.712

	Date Submitted to EPA	Date Approved by EPA	Federal Register
Recodification	1/11/1993	10/20/1994	59 FR 52916
1 st Revision	12/21/1994	6/16/1999	64 FR 32346
2 nd Revision	4/15/1996	6/16/1999	64 FR 32346
3 rd Revision	4/1/2022	1/22/2024	89 FR 3886